TEST REPORT

APPLICANT	:	Nubia Technology Co.,Ltd.
PRODUCT NAME	:	5G Mobile Phone
MODEL NAME	:	NX669J
BRAND NAME	:	REDMAGIC
FCC ID	:	2AHJO-NX669J
STANDARD(S)	:	47 CFR Part 2 47 CFR Part 90, Subpart S
RECEIPT DATE	:	2020-12-29
TEST DATE	:	2021-01-02 to 2021-03-05
ISSUE DATE	:	2021-03-10

Edited by: Peng Mi (Rapporteur)

Approved by: Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB
SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China
Tel: 86-755-36698555 Fax: 86-755-36698525
Http://www.morlab.cn E-mail: service@morlab.cn

DIRECTORY

1. Technical Information ····· 3
1.1. Applicant and Manufacturer Information ····· 3
1.2. Equipment Under Test (EUT) Description ····· 3
1.3. Maxium E.R.P./E.I.R.P. and Emission Designator ····· 5
1.4. Test Standards and Results ····· 6
1.5. Environmental Conditions ····· 7
2. 47 CFR Part 2, Part 90S Requirements ····· 8
2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P. ····· 8
2.2. Occupied Bandwidth ····· 19
2.3. Frequency Stability ····· 29
2.4. Peak to Average Radio ····· 31
2.5. Conducted Spurious Emissions ····· 32
2.6. Band Edge ····· 40
2.7. Radiated Spurious Emissions ····· 44
Annex A Test Uncertainty ····· 59
Annex B Testing Laboratory Information ····· 60

Change History		
Version	Date	Reason for change
1.0	2021-03-10	First edition

1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Nubia Technology Co.,Ltd.
Applicant Address:	Room 1801, Building 2, Chongwen Park, Nanshan Zhiyuan, No.3370, Liuxian Rd, Nanshan District, Shenzhen City, Guangdong Province, P. R. China
Manufacturer:	Nubia Technology Co.,Ltd.
Manufacturer Address:	Room 1801, Building 2, Chongwen Park, Nanshan Zhiyuan, No.3370, Liuxian Rd, Nanshan District, Shenzhen City, Guangdong Province, P. R. China

1.2. Equipment Under Test (EUT) Description

Product Name:	5G Mobile Phone	
Serial No.:	(N/A, marked #1 by test site)	
Hardware Version:	NX669J_V1AMB	
Software Version:	NX669J_EUCommon_V3.05	
Modulation Type:	QPSK, 16QAM, 64QAM	
Operation Band:	Band 18 / 26	
Frequency Range:	LTE Band 18	Tx: 815MHz–830MHz
		Rx: 860MHz–875MHz
	LTE Band 26	Tx: 814MHz–824MHz
		Rx: 859MHz–869MHz
Channel Bandwidth	LTE Band 18	5MHz
	LTE Band 26	1.4MHz, 3MHz, 5MHz, 10MHz
Antenna Type:	Fixed Antenna	
Antenna Gain:	LTE Band 18	-1.0dBi
	LTE Band 26	-1.0dBi

Accessory Information:	Battery	
	Brand Name:	nubia
	Model No.:	Li3945T44P8h906455
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	4960mAh
	Rated Voltage:	3.87V
	Charge Limit:	4.45V
	Manufacturer:	Dongguan Amperex Technology Limited
	AC Adapter	
	Brand Name:	nubia
	Model No.:	NB-A930A-A, NB-A930A-USBA-1
	Serial No.:	(N/A, marked #1 by test site)
	Rated Output:	5V⎓3A, 9V⎓3A, 12V⎓2.5A, 15V⎓2A,
	Rated Input:	100-240V~50/60Hz, Max 0.8A
	Manufacturer:	ShenZhen Kingfulin Technology Co., Ltd

Note 1: SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

LTE Band 18	Maximum E.R.P./E.I.R.P. (W)			Emission Designator (99%OBW)		
BW(MHz)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
5	0.206	0.186	0.151	4M49G7D	4M49W7D	4M50W7D
LTE Band 26	**Maximum E.R.P./E.I.R.P. (W)**			**Emission Designator (99%OBW)**		
BW(MHz)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
10	0.197	0.167	0.134	9M00G7D	8M99W7D	8M99W7D
5	0.192	0.186	0.157	4M50G7D	4M50W7D	4M49W7D
3	0.189	0.188	0.156	2M70G7D	2M69W7D	2M69W7D
1.4	0.189	0.182	0.144	1M09G7D	1M09W7D	1M09W7D

1.4. Test Standards and Results

The objective of the report is to perform testing according to Part 2 and Part 90 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 90	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
2.1046, 90.635(b)	Transmitter Conducted Output Power and ERP/EIRP	Mar 05, 2021	Chen Hao Gao Jianrou	PASS	No deviation
90.209	Occupied Bandwidth	Jan 11&23, 2021	Ling Keye	PASS	No deviation
2.1055, 90.213	Frequency Stability	Feb 18, 2021	Ling Keye	PASS	No deviation
2.1051, 90.691	Conducted Spurious Emissions	Jan 11&28, 2021	Ling Keye	PASS	No deviation
2.1051, 90.691	Band Edge	Jan 02, 2021	Ling Keye	PASS	No deviation
2.1051, 90.691	Radiated Spurious Emissions	Jan 13, 2021 Feb 09, 2021	Gao Jianrou	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03 and ANSI/TIA-603-E-2016.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 23.5dB contains two parts that cable loss 13.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% risk level.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR Part 2, Part 90S Requirements

2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P.

2.1.1. Requirement

According to FCC section 2.1046(a), for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

2.1.2. Test Description



The EUTis coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.1.3. Test procedure

KDB 971168 D01v03 Section 5.2 and ANSI/TIA-603-E-2016.

EIRP (dBm) = Conducted Output Power (dBm) + Antenna Gain (dBi)
ERP (dBm) = EIPR (dBm) - 2.15

2.1.4. Result

Conducted Output Power:

LTE Band 18						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				23875	23895	23915
Frequency (MHz)				817.5	819.5	821.5
5	QPSK	1	0	22.88	23.00	23.06
5	QPSK	1	12	23.05	23.10	23.14
5	QPSK	1	24	23.05	23.05	23.13
5	QPSK	12	0	22.09	22.13	22.14
5	QPSK	12	7	22.21	22.14	22.21
5	QPSK	12	13	22.25	22.14	22.09
5	QPSK	25	0	22.19	22.15	22.12
5	16QAM	1	0	22.21	22.57	22.45
5	16QAM	1	12	22.12	22.65	22.67
5	16QAM	1	24	22.16	22.39	22.69
5	16QAM	12	0	22.13	22.10	22.04
5	16QAM	12	7	22.15	22.15	22.14
5	16QAM	12	13	22.34	22.00	22.12
5	16QAM	25	0	22.20	22.01	22.01
5	64QAM	1	0	21.21	21.54	21.51
5	64QAM	1	12	21.17	21.37	21.80
5	64QAM	1	24	21.12	21.66	21.71
5	64QAM	12	0	21.26	21.49	21.47
5	64QAM	12	7	21.18	21.64	21.61
5	64QAM	12	13	21.34	21.57	21.48
5	64QAM	25	0	21.09	21.68	21.53

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				/	26740	/
Frequency (MHz)				/	819.0	/
10	QPSK	1	0	/	22.87	/
10	QPSK	1	25	/	22.95	/
10	QPSK	1	49	/	22.71	/
10	QPSK	25	0	/	21.93	/
10	QPSK	25	12	/	22.00	/
10	QPSK	25	25	/	21.92	/
10	QPSK	50	0	/	21.99	/
10	16QAM	1	0	/	22.06	/
10	16QAM	1	25	/	22.12	/
10	16QAM	1	49	/	22.22	/
10	16QAM	25	0	/	21.65	/
10	16QAM	25	12	/	21.66	/
10	16QAM	25	25	/	21.63	/
10	16QAM	50	0	/	21.00	/
10	64QAM	1	0	/	21.26	/
10	64QAM	1	25	/	21.22	/
10	64QAM	1	49	/	21.23	/
10	64QAM	25	0	/	21.05	/
10	64QAM	25	12	/	21.22	/
10	64QAM	25	25	/	21.01	/
10	64QAM	50	0	/	20.92	/

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26715	26740	26765
Frequency (MHz)				816.5	819.0	821.5
5	QPSK	1	0	22.53	22.63	22.64
5	QPSK	1	12	22.83	22.73	22.70
5	QPSK	1	24	22.80	22.76	22.60
5	QPSK	12	0	21.72	21.81	21.81
5	QPSK	12	7	21.83	21.81	21.88
5	QPSK	12	13	21.90	21.79	21.78
5	QPSK	25	0	21.78	21.77	21.83
5	16QAM	1	0	22.26	22.70	22.42
5	16QAM	1	12	21.96	22.16	22.23
5	16QAM	1	24	21.96	22.22	22.29
5	16QAM	12	0	21.24	21.50	21.61
5	16QAM	12	7	21.46	21.57	21.68
5	16QAM	12	13	21.42	21.58	21.59
5	16QAM	25	0	21.39	21.60	21.59
5	64QAM	1	0	21.22	21.67	21.57
5	64QAM	1	12	21.39	21.96	21.66
5	64QAM	1	24	21.19	21.66	21.40
5	64QAM	12	0	21.13	21.38	21.30
5	64QAM	12	7	21.21	21.35	21.35
5	64QAM	12	13	21.21	21.26	21.34
5	64QAM	25	0	21.11	21.38	21.42

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26705	26740	26775
Frequency (MHz)				815.5	819.0	822.5
3	QPSK	1	0	22.57	22.61	22.57
3	QPSK	1	8	22.73	22.71	22.70
3	QPSK	1	14	22.77	22.61	22.61
3	QPSK	8	0	22.08	22.10	22.13
3	QPSK	8	4	22.14	22.20	22.22
3	QPSK	8	7	22.10	22.18	22.12
3	QPSK	15	0	21.76	21.70	21.69
3	16QAM	1	0	21.95	22.08	21.74
3	16QAM	1	8	22.20	22.47	22.32
3	16QAM	1	14	22.22	22.74	22.26
3	16QAM	8	0	21.21	21.55	21.61
3	16QAM	8	4	21.22	21.72	21.59
3	16QAM	8	7	21.08	21.65	21.46
3	16QAM	15	0	21.17	21.61	21.67
3	64QAM	1	0	21.48	21.72	21.80
3	64QAM	1	8	21.49	21.93	21.80
3	64QAM	1	14	21.56	21.66	21.69
3	64QAM	8	0	21.47	21.42	21.53
3	64QAM	8	4	21.11	21.58	21.63
3	64QAM	8	7	21.16	21.51	21.51
3	64QAM	15	0	21.16	21.53	21.63

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26697	26740	26783
Frequency (MHz)				814.7	819.0	823.3
1.4	QPSK	1	0	22.56	22.50	22.48
1.4	QPSK	1	3	22.72	22.54	22.59
1.4	QPSK	1	5	22.76	22.42	22.50
1.4	QPSK	3	0	22.07	22.57	22.50
1.4	QPSK	3	1	22.13	22.55	22.57
1.4	QPSK	3	3	22.09	22.44	22.47
1.4	QPSK	6	0	22.06	22.51	22.09
1.4	16QAM	1	0	22.04	22.41	22.59
1.4	16QAM	1	3	22.19	22.02	22.40
1.4	16QAM	1	5	22.21	22.30	22.35
1.4	16QAM	3	0	21.20	21.44	21.45
1.4	16QAM	3	1	21.21	21.54	21.64
1.4	16QAM	3	3	21.07	21.51	21.58
1.4	16QAM	6	0	21.16	21.60	21.54
1.4	64QAM	1	0	20.89	21.00	21.06
1.4	64QAM	1	3	20.96	21.02	21.38
1.4	64QAM	1	5	21.49	21.33	21.48
1.4	64QAM	3	0	20.89	21.32	21.29
1.4	64QAM	3	1	21.10	21.24	21.29
1.4	64QAM	3	3	21.15	21.31	21.47
1.4	64QAM	6	0	21.15	21.54	21.57

Effective Radiated Power and Effective Isotropic Radiated Power:

LTE Band 18				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26715		26740		26765	
Frequency (MHz)				816.5		819.0		821.5	
				dBm	W	dBm	W	dBm	W
5	QPSK	1	0	22.88	0.194	23.00	0.200	23.06	0.202
5	QPSK	1	12	23.05	0.202	23.10	0.204	23.14	0.206
5	QPSK	1	24	23.05	0.202	23.05	0.202	23.13	0.206
5	QPSK	12	0	22.09	0.162	22.13	0.163	22.14	0.164
5	QPSK	12	7	22.21	0.166	22.14	0.164	22.21	0.166
5	QPSK	12	13	22.25	0.168	22.14	0.164	22.09	0.162
5	QPSK	25	0	22.19	0.166	22.15	0.164	22.12	0.163
5	16QAM	1	0	22.21	0.166	22.57	0.181	22.45	0.176
5	16QAM	1	12	22.12	0.163	22.65	0.184	22.67	0.185
5	16QAM	1	24	22.16	0.164	22.39	0.173	22.69	0.186
5	16QAM	12	0	22.13	0.163	22.10	0.162	22.04	0.160
5	16QAM	12	7	22.15	0.164	22.15	0.164	22.14	0.164
5	16QAM	12	13	22.34	0.171	22.00	0.158	22.12	0.163
5	16QAM	25	0	22.20	0.166	22.01	0.159	22.01	0.159
5	64QAM	1	0	21.21	0.132	21.54	0.143	21.51	0.142
5	64QAM	1	12	21.17	0.131	21.37	0.137	21.80	0.151
5	64QAM	1	24	21.12	0.129	21.66	0.147	21.71	0.148
5	64QAM	12	0	21.26	0.134	21.49	0.141	21.47	0.140
5	64QAM	12	7	21.18	0.131	21.64	0.146	21.61	0.145
5	64QAM	12	13	21.34	0.136	21.57	0.144	21.48	0.141
5	64QAM	25	0	21.09	0.129	21.68	0.147	21.53	0.142

LTE Band 26				Measured E.R.P.			
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.	Middle Ch. / Freq.		High Ch. / Freq.
Channel				/	26740		/
Frequency (MHz)				/	819		/
				/	dBm	W	/
10	QPSK	1	0	/	22.87	0.194	/
10	QPSK	1	25	/	22.95	0.197	/
10	QPSK	1	49	/	22.71	0.187	/
10	QPSK	25	0	/	21.93	0.156	/
10	QPSK	25	12	/	22.00	0.158	/
10	QPSK	25	25	/	21.92	0.156	/
10	QPSK	50	0	/	21.99	0.158	/
10	16QAM	1	0	/	22.06	0.161	/
10	16QAM	1	25	/	22.12	0.163	/
10	16QAM	1	49	/	22.22	0.167	/
10	16QAM	25	0	/	21.65	0.146	/
10	16QAM	25	12	/	21.66	0.147	/
10	16QAM	25	25	/	21.63	0.146	/
10	16QAM	50	0	/	21.00	0.126	/
10	64QAM	1	0	/	21.26	0.134	/
10	64QAM	1	25	/	21.22	0.132	/
10	64QAM	1	49	/	21.23	0.133	/
10	64QAM	25	0	/	21.05	0.127	/
10	64QAM	25	12	/	21.22	0.132	/
10	64QAM	25	25	/	21.01	0.126	/
10	64QAM	50	0	/	20.92	0.124	/

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26715		26740		26765	
Frequency (MHz)				816.5		819.0		821.5	
				dBm	W	dBm	W	dBm	W
5	QPSK	1	0	22.53	0.179	22.63	0.183	22.64	0.184
5	QPSK	1	12	22.83	0.192	22.73	0.187	22.70	0.186
5	QPSK	1	24	22.80	0.191	22.76	0.189	22.60	0.182
5	QPSK	12	0	21.72	0.149	21.81	0.152	21.81	0.152
5	QPSK	12	7	21.83	0.152	21.81	0.152	21.88	0.154
5	QPSK	12	13	21.90	0.155	21.79	0.151	21.78	0.151
5	QPSK	25	0	21.78	0.151	21.77	0.150	21.83	0.152
5	16QAM	1	0	22.26	0.168	22.70	0.186	22.42	0.175
5	16QAM	1	12	21.96	0.157	22.16	0.164	22.23	0.167
5	16QAM	1	24	21.96	0.157	22.22	0.167	22.29	0.169
5	16QAM	12	0	21.24	0.133	21.50	0.141	21.61	0.145
5	16QAM	12	7	21.46	0.140	21.57	0.144	21.68	0.147
5	16QAM	12	13	21.42	0.139	21.58	0.144	21.59	0.144
5	16QAM	25	0	21.39	0.138	21.60	0.145	21.59	0.144
5	64QAM	1	0	21.22	0.132	21.67	0.147	21.57	0.144
5	64QAM	1	12	21.39	0.138	21.96	0.157	21.66	0.147
5	64QAM	1	24	21.19	0.132	21.66	0.147	21.40	0.138
5	64QAM	12	0	21.13	0.130	21.38	0.137	21.30	0.135
5	64QAM	12	7	21.21	0.132	21.35	0.136	21.35	0.136
5	64QAM	12	13	21.21	0.132	21.26	0.134	21.34	0.136
5	64QAM	25	0	21.11	0.129	21.38	0.137	21.42	0.139

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26705		26740		26775	
Frequency (MHz)				815.5		819.0		822.5	
				dBm	W	dBm	W	dBm	W
3	QPSK	1	0	22.57	0.181	22.61	0.182	22.57	0.181
3	QPSK	1	8	22.73	0.187	22.71	0.187	22.70	0.186
3	QPSK	1	14	22.77	0.189	22.61	0.182	22.61	0.182
3	QPSK	8	0	22.08	0.161	22.10	0.162	22.13	0.163
3	QPSK	8	4	22.14	0.164	22.20	0.166	22.22	0.167
3	QPSK	8	7	22.10	0.162	22.18	0.165	22.12	0.163
3	QPSK	15	0	21.76	0.150	21.70	0.148	21.69	0.148
3	16QAM	1	0	21.95	0.157	22.08	0.161	21.74	0.149
3	16QAM	1	8	22.20	0.166	22.47	0.177	22.32	0.171
3	16QAM	1	14	22.22	0.167	22.74	0.188	22.26	0.168
3	16QAM	8	0	21.21	0.132	21.55	0.143	21.61	0.145
3	16QAM	8	4	21.22	0.132	21.72	0.149	21.59	0.144
3	16QAM	8	7	21.08	0.128	21.65	0.146	21.46	0.140
3	16QAM	15	0	21.17	0.131	21.61	0.145	21.67	0.147
3	64QAM	1	0	21.48	0.141	21.72	0.149	21.80	0.151
3	64QAM	1	8	21.49	0.141	21.93	0.156	21.80	0.151
3	64QAM	1	14	21.56	0.143	21.66	0.147	21.69	0.148
3	64QAM	8	0	21.47	0.140	21.42	0.139	21.53	0.142
3	64QAM	8	4	21.11	0.129	21.58	0.144	21.63	0.146
3	64QAM	8	7	21.16	0.131	21.51	0.142	21.51	0.142
3	64QAM	15	0	21.16	0.131	21.53	0.142	21.63	0.146

LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26697		26740		26783	
Frequency (MHz)				814.7		819.0		823.3	
				dBm	W	dBm	W	dBm	W
1.4	QPSK	1	0	22.56	0.180	22.50	0.178	22.48	0.177
1.4	QPSK	1	3	22.72	0.187	22.54	0.179	22.59	0.182
1.4	QPSK	1	5	22.76	0.189	22.42	0.175	22.50	0.178
1.4	QPSK	3	0	22.07	0.161	22.57	0.181	22.50	0.178
1.4	QPSK	3	1	22.13	0.163	22.55	0.180	22.57	0.181
1.4	QPSK	3	3	22.09	0.162	22.44	0.175	22.47	0.177
1.4	QPSK	6	0	22.06	0.161	22.51	0.178	22.09	0.162
1.4	16QAM	1	0	22.04	0.160	22.41	0.174	22.59	0.182
1.4	16QAM	1	3	22.19	0.166	22.02	0.159	22.40	0.174
1.4	16QAM	1	5	22.21	0.166	22.30	0.170	22.35	0.172
1.4	16QAM	3	0	21.20	0.132	21.44	0.139	21.45	0.140
1.4	16QAM	3	1	21.21	0.132	21.54	0.143	21.64	0.146
1.4	16QAM	3	3	21.07	0.128	21.51	0.142	21.58	0.144
1.4	16QAM	6	0	21.16	0.131	21.60	0.145	21.54	0.143
1.4	64QAM	1	0	20.89	0.123	21.00	0.126	21.06	0.128
1.4	64QAM	1	3	20.96	0.125	21.02	0.126	21.38	0.137
1.4	64QAM	1	5	21.49	0.141	21.33	0.136	21.48	0.141
1.4	64QAM	3	0	20.89	0.123	21.32	0.136	21.29	0.135
1.4	64QAM	3	1	21.10	0.129	21.24	0.133	21.29	0.135
1.4	64QAM	3	3	21.15	0.130	21.31	0.135	21.47	0.140
1.4	64QAM	6	0	21.15	0.130	21.54	0.143	21.57	0.144

2.2. Occupied Bandwidth

2.2.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission.Occupied bandwidth is also known as the 99% emission bandwidth.

2.2.2. Test Description



The EUTis coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.2.3. Test procedure

KDB 971168 D01v03 Section 4.1 and ANSI/TIA-603-E-2016.

2.2.4. Test Result

LTE Band 18				
BW(MHz)	Channel Level	Modulation	99% BW(MHz)	26dB BW(MHz)
5	Low	QPSK	4.49	4.97
	Low	16QAM	4.49	4.96
	Low	64QAM	4.50	4.93
	Mid	QPSK	4.49	4.99
	Mid	16QAM	4.49	4.93
	Mid	64QAM	4.49	4.97
	High	QPSK	4.49	4.94
	High	16QAM	4.49	4.95
	High	64QAM	4.49	4.93

LTE Band 26				
BW(MHz)	Channel Level	Modulation	99% BW(MHz)	26dB BW(MHz)
1.4	Low	QPSK	1.09	1.23
	Low	16QAM	1.09	1.23
	Low	64QAM	1.09	1.24
	Mid	QPSK	1.09	1.23
	Mid	16QAM	1.09	1.22
	Mid	64QAM	1.09	1.23
	High	QPSK	1.09	1.22
	High	16QAM	1.09	1.23
	High	64QAM	1.09	1.22
3	Low	QPSK	2.70	2.97
	Low	16QAM	2.69	2.99
	Low	64QAM	2.69	2.99
	Mid	QPSK	2.69	2.99
	Mid	16QAM	2.69	2.99
	Mid	64QAM	2.69	2.96
	High	QPSK	2.69	2.99
	High	16QAM	2.69	2.98
	High	64QAM	2.69	2.98
5	Low	QPSK	4.50	4.98
	Low	16QAM	4.49	4.97
	Low	64QAM	4.49	4.97
	Mid	QPSK	4.50	4.99
	Mid	16QAM	4.50	4.97
	Mid	64QAM	4.49	4.97
	High	QPSK	4.50	4.98
	High	16QAM	4.50	4.96
	High	64QAM	4.49	4.95
10	Mid	QPSK	9.00	9.78
	Mid	16QAM	8.99	9.76
	Mid	64QAM	8.99	9.79

Band18 / 5MHz / Low CH / QPSK

Band18 / 5MHz / Low CH / 16QAM



Band18 / 5MHz / Low CH / 64QAM

Band18 / 5MHz / Mid CH / QPSK

Band18 / 5MHz / Mid CH / 16QAM

Band18 / 5MHz / Mid CH / 64QAM

Band18 / 5MHz / High CH / QPSK

Band18 / 5MHz / High CH / 16QAM

Band18 / 5MHz / High CH / 64QAM

Band26 / 1.4MHz / Low CH / QPSK

Band26 / 1.4MHz / Low CH / 16QAM

Band26 / 1.4MHz / Low CH / 64QAM

Band26 / 1.4MHz / Mid CH / QPSK



Band26 / 1.4MHz / Mid CH / 16QAM

Band26 / 1.4MHz / Mid CH / 64QAM

Band26 / 1.4MHz / High CH / QPSK



Band26 / 1.4MHz / High CH / 16QAM

Band26 / 1.4MHz / High CH / 64QAM

Band26 / 3MHz / Low CH / QPSK

Band26 / 3MHz / Low CH / 16QAM



Band26 / 3MHz / Low CH / 64QAM

Band26 / 3MHz / Mid CH / QPSK

Band26 / 3MHz / Mid CH / 16QAM

Band26 / 3MHz / Mid CH / 64QAM

Band26 / 3MHz / High CH / QPSK

Band26 / 3MHz / High CH / 16QAM



Band26 / 3MHz / High CH / 64QAM

Band26 / 5MHz / Low CH / QPSK

Band26 / 5MHz / Low CH / 16QAM

Band26 / 5MHz / Low CH / 64QAM

Band26 / 5MHz / Mid CH / QPSK

Band26 / 5MHz / Mid CH / 16QAM

Band26 / 5MHz / Mid CH / 64QAM

Band26 / 5MHz / High CH / QPSK

Band26 / 5MHz / High CH / 16QAM

Band26 / 5MHz / High CH / 64QAM

Band26 / 10MHz / Mid CH / QPSK

Band26 / 10MHz / Mid CH / 16QAM

Band26 / 10MHz / Mid CH / 64QAM

2.3. Frequency Stability

2.3.1. Requirement

According to FCC section 2.1055 & 90.213, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

(a) The temperature is varied from -30°C to +50°C at intervals of not more than 10°C.

(b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from 0°C to 40°C, which are specified by the applicant.

2.3.2. Test Description



The EUT which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power. A call is established between the EUT and the SS via a Common Antenna.

2.3.3. Test procedure

KDB 971168 D01v03 Section 9.0 and ANSI/TIA-603-E-2016.

2.3.4. Test Result

The nominal, highest and lowest extreme voltages are separately 3.87V, 4.45V and 3.45V, which are specified by the applicant; the normal temperature here used is 20°C.

LTE Band 18, QPSK, Channel 23895, Frequency 819.5MHz Limit =±2.5ppm					
Voltage (%)	**Power (VDC)**	**Temp(°C)**	**Fre. Dev.(Hz)**	**Deviation (ppm)**	**Result**
100	3.87	+20(Ref)	26	0.032	PASS
100		0	-14	-0.017	
100		+10	21	0.026	
100		+20	17	0.021	
100		+30	14	0.017	
100		+40	-15	-0.018	
115	4.45	+20	-14	-0.017	
85	3.45	+20	37	0.045	

LTE Band 26, QPSK, Channel 26740, Frequency 819MHz Limit =±2.5ppm					
Voltage (%)	**Power (VDC)**	**Temp(°C)**	**Fre. Dev.(Hz)**	**Deviation (ppm)**	**Result**
100	3.87	+20(Ref)	-16	-0.020	PASS
100		0	17	0.021	
100		+10	26	0.032	
100		+20	11	0.013	
100		+30	19	0.023	
100		+40	-12	-0.015	
115	4.45	+20	16	0.020	
85	3.45	+20	-12	-0.015	

2.4. Peak to Average Radio

2.4.1. Requirement

2.4.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.4.3. Test procedure

KDB 971168 D01v03 Section 5.7 and ANSI/TIA-603-E-2016.

2.4.4. Test Result

Note: This test case does not apply this kind of EUT for part 90.

2.5. Conducted Spurious Emissions

2.5.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

2.5.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.5.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.

2.5.4. Test Result

Band18 / 5MHz / Low CH / QPSK



Band18 / 5MHz / Low CH / 16QAM



Band18 / 5MHz / Low CH / 64QAM



Band18 / 5MHz / Mid CH / QPSK



Band18 / 5MHz / Mid CH / 16QAM



Band18 / 5MHz / Mid CH / 64QAM



Band18/ 5MHz / High CH / QPSK



Band18 / 5MHz / High CH / 16QAM



Band18 / 5MHz / High CH / 64QAM



Band26 / 1.4MHz / Low CH / QPSK



Band26 / 1.4MHz / Low CH / 16QAM



Band26 / 1.4MHz / Low CH / 64QAM



Band26 / 1.4MHz / Mid CH / QPSK



Band26 / 1.4MHz / Mid CH / 16QAM



Band26 / 1.4MHz / Mid CH / 64QAM



Band26 / 1.4MHz / High CH / QPSK



Band26 / 1.4MHz / High CH / 16QAM



Band26 / 1.4MHz / High CH / 64QAM



Band26 / 3MHz / Low CH / QPSK



Band26 / 3MHz / Low CH / 16QAM



Band26 / 3MHz / Low CH / 64QAM



Band26 / 3MHz / Mid CH / QPSK



Band26 / 3MHz / Mid CH / 16QAM



Band26 / 3MHz / Mid CH / 64QAM



Band26 / 3MHz / High CH / QPSK



Band26 / 3MHz / High CH / 16QAM



Band26 / 3MHz / High CH / 64QAM



Band26 / 5MHz / Low CH / QPSK



Band26 / 5MHz / Low CH / 16QAM

Band26 / 5MHz / Low CH / 64QAM



Band26 / 5MHz / Mid CH / QPSK



Band26 / 5MHz / Mid CH / 16QAM



Band26 / 5MHz / Mid CH / 64QAM



Band26 / 5MHz / High CH / QPSK



Band26 / 5MHz / High CH / 16QAM

Band26 / 5MHz / High CH / 64QAM



Band26 / 10MHz / Mid CH / QPSK



Band26 / 10MHz / Mid CH / 16QAM



Band26 / 10MHz / Mid CH / 64QAM



2.6. Band Edge

2.6.1. Requirement

According to FCC section 90.961, The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

2.6.2. Test Description



The EUTis coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.6.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.

2.6.4. Test Result

Band18 / 5MHz / Low CH / QPSK / 1 RB	Band18 / 5MHz / Low CH / QPSK / FULL RB
	

Band26 / 1.4MHz / Low CH / QPSK / 1 RB



Band26 / 1.4MHz / Low CH / QPSK / FULL RB



Band26 / 3MHz / Low CH / QPSK / 1 RB

Band26 / 3MHz / Low CH / QPSK / FULL RB



Band26 / 5MHz / Low CH / QPSK / 1 RB

Band26 / 5MHz / Low CH / QPSK / FULL RB



Band26 / 10MHz / Low CH / QPSK / 1 RB	Band26 / 10MHz / Low CH / QPSK / FULL RB
	

Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude	Δ Limit
1	1	808.00 MHz	813.96 MHz	110.0 kHz	813.803500 MHz	-44.10 dBm	-31.10 dB
2	2	813.96 MHz	814.00 MHz	110.0 kHz	813.995625 MHz	-27.24 dBm	-7.239 dB
3	3	814.00 MHz	820.00 MHz	1.000 MHz	814.610000 MHz	-22.34 dBm	-7.658 dB

Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude	Δ Limit
1	1	808.00 MHz	813.96 MHz	110.0 kHz	813.783625 MHz	-31.40 dBm	-18.40 dB
2	2	813.96 MHz	814.00 MHz	110.0 kHz	813.998500 MHz	-26.96 dBm	-6.955 dB
3	3	814.00 MHz	820.00 MHz	1.000 MHz	817.490000 MHz	-12.70 dBm	-17.30 dB

2.7. Radiated Spurious Emissions

2.7.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43+10*log(P)dB. This calculated to be -13dBm.

2.7.2. Test Description



(For the test frequency from 30MHz to1GHz)



(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading.
A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.
In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360°to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.7.3. Test procedure

KDB 971168 D01v03 Section 5.8 and ANSI/TIA-603-E-2016.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.

2.7.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$A_{SUBST} = P_{SUBST_TX} - P_{SUBST_RX} - L_{SUBST_CABLES} + G_{SUBST_TX_ANT}$

$A_{TOT} = L_{CABLES} + A_{SUBST}$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

P_{SUBST_TX} is signal generator level,

P_{SUBST_RX} is receiver level,

L_{SUBST_CABLES} is cable losses including TX cable,

$G_{SUBST_TX_ANT}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of A_{TOT}.

Note 1: The power of the EUT transmitting frequency should be ignored.

Note 2: All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note 3: All bandwidth and modulation were considered and evaluated respectively by performing full test for each band, only the worst cases (Max Bandwidth and QPSK mode) were recorded in this test report.

Note 4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

Top Antenna

LTE Band 18, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-53.76	-13.00	Horizontal	N/A
2	864.200	-51.02	-13.00	Horizontal	N/A
3	1288.115	-44.31	-13.00	Horizontal	PASS
4	2197.279	-42.68	-13.00	Horizontal	PASS
5	5117.658	-46.03	-13.00	Horizontal	PASS
6	9152.555	-37.53	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-53.11	-13.00	Vertical	N/A
2	864.200	-61.84	-13.00	Vertical	N/A
3	1240.736	-45.27	-13.00	Vertical	PASS
4	2417.527	-43.87	-13.00	Vertical	PASS
5	5739.689	-44.68	-13.00	Vertical	PASS
6	9097.181	-37.61	-13.00	Vertical	PASS

LTE Band 18, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-55.29	-13.00	Horizontal	N/A
2	864.200	-50.34	-13.00	Horizontal	N/A
3	1244.578	-44.59	-13.00	Horizontal	PASS
4	2264.506	-43.25	-13.00	Horizontal	PASS
5	4462.402	-46.76	-13.00	Horizontal	PASS
6	7915.876	-40.71	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-57.42	-13.00	Vertical	N/A
2	864.200	-59.98	-13.00	Vertical	N/A
3	1325.890	-44.88	-13.00	Vertical	PASS
4	3288.480	-47.04	-13.00	Vertical	PASS
5	5008.756	-46.36	-13.00	Vertical	PASS
6	9728.442	-36.90	-13.00	Vertical	PASS

LTE Band 18, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-51.08	-13.00	Horizontal	N/A
2	865.170	-50.29	-13.00	Horizontal	N/A
3	1306.042	-44.33	-13.00	Horizontal	PASS
4	4274.132	-47.82	-13.00	Horizontal	PASS
5	6459.547	-43.28	-13.00	Horizontal	PASS
6	10420.613	-36.88	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	822.490	-51.80	-13.00	Vertical	N/A
2	865.170	-59.95	-13.00	Vertical	N/A
3	1307.963	-45.09	-13.00	Vertical	PASS
4	3873.595	-49.83	-13.00	Vertical	PASS
5	6404.173	-43.86	-13.00	Vertical	PASS
6	9069.494	-37.73	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	815.700	-23.51	-13.00	Horizontal	N/A
2	863.230	-55.89	-13.00	Horizontal	N/A
3	1284.274	-44.64	-13.00	Horizontal	PASS
4	2395.118	-43.64	-13.00	Horizontal	PASS
5	5763.684	-44.92	-13.00	Horizontal	PASS
6	8342.253	-40.29	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-12.99	-13.00	Vertical	N/A
2	863.230	-67.54	-13.00	Vertical	N/A
3	1306.042	-44.52	-13.00	Vertical	PASS
4	2210.724	-44.17	-13.00	Vertical	PASS
5	5669.549	-46.44	-13.00	Vertical	PASS
6	9110.102	-37.65	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	820.550	-24.23	-13.00	Horizontal	N/A
2	863.230	-54.50	-13.00	Horizontal	N/A
3	1426.411	-45.57	-13.00	Horizontal	PASS
4	2224.810	-43.32	-13.00	Horizontal	PASS
5	5102.891	-46.84	-13.00	Horizontal	PASS
6	10819.304	-36.42	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	818.610	-12.19	-13.00	Vertical	N/A
2	866.140	-66.41	-13.00	Vertical	N/A
3	1304.122	-44.67	-13.00	Vertical	PASS
4	2389.996	-43.90	-13.00	Vertical	PASS
5	4835.252	-46.95	-13.00	Vertical	PASS
6	8997.509	-38.02	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	820.550	-23.88	-13.00	Horizontal	N/A
2	864.200	-53.94	-13.00	Horizontal	N/A
3	1288.115	-45.39	-13.00	Horizontal	PASS
4	2344.538	-43.36	-13.00	Horizontal	PASS
5	5735.997	-45.18	-13.00	Horizontal	PASS
6	8938.443	-37.61	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-14.62	-13.00	Vertical	N/A
2	867.110	-65.29	-13.00	Vertical	N/A
3	1304.122	-45.30	-13.00	Vertical	PASS
4	2240.816	-43.55	-13.00	Vertical	PASS
5	4602.682	-46.95	-13.00	Vertical	PASS
6	9479.260	-37.71	-13.00	Vertical	PASS

Bottom Antenna

LTE Band 18, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-53.65	-13.00	Horizontal	N/A
2	864.200	-51.31	-13.00	Horizontal	N/A
3	1351.501	-44.06	-13.00	Horizontal	PASS
4	2917.476	-51.05	-13.00	Horizontal	PASS
5	4593.453	-48.00	-13.00	Horizontal	PASS
6	9726.596	-37.64	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-57.12	-13.00	Vertical	N/A
2	864.200	-60.03	-13.00	Vertical	N/A
3	1297.719	-44.91	-13.00	Vertical	PASS
4	2303.561	-43.75	-13.00	Vertical	PASS
5	3803.455	-47.18	-13.00	Vertical	PASS
6	7194.172	-40.36	-13.00	Vertical	PASS

LTE Band 18, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-54.38	-13.00	Horizontal	N/A
2	863.230	-50.04	-13.00	Horizontal	N/A
3	1348.299	-44.41	-13.00	Horizontal	PASS
4	2341.977	-42.29	-13.00	Horizontal	PASS
5	5038.289	-46.84	-13.00	Horizontal	PASS
6	9350.055	-38.06	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-59.79	-13.00	Vertical	N/A
2	864.200	-60.09	-13.00	Vertical	N/A
3	1306.683	-44.77	-13.00	Vertical	PASS
4	2416.887	-43.61	-13.00	Vertical	PASS
5	5328.078	-44.46	-13.00	Vertical	PASS
6	7912.184	-39.10	-13.00	Vertical	PASS

LTE Band 18, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	823.460	-52.22	-13.00	Horizontal	N/A
2	867.110	-50.23	-13.00	Horizontal	N/A
3	1279.152	-44.33	-13.00	Horizontal	PASS
4	2251.701	-43.33	-13.00	Horizontal	PASS
5	4074.786	-48.43	-13.00	Horizontal	PASS
6	7101.882	-40.60	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	823.460	-51.87	-13.00	Vertical	N/A
2	866.140	-61.84	-13.00	Vertical	N/A
3	1300.280	-44.88	-13.00	Vertical	PASS
4	2323.409	-43.67	-13.00	Vertical	PASS
5	4443.944	-48.35	-13.00	Vertical	PASS
6	8964.284	-38.13	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Low Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-53.59	-13.00	Horizontal	N/A
2	863.230	-48.81	-13.00	Horizontal	N/A
3	1391.196	-50.47	-13.00	Horizontal	PASS
4	2194.078	-47.25	-13.00	Horizontal	PASS
5	4455.019	-48.58	-13.00	Horizontal	PASS
6	9073.186	-39.52	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-60.44	-13.00	Vertical	N/A
2	863.230	-59.37	-13.00	Vertical	N/A
3	1287.475	-45.64	-13.00	Vertical	PASS
4	2217.767	-44.21	-13.00	Vertical	PASS
5	3157.429	-51.90	-13.00	Vertical	PASS
6	6597.981	-42.79	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, Mid Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-59.86	-13.00	Horizontal	N/A
2	866.140	-48.80	-13.00	Horizontal	N/A
3	1329.092	-49.48	-13.00	Horizontal	PASS
4	2220.328	-47.53	-13.00	Horizontal	PASS
5	5154.574	-47.05	-13.00	Horizontal	PASS
6	9721.058	-38.57	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-62.63	-13.00	Vertical	N/A
2	863.230	-58.44	-13.00	Vertical	N/A
3	1295.798	-45.82	-13.00	Vertical	PASS
4	2208.163	-44.47	-13.00	Vertical	PASS
5	5073.359	-46.99	-13.00	Vertical	PASS
6	7159.102	-40.06	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	822.490	-54.90	-13.00	Horizontal	N/A
2	867.110	-49.44	-13.00	Horizontal	N/A
3	1336.775	-49.01	-13.00	Horizontal	PASS
4	2391.277	-48.15	-13.00	Horizontal	PASS
5	3827.450	-48.98	-13.00	Horizontal	PASS
6	8967.976	-39.49	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	822.490	-57.90	-13.00	Vertical	N/A
2	865.170	-59.20	-13.00	Vertical	N/A
3	1277.871	-44.71	-13.00	Vertical	PASS
4	2201.761	-43.23	-13.00	Vertical	PASS
5	3670.558	-49.47	-13.00	Vertical	PASS
6	5870.740	-45.66	-13.00	Vertical	PASS

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	±2.22 dB
Bandwidth	±5%
Conducted Spurious Emission	±2.77 dB
Band Edge	±2.77 dB
Equivalent Isotropic Radiated Power	±2.22 dB
Radiated Spurious Emissions	±6 dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.

4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Power Splitter	NW521	1506A	Weinschel	2020.04.15	2021.04.14
Attenuator 1	(N/A.)	10dB	Resnet	N/A	N/A
Attenuator 2	(N/A.)	3dB	Resnet	N/A	N/A
EXA Signal Analzyer	MY51511149	N9020A	Agilent	2020.07.27	2021.07.26
USB Power Sensor	MY54210011	U2021XA	Agilent	2020.04.01	2021.03.31
System Simulator	6200995016	MT8820C	Anritsu	2020.10.28	2021.10.27
System Simulator	6261830572	MT8821C	Anritsu	2020.02.25	2021.02.24
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Temperature Chamber	HA06-21216 2-3-3-II	HUT705P	CHONGQING HANBA EXPERIMENTAL EQUIPMENT CO.,LTD	2020.03.25	2021.03.24
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Radiated Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due
System Simulator	152038	CMW500	R&S	2020.11.19	2021.11.18
System Simulator	6200995016	MT8820C	Anritsu	2020.10.28	2021.10.27
Receiver	MY54130016	N9038A	Agilent	2020.07.21	2021.07.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2019.07.26	2022.07.25
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2022.07.25
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L3203	Tonscend	2020.07.21	2021.07.20
18-26.5GHz pre-Amplifier	46732	S10M100L3802	Tonscend	2020.07.21	2021.07.20
26-40GHz pre-Amplifier	56774	S40M400L4002	Tonscend	2020.07.21	2021.07.20
Notch Filter	N/A	WRCGV -LTE 26	Wainwright	2020.07.21	2021.07.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2019.07.13	2022.07.12

END OF REPORT