

RF Exposure Evaluation Report

Product : Yanshee Robot
Trade mark : UBTCH
Model/Type reference : ERHA101
Serial Number : N/A
Report Number : EED32L00193804
FCC ID : 2AHJX-YANSHEE-1
Date of Issue : Aug. 26, 2019
: IEEE C95.1 2005
: KDB 447498 D03
Test Standards : 47 C.F.R. Part 1, Subpart I, Section 1.1310
: 47 C.F.R. Part 2, Subpart J, Section 2.1091
Test result : PASS

Prepared for:

UBTECH ROBOTICS CORP LTD

**16th and 22nd Floor, Block C1, Nanshan I Park, No.1001
Xueyuan Road, Nanshan District, Shenzhen City, P.R.CHINA**

Prepared by:

**Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China**

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested By:

Jay Zheng

Jay Zheng

Compiled by:

Alex Wu

Alex Wu

Reviewed by:

Ware Xin

Ware Xin

Approved by:

Kevin Yang

Kevin Yang

Date:

Aug. 26, 2019

Check No.: 3096399624



2 Version

Version No.	Date	Description
00	2019-08-26	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	5
4.4 TEST LOCATION.....	6
4.5 DEVIATION FROM STANDARDS.....	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION.....	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	8
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	9

4 General Information

4.1 Client Information

Applicant:	UBTECH ROBOTICS CORP LTD
Address of Applicant:	16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen City, P.R.CHINA
Manufacturer:	UBTECH ROBOTICS CORP LTD
Address of Manufacturer:	16th and 22nd Floor, Block C1, Nanshan I Park, No.1001 Xueyuan Road, Nanshan District, Shenzhen City, P.R.CHINA
Factory:	UBTECH ROBOTICS CORP LTD BAOAN BRANCH
Address of Factory:	1-2 Floor, B Block, Huilongda Industry Park, Shilongzai, Shiyan Street, Baoan District, Shenzhen City, P.R.CHINA

4.2 General Description of EUT

Product Name:	Yanshee Robot
Model No.(EUT):	ERHA101
Trade Mark:	UBTCH
EUT Supports Radios application	4.1 BT Dual mode, WiFi 802.11b/g/n(20MHz)

4.3 Product Specification subjective to this standard

Frequency Range:	BT: 2402MHz to 2480MHz WIFI: 2412MHz to 2462MHz		
Modulation Type:	GFSK, 8DPSK, π /4DQPSK, OFDM, DSSS		
Number of Channels:	BT 3.0: 79 Channels BLE 4.1: 40 Channels WIFI: 11 Channels		
Test Power Grade:	802.11b:18 802.11g:12/11/11 802.11n:11/11/10		
Test Software of EUT:	War exe (manufacturer declare)		
Antenna Type:	Chip antenna		
Antenna Gain:	2.4GHz	Antenna Gain :	1.50 dBi (Numeric gain: 1.41)
Power Supply:	AC adapter	MODEL: HKA03609640-8A INPUT: 100-240V 1.5A, 50/60Hz OUTPUT: 9.6V---4.0A	
	Battery:	Model: Yanshee 1.1-2S1P Capacity: 7.4V, 3000mAh/ 22.2Wh	
Conducted Peak Output Power:	BT		
	GFSK:	6.00 dBm	(3.981 mW)
	π /4DQPSK:	3.00 dBm	(1.995 mW)
	8DPSK:	3.00 dBm	(1.995 mW)
	BLE:	6.00 dBm	(3.981 mW)
	Wi-Fi		
	IEEE 802.11b Mode:	18.50 dBm	(70.795 mW)
	IEEE 802.11g Mode:	18.00 dBm	(63.096 mW)
	IEEE 802.11n HT 20 Mode:	17.00 dBm	(50.119 mW)
	The Conducted Peak Output Power data refer to the report EED32L00193801, EED32L00193803		
Sample Received Date:	Jul. 22, 2019		
Sample tested Date:	Jul. 22, 2019 to Aug. 23, 2019		
The tested sample(s) and the sample information are provided by the client.			

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{377 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
78	2480	3.981	1.41	20	0.0011	1

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
6	2437	70.795	1.41	20	0.0199	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
1	2412	63.096	1.41	20	0.0177	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
6	2437	50.119	1.41	20	0.0141	1

Remark: WLAN and Bluetooth technology can not transmit at same time.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32L00193801 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.