

# INTERTEK TESTING SERVICES

---

## RF Exposure

The Equipment Under Test (EUT) is a Security System Fob operating at 433.9MHz. The EUT is powered by DC 3V by battery. For more detailed features description, please refer to the user's manual.

Modulation Type: FSK

Antenna Type: Integral antenna.

Antenna Gain: 0 dBi Max

The nominal conducted output power specified: -25dBm (+/-3dB).

The nominal radiated output power (e.i.r.p) specified: -25dBm (+/- 3dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 72.4dBμV/m at 3m in the frequency 433.9MHz.

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -22.83dBm  
which is within the production variation.

The maximum conducted output power specified is -22dBm = 0.0063mW

The source- based time-averaging conducted output power

= 0.0063 \* Duty factor mW (where Duty Factor  $\leq 1$ )

= 0.0063 mW

The SAR Exclusion Threshold Level:

=  $3.0 * (\text{min. test separation distance, mm}) / \text{sqrt}(\text{freq. in GHz})$

=  $3.0 * 5 / \text{sqrt}(0.4339)$  mW

= 22.77 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.