

# FCC ID: 2AHKA-VSS014M7

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm

and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

| Transmit Frequency (GHz) | Mode           | EIRP (dBm)  | tune up maximum power | Result calculation | 1-g SAR |
|--------------------------|----------------|-------------|-----------------------|--------------------|---------|
| 2.402                    | GFSK           | -0.79       | 0                     | 0.31               | 3.0     |
| 2.441                    | GFSK           | 3.64        | 5                     | 0.99               | 3.0     |
| 2.480                    | GFSK           | <b>5.51</b> | 6                     | 1.25               | 3.0     |
| 2.402                    | $\pi/4$ -DQPSK | -3.0        | -2                    | 0.20               | 3.0     |
| 2.441                    | $\pi/4$ -DQPSK | 1.65        | 3                     | 0.62               | 3.0     |
| 2.480                    | $\pi/4$ -DQPSK | 3.78        | 5                     | 1.00               | 3.0     |
| 2.402                    | 8DPSK          | -2.35       | -2                    | 0.20               | 3.0     |
| 2.441                    | 8DPSK          | 2.05        | 3                     | 0.62               | 3.0     |
| 2.480                    | 8DPSK          | 4.18        | 5                     | 1.00               | 3.0     |

Conclusion:

For the max result :  $1.25 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2016-08-18

**NAME AND TITLE (Please print or type):** David Lee/Manager

**COMPANY (Please print or type):** EMTEK(Shenzhen) Co.,Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,Guangdong,China