




FCC RADIO TEST REPORT

FCC ID : 2AHKM-HIVE2200
Equipment : 2x2 DBCC WiFi Extender
Brand Name : hitron
Model Name : HIXE12AWR
Applicant : Hitron Technologies Inc.
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,
Hsinchu 30078, Taiwan
Manufacturer : Hitron Technologies Inc.
No. 1-8, Li-Hsin 1st Rd. Hsinchu Science Park,
Hsinchu 30078, Taiwan
Standard : 47 CFR FCC Part 15.247

The product was received on Jan. 04, 2019, and testing was started from Jan. 08, 2019 and completed on Jan. 23, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Information.....	5
1.2 Testing Applied Standards	8
1.3 Testing Location Information	8
1.4 Measurement Uncertainty	8
2 Test Configuration of EUT	9
2.1 Test Channel Mode	9
2.2 The Worst Case Measurement Configuration.....	9
2.3 EUT Operation during Test	9
2.4 Accessories	10
2.5 Support Equipment.....	10
2.6 Test Setup Diagram	11
3 Transmitter Test Result	13
3.1 AC Power-line Conducted Emissions	13
3.2 Maximum Conducted Output Power	15
3.3 Emissions in Restricted Frequency Bands.....	16
4 Test Equipment and Calibration Data	19
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of Maximum Conducted Output Power	
Appendix C. Test Results of Emissions in Restricted Frequency Bands	
Appendix D. Test Photos	
Photographs of EUT v01	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB Ver1.0



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(b)	Maximum Conducted Output Power	PASS	-
3.3	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Cliff Chang

Report Producer: Wendy Pan

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Version	Ch. Frequency (MHz)	Channel Number
2400-2483.5	BR / EDR	2402-2480	0-78 [79]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-BR(1Mbps)	1	1TX
2.4-2.4835GHz	BT-EDR(2Mbps)	1	1TX
2.4-2.4835GHz	BT-EDR(3Mbps)	1	1TX

Note:

- ♦ Bluetooth BR uses a GFSK (1Mbps).
- ♦ Bluetooth EDR uses a combination of $\pi/4$ -DQPSK (2Mbps) and 8DPSK (3Mbps).
- ♦ Bluetooth BR/EDR uses as a system using FHSS modulation.
- ♦ BWch is the nominal channel bandwidth.
- ♦ Nss-Min is the minimum number of spatial streams.
- ♦ Nant is the number of outputs. e.g., 2(2, 3) means have 2 outputs for port 2 and port 3. 2 means have 2 outputs for port 1 and port 2.

**1.1.2 Antenna Information**

Ant.	Port	Brand	Model Name	P/N	Antenna Type	Connector	Gain (dBi)
1	1	Ethertronics	XE1v2	-	PCB Antenna	I-PEX	Note
2	2	Ethertronics	XE1v2	-	PCB Antenna	I-PEX	
3	1	PSA	-	RFECA3216060A1T	CERAMIC Antenna	N/A	

Note 1:

Ant.	Port	Gain (dBi)					
		WLAN 2.4G	WLAN 5G Band 1	WLAN 5G Band 2	WLAN 5G Band 3	WLAN 5G Band 4	BT
1	1	4.4	4.8	4.8	5.4	5.5	-
2	2	3.1	3.8	4.0	4.9	3.8	-
3	1	-		-	-		2.09

Note 2: The EUT has three antennas.

Note 3: The above information was declared by manufacturer.

<For 2.4GHz Band>**For IEEE 802.11b/g/n mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For 5GHz Band>**For IEEE 802.11a/n/ac mode (2TX/2RX)**

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For Bluetooth>**For BT function (1TX/1RX)**

Only Port 1 can be used as transmitting/receiving antenna.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-BR(1Mbps)	0.795	0.996	2.928m	1k
BT-EDR(2Mbps)	0.758	1.203	2.957m	1k
BT-EDR(3Mbps)	0.754	1.226	2.957m	1k

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	Internal power supply
Test Software Version	Telnet(v.25.1)

1.1.5 Table for EUT support type

Function	support type
AP Router	Master
Extender	Master + Slave
Mesh	Master + Slave

1.1.6 Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR862827AC

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1.Updating the hardware version to "SR3" from "SR2". The detail differences as below. a) Updating the design for antenna. b) Change LED to DIP lamp from SMD chip c) Removing the absorber of the device. d) Adding U4 and U4 related components on the mother board. e) Change the opening size for pin header on the main frame.	1. AC Power-line Conducted Emissions 2. Maximum Conducted Output Power 3. Emissions in Restricted Frequency Bands For above 1GHz after evaluating test, the worst case is found at BT-EDR(3Mbps) CH0 (2402Hz) and retest this channel only.
2.Adding beamforming for Band 1 ~ Band 4. 3.Adding 5GHz band 2 and band 3 (5250~5350 MHz, 5470~5725 MHz) for this device.	There's no influence on this test report.



1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ FCC Public Notice DA 00-705

1.3 Testing Location Information

Testing Location				
☐	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)	TEL : 886-3-327-3456	FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.	TEL : 886-3-656-9065	FAX : 886-3-656-9085

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-CB	Owen Hsu	25°C / 65%	Jan. 15, 2019 ~ Jan. 23, 2019
Radiated (Above 1GHz)	03CH01-CB	RJ Huang	22°C / 54%	Jan. 08, 2019 ~ Jan. 23, 2019
Radiated (Below 1GHz)	03CH01-CB	RJ Huang	22°C / 54%	Jan. 22, 2019
AC Conduction	CO02-CB	Wei Li	25°C / 65%	Jan. 14, 2019

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	2.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.7 dB	Confidence levels of 95%
Output Power Measurement	1.33 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Channel Mode

Mode	PowerSetting
BT-EDR(3Mbps)	-
2402MHz	8

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	1 CTX-BT

The Worst Case Mode for Following Conformance Tests	
Tests Item	Maximum Conducted Output Power
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	The EUT was performed at Y axis and Z axis position for Emissions in Restricted Frequency Bands above 1GHz test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.
1	CTX - EUT in Y axis-BT
Operating Mode > 1GHz	The EUT was performed at Y axis and Z axis position for Emissions in Restricted Frequency Bands test, and the worst case was found at Y axis. So the measurement will follow this same test configuration.
1	EUT in Y axis

2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



2.4 Accessories

N/A

2.5 Support Equipment


For Test Site No: CO02-CB


N/A

For Test Site No: 03CH01-CB and TH01-CB

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A

2.6 Test Setup Diagram



Test Setup Diagram - Radiated Test


Item	Connection	Shielded	Length
1	Power cable	No	1.8m
2	RJ-45 cable	No	10m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 Maximum Conducted Output Power

3.2.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
▪ 902-928 MHz Band:	
	▪ $N \geq 50$; Power 30dBm; EIRP 36dBm
	▪ $50 > N \geq 25$; Power 24dBm; EIRP 30dBm
▪ 2400-2483.5 MHz Band:	
	▪ $N \geq 75$; Power 30dBm; EIRP 36dBm
	▪ $75 > N \geq 15$; Power 21dBm; EIRP 27dBm
▪ 5725-5850 MHz Band:	
	▪ $N \geq 75$; Power 30dBm; EIRP 36dBm
N: Number of Hopping Frequencies	

3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2013, clause 7.8.5 for output power measurement.

3.2.4 Test Setup

Maximum Conducted Output Power (Peak Power Meter)
 The diagram illustrates the test setup for measuring Maximum Conducted Output Power. A Power Meter, represented by a blue and white electronic device with a probe, is connected via a black cable to a pink rectangular block labeled 'EUT' (Equipment Under Test). The Power Meter is also connected to a computer monitor and keyboard, indicating data recording or analysis.

3.2.5 Test Result of Maximum Conducted Output Power

Refer as Appendix B



3.3 Emissions in Restricted Frequency Bands

3.3.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
▪ The average emission levels shall be measured in [hopping duty factor].	
▪ Refer as ANSI C63.10; clause 6.9.2.2 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
▪ For the transmitter unwanted emissions shall be measured using following options below:	
	▪ Refer as ANSI C63.10, clause 4.1.4.2.1 QP value.
	▪ Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak.
	▪ Refer as ANSI C63.10, clause 4.1.4.2.4 average value of hopping pulsed emissions.

3.3.4 Test Setup





3.3.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10 harmonic or 40 GHz, whichever is appropriate.

3.3.6 Transmitter Radiated Unwanted Emissions

Refer as Appendix C



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 21, 2018	Nov. 20, 2019	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 05, 2018	Nov. 04, 2019	Conduction (CO02-CB)
EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8.4GHz	Jan. 17, 2018	Jan. 16, 2019	Conduction (CO02-CB)
COND Cable	Woken	Cable	2	0.15MHz ~ 30MHz	Nov. 06, 2018	Nov. 05, 2019	Conduction (CO02-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	N.C.R.	Conduction (CO02-CB)
BILOG ANTENNA with 6dB Attenuator	TESEQ & EMCI	CBL6112D & N-6-06	37880 & AT-N0609	20MHz ~ 2GHz	Aug. 27, 2018	Aug. 26, 2019	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2018	Mar. 15, 2019	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz ~ 18GHz	Nov. 13, 2018	Nov. 12, 2019	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Jun. 28, 2018	Jun. 27, 2019	Radiation (03CH01-CB)
Pre-Amplifier	EMCI	EMC330N	980332	20MHz ~ 3GHz	May 02, 2018	May 01, 2019	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 09, 2018	Jan. 08, 2019	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Jan. 08, 2019	Jan. 07, 2020	Radiation (03CH01-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 04, 2018	Jul. 03, 2019	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100080	9kHz~40GHz	Oct. 03, 2018	Oct. 02, 2019	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS	100359	9kHz ~ 2.75GHz	Jul. 03, 2018	Jul. 02, 2019	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-16+17	N/A	30 MHz ~ 1GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16	N/A	1 GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-16+17	N/A	1 GHz ~ 18GHz	Oct. 08, 2018	Oct. 07, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G#1	N/A	18GHz ~ 40GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-40G#2	N/A	18GHz ~ 40GHz	Jul. 27, 2018	Jul. 26, 2019	Radiation (03CH01-CB)




Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Spectrum analyzer	R&S	FSV40	101027	9kHz~40GHz	Jun. 22, 2018	Jun. 21, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz – 26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz –26.5 GHz	Oct. 08, 2018	Oct. 07, 2019	Conducted (TH01-CB)
Power Sensor	Agilent	U2021XA	MY53410001	50MHz~18GHz	Nov. 05, 2018	Nov. 04, 2019	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

N.C.R. means Non-Calibration required.


Test Mode	Mode 1	Frequency Range	0.15 MHz to 30 MHz
-----------	--------	-----------------	--------------------

Line



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1508	44.77	-11.19	55.96	34.60	10.15	0.02	Average	LINE
2	0.1508	58.00	-7.96	65.96	47.83	10.15	0.02	QP	LINE
3	0.1540	43.41	-12.37	55.78	33.24	10.15	0.02	Average	LINE
4	0.1540	57.37	-8.41	65.78	47.20	10.15	0.02	QP	LINE
5	0.1685	41.50	-13.53	55.03	31.33	10.15	0.02	Average	LINE
6	0.1685	55.48	-9.55	65.03	45.31	10.15	0.02	QP	LINE
7	0.1894	39.27	-14.79	54.06	29.10	10.15	0.02	Average	LINE
8	0.1894	52.63	-11.43	64.06	42.46	10.15	0.02	QP	LINE
9	0.2128	36.65	-16.45	53.10	26.48	10.15	0.02	Average	LINE
10	0.2128	49.70	-13.40	63.10	39.53	10.15	0.02	QP	LINE
11	0.2391	31.21	-20.92	52.13	21.04	10.15	0.02	Average	LINE
12	0.2391	47.38	-14.75	62.13	37.21	10.15	0.02	QP	LINE
13	0.2658	29.33	-21.92	51.25	19.16	10.15	0.02	Average	LINE
14	0.2658	45.48	-15.77	61.25	35.31	10.15	0.02	QP	LINE
15	0.3003	28.01	-22.23	50.24	17.83	10.16	0.02	Average	LINE
16	0.3003	43.44	-16.80	60.24	33.26	10.16	0.02	QP	LINE
17	0.3374	26.27	-23.00	49.27	16.09	10.16	0.02	Average	LINE
18	0.3374	41.34	-17.93	59.27	31.16	10.16	0.02	QP	LINE
19	0.3914	22.93	-25.10	48.03	12.75	10.16	0.02	Average	LINE
20	0.3914	38.24	-19.79	58.03	28.06	10.16	0.02	QP	LINE

Neutral



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.1516	45.46	-10.45	55.91	35.31	10.13	0.02	Average	NEUTRAL
2	0.1516	59.22	-6.69	65.91	49.07	10.13	0.02	QP	NEUTRAL
3	0.1685	42.99	-12.04	55.03	32.84	10.13	0.02	Average	NEUTRAL
4	0.1685	56.75	-8.28	65.03	46.60	10.13	0.02	QP	NEUTRAL
5	0.1955	40.66	-13.14	53.80	30.51	10.13	0.02	Average	NEUTRAL
6	0.1955	52.80	-11.00	63.80	42.65	10.13	0.02	QP	NEUTRAL
7	0.2106	38.13	-15.05	53.18	27.98	10.13	0.02	Average	NEUTRAL
8	0.2106	51.05	-12.13	63.18	40.90	10.13	0.02	QP	NEUTRAL
9	0.2535	32.78	-18.86	51.64	22.63	10.13	0.02	Average	NEUTRAL
10	0.2535	47.21	-14.43	61.64	37.06	10.13	0.02	QP	NEUTRAL
11	0.3019	30.43	-19.76	50.19	20.27	10.14	0.02	Average	NEUTRAL
12	0.3019	44.26	-15.93	60.19	34.10	10.14	0.02	QP	NEUTRAL
13	0.3502	28.35	-20.61	48.96	18.19	10.14	0.02	Average	NEUTRAL
14	0.3502	41.56	-17.40	58.96	31.40	10.14	0.02	QP	NEUTRAL
15	0.3914	25.83	-22.20	48.03	15.67	10.14	0.02	Average	NEUTRAL
16	0.3914	39.48	-18.55	58.03	29.32	10.14	0.02	QP	NEUTRAL
17	0.4351	33.47	-13.68	47.15	23.31	10.14	0.02	Average	NEUTRAL
18	0.4351	38.89	-18.26	57.15	28.73	10.14	0.02	QP	NEUTRAL
19	0.4941	37.63	-8.47	46.10	27.47	10.14	0.02	Average	NEUTRAL
20	0.4941	40.53	-15.57	56.10	30.37	10.14	0.02	QP	NEUTRAL

**Summary**

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-EDR(3Mbps)	-6.57	0.00022

Result

Mode	Result	Gain	Power	Power Limit
		(dBi)	(dBm)	(dBm)
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.09	-6.57	21.00

Summary


Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-EDR(3Mbps)	-4.73	0.00034

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.09	-4.73	21.00


Test Mode	Mode 1	Frequency Range	30 MHz to 1,000 MHz
-----------	--------	-----------------	---------------------

Vertical 30 MHz to 1,000 MHz



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	35.82	28.64	40.00	-11.36	39.80	0.58	20.68	32.42	150	114 QP	VERTICAL
2	42.61	28.30	40.00	-11.70	43.10	0.64	16.98	32.42	100	16 QP	VERTICAL
3	50.37	32.12	40.00	-7.88	50.31	0.73	13.50	32.42	100	41 QP	VERTICAL
4	133.79	26.64	43.50	-16.86	40.06	1.19	17.73	32.34	100	131 Peak	VERTICAL
5	562.53	36.38	46.00	-9.62	41.83	2.51	24.41	32.37	100	213 Peak	VERTICAL
6	729.37	35.46	46.00	-10.54	39.31	2.89	25.53	32.27	100	47 Peak	VERTICAL

Horizontal 30 MHz to 1,000 MHz



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	32.91	31.67	40.00	-8.33	41.16	0.54	22.40	32.43	100	28 Peak	HORIZONTAL
2	51.34	26.66	40.00	-13.34	45.03	0.74	13.31	32.42	300	91 Peak	HORIZONTAL
3	134.76	25.45	43.50	-18.05	38.93	1.20	17.66	32.34	200	81 Peak	HORIZONTAL
4	171.62	25.54	43.50	-17.96	40.84	1.35	15.66	32.31	125	219 Peak	HORIZONTAL
5	562.53	33.79	46.00	-12.21	39.24	2.51	24.41	32.37	150	99 Peak	HORIZONTAL
6	649.83	33.07	46.00	-12.93	37.55	2.73	25.16	32.37	125	357 Peak	HORIZONTAL



RSE TX above 1GHz Result

Appendix C.2


Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-EDR(3Mbps)	Pass	AV	2.3828G	45.44	54.00	-8.56	33.08	3	Horizontal	246	1.12	-

BT-EDR(3Mbps)

2402MHz_TX

14/01/2019




EUT Y_1TX
Setting 8
04-B-1
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	2.3802G	56.75	74.00	-17.25	33.07	3	Vertical	62	1.25	-						
AV	2.3848G	45.41	54.00	-8.59	33.08	3	Vertical	62	1.25	-						
PK	2.4018G	84.75	Inf	-Inf	33.09	3	Vertical	62	1.25	-						
AV	2.4016G	80.37	Inf	-Inf	33.09	3	Vertical	62	1.25	-						

BT-EDR(3Mbps)

2402MHz_TX

14/01/2019




EUT Y_1TX
Setting 8
04-B-1
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	2.365G	57.01	74.00	-16.99	33.06	3	Horizontal	246	1.12	-
AV	2.3828G	45.44	54.00	-8.56	33.08	3	Horizontal	246	1.12	-
PK	2.402G	80.18	Inf	-Inf	33.09	3	Horizontal	246	1.12	-
AV	2.4016G	76.68	Inf	-Inf	33.09	3	Horizontal	246	1.12	-

BT-EDR(3Mbps)

14/01/2019

2402MHz_TX




EUT Y_1TX
Setting 8
04-B-1
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments						
PK	4.80291G	48.51	74.00	-25.49	7.06	3	Vertical	201	2.44	-						
AV	4.80358G	36.68	54.00	-17.32	7.06	3	Vertical	201	2.44	-						

BT-EDR(3Mbps)

14/01/2019

2402MHz_TX



EUT Y_1TX
Setting 8
04-B-1
FSP(100142)

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	4.80308G	47.90	74.00	-26.10	7.06	3	Horizontal	356	1.10	-
AV	4.80361G	35.51	54.00	-18.49	7.06	3	Horizontal	356	1.10	-