DEKRA Certification, Inc.
405 Glenn Dr. Suite 12,
Sterling, VA 20164
United States of America

DEKRA

FCC LISTED, REGISTRATION NUMBER: 2764.01

ISED LISTED REGISTRATION NUMBER: 23595-1

Test report No:

4606ERM.004A1

Partial Test report

USA FCC Part 15.247, 15.407 15.209, 15.207
CANADA RSS-247, RSS-Gen

(*) Identification of item tested	Infotainment Head Unit Android Based
(*) Trademark	HARMAN
(*) Model and /or type reference tested	TAS700 BRA
Other identification of the product	Model: C-Plat FCC ID: 2AHPN-BE2874
(*) Features	AM/FM receiver, Bluetooth EDR, Wi-Fi 2.4GHz & 5GHz
Manufacturer	Harman da Amazonia. Av. Cupiúba, 401 – Distrito Industrial Manaus, Amazonas, 69075-060, Brasil
Test method requested, standard	USA FCC Part 15.247 (06-1-20): Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz USA FCC Part 15.407 (03-28-24) : Unlicensed National Information Infrastructure Devices. General technical requirements. USA FCC Part 15.209 (06-28-21): Radiated emission limits; general requirements. CANADA RSS-247 Issue 3 (August 2023). CANADA RSS-Gen Issue 5 amendment 1 (March 2019). 558074 D01 15.247 Meas Guidance v05r02. Guidance for Compliance Measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under section §15.247 of the FCC Rules ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	See Appendix A
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager Digitally signed by Domingo Galvez DN: cn=Domingo Galvez, o=Dekra Certification Inc., ou=Regulatory Lab Manager, email=domingo.galvez@dekra.com, c=US
Date of issue	07-25-2024
Report template No	FDT08_23 (*) “Data provided by the client”

Index

Competences and guarantees 3
General conditions 3
Uncertainty 3
Data provided by the client 4
Usage of samples 4
Test sample description 5
Identification of the client 5
Testing period and place 7
Document history 7
Environmental conditions 7
Remarks and comments 8
Testing verdicts 8
Summary 8
List of equipment used during the test 10
Appendix A: Test results (Multi-transmitter) 11

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Certification internal document PODT000.

Test case	Frequency (MHz)	U (k=2)	Units
Radiated Spurious Emission	30-180	4.27	dB
	180-1000	3.14	dB
	1000-18000	3.30	dB
	18000-40000	3.49	dB

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of a Receiver Assy, Radio & Display.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples used for test have been selected by: The client.

Sample S/01 is composed of the following elements:

Id	Control Number	Description	Model	Serial Nº	Date of Reception	Application
S/01	4415/09	Infotainment Unit - BRA C (Radiated)	TAS700	T2855HR046900002	02/23/2024	Element Under Test

Sample S/01 is composed of the following accessories:

Id	Control Number	Description	Model	Serial Nº	Date of Reception	Application
S/01	4415/26	USB C-Type Hub Harness	-	-	04/04/2024	Accessory
S/01	4415/30	USB Cables (Type A)	-	-	04/04/2024	Accessory
S/01	4415/31	HU Power Harness	-	-	04/04/2024	Accessory
S/01	4415/34	AM/FM and GPS Antennas	-	-	04/04/2024	Accessory

Sample S/01 was used for following test(s): All Radiated tests indicated in appendix A.

Test sample description

Ports…… :	Port name and description	Cable			
		Specified max length [m]	Attached during test	Shielded	Coupled to patient (3)
	RF_Port 1 = BT/WLAN-5GHz (Module Pin C01)	.....	[X]	[X]	[ ]
	RF_Port 2 = WLAN 2,4GHz (Module Pin K02)	.....	[X]	[X]	[ ]
	No Data Provided	.....	[ ]	[ ]	[ ]
	No Data Provided	.....	[ ]	[ ]	[ ]
	No Data Provided	.....	[ ]	[ ]	[ ]
	No Data Provided	.....	[ ]	[ ]	[ ]
Supplementary information to the ports…… :	No Data Provided				

Rated power supply ..... :	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	[ ]	AC:	[ ]	[ ]	[ ]	[ ]	[ ]
	[ ]	AC:	[ ]	[ ]	[ ]	[ ]	[ ]
	[X]	DC: 12 V nominal Car battery, 8V to 16V max					
	[ ]	DC:					

Rated Power ..... :	No Data Provided	
Clock frequencies ..... :	No Data Provided	
Other parameters..... :	No Data Provided	
Software version ..... :	R5.2	
Hardware version..... :	C1	
Dimensions in cm (W x H x D)..... :	No Data Provided	
Mounting position..... :	[ ]	Tabletop equipment
	[ ]	Wall/Ceiling mounted equipment

	[ ]	Floor standing equipment		
	[ ]	Hand-held equipment		
	[X]	Other:		
Modules/parts ..... :	Module/parts of test item		Type	Manufacturer
	No Data Provided		.....	.....
Accessories (not part of the test item) ..... :	Description		Type	Manufacturer
	Bench Setup + antenna			
	Cable Harness			
Documents as provided by the applicant ..... :	Description		File name	Issue date
	Declaration Equipment Data		FDT30_18 Declaration Equipment Data	04/30/2024

Copy of marking plate:

Identification of the client

Harman International Industries, Inc.
3001 Cabot Drive,
Novi, MI 48377
USA

Testing period and place

Test Location	DEKRA Certification Inc.
Date (start)	04-30-2024
Date (finish)	05-01-2024

Document history

Report number	Date	Description
4606ERM.004	05-23-2024	First release
4606ERM.004A1	07-25-2024	Second release. On page 13, antenna type information was updated. This modified report cancels and replaces the report 4606ERM.004.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semi anechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

1. The tests have been performed by the technical personnel: Wang Yuqi and Koji Nishimoto.

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

FCC PART 15 PARAGRAPH / RSS-247 (Bluetooth BR/EDR)					
Report Section	**15.247 Spec Clause**	**RSS Spec Clause**	**Test Description**	**Verdict**	**Remark**
-	§ 2.1049 & § 15.247 (a) (1)	RSS-247 5.1 (b)	20dB Emission Bandwidth, Occupied Bandwidth & Carrier Frequency Separation	N/M	Refer 1
-	§ 15.247 (a) (1) (iii)	RSS-247 5.1 (d)	Number of hopping channels	N/M	Refer 1
-	§ 15.247 (a) (1) (iii)	RSS-247 5.1 (d)	Time of Occupancy (Dwell Time)	N/M	Refer 1
-	§ 15.247 (b) (3)	RSS-247 5.4 (b)	Maximum peak conducted output power and antenna gain	N/M	Refer 1
-	§ 15.247 (d)	RSS-247 5.5	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
-	§ 15.247 (d)	RSS-247 5.5	Emission limitations Conducted (Transmitter)	N/M	Refer 1
A.1	§ 15.247 (d)	RSS-247 5.5	Emission limitations Radiated (Transmitter)	P	N/A

Supplementary information and remarks:

1) Only multi-transmitter radiated spurious emission test was requested.

FCC PART 15 PARAGRAPH (Wi-Fi 2.4GHz)					
Report Section	15.247 Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
-	§ 2.1049 & §15.247 (a) (2)	RSS-247 5.2 (a)	99% Occupied Bandwidth & 6dB Bandwidth	N/M	Refer 1
-	§ 15.247 (b)	RSS-247 5.4 (d)	Maximum Output Power and antenna gain	N/M	Refer 1
-	§ 15.247 (d)	RSS-247 5.5	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
-	§ 15.247 (e)	RSS-247 5.2 (b)	Power Spectral Density	N/M	Refer 1
-	§15.247(d)	RSS-247 5.5	Emission limitations Conducted (Transmitter)	N/M	Refer 1
A.1	§15.247 (d)	RSS-247 5.5	Emission limitations Radiated (Transmitter)	P	N/A
Supplementary information and remarks: 1) Only multi-transmitter radiated spurious emission test was requested.					

FCC PART 15 PARAGRAPH / RSS-247 (Wi-Fi 5GHz) UNII-1 5.150 - 5.250 GHz Band, UNII-3 5.725 - 5.825 GHz Band					
Report Section	15.407 Spec Clause	RSS Spec Clause	Test Description	Verdict	Remark
	§ 15.403 KDB 789033 D02	RSS 247 6.2.4	26dB Emission Bandwidth & Occupied Bandwidth	N/M	Refer 1
	§ 15.407 (e)	RSS 247 6.2.4.1	6dB Bandwidth	N/M	Refer 1
	§ 15.407 (a)(3)	RSS 247 6.2.4.1	Power Limits. Maximum Output Power	N/M	Refer 1
	§ 15.407 (a)(3)	RSS-247 6.2.4.1	Maximum Power Spectral Density	N/M	Refer 1
	§ 15.407 (b)(4)	RSS-247 6.2.4.2	Band-edge conducted emissions compliance (Transmitter)	N/M	Refer 1
	§ 15.407 (b)(6) § 15.207	RSS-Gen 8.8	Emission limitations Conducted (Transmitter)	N/M	Refer 1
A.1	§ 15.407 (b) (1), b(4)(i) § 15.209 § 15.205	RSS-247 6.2.4.2 RSS-Gen 8.9 & 8.10	Undesirable radiated emissions (Transmitter)	P	N/A
	§ 15.407 (g)	RSS-Gen 6.11 & 8.11	Frequency Stability	N/M	Refer 1
Supplementary information and remarks: 1) Only multi-transmitter radiated spurious emission test was requested.					

List of equipment used during the test

Radiated Measurements

CONTROL NUMBER	DESCRIPTION	MANUFACTURER	MODEL	LAST CALIBRATION	NEXT CALIBRATION
878	Power supply (AMETEK / PROG-DC-PS)	N/A	1707A01783	N/A	N/A
1012	EMI Test Receiver	Rohde & Schwarz	ESR26	2023-01-18	2025-01-18
1014	FSV40 Signal Analyzer 40GHz	Rohde & Schwarz	FSV40	2022-08-01	2024-08-01
1056	3116C Double-Ridged Waveguide Horn Antenna 18-40 GHz	ETS LINDGREN	213179	2023-02-23	2026-02-23
1058	3115 Double-Ridged Waveguide Horn Antenna 1-18 GHz	ETS LINDGREN	211373	2023-06-26	2026-06-26
1064	3142E Biconilog Antenna	ETS LINDGREN	208587	2021-12-13	2024-12-13
1108	Ethernet SNMP Thermometer- CR Room	HW Group	HWg-STE Plain	2022-10-18	2024-10-18
1111	Ethernet SNMP Thermometer	HW Group	HWg-STE Plain	2022-10-18	2024-10-18
1179	Semi anechoic Absorber Lined Chamber	Frankonia	SAC 3 plus “L”	N/A	N/A
1314	Wireless Measurement Software R&S EMC32	Rohde & Schwarz	N/A	N/A	N/A
1461	Low Noise Preamplifier (1-18GHz)	Bonn Elektronik	2213857B	2022-06-01	2024-06-01

Appendix A: Test results (Multi-transmitter)

Appendix A Content

PRODUCT INFORMATION 13
DESCRIPTION OF TEST CONDITIONS 14
TEST A.1: EMISSION LIMITATIONS RADIATED (TRANSMITTER) 15

PRODUCT INFORMATION

Information	Description
Modulation	BR/EDR: GFSK, π/4-DQPSK, 8-DPSK Wi-Fi 2.4 GHz: DSSS, OFDM, SISO- MCS4 Wi-Fi 5 GHz: DSSS, OFDM, SISO- MCS4
Operation mode 1: Single Antenna Equipment	
- Operating Frequency Range	BR/EDR: 2400 - 2483.5 MHz Wi-Fi 2.4 GHz: 2.400 - 2.483.5 GHz Wi-Fi 5 GHz: 5.150 - 5.250 GHz 5.725 - 5.875 GHz
- Nominal Channel Bandwidth	BR/EDR: 1 MHz Wi-Fi 2.4 GHz: 20MHz, 40MHz Wi-Fi 5 GHz: 20MHz, 40MHz, 80MHz
- RF Output Power	BR/EDR: 13.47 dBm Wi-Fi 2.4 GHz: 15 dBm Wi-Fi 5 GHz: 15 dBm
Antenna type	Internal PCB trace antenna
Antenna gain	BR/EDR: 4.17 dBi Wi-Fi 2.4 GHz: 4.53 dBi Wi-Fi 5 GHz: 5.74 dBi
Nominal Voltage	
- Supply Voltage	12 Vdc
- Type of power source	DC voltage
Equipment type	Bluetooth, Wi-Fi 2.4 GHz, and Wi-Fi 5 GHz
Geo-location capability	No

DESCRIPTION OF TEST CONDITIONS

<table>
<tr><th>TEST CONDITIONS</th><th>DESCRIPTION</th></tr>
<tr><td>TC#01(1)</td><td>
<u>Power supply (V):</u>
DC 12 V

<u>Test Frequencies for Radiated tests:</u>
<table>
<tr><th>Technology</th><th>Tested Frequency</th><th>BW (MHz)</th><th>Modulation</th><th>Mode</th></tr>
<tr><td>Bluetooth</td><td>2402</td><td>1</td><td>DSSS</td><td>GFSK</td></tr>
<tr><td>Wi-Fi 2.4 GHz SISO</td><td>2462</td><td>20</td><td>OFDM</td><td>b mode</td></tr>
</table>
The test was performed with the equipment transmitting with Bluetooth and Wi-Fi 2.4GHz radios simultaneously. These measurements have been performed in order to check the impact of the multi-transmitter of all radio interfaces that can be transmitting simultaneously.
</td></tr>
<tr><td>TC#02(1)</td><td>
<u>Power supply (V):</u>
DC 12 V

<u>Test Frequencies for Radiated tests:</u>
<table>
<tr><th>Technology</th><th>Tested Frequency</th><th>BW (MHz)</th><th>Modulation</th><th>Mode</th></tr>
<tr><td>Bluetooth</td><td>2441</td><td>1</td><td>DSSS</td><td>GFSK</td></tr>
<tr><td>Wi-Fi 5 GHz SISO</td><td>5795</td><td>40</td><td>MCS4</td><td>ac mode</td></tr>
</table>
The test was performed with the equipment transmitting with Bluetooth and Wi-Fi 5GHz radios simultaneously. These measurements have been performed in order to check the impact of the multi-transmitter of all radio interfaces that can be transmitting simultaneously.
</td></tr>
</table>

Note (1): Preliminary scan was performed to determine the worst case. The following tables and plots show the results for the worst case in SISO (2.4 GHz or 5 GHz) + BT.

TEST A.1: EMISSION LIMITATIONS RADIATED (TRANSMITTER)

LIMITS:	Product standard:	Part 15 Subpart C §15.247, Part 15.31(h), and RSS-247
	Test standard:	Part 15 Subpart C §15.247 (d) and RSS-Gen 8.9 and 8.10

LIMITS

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

TEST SETUP

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz (Double ridge horn antenna), and 1m for the frequency range 18 GHz- 26 GHz (Double ridge horn antenna).

For radiated emissions in the range 18 - 26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360º and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

TEST SETUP (CONT.)

Radiated measurements Setup f < 1 GHz



Radiated measurements setup f: 1-18 GHz



Radiated measurements setup f > 18 GHz



TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#01
TEST RESULTS:	30-1000 MHz

Frequency range 9KHz – 30 MHz

No radiofrequency signal generated in the device found below 10º sub-armonic, no further investigation required.

Frequency range 30 MHz – 1000 MHz

Results:



Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)
131.995500	24.2	12.2	H	31.3	43.5
170.165000	25.8	14.0	V	29.6	43.5
242.236000	31.4	21.3	H	24.7	46.0
326.577500	30.2	17.0	H	29.0	46.0
406.311500	34.5	21.4	H	24.6	46.0
965.128500	42.9	30.1	V	24.0	54.0

TEST RESULTS (Cont.):	1-18 GHz



PK+_MAXH
TX limits to Spurious Emission FCC15.247(1-26G) Restricted Bands AVG Limit
TX limits to Spurious Emission FCC15.247 Restricted Bands PK Limit
RMS_MAXH

Final Result

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)	Comment
2402.000000	98.8	98.2	V	---	---	BT Fundamental
2461.500000	101.8	98.0	H	---	---	WIFI 2.4G Fundamental

TEST RESULTS (Cont.):	18 – 26 GHz



AVG_MAXH
PK+_MAXH
TX limits to Spurious Emission FCC15.247(1-26G) Restricted Bands AVG Limit
TX limits to Spurious Emission FCC15.247 Restricted Bands PK Limit

Final Result

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
20036.500000	48.4	38.1	H	15.9	54.0
23846.000000	46.7	36.9	H	17.1	54.0

TEST RESULTS (Cont.):	Restricted Bands (2.31 GHz – 2.5 GHz)



PK+_MAXH
TX limits to Spurious Emission FCC15.247(1-26G) Restricted Bands AVG Limit
TX limits to Spurious Emission FCC15.247 Restricted Bands PK Limit
RMS_MAXH

TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	TC#02
TEST RESULTS :	30-1000 MHz

Frequency range 9KHz – 30 MHz

No radiofrequency signal generated in the device found below 10º sub-armonic, no further investigation required.

Frequency range 30 MHz – 1000 MHz

Results:



Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	QuasiPeak (dBµV/m)	Pol	Margin - QPK (dB)	Limit - QPK (dBµV/m)
135.730000	23.9	12.3	V	31.3	43.5
171.523000	26.8	14.1	H	29.4	43.5
245.097500	29.6	18.4	V	27.6	46.0
326.674500	29.6	16.7	H	29.3	46.0
406.505500	34.0	21.5	V	24.5	46.0
612.145500	40.6	26.6	H	19.4	46.0

TEST RESULTS (Cont.):	1-18 GHz



PK+_MAXH
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands PK Limit
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands AVG Limit
AVG_MAXH

Final Result

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)	Comment
2402.000000	96.4	95.6	V	---	---	BT Fundamental
5780.500000	92.8	85.2	H	---	---	WIFI 5G Fundamental
11910.583333	40.3	31.0	V	23.0	54.0	

TEST RESULTS (Cont.):	18 – 40 GHz



AVG_MAXH
PK+_MAXH
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands PK Limit
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands AVG Limit

Final Result

Frequency (MHz)	PK+_MAXH (dBµV/m)	AVG_MAXH (dBµV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBµV/m)
19405.250000	39.7	30.6	H	23.4	54.0
19986.875000	38.7	29.4	H	24.6	54.0
31724.562500	35.7	27.5	H	26.5	54.0

TEST RESULTS (Cont.):	Restricted Bands (2.3 GHz – 2.5 GHz)



PK+_MAXH
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands PK Limit
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands AVG Limit
AVG_MAXH

TEST RESULTS (Cont.):	Restricted Bands (5.1 GHz – 6 GHz)



PK+_MAXH
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands PK Limit
TX limits to Spurious Emission FCC15.407 (1GHz to 40 GHz) Restricted Bands AVG Limit
AVG_MAXH