



FCC REPORT

FCC ID:

Applicant: Positioning Universal Inc
Address of Applicant: 4660 La Jolla Village Drive Suite 1100, San Diego, California
92122, United States

ISED:

Applicant: Positioning Universal
Address of Applicant: 4660 La Jolla Village Dr., Suite 1100 SAN DIEGO CA 92122
United States Of America

Manufacturer: Positioning Universal Inc
Address of Manufacturer: 4660 La Jolla Village Drive Suite 1100, San Diego, California
92122, United States
Equipment Under Test (EUT)

Product Name: Vehicle LTE CAT 1 Radio Telecommunications Unit

Model No.: VCM550, DCM550

FCC ID: 2AHRH-DCD710LA

IC: 24008-DCD710LA

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249
RSS-Gen Issue 5: April 2018
RSS-210 Issue 9: August 2016

Date of sample receipt: November 01, 2018

Date of Test: November 01-12, 2018

Date of report issued: November 12, 2018

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	November 12, 2018	Original

Prepared By: Tiger Chen **Date:** November 12, 2018
Project Engineer

Check By: Robinson **Date:** November 12, 2018
Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
5.6 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 RADIATED EMISSION METHOD	14
7.3.1 Field Strength of The Fundamental Signal	16
7.3.2 Spurious emissions	17
7.3.3 Bandedge emissions	22
7.4 20dB OCCUPY BANDWIDTH	24
8 TEST SETUP PHOTO	26
9 EUT CONSTRUCTIONAL DETAILS	27

4 Test Summary

Test Item	Section	Result
Antenna requirement	15.203 RSS-Gen Clause 6.8	Pass
AC Power Line Conducted Emission	15.207 RSS-Gen Clause 8.8	Pass
Field strength of the fundamental signal	15.249 (a) RSS-210 A2.9(a)	Pass
Spurious emissions	15.249 (a) (d)/15.209 RSS-210 A2.9(b)	Pass
Band edge	15.249 (d)/15.205 RSS-Gen 8.9 & RSS-Gen 8.10	Pass
20dB Occupied Bandwidth / 99% Occupied Bandwidth	15.215 (c) RSS-Gen Clause 6.6	Pass

Remarks:

1. Test according to ANSI C63.10: 2013.
2. Pass: The EUT complies with the essential requirements in the standard.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	$\pm 4.34\text{dB}$	(1)
Radiated Emission	30MHz ~ 1000MHz	$\pm 4.24\text{dB}$	(1)
Radiated Emission	1GHz ~ 26.5GHz	$\pm 4.68\text{dB}$	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	$\pm 3.45\text{dB}$	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	Vehicle LTE CAT 1 Radio Telecommunications Unit
Model No.:	VCM550, DCM550
Test Model No:	VCM550
<i>Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The only difference is the model name for commercial purpose.</i>	
Serial No.:	0000064567
Hardware version:	DCD710-P2
Software version:	6005.1.0.0
Test sample(s) ID:	GTS201811000009-3
Sample(s) Status	Engineered sample
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	40
Channel separation:	2MHz
Modulation type:	GFSK
Antenna Type:	Integral antenna
Antenna gain:	0.5dBi(declared by manufacturer)
Power supply:	DC 12V

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	86.45	87.46	85.23

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
GS	Lead-Acid battery	S5D26R-MFZ	9442804454

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Additional Instructions

Special test software was pre-built-in by manufacturer, power set as default.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS588	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019


RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 27 2018	June 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:
FCC part 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
RSS-Gen 6.8: A transmitter can only be sold or operated with antennas with which it was approved. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. For transmitters of RF output power of 10 milliwatts or less, only the portion of the antenna gain that is in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power to demonstrate compliance with the radiated power limits specified in the applicable standard. For transmitters of output power greater than 10 milliwatts, the total antenna gain shall be added to the measured RF output power to demonstrate compliance to the specified radiated power limits.
EUT Antenna:
<i>The antenna is integral antenna, the best case gain of the antenna is 0.5dBi</i> 

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207 & RSS-Gen 8.8						
Test Method:	ANSI C63.4:2014 and ANSI C63.10:2013 & RSS-Gen						
Test Frequency Range:	150KHz to 30MHz						
Class / Severity:	Class B						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto						
Limit:	Frequency range (MHz)		Limit (dBuV)				
			Quasi-peak		Average		
	0.15-0.5		66 to 56*		56 to 46*		
	0.5-5		56		46		
	5-30		60		50		
* Decreases with the logarithm of the frequency.							
Test setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m						
Test procedure:	1. The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	
Test voltage:	AC 120V, 60Hz						
Test results:	Pass						


Measurement data

Line:



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.27	29.76	0.40	0.10	30.26	61.03	-30.77	QP
0.27	4.76	0.40	0.10	5.26	51.03	-45.77	Average
0.56	24.49	0.30	0.12	24.91	56.00	-31.09	QP
0.56	0.28	0.30	0.12	0.70	46.00	-45.30	Average
0.91	23.72	0.22	0.14	24.08	56.00	-31.92	QP
0.91	12.77	0.22	0.14	13.13	46.00	-32.87	Average
1.80	10.05	0.20	0.17	10.42	56.00	-45.58	QP
1.80	-2.68	0.20	0.17	-2.31	46.00	-48.31	Average
7.10	9.26	0.20	0.19	9.65	60.00	-50.35	QP
7.10	-2.66	0.20	0.19	-2.27	50.00	-52.27	Average
25.59	24.84	0.36	0.23	25.43	60.00	-34.57	QP
25.59	16.88	0.36	0.23	17.47	50.00	-32.53	Average

Neutral:






Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.24	37.49	0.40	0.11	38.00	62.22	-24.22	QP
0.24	18.17	0.40	0.11	18.68	52.22	-33.54	Average
0.51	35.60	0.31	0.11	36.02	56.00	-19.98	QP
0.51	10.39	0.31	0.11	10.81	46.00	-35.19	Average
0.91	24.19	0.22	0.14	24.55	56.00	-31.45	QP
0.91	16.96	0.22	0.14	17.32	46.00	-28.68	Average
2.09	18.02	0.20	0.18	18.40	56.00	-37.60	QP
2.09	-0.57	0.20	0.18	-0.19	46.00	-46.19	Average
6.42	10.77	0.20	0.18	11.15	60.00	-48.85	QP
6.42	-2.74	0.20	0.18	-2.36	50.00	-52.36	Average
25.59	17.21	0.36	0.23	17.80	60.00	-42.20	QP
25.59	9.73	0.36	0.23	10.32	50.00	-39.68	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 RSS-210 A2.9(a) & RSS-Gen 8.9 & RSS-Gen 8.10				
Test Method:	ANSI C63.10: 2013 & RSS-Gen				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark
	2400MHz-2483.5MHz		94.00		Average Value
			114.00		Peak Value
Limit: (Spurious Emissions)	Frequency		Limit (uV/m)		Remark
	0.009MHz-0.490MHz		2400/F(kHz) @300m		Quasi-peak Value
	0.490MHz-1.705MHz		24000/F(kHz) @30m		Quasi-peak Value
	1.705MHz-30.0MHz		30 @30m		Quasi-peak Value
	30MHz-88MHz		100 @3m		Quasi-peak Value
	88MHz-216MHz		150 @3m		Quasi-peak Value
	216MHz-960MHz		200 @3m		Quasi-peak Value
	960MHz-1GHz		500 @3m		Quasi-peak Value
	Above 1GHz		500 @3m		Average Value
5000 @3m			Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz				
					
	For radiated emissions from 30MHz to1GHz				

	 For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1012mbar
Test voltage:	AC 120V, 60Hz
Test results:	Pass

Measurement data:

7.3.1 Field Strength of The Fundamental Signal

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	88.04	27.58	5.39	34.01	87.00	114.00	-27.00	Vertical
2402.00	83.71	27.58	5.39	34.01	82.67	114.00	-31.33	Horizontal
2440.00	88.51	27.48	5.43	33.96	87.46	114.00	-26.54	Vertical
2440.00	82.74	27.48	5.43	33.96	81.69	114.00	-32.31	Horizontal
2480.00	88.05	27.52	5.47	33.92	87.12	114.00	-26.88	Vertical
2480.00	82.39	27.52	5.47	33.92	81.46	114.00	-32.54	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	78.75	27.58	5.39	34.01	77.71	94.00	-16.29	Vertical
2402.00	73.91	27.58	5.39	34.01	72.87	94.00	-21.13	Horizontal
2440.00	78.38	27.48	5.43	33.96	77.33	94.00	-16.67	Vertical
2440.00	72.09	27.48	5.43	33.96	71.04	94.00	-22.96	Horizontal
2480.00	77.33	27.52	5.47	33.92	76.40	94.00	-17.60	Vertical
2480.00	72.15	27.52	5.47	33.92	71.22	94.00	-22.78	Horizontal


7.3.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.


■ Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
35.005	40.49	11.33	0.61	35.36	17.07	40.00	-22.93	QP
41.713	39.21	12.22	0.68	35.76	16.35	40.00	-23.65	QP
47.492	39.68	12.28	0.74	36.06	16.64	40.00	-23.36	QP
53.505	38.95	11.93	0.80	36.23	15.45	40.00	-24.55	QP
61.778	38.59	10.61	0.87	36.34	13.73	40.00	-26.27	QP
112.920	40.98	10.59	1.30	36.83	16.04	43.50	-27.46	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
36.637	40.19	11.61	0.63	35.46	16.97	40.00	-23.03	QP
58.819	40.97	11.43	0.85	36.31	16.94	40.00	-23.06	QP
112.920	40.78	10.59	1.30	36.83	15.84	43.50	-27.66	QP
255.623	35.11	12.33	2.15	37.38	12.21	46.00	-33.79	QP
429.523	34.75	15.95	2.99	37.52	16.17	46.00	-29.83	QP
782.345	34.56	21.09	4.40	37.62	22.43	46.00	-23.57	QP

■ Above 1GHz

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	38.36	31.78	8.60	32.09	46.65	74.00	-27.35	Vertical
7206.00	30.54	36.15	11.65	32.00	46.34	74.00	-27.66	Vertical
9608.00	30.32	37.95	14.14	31.62	50.79	74.00	-23.21	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	39.25	31.78	8.60	32.09	47.54	74.00	-26.46	Horizontal
7206.00	32.13	36.15	11.65	32.00	47.93	74.00	-26.07	Horizontal
9608.00	29.56	37.95	14.14	31.62	50.03	74.00	-23.97	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	30.55	31.78	8.60	32.09	38.84	54.00	-15.16	Vertical
7206.00	19.45	36.15	11.65	32.00	35.25	54.00	-18.75	Vertical
9608.00	18.65	37.95	14.14	31.62	39.12	54.00	-14.88	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	28.56	31.78	8.60	32.09	36.85	54.00	-17.15	Horizontal
7206.00	21.49	36.15	11.65	32.00	37.29	54.00	-16.71	Horizontal
9608.00	18.22	37.95	14.14	31.62	38.69	54.00	-15.31	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Remarks:

1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	38.52	31.85	8.67	32.12	46.92	74.00	-27.08	Vertical
7320.00	30.65	36.37	11.72	31.89	46.85	74.00	-27.15	Vertical
9760.00	30.42	38.35	14.25	31.62	51.40	74.00	-22.60	Vertical
12200.00	*					74.00		Vertical
14640.00	*					74.00		Vertical
4880.00	39.45	31.85	8.67	32.12	47.85	74.00	-26.15	Horizontal
7320.00	32.25	36.37	11.72	31.89	48.45	74.00	-25.55	Horizontal
9760.00	29.67	38.35	14.25	31.62	50.65	74.00	-23.35	Horizontal
12200.00	*					74.00		Horizontal
14640.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	30.68	31.85	8.67	32.12	39.08	54.00	-14.92	Vertical
7320.00	19.54	36.37	11.72	31.89	35.74	54.00	-18.26	Vertical
9760.00	18.73	38.35	14.25	31.62	39.71	54.00	-14.29	Vertical
12200.00	*					54.00		Vertical
14640.00	*					54.00		Vertical
4880.00	28.71	31.85	8.67	32.12	37.11	54.00	-16.89	Horizontal
7320.00	21.60	36.37	11.72	31.89	37.80	54.00	-16.20	Horizontal
9760.00	18.31	38.35	14.25	31.62	39.29	54.00	-14.71	Horizontal
12200.00	*					54.00		Horizontal
14640.00	*					54.00		Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*” means this data is too weak instrument of signal is unable to test.

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	38.39	31.93	8.73	32.16	46.89	74.00	-27.11	Vertical
7440.00	30.56	36.59	11.79	31.78	47.16	74.00	-26.84	Vertical
9920.00	30.34	38.81	14.38	31.88	51.65	74.00	-22.35	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	39.28	31.93	8.73	32.16	47.78	74.00	-26.22	Horizontal
7440.00	32.14	36.59	11.79	31.78	48.74	74.00	-25.26	Horizontal
9920.00	29.58	38.81	14.38	31.88	50.89	74.00	-23.11	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	30.59	31.93	8.73	32.16	39.09	54.00	-14.91	Vertical
7440.00	19.48	36.59	11.79	31.78	36.08	54.00	-17.92	Vertical
9920.00	18.67	38.81	14.38	31.88	39.98	54.00	-14.02	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	28.61	31.93	8.73	32.16	37.11	54.00	-16.89	Horizontal
7440.00	21.53	36.59	11.79	31.78	38.13	54.00	-15.87	Horizontal
9920.00	18.25	38.81	14.38	31.88	39.56	54.00	-14.44	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. “*”, means this data is the too weak instrument of signal is unable to test.

7.3.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.49	27.91	5.30	24.64	53.06	74.00	-20.94	Horizontal
2390.00	44.51	27.59	5.38	24.71	52.77	74.00	-21.23	Horizontal
2400.00	47.24	27.41	5.39	24.72	55.32	74.00	-18.68	Horizontal
2310.00	45.20	27.91	5.30	24.64	53.77	74.00	-20.23	Vertical
2390.00	45.72	27.59	5.38	24.71	53.98	74.00	-20.02	Vertical
2400.00	46.21	27.41	5.39	24.72	54.29	74.00	-19.71	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.68	27.91	5.30	24.64	43.25	54.00	-10.75	Horizontal
2390.00	34.01	27.59	5.38	24.71	42.27	54.00	-11.73	Horizontal
2400.00	35.15	27.41	5.39	24.72	43.23	54.00	-10.77	Horizontal
2310.00	34.74	27.91	5.30	24.64	43.31	54.00	-10.69	Vertical
2390.00	34.81	27.59	5.38	24.71	43.07	54.00	-10.93	Vertical
2400.00	35.80	27.41	5.39	24.72	43.88	54.00	-10.12	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.79	27.53	5.47	24.80	54.99	74.00	-19.01	Horizontal
2500.00	45.65	27.55	5.49	24.86	53.83	74.00	-20.17	Horizontal
2483.50	47.90	27.53	5.47	24.80	56.10	74.00	-17.90	Vertical
2500.00	46.81	27.55	5.49	24.86	54.99	74.00	-19.01	Vertical


Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	35.53	27.53	5.47	24.80	43.73	54.00	-10.27	Horizontal
2500.00	35.30	27.55	5.49	24.86	43.48	54.00	-10.52	Horizontal
2483.50	35.77	27.53	5.47	24.80	43.97	54.00	-10.03	Vertical
2500.00	35.35	27.55	5.49	24.86	43.53	54.00	-10.47	Vertical

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*

7.4 20dB Occupy Bandwidth


Test Requirement:	FCC Part15 C Section 15.249/15.215 & RSS-Gen 6.6
Test Method:	ANSI C63.10:2013 and RSS-Gen
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data


Test channel	20dB bandwidth(MHz)	Result
Lowest	1.246	Pass
Middle	1.255	Pass
Highest	1.256	Pass

Test channel	99% bandwidth(MHz)	Result
Lowest	1.0684	Pass
Middle	1.0778	
Highest	1.0819	


Test plot as follows:



Lowest channel




Middle channel



Highest channel

8 Test Setup Photo

Radiated Emission



Conducted Emission



9 EUT Constructional Details

Reference to the test report No. GTS201811000009-01

-----End-----