

FCC REPORT

Applicant: SHENZHEN COOTEL FONE TECHNOLOGY CO., LTD

Address of Applicant: 5D-F, Buliding R1-A, MCM, Hi-tech Park, Nanshan District, Shenzhen

Equipment Under Test (EUT)

Product Name: smart phone

Model No.: S32

FCC ID: 2AHS2-CTF-S32

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 24 Mar., 2016

Date of Test: 24 Mar., to 11 Apr., 2016

Date of report issued: 12 Apr., 2016

Test Result: Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	12 Apr., 2016	Original

Tested by:

Steven Liu

Date:

12 Apr., 2016

Test Engineer

Reviewed by:

Carrey Chen

Date:

12 Apr., 2016

Project Engineer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY.....	4
5	GENERAL INFORMATION.....	5
5.1	CLIENT INFORMATION	5
5.2	GENERAL DESCRIPTION OF E.U.T.	5
5.3	TEST MODE.....	5
5.4	DESCRIPTION OF SUPPORT UNITS	6
5.5	LABORATORY FACILITY	6
5.6	LABORATORY LOCATION	6
5.7	TEST INSTRUMENTS LIST.....	7
6	TEST RESULTS AND MEASUREMENT DATA.....	8
6.1	CONDUCTED EMISSION.....	8
6.2	RADIATED EMISSION	11
7	TEST SETUP PHOTO	17
8	EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	SHENZHEN COOTEL FONE TECHNOLOGY CO., LTD
Address of Applicant:	5D-F, Buliding R1-A, MCM, Hi-tech Park, Nanshan District, Shenzhen
Manufacturer	SHENZHEN COOTEL FONE TECHNOLOGY CO., LTD
Address of Manufacturer:	5D-F, Buliding R1-A, MCM, Hi-tech Park, Nanshan District, Shenzhen
Factory:	Dongguan Changhua Electronic Technology Co., Ltd.
Address of Factory:	2th floor, 1st industrial building of Dongxinwei, west Fuxing Road, Xiagang Community, Changan Town, Dongguan City, Guangdong Province

5.2 General Description of E.U.T.

Product Name:	smart phone
Model No.:	S32
Power supply:	Rechargeable Li-ion Battery DC3.8V-2910mAh
AC adapter :	Model: U0D2F0A050150 Input: AC100-240V 50/60Hz 250mA Output: DC 5.0V, 1.5A

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID
NAKAMICHI	Bluetooth earphone	T8	N/A	FCC ID

5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 817957, February 27, 2012.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282
Fax: +86-755-23116366


5.7 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	03-25-2016	03-25-2017
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	03-25-2016	03-25-2017
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2016	03-31-2017
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2016	03-31-2017
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	03-28-2016	03-28-2017
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	03-28-2016	03-28-2017

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-24-2016	03-24-2017
3	LISN	CHASE	MN2050D	CCIS0074	03-26-2016	03-26-2017
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2016	03-31-2017


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Method:	ANSI C63.4:2009		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 Remark: E.U.T.: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement.		
Test environment:	Temp.: 23 °C	Humid.: 56%	Press.: 101kPa
Measurement Record:	Uncertainty: ± 3.28 dB		
Test Instruments:	Refer to section 5.7 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data:

Line:




Trace: 17

Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN LINE
 EUT : smart phone
 Model : S32
 Test Mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: steven
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	29.79	0.26	10.78	40.83	56.00	-15.17	Average
2	0.214	28.43	0.26	10.76	39.45	53.05	-13.60	Average
3	0.361	40.41	0.26	10.73	51.40	58.69	-7.29	QP
4	0.502	38.99	0.27	10.76	50.02	56.00	-5.98	QP
5	0.651	38.45	0.28	10.77	49.50	56.00	-6.50	QP
6	0.862	24.93	0.28	10.83	36.04	46.00	-9.96	Average
7	0.938	38.42	0.28	10.85	49.55	56.00	-6.45	QP
8	1.000	39.41	0.29	10.87	50.57	56.00	-5.43	QP
9	1.010	26.66	0.29	10.87	37.82	46.00	-8.18	Average
10	1.088	37.91	0.29	10.88	49.08	56.00	-6.92	QP
11	1.147	26.07	0.29	10.89	37.25	46.00	-8.75	Average
12	1.296	22.76	0.29	10.90	33.95	46.00	-12.05	Average

Neutral:



Trace: 19



Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN NEUTRAL
 EUT : smart phone
 Model : S32
 Test Mode : PC mode
 Power Rating : AC120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: steven
 Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.219	40.91	0.16	10.76	51.83	62.88	-11.05	QP
2	0.219	25.96	0.16	10.76	36.88	52.88	-16.00	Average
3	0.361	37.42	0.16	10.73	48.31	58.69	-10.38	QP
4	0.361	25.42	0.16	10.73	36.31	48.69	-12.38	Average
5	0.505	34.58	0.16	10.76	45.50	56.00	-10.50	QP
6	0.505	25.64	0.16	10.76	36.56	46.00	-9.44	Average
7	0.651	34.04	0.17	10.77	44.98	56.00	-11.02	QP
8	0.651	25.33	0.17	10.77	36.27	46.00	-9.73	Average
9	0.933	34.08	0.18	10.85	45.11	56.00	-10.89	QP
10	0.938	25.32	0.18	10.85	36.35	46.00	-9.65	Average
11	1.153	35.02	0.19	10.89	46.10	56.00	-9.90	QP
12	1.153	25.74	0.19	10.89	36.82	46.00	-9.18	Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

6.2 Radiated Emission


Test Requirement:	FCC Part 15 B Section 15.109				
Test Method:	ANSI C63.4:2009				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
		74.0		Peak Value	
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.: 1 01kPa
Measurement Record:	Uncertainty: ±4.88dB				
Test Instruments:	Refer to section 5.7 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed				

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL
 EUT : Smart Phone
 Model : S32
 Test mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: steven
 REMARK :

		ReadAntenna	Cable Preamp			Limit	Over	
Freq	Level	Factor	Loss Factor	Level	Line	Limit	Remark	
-----MHz	-----dBUV	-----dB/m	-----dB	-----dB	dBUV/m	dBUV/m	-----dB	-----
1	55.609	47.97	12.38	1.36	29.80	31.91	40.00	-8.09 QP
2	143.830	41.67	11.34	2.44	29.25	26.20	43.50	-17.30 QP
3	191.745	47.34	9.79	2.81	28.89	31.05	43.50	-12.45 QP
4	238.310	52.45	11.76	2.82	28.60	38.43	46.00	-7.57 QP
5	595.133	40.35	18.46	3.94	28.95	33.80	46.00	-12.20 QP
6	724.261	40.56	19.76	4.27	28.58	36.01	46.00	-9.99 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) VERTICAL
 EUT : Smart Phone
 Model : S32
 Test mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: steven
 REMARK :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
		Level	Factor	Loss Factor	Level	Line	Limit Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m
1	55.415	51.56	12.51	1.36	29.80	35.63	40.00 -4.37 QP
2	143.830	48.75	11.34	2.44	29.25	33.28	43.50 -10.22 QP
3	199.986	53.01	10.20	2.87	28.83	37.25	43.50 -6.25 QP
4	238.310	43.94	11.76	2.82	28.60	29.92	46.00 -16.08 QP
5	564.639	34.69	18.21	3.90	29.05	27.75	46.00 -18.25 QP
6	719.200	41.27	19.68	4.25	28.59	36.61	46.00 -9.39 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL
 EUT : Smart Phone
 Model : S32
 Test mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: steven
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier	Level	Limit	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2956.525	47.30	28.44	7.74	40.55	42.93	74.00	-31.07	Peak
2	2956.525	37.13	28.44	7.74	40.55	32.76	54.00	-21.24	Average
3	3819.945	46.26	29.63	9.33	40.63	44.59	74.00	-29.41	Peak
4	3819.945	37.58	29.63	9.33	40.63	35.91	54.00	-18.09	Average
5	4856.567	46.45	31.56	10.63	40.17	48.47	74.00	-25.53	Peak
6	4856.567	37.91	31.56	10.63	40.17	39.93	54.00	-14.07	Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL
 EUT : Smart Phone
 Model : S32
 Test mode : PC Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: steven
 REMARK :

	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over	
	MHz	Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	2988.480	49.73	25.57	7.81	40.53	42.58	74.00	-31.42 Peak
2	2988.480	40.04	25.57	7.81	40.53	32.89	54.00	-21.11 Average
3	3861.233	44.73	31.06	9.39	40.74	44.44	74.00	-29.56 Peak
4	3861.233	35.89	31.06	9.39	40.74	35.60	54.00	-18.40 Average
5	4830.532	40.84	36.12	10.60	40.22	47.34	74.00	-26.66 Peak
6	4830.532	33.25	36.12	10.60	40.22	39.75	54.00	-14.25 Average