FCC RF Test Report

APPLICANT	:	Altocumulous LLC
EQUIPMENT	:	Digital Media Receiver
MODEL NAME	:	RS03QR
FCC ID	:	2AHSE-2045
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The testing was completed on Jun. 29, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

TABLE OF CONTENTS

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Product Feature of Equipment Under Test 5
1.3 Product Specification of Equipment Under Test 5
1.4 Modification of EUT 5
1.5 Testing Location 6
1.6 Applicable Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**

2.1 Descriptions of Test Mode 7
2.2 Test Mode 7
2.3 Connection Diagram of Test System 8
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 9

3 TEST RESULT **10**

3.1 6dB and 99% Bandwidth Measurement 10
3.2 Peak Output Power Measurement 15
3.3 Power Spectral Density Measurement 16
3.4 Conducted Band Edges and Spurious Emission Measurement 21
3.5 Radiated Band Edges and Spurious Emission Measurement 26
3.6 AC Conducted Emission Measurement 30
3.7 Antenna Requirements 34

4 LIST OF MEASURING EQUIPMENT **35**

5 UNCERTAINTY OF EVALUATION **36**

APPENDIX A. RADIATED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS

APPENDIX D. DUTY CYCLE

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR631725-01B	Rev. 01	Initial issue of report	Jul. 01, 2016
FR631725-01B	Rev. 02	Update report of revising AC Conducted Emission test data and RSE test data	Jul. 19, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass
3.1	-	99% Bandwidth	-	Pass
3.2	15.247(b)(1)	Peak Output Power	≤ 30dBm	Pass
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass
3.6	15.207	AC Conducted Emission	15.207(a)	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass

1 General Description

1.1 Applicant

Altocumulous LLC
300 E. Business Way, Suite 200, Summit Woods Corporate Center Cincinnati, Ohio 45241

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	RS03QR
FCC ID	2AHSE-2045
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth v4.1 EDR/LE

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	7.35 dBm (0.0054 W)
99% Occupied Bandwidth	0.998 MHz
Antenna Type	Fixed Internal Antenna type with gain 1.47 dBi
Type of Modulation	Bluetooth LE : GFSK

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH13-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
- ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

The RF output power was recorded in the following table:

Channel	Frequency	Bluetooth 4.1 – LE RF Output Power
		Data Rate / Modulation
		GFSK
		1Mbps
Ch00	2402MHz	7.35 dBm
Ch19	2440MHz	7.33 dBm
Ch39	2480MHz	7.29 dBm

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

b. AC power line Conducted Emission was tested under maximum output power.

2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth 4.1 – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1: WLAN (2.4GHz) Link + Bluetooth Link + MP3 + USB Cable (Charging from Adapter)

2.3 Connection Diagram of Test System

<Bluetooth 4.1 – LE Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Speaker	JAWBONE	JAMBOX	V3J-JBE	N/A	N/A
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, programmed RF utility, “Compliance.exe” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Test data refer to Appendix A.

6 dB Bandwidth Plot on Channel 00



Date: 19.JUN.2016 17:04:16

6 dB Bandwidth Plot on Channel 19



Date: 19.JUN.2016 17:11:10

6 dB Bandwidth Plot on Channel 39



Date: 19.JUN.2016 17:15:41

3.1.6 Test Result of 99% Occupied Bandwidth

Test data refer to Appendix A.

99% Bandwidth Plot on Channel 00



Date: 19.JUN.2016 17:08:17

99% Occupied Bandwidth Plot on Channel 19



Date: 19.JUN.2016 17:13:55

99% Occupied Bandwidth Plot on Channel 39



Date: 19.JUN.2016 17:18:32

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r05 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Test data refers to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Test data refers to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 19.JUN.2016 17:06:21

PSD 100kHz Plot on Channel 19



Date: 19.JUN.2016 17:12:33

PSD 100kHz Plot on Channel 39



Date: 19.JUN.2016 17:17:09

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 19.JUN.2016 17:05:33

PSD 3kHz Plot on Channel 19



Date: 19.JUN.2016 17:12:02

PSD 3kHz Plot on Channel 39



Date: 19.JUN.2016 17:16:34

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 19.JUN.2016 17:06:36

High Band Edge Plot on Channel 39



Date: 19.JUN.2016 17:17:46

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 19.JUN.2016 17:06:48

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 19.JUN.2016 17:06:56

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 19.JUN.2016 17:12:46

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 19.JUN.2016 17:12:55

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 19.JUN.2016 17:17:58

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 19.JUN.2016 17:18:07

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B and C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	24~25℃
Test Engineer :	Kai-Chun Chu	**Relative Humidity :**	49~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MP3 + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	48.6	Off	L1	19.6	17.4	66.0
0.174000	46.0	Off	L1	19.6	18.8	64.8
0.238000	38.3	Off	L1	19.6	23.9	62.2
0.278000	37.6	Off	L1	19.6	23.3	60.9
0.582000	35.0	Off	L1	19.6	21.0	56.0
1.126000	25.0	Off	L1	19.7	31.0	56.0
6.478000	25.3	Off	L1	19.9	34.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	35.7	Off	L1	19.6	20.3	56.0
0.174000	33.0	Off	L1	19.6	21.8	54.8
0.238000	25.8	Off	L1	19.6	26.4	52.2
0.278000	25.4	Off	L1	19.6	25.5	50.9
0.582000	29.3	Off	L1	19.6	16.7	46.0
1.126000	20.4	Off	L1	19.7	25.6	46.0
6.478000	18.7	Off	L1	19.9	31.3	50.0

Test Mode :	Mode 1	**Temperature :**	24~25℃
Test Engineer :	Kai-Chun Chu	**Relative Humidity :**	49~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	WLAN (2.4GHz) Link + Bluetooth Link + MP3 + USB Cable (Charging from Adapter)		



Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	49.2	Off	N	19.6	16.8	66.0
0.174000	46.0	Off	N	19.6	18.8	64.8
0.222000	41.7	Off	N	19.6	21.0	62.7
0.302000	35.1	Off	N	19.6	25.1	60.2
0.590000	34.9	Off	N	19.6	21.1	56.0
1.070000	25.3	Off	N	19.6	30.7	56.0
6.734000	25.0	Off	N	19.9	35.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	36.2	Off	N	19.6	19.8	56.0
0.174000	33.8	Off	N	19.6	21.0	54.8
0.222000	28.8	Off	N	19.6	23.9	52.7
0.302000	25.2	Off	N	19.6	25.0	50.2
0.590000	26.6	Off	N	19.6	19.4	46.0
1.070000	19.8	Off	N	19.6	26.2	46.0
6.734000	18.1	Off	N	19.9	31.9	50.0

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 08, 2016	Jun. 14, 2016 ~ Jun. 19, 2016	Jan. 07, 2017	Conducted (TH02-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 07, 2016	Jun. 14, 2016 ~ Jun. 19, 2016	Jan. 06, 2017	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 18, 2015	Jun. 14, 2016 ~ Jun. 16, 2016	Jun. 17, 2016	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 17, 2016	Jun. 17, 2016 ~ Jun. 19, 2016	Jun. 16, 2017	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 29, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Jun. 29, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Jun. 29, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Jun. 17, 2016 ~ Jun. 21, 2016	Sep. 01, 2016	Radiation (03CH13-HY)
Preamplifier	MITEQ	TTA0204	1872107	2GHz~40GHz	Feb. 15, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Feb. 14, 2017	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	10MHz~1GHz	Dec. 31, 2015	Jun. 17, 2016 ~ Jun. 21, 2016	Dec. 30, 2016	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D	40103	30MHz to 1GHz	Jan. 13, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Jan. 12, 2017	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A (MXE)	MY55420170	N/A	Mar. 10, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Mar. 09, 2017	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Apr. 25, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Apr. 24, 2017	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Jan. 30, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Jan. 29, 2017	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	N/A	Mar. 14, 2016	Jun. 17, 2016 ~ Jun. 21, 2016	Mar. 13, 2017	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jun. 17, 2016 ~ Jun. 21, 2016	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 17, 2016 ~ Jun. 21, 2016	N/A	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Jun. 17, 2016 ~ Jun. 21, 2016	Nov. 01, 2016	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.26**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.70**

Appendix A. Conducted Test Results

Report Number : FR631725-01B

Bluetooth Low Energy

Test Engineer:	Osolemio Chang and Derek Hsu	Temperature:	21~25	°C
Test Date:	2016/06/14 ~ 2016/06/19	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.00	0.65	0.50	Pass
BLE	1Mbps	1	19	2440	1.00	0.65	0.50	Pass
BLE	1Mbps	1	39	2480	0.99	0.65	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	7.35	30.00	1.47	8.82	36.00	Pass
BLE	1Mbps	1	19	2440	7.33	30.00	1.47	8.80	36.00	Pass
BLE	1Mbps	1	39	2480	7.29	30.00	1.47	8.76	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.20	7.09
BLE	1Mbps	1	19	2440	2.20	7.06
BLE	1Mbps	1	39	2480	2.20	7.00

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	6.74	5.92	1.47	8.00	Pass
BLE	1Mbps	1	19	2440	6.72	5.91	1.47	8.00	Pass
BLE	1Mbps	1	39	2480	6.61	5.81	1.47	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. Radiated Spurious Emission

Test Engineer :	Bill Chang and Elvis Chen and Alex Jeng	Temperature :	20~24°C
		Relative Humidity :	45~50%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2390	53.44	-20.56	74	50.25	27.15	7.31	31.27	118	94	P	H
		2388.225	45.69	-8.31	54	42.51	27.15	7.31	31.28	118	94	A	H
	*	2402	101.79	-	-	98.6	27.15	7.31	31.27	118	94	P	H
	*	2402	101.16	-	-	98.57	27.15	7.31	31.27	118	94	A	H
													H
													H
		2379.09	53.08	-20.92	74	50.01	27.11	7.24	31.28	108	15	P	V
		2375.415	45.35	-8.65	54	42.28	27.11	7.24	31.28	108	15	A	V
	*	2402	96.79	-	-	93.6	27.15	7.31	31.27	108	15	P	V
	*	2402	96.13	-	-	93.64	27.15	7.31	31.27	108	15	A	V
													V
													V
BLE CH 19 2440MHz		2325.73	52.95	-21.05	74	50.08	26.99	7.18	31.3	119	91	P	H
		2365.9	45.88	-8.12	54	42.85	27.07	7.24	31.28	119	91	A	H
	*	2440	102.7	-	-	99.32	27.28	7.36	31.26	119	91	P	H
	*	2440	102.08	-	-	99.2	27.28	7.36	31.26	119	91	A	H
		2487.19	53.63	-20.37	74	50.12	27.36	7.4	31.25	119	91	P	H
		2486.28	45.71	-8.29	54	42.2	27.36	7.4	31.25	119	91	A	H
		2359.79	53.53	-20.47	74	50.51	27.07	7.24	31.29	103	6	P	V
		2345.62	45.37	-8.63	54	42.39	27.03	7.24	31.29	103	6	A	V
	*	2440	99.86	-	-	96.48	27.28	7.36	31.26	103	6	P	V
	*	2440	99.27	-	-	96.39	27.28	7.36	31.26	103	6	A	V
		2488.17	53.94	-20.06	74	50.39	27.4	7.4	31.25	103	6	P	V
		2485.16	45.9	-8.1	54	42.39	27.36	7.4	31.25	103	6	A	V

BLE CH 39 2480MHz	*	2480	102.47	-	-	98.96	27.36	7.4	31.25	141	86	P	H
	*	2480	101.8	-	-	98.87	27.36	7.4	31.25	141	86	A	H
		2483.56	64.03	-9.97	74	60.52	27.36	7.4	31.25	141	86	P	H
		2483.6	52.57	-1.43	54	49.06	27.36	7.4	31.25	141	86	A	H
													H
													H
	*	2480	100.63	-	-	97.12	27.36	7.4	31.25	100	2	P	V
	*	2480	100.04	-	-	97.13	27.36	7.4	31.25	100	2	A	V
		2483.52	61.95	-12.05	74	58.44	27.36	7.4	31.25	100	2	P	V
		2483.68	51.26	-2.74	54	47.75	27.36	7.4	31.25	100	2	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	40.42	-33.58	74	48.57	31.2	11.83	51.18	100	0	P	H
													H
													H
													H
		4804	39.04	-34.96	74	47.19	31.2	11.83	51.18	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	39.45	-34.55	74	47.76	31.31	11.53	51.15	100	0	P	H
		7320	45.57	-28.43	74	46.24	36.32	13.81	50.8	100	0	P	H
													H
													H
		4880	38.19	-35.81	74	46.5	31.31	11.53	51.15	100	0	P	V
		7320	45.55	-28.45	74	46.22	36.32	13.81	50.8	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	38.23	-35.77	74	46.69	31.44	11.22	51.12	100	0	P	H
		7440	46.08	-27.92	74	46.17	36.66	14.05	50.8	100	0	P	H
													H
													H
		4960	38.83	-35.17	74	47.29	31.44	11.22	51.12	100	0	P	V
		7440	46.67	-27.33	74	46.76	36.66	14.05	50.8	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		101.28	31.81	-11.69	43.5	46.47	16.2	1.03	31.89	125	60	P	H
		181.74	23.19	-20.31	43.5	38.29	15.31	1.41	31.82	-	-	P	H
		210.09	28.2	-15.3	43.5	42.35	16.1	1.55	31.8	-	-	P	H
		418.3	23.74	-22.26	46	30.78	22.46	2.28	31.78	-	-	P	H
		573	25.86	-20.14	46	30.31	24.76	2.72	31.93	-	-	P	H
		906.9	30.84	-15.16	46	29.82	29.06	3.44	31.48	-	-	P	H
													H
													H
													H
													H
													H
													H
		59.97	34.81	-5.19	40	54.08	11.8	0.84	31.91	130	40	P	V
		89.13	35.88	-7.62	43.5	52.08	14.69	1.01	31.9	-	-	P	V
		143.13	32.66	-10.84	43.5	45.57	17.69	1.26	31.86	-	-	P	V
		320.3	27.16	-18.84	46	36.91	20.11	1.89	31.75	-	-	P	V
		358.1	26.24	-19.76	46	34.77	21.19	2.04	31.76	-	-	P	V
		804.7	29.37	-16.63	46	30.13	27.85	3.29	31.9	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Radiated Spurious Emission

Test Engineer :	Bill Chang and Elvis Chen and Alex Jeng	**Temperature :**	20~24°C
		Relative Humidity :	45~50%

Note symbol

-L	**Low channel location**
-R	**High channel location**

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 4	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 4
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 4	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak		
Avg		

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	Left blank
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 5	Left blank

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 HORIZONTAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6
Avg.	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6	 Site : 03CH13-HY Condition : 15.209(AVG) 3m HORN_9120D_1241 VERTICAL : RBW:1000.000KHz VBW:10.000KHz SWT:Auto Detector : Peak Project : 631725-01 Mode : 6

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 631725-01 Mode : 4	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 631725-01 Mode : 4

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 631725-01 Mode : 5	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 631725-01 Mode : 5

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 HORIZONTAL Detector : Peak Project : 631725-01 Mode : 6	 Site : 03CH13-HY Condition : 15.209(PEAK) 3m SHF_HORN_584 VERTICAL Detector : Peak Project : 631725-01 Mode : 6

Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak		

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth 4.1 - LE	60.26	376	2.660	3kHz

Bluetooth 4.1 - LE



Date: 14.JUN.2016 01:10:03