RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.

FOR

USB/Bluetooth conference speakerphone

ISSUED TO
ADDASOUND DENMARK A/S

Skalhuse 5, DK-9240 Nibe, Denmark

Tested by: Ye Hongji
Date Sep. 24, 2021

Approved by: Liao Jianming
(Technical Director)
Date Sep. 24, 2021

Report No.:	BL-EC2170804-601
EUT Name:	USB/Bluetooth conference speakerphone
Model Name:	S1000
Brand Name:	ADDASOUND
Test Standard:	47 CFR Part 15 Subpart C
FCC ID:	2AHSP-S1000
Test conclusion:	Pass
Test Date:	Aug. 05, 2021 ~ Sep. 22, 2021
Date of Issue:	Sep. 24, 2021

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055
TEL: +86-755-66850100, FAX: +86-755-61824271
Email: qc@baluntek.com
www.baluntek.com

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Sep. 10, 2021	Initial Issue
Rev. 02	Sep. 24, 2021	Add π/4-DQPSK Radiated Spurious Emission and Radiated Band Edge data

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION) 5

1.1 Identification of the Testing Laboratory 5

1.2 Identification of the Responsible Testing Location 5

1.3 Laboratory Condition 5

1.4 Announce 5

2 PRODUCT INFORMATION 6

2.1 Applicant Information 6

2.2 Manufacturer Information 6

2.3 Factory Information 6

2.4 General Description for Equipment under Test (EUT) 6

2.5 Technical Information 7

2.6 Additional Instructions 8

3 SUMMARY OF TEST RESULTS 9

3.1 Test Standards 9

3.2 Verdict 9

4 GENERAL TEST CONFIGURATIONS 10

4.1 Test Environments 10

4.2 Test Equipment List 10

4.3 Measurement Uncertainty 10

4.4 Description of Test Setup 11

4.4.1 For Antenna Port Test 11

4.4.2 For AC Power Supply Port Test 11

4.4.3 For Radiated Test (Below 30 MHz) 12

4.4.4 For Radiated Test (30 MHz-1 GHz) 12

4.4.5 For Radiated Test (Above 1 GHz) 13

4.5 Measurement Results Explanation Example 14

4.5.1 For conducted test items: 14

5 TEST ITEMS 15
5.1 Antenna Requirements 15
5.1.1 Relevant Standards 15
5.1.2 Antenna Anti-Replacement Construction 15
5.1.3 Antenna Gain 15
5.2 Frequency Hopping Systems 16
5.2.1 Relevant Standards 16
5.2.2 Description of the systems 16
5.3 Number of Hopping Frequencies 18
5.3.1 Limit 18
5.3.2 Test Setup 18
5.3.3 Test Procedure 18
5.3.4 Test Result 18
5.4 Peak Output Power and E.I.R.P 19
5.4.1 Test Limit 19
5.4.2 Test Setup 19
5.4.3 Test Procedure 19
5.4.4 Test Result 19
5.5 Occupied Bandwidth 20
5.5.1 Limit 20
5.5.2 Test Setup 20
5.5.3 Test Procedure 20
5.5.4 Test Result 20
5.6 Carrier Frequency Separation 21
5.6.1 Limit 21
5.6.2 Test Setup 21
5.6.3 Test Procedure 21
5.6.4 Test Result 21
5.7 Time of Occupancy (Dwell time) 22
5.7.1 Limit 22
5.7.2 Test Setup 22
5.7.3 Test Procedure 22
5.7.4 Test Result 23

5.8 Conducted Spurious Emission & Authorized-band band-edge 24
5.8.1 Limit 24
5.8.2 Test Setup 24
5.8.3 Test Procedure 24
5.8.4 Test Result 24
5.9 Conducted Emission 25
5.9.1 Limit 25
5.9.2 Test Setup 25
5.9.3 Test Procedure 25
5.9.4 Test Result 25
5.10 Radiated Spurious Emission 26
5.10.1 Limit 26
5.10.2 Test Setup 26
5.10.3 Test Procedure 26
5.10.4 Test Result 27
5.11 Band Edge (Restricted-band band-edge) 28
5.11.1 Limit 28
5.11.2 Test Setup 28
5.11.3 Test Procedure 28
5.11.4 Test Result 28
ANNEX A TEST RESULT 29
A.1 Number of Hopping Frequency 29
A.2 Peak Output Power and E.I.R.P 30
A.3 20 dB and 99% bandwidth 33
A.4 Hopping Frequency Separation 38
A.5 Average Time of Occupancy 39
A.6 Conducted Spurious Emissions & Authorized-band band-edge 42
A.7 Conducted Emissions 49
A.8 Radiated Spurious Emission 51
A.9 Band Edge (Restricted-band band-edge) 77
ANNEX B TEST SETUP PHOTOS 82
ANNEX C EUT EXTERNAL PHOTOS 82
ANNEX D EUT INTERNAL PHOTOS 82

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20℃ to 25℃
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

(1) The test report reference to the report template version v5.7.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

(5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.

(6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	ADDASOUND DENMARK A/S
Address	Skalhuse 5, DK-9240 Nibe, Denmark

2.2 Manufacturer Information

Manufacturer	ADDASOUND DENMARK A/S
Address	Skalhuse 5, DK-9240 Nibe, Denmark

2.3 Factory Information

Factory	Maanshan ADDASOUND Electronic Technology Co., Ltd.
Address	Building 3, NO.68 South Hongqi Road, Economic & Technology Development Zone, Maanshan City

2.4 General Description for Equipment under Test (EUT)

EUT Name	USB/Bluetooth conference speakerphone
Model Name Under Test	S1000
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V1.0
Software Version	V1.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, π/4-DQPSK, 8-DPSK
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	1.7 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	**2402**	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	**78**	**2480**
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	**39**	**2441**	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Test Software Version	BT FCC Tool V2.24		
Support Units (Software installation media)	Description	Manufacturer	Model
	Notebook	Lenovo	ThinkPad E485
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	Power parameter Settings is 1
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note [1]
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note [2]
3	Peak Output Power and E.I.R.P	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	Note [2]
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note [2]
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note [2]
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Low/Middle/High	ANNEX A.6	Pass	Note [2]
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note [2]
9	Radiated Spurious Emission	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note [2]
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note [2]
11	Receiver Spurious Emissions	--	--	--	N/A	Note [3]

Note [1]: Please refer to section 5.1

Note [2]: π/4-DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in π/4-DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note [3]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	DC 5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-40	101544	2021.04.01	2022.03.31
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2021.06.01	2022.05.31
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2021.06.01	2022.05.31
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.06.01	2022.05.31
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.01	2022.05.31
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2019.10.29	2021.10.28
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2019.07.02	2022.07.01
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1917	2019.07.02	2022.07.01
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2021.01.05	2023.01.04
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2022.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±2.8%
RF output power, conducted	±1.28 dB
Power Spectral Density, conducted	±1.30 dB
Unwanted Emissions, conducted	±1.84 dB
All emissions, radiated	±5.36 dB
Temperature	±0.82°C
Humidity	±4.1%

4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.4.2 For AC Power Supply Port Test



(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b);
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.
Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).
Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.
Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.
For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.
Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents	
	

3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwith and transmitted bandwith are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn’t short burst systems.
7. EUT can’t have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii);

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power and E.I.R.P

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a);

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a);

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span

Video (or Average) Bandwidth (VBW) ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a);

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
Span: Zero span, centered on a hopping channel
RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel
Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel
Detector function: Peak
Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:
For GFSK and 8-DPSK:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (1600 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (1600 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (1600 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For AFH Mode:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (800 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (800 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (800 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5.

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW = 300 kHz
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207;

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50µH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBµV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d);

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBµV/m) = 20*log[Field Strength (µV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto

Detector function = peak
Trace = max hold
For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT

A.1 Number of Hopping Frequency

Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	0.556	1.14	21	125	Pass
Middle	0.196	1.05			Pass
High	-0.574	0.88			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	0.540	1.13	0.060	1.01	21	125	Pass
Middle	0.187	1.04	-0.266	0.94			Pass
High	-0.592	0.87	-1.017	0.79			Pass

Test plots

GFSK LOW CHANNEL

GFSK MIDDLE CHANNEL

GFSK HIGH CHANNEL

π/4-DQPSK LOW CHANNEL

π/4-DQPSK MIDDLE CHANNEL

π/4-DQPSK HIGH CHANNEL

8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL

8-DPSK HIGH CHANNEL

A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.939941	0.875601
Middle	0.945068	0.858036
High	0.945068	0.855786
π/4-DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.279785	1.177058
Middle	1.279785	1.172249
High	1.279785	1.169261
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.255127	1.167032
Middle	1.250000	1.157300
High	1.244873	1.156161

Test plots

20 dB Bandwidth

GFSK LOW CHANNEL

GFSK MIDDLE CHANNEL

GFSK HIGH CHANNEL

π/4-DQPSK LOW CHANNEL

π/4-DQPSK MIDDLE CHANNEL

π/4-DQPSK HIGH CHANNEL

8-DPSK LOW CHANNEL

8-DPSK MIDDLE CHANNEL

8-DPSK HIGH CHANNEL

99% Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



π/4-DQPSK LOW CHANNEL



π/4-DQPSK MIDDLE CHANNEL



π/4-DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	0.975	0.630045	Pass
8-DPSK	0.995	0.836751	Pass

Test Plots

GFSK



8-DPSK

A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.373	119.360	0.4	Pass
DH 3	1.625	260.000	0.4	Pass
DH 5	2.878	306.987	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.752	240.640	0.4	Pass
DH 3	1.620	259.200	0.4	Pass
DH 5	2.878	306.987	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.373	59.680	0.4	Pass
DH 3	1.627	130.160	0.4	Pass
DH 5	2.870	153.067	0.4	Pass

Test Plots

GFSK DH1



GFSK DH3



GFSK DH5



8-DPSK DH1



8-DPSK DH3



8-DPSK DH5



AFH Mode DH1



AFH Mode DH3



AFH Mode DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-52.947	0.318	-19.682	Pass
Middle	-54.476	-0.034	-20.034	Pass
High	-53.245	-0.840	-20.840	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-52.830	-0.176	-20.176	Pass
Middle	-53.267	-0.539	-20.539	Pass
High	-54.155	-1.324	-21.324	Pass

Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-54.094	0.189	-19.811	Pass
8-DPSK	-53.656	0.128	-19.872	Pass

Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL

GFSK LOW CHANNEL, BAND EDGE



GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK MIDDLE CHANNEL, CARRIER LEVEL

GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK HIGH CHANNEL, CARRIER LEVEL

GFSK HIGH CHANNEL, BAND EDGE



GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK LOW CHANNEL, CARRIER LEVEL

8-DPSK LOW CHANNEL, BAND EDGE

8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK MIDDLE CHANNEL, CARRIER LEVEL



8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK HIGH CHANNEL, CARRIER LEVEL



8-DPSK HIGH CHANNEL, BAND EDGE



8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)

GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



8-DPSK HOPPING, CARRIER LEVEL



8-DPSK Hopping BAND EDGE (LOW)

8-DPSK Hopping BAND EDGE (HIGH)

8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



8-DPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



A.7 Conducted Emissions

Note [1]: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.
Note [2]: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.
Note [3]: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.416	36.47	10.46	57.53	-21.06	Peak	L	Pass
1**	0.416	29.48	10.46	47.53	-18.05	AV	L	Pass
2	0.664	33.35	10.19	56.00	-22.65	Peak	L	Pass
2**	0.664	22.46	10.19	46.00	-23.54	AV	L	Pass
3	1.248	35.87	10.23	56.00	-20.13	Peak	L	Pass
3**	1.248	29.16	10.23	46.00	-16.84	AV	L	Pass
4	2.076	33.94	10.19	56.00	-22.06	Peak	L	Pass
4**	2.076	24.50	10.19	46.00	-21.50	AV	L	Pass
5	7.062	35.38	10.32	60.00	-24.62	Peak	L	Pass
5**	7.062	25.81	10.32	50.00	-24.19	AV	L	Pass
6	15.380	38.40	10.58	60.00	-21.60	Peak	L	Pass
6**	15.380	24.62	10.58	50.00	-25.38	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.416	40.93	10.46	57.53	-16.60	Peak	N	Pass
1**	0.416	37.09	10.46	47.53	-10.44	AV	N	Pass
2	1.250	40.56	10.23	56.00	-15.44	Peak	N	Pass
2**	1.250	37.07	10.23	46.00	-8.93	AV	N	Pass
3	2.082	37.99	10.17	56.00	-18.01	Peak	N	Pass
3**	2.082	33.69	10.17	46.00	-12.31	AV	N	Pass
4	6.242	39.81	10.34	60.00	-20.19	Peak	N	Pass
4**	6.242	31.05	10.34	50.00	-18.95	AV	N	Pass
5	7.074	39.35	10.32	60.00	-20.65	Peak	N	Pass
5**	7.074	31.46	10.32	50.00	-18.54	AV	N	Pass
6	14.568	43.15	10.52	60.00	-16.85	Peak	N	Pass
6**	14.568	33.85	10.52	50.00	-16.15	AV	N	Pass

A.8 Radiated Spurious Emission

Test Data and Plots

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and DH5-Hopping mode is the worst.

Note [4]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	52.553	21.98	-25.50	40.0	-18.02	Peak	218.00	100	Vertical	Pass
2	95.232	17.21	-27.93	43.5	-26.29	Peak	87.00	100	Vertical	Pass
3	175.258	25.63	-27.86	43.5	-17.87	Peak	284.00	100	Vertical	Pass
4	298.690	24.57	-23.65	46.0	-21.43	Peak	87.00	100	Vertical	Pass
5	422.122	23.26	-20.73	46.0	-22.74	Peak	124.00	100	Vertical	Pass
6	844.073	24.73	-12.31	46.0	-21.27	Peak	51.00	100	Vertical	Pass

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	53.523	11.40	-25.49	40.0	-28.60	Peak	169.00	100	Horizontal	Pass
2	96.445	9.73	-27.66	43.5	-33.77	Peak	3.00	100	Horizontal	Pass
3	175.258	25.64	-27.86	43.5	-17.86	Peak	254.00	200	Horizontal	Pass
4	320.030	22.65	-23.06	46.0	-23.35	Peak	89.00	100	Horizontal	Pass
5	594.297	21.25	-16.56	46.0	-24.75	Peak	180.00	100	Horizontal	Pass
6	892.088	25.96	-11.47	46.0	-20.04	Peak	67.00	100	Horizontal	Pass

Test Data and Plots (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1199.500	39.51	-16.43	74.0	-34.49	Peak	135.00	100	Vertical	Pass
1**	1199.500	24.35	-16.43	54.0	-29.65	AV	135.00	100	Vertical	Pass
2	1992.500	40.48	-14.10	74.0	-33.52	Peak	159.00	100	Vertical	Pass
2**	1992.500	26.40	-14.10	54.0	-27.60	AV	159.00	100	Vertical	Pass
3	2402.000	99.30	-12.10	74.0	25.30	Peak	205.00	100	Vertical	N/A
3**	2402.000	94.03	-12.10	54.0	40.03	AV	205.00	100	Vertical	N/A
4	3194.000	48.75	-7.10	74.0	-25.25	Peak	155.00	100	Vertical	Pass
4**	3194.000	31.12	-7.10	54.0	-22.88	AV	155.00	100	Vertical	Pass
5	6501.000	51.12	1.87	74.0	-22.88	Peak	214.00	100	Vertical	Pass
5**	6501.000	39.54	1.87	54.0	-14.46	AV	214.00	100	Vertical	Pass
6	14634.000	53.30	12.01	74.0	-20.70	Peak	85.00	100	Vertical	Pass
6**	14634.000	43.43	12.01	54.0	-10.57	AV	85.00	100	Vertical	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1430.000	37.11	-15.70	74.0	-36.89	Peak	57.00	100	Horizontal	Pass
1**	1430.000	23.89	-15.70	54.0	-30.11	AV	57.00	100	Horizontal	Pass
2	2402.000	104.71	-12.10	74.0	30.71	Peak	124.00	100	Horizontal	N/A
2**	2402.000	98.99	-12.10	54.0	44.99	AV	124.00	100	Horizontal	N/A
3	3466.000	43.13	-6.26	74.0	-30.87	Peak	357.00	100	Horizontal	Pass
3**	3466.000	31.42	-6.26	54.0	-22.58	AV	357.00	100	Horizontal	Pass
4	6611.000	52.08	2.38	74.0	-21.92	Peak	334.00	100	Horizontal	Pass
4**	6611.000	39.42	2.38	54.0	-14.58	AV	334.00	100	Horizontal	Pass
5	11292.750	49.69	6.60	74.0	-24.31	Peak	340.00	100	Horizontal	Pass
5**	11292.750	40.73	6.60	54.0	-13.27	AV	340.00	100	Horizontal	Pass
6	14598.250	53.55	12.46	74.0	-20.45	Peak	250.00	100	Horizontal	Pass
6**	14598.250	43.98	12.46	54.0	-10.02	AV	250.00	100	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1197.000	38.90	-17.06	74.0	-35.10	Peak	0.00	100	Vertical	Pass
1**	1197.000	24.51	-17.06	54.0	-29.49	AV	0.00	100	Vertical	Pass
2	1594.500	40.02	-16.54	74.0	-33.98	Peak	163.00	100	Vertical	Pass
2**	1594.500	23.15	-16.54	54.0	-30.85	AV	163.00	100	Vertical	Pass
3	2441.000	100.52	-12.31	74.0	26.52	Peak	113.00	100	Vertical	N/A
3**	2441.000	95.22	-12.31	54.0	41.22	AV	113.00	100	Vertical	N/A
4	4787.000	50.81	-2.70	74.0	-23.19	Peak	115.00	100	Vertical	Pass
4**	4787.000	33.21	-2.70	54.0	-20.79	AV	115.00	100	Vertical	Pass
5	9268.750	48.07	3.55	74.0	-25.93	Peak	277.00	100	Vertical	Pass
5**	9268.750	38.06	3.55	54.0	-15.94	AV	277.00	100	Vertical	Pass
6	14537.750	52.61	11.42	74.0	-21.39	Peak	204.00	100	Vertical	Pass
6**	14537.750	43.89	11.42	54.0	-10.11	AV	204.00	100	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1597.500	39.04	-16.52	74.0	-34.96	Peak	100.00	100	Horizontal	Pass
1**	1597.500	23.08	-16.52	54.0	-30.92	AV	100.00	100	Horizontal	Pass
2	2441.000	103.77	-12.31	74.0	29.77	Peak	138.00	100	Horizontal	N/A
2**	2441.000	98.96	-12.31	54.0	44.96	AV	138.00	100	Horizontal	N/A
3	3191.000	48.78	-7.49	74.0	-25.22	Peak	140.00	100	Horizontal	Pass
3**	3191.000	30.47	-7.49	54.0	-23.53	AV	140.00	100	Horizontal	Pass
4	5705.000	48.75	-0.66	74.0	-25.25	Peak	343.00	100	Horizontal	Pass
4**	5705.000	37.39	-0.66	54.0	-16.61	AV	343.00	100	Horizontal	Pass
5	9268.750	48.08	3.55	74.0	-25.92	Peak	89.00	100	Horizontal	Pass
5**	9268.750	38.01	3.55	54.0	-15.99	AV	89.00	100	Horizontal	Pass
6	14612.000	53.60	12.21	74.0	-20.40	Peak	249.00	100	Horizontal	Pass
6**	14612.000	44.55	12.21	54.0	-9.45	AV	249.00	100	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.000	43.37	-16.53	74.0	-30.63	Peak	155.00	100	Vertical	Pass
1**	1596.000	25.16	-16.53	54.0	-28.84	AV	155.00	100	Vertical	Pass
2	2480.000	99.56	-11.65	74.0	25.56	Peak	103.00	100	Vertical	N/A
2**	2480.000	94.37	-11.65	54.0	40.37	AV	103.00	100	Vertical	N/A
3	3199.000	49.70	-6.82	74.0	-24.30	Peak	176.00	100	Vertical	Pass
3**	3199.000	30.97	-6.82	54.0	-23.03	AV	176.00	100	Vertical	Pass
4	4798.000	51.00	-2.48	74.0	-23.00	Peak	122.00	100	Vertical	Pass
4**	4798.000	33.16	-2.48	54.0	-20.84	AV	122.00	100	Vertical	Pass
5	9296.250	48.03	4.32	74.0	-25.97	Peak	251.00	100	Vertical	Pass
5**	9296.250	39.24	4.32	54.0	-14.76	AV	251.00	100	Vertical	Pass
6	14579.000	52.80	12.16	74.0	-21.20	Peak	91.00	100	Vertical	Pass
6**	14579.000	42.98	12.16	54.0	-11.02	AV	91.00	100	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1995.500	40.03	-13.86	74.0	-33.97	Peak	222.00	100	Horizontal	Pass
1**	1995.500	24.73	-13.86	54.0	-29.27	AV	222.00	100	Horizontal	Pass
2	2480.000	101.53	-11.65	74.0	27.53	Peak	145.00	100	Horizontal	N/A
2**	2480.000	96.42	-11.65	54.0	42.42	AV	145.00	100	Horizontal	N/A
3	3196.000	49.24	-6.55	74.0	-24.76	Peak	135.00	100	Horizontal	Pass
3**	3196.000	31.38	-6.55	54.0	-22.62	AV	135.00	100	Horizontal	Pass
4	6629.000	51.36	2.77	74.0	-22.64	Peak	69.00	100	Horizontal	Pass
4**	6629.000	39.17	2.77	54.0	-14.83	AV	69.00	100	Horizontal	Pass
5	9227.500	47.02	3.71	74.0	-26.98	Peak	270.00	100	Horizontal	Pass
5**	9227.500	38.68	3.71	54.0	-15.32	AV	270.00	100	Horizontal	Pass
6	14394.750	53.05	11.94	74.0	-20.95	Peak	97.00	100	Horizontal	Pass
6**	14394.750	43.27	11.94	54.0	-10.73	AV	97.00	100	Horizontal	Pass

π/4-DQPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.600	42.28	-17.77	74.0	-31.72	Peak	60.00	100	Vertical	Pass
1**	1596.600	26.44	-17.77	54.0	-27.56	AV	60.00	100	Vertical	Pass
2	2093.400	46.13	-15.05	74.0	-27.87	Peak	85.00	100	Vertical	Pass
2**	2093.400	35.25	-15.05	54.0	-18.75	AV	85.00	100	Vertical	Pass
3	2401.900	97.37	-12.88	74.0	23.37	Peak	249.00	100	Vertical	N/A
3**	2401.900	89.77	-12.88	54.0	35.77	AV	249.00	100	Vertical	N/A
4	2791.700	52.68	-10.72	74.0	-21.32	Peak	20.00	100	Vertical	Pass
4**	2791.700	36.21	-10.72	54.0	-17.79	AV	20.00	100	Vertical	Pass
5	7205.250	54.13	1.18	74.0	-19.87	Peak	230.00	100	Vertical	Pass
5**	7205.250	45.66	1.18	54.0	-8.34	AV	230.00	100	Vertical	Pass
6	14535.000	52.20	0.02	74.0	-21.80	Peak	185.00	100	Vertical	Pass
6**	14535.000	42.06	0.02	54.0	-11.94	AV	185.00	100	Vertical	Pass

π/4-DQPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.500	41.46	-17.78	74.0	-32.54	Peak	314.00	100	Horizontal	Pass
1**	1598.500	27.69	-17.78	54.0	-26.31	AV	314.00	100	Horizontal	Pass
2	2402.100	103.61	-12.87	74.0	29.61	Peak	312.00	100	Horizontal	N/A
2**	2402.100	97.62	-12.87	54.0	43.62	AV	312.00	100	Horizontal	N/A
3	2796.600	48.77	-10.94	74.0	-25.23	Peak	190.00	100	Horizontal	Pass
3**	2796.600	31.25	-10.94	54.0	-22.75	AV	190.00	100	Horizontal	Pass
4	5767.500	53.69	-0.44	74.0	-20.31	Peak	105.00	100	Horizontal	Pass
4**	5767.500	45.63	-0.44	54.0	-8.37	AV	105.00	100	Horizontal	Pass
5	9636.000	48.76	-3.14	74.0	-25.24	Peak	205.00	100	Horizontal	Pass
5**	9636.000	40.19	-3.14	54.0	-13.81	AV	205.00	100	Horizontal	Pass
6	13095.999	52.18	0.34	74.0	-21.82	Peak	72.00	100	Horizontal	Pass
6**	13095.999	42.19	0.34	54.0	-11.81	AV	72.00	100	Horizontal	Pass

π/4-DQPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.200	43.15	-17.78	74.0	-30.85	Peak	61.00	100	Vertical	Pass
1**	1599.200	31.66	-17.78	54.0	-22.34	AV	61.00	100	Vertical	Pass
2	2440.900	99.22	-12.90	74.0	25.22	Peak	240.00	100	Vertical	N/A
2**	2440.900	91.49	-12.90	54.0	37.49	AV	240.00	100	Vertical	N/A
3	3725.500	55.92	-3.90	74.0	-18.08	Peak	62.00	100	Vertical	Pass
3**	3725.500	37.77	-3.90	54.0	-16.23	AV	62.00	100	Vertical	Pass
4	5594.000	52.65	-2.06	74.0	-21.35	Peak	216.00	100	Vertical	Pass
4**	5594.000	40.68	-2.06	54.0	-13.32	AV	216.00	100	Vertical	Pass
5	10550.000	50.11	-2.64	74.0	-23.89	Peak	143.00	100	Vertical	Pass
5**	10550.000	40.97	-2.64	54.0	-13.03	AV	143.00	100	Vertical	Pass
6	14610.500	52.35	0.79	74.0	-21.65	Peak	352.00	100	Vertical	Pass
6**	14610.500	42.57	0.79	54.0	-11.43	AV	352.00	100	Vertical	Pass

π/4-DQPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1729.100	43.74	-17.43	74.0	-30.26	Peak	289.00	100	Horizontal	Pass
1**	1729.100	40.43	-17.43	54.0	-13.57	AV	289.00	100	Horizontal	Pass
2	2440.800	100.21	-12.89	74.0	26.21	Peak	310.00	100	Horizontal	N/A
2**	2440.800	88.74	-12.89	54.0	34.74	AV	310.00	100	Horizontal	N/A
3	2820.800	45.67	-11.13	74.0	-28.33	Peak	192.00	100	Horizontal	Pass
3**	2820.800	33.63	-11.13	54.0	-20.37	AV	192.00	100	Horizontal	Pass
4	7322.250	54.41	1.24	74.0	-19.59	Peak	306.00	100	Horizontal	Pass
4**	7322.250	44.94	1.24	54.0	-9.06	AV	306.00	100	Horizontal	Pass
5	8905.000	49.10	-3.26	74.0	-24.90	Peak	0.00	100	Horizontal	Pass
5**	8905.000	39.45	-3.26	54.0	-14.55	AV	0.00	100	Horizontal	Pass
6	15170.500	52.36	0.29	74.0	-21.64	Peak	95.00	100	Horizontal	Pass
6**	15170.500	41.82	0.29	54.0	-12.18	AV	95.00	100	Horizontal	Pass

π/4-DQPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1729.100	42.19	-17.43	74.0	-31.81	Peak	195.00	100	Vertical	Pass
1**	1729.100	37.36	-17.43	54.0	-16.64	AV	195.00	100	Vertical	Pass
2	2479.900	98.20	-12.61	74.0	24.20	Peak	308.00	100	Vertical	N/A
2**	2479.900	88.70	-12.61	54.0	34.70	AV	308.00	100	Vertical	N/A
3	2790.900	52.30	-10.69	74.0	-21.70	Peak	184.00	100	Vertical	Pass
3**	2790.900	37.66	-10.69	54.0	-16.34	AV	184.00	100	Vertical	Pass
4	3725.500	50.38	-3.90	74.0	-23.62	Peak	208.00	100	Vertical	Pass
4**	3725.500	37.78	-3.90	54.0	-16.22	AV	208.00	100	Vertical	Pass
5	6865.500	54.72	1.04	74.0	-19.28	Peak	318.00	100	Vertical	Pass
5**	6865.500	44.18	1.04	54.0	-9.82	AV	318.00	100	Vertical	Pass
6	12781.000	51.54	-1.53	74.0	-22.46	Peak	0.00	100	Vertical	Pass
6**	12781.000	42.07	-1.53	54.0	-11.93	AV	0.00	100	Vertical	Pass

π/4-DQPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1599.800	42.38	-17.78	74.0	-31.62	Peak	58.00	100	Horizontal	Pass
1**	1599.800	27.41	-17.78	54.0	-26.59	AV	58.00	100	Horizontal	Pass
2	2479.700	93.82	-12.62	74.0	19.82	Peak	248.00	100	Horizontal	N/A
2**	2479.700	90.69	-12.62	54.0	36.69	AV	248.00	100	Horizontal	N/A
3	2790.000	51.61	-10.65	74.0	-22.39	Peak	151.00	100	Horizontal	Pass
3**	2790.000	43.21	-10.65	54.0	-10.79	AV	151.00	100	Horizontal	Pass
4	5591.750	52.68	-2.09	74.0	-21.32	Peak	250.00	100	Horizontal	Pass
4**	5591.750	40.84	-2.09	54.0	-13.16	AV	250.00	100	Horizontal	Pass
5	10857.500	50.03	-2.11	74.0	-23.97	Peak	21.00	100	Horizontal	Pass
5**	10857.500	40.24	-2.11	54.0	-13.76	AV	21.00	100	Horizontal	Pass
6	15259.000	52.72	0.78	74.0	-21.28	Peak	1.00	100	Horizontal	Pass
6**	15259.000	43.89	0.78	54.0	-10.11	AV	1.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1594.000	42.18	-16.63	74.0	-31.82	Peak	158.00	100	Vertical	Pass
1**	1594.000	22.86	-16.63	54.0	-31.14	AV	158.00	100	Vertical	Pass
2	2402.000	100.00	-12.10	74.0	26.00	Peak	95.00	100	Vertical	N/A
2**	2402.000	94.05	-12.10	54.0	40.05	AV	95.00	100	Vertical	N/A
3	3197.000	49.66	-6.66	74.0	-24.34	Peak	64.00	100	Vertical	Pass
3**	3197.000	31.83	-6.66	54.0	-22.17	AV	64.00	100	Vertical	Pass
4	4786.000	53.92	-2.62	74.0	-20.08	Peak	110.00	100	Vertical	Pass
4**	4786.000	33.14	-2.62	54.0	-20.86	AV	110.00	100	Vertical	Pass
5	9271.500	47.60	3.57	74.0	-26.40	Peak	157.00	100	Vertical	Pass
5**	9271.500	38.34	3.57	54.0	-15.66	AV	157.00	100	Vertical	Pass
6	14587.250	53.47	12.38	74.0	-20.53	Peak	360.00	100	Vertical	Pass
6**	14587.250	45.19	12.38	54.0	-8.81	AV	360.00	100	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.500	39.64	-16.61	74.0	-34.36	Peak	228.00	100	Horizontal	Pass
1**	1596.500	23.42	-16.61	54.0	-30.58	AV	228.00	100	Horizontal	Pass
2	2402.000	101.91	-12.10	74.0	27.91	Peak	148.00	100	Horizontal	N/A
2**	2402.000	97.42	-12.10	54.0	43.42	AV	148.00	100	Horizontal	N/A
3	3198.000	48.30	-6.78	74.0	-25.70	Peak	129.00	100	Horizontal	Pass
3**	3198.000	30.03	-6.78	54.0	-23.97	AV	129.00	100	Horizontal	Pass
4	6726.000	50.91	2.15	74.0	-23.09	Peak	349.00	100	Horizontal	Pass
4**	6726.000	39.96	2.15	54.0	-14.04	AV	349.00	100	Horizontal	Pass
5	11224.001	50.12	6.92	74.0	-23.88	Peak	199.00	100	Horizontal	Pass
5**	11224.001	40.12	6.92	54.0	-13.88	AV	199.00	100	Horizontal	Pass
6	14636.750	53.82	12.01	74.0	-20.18	Peak	106.00	100	Horizontal	Pass
6**	14636.750	43.44	12.01	54.0	-10.56	AV	106.00	100	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.000	40.15	-16.53	74.0	-33.85	Peak	145.00	100	Vertical	Pass
1**	1596.000	24.41	-16.53	54.0	-29.59	AV	145.00	100	Vertical	Pass
2	2441.000	100.69	-12.31	74.0	26.69	Peak	115.00	100	Vertical	N/A
2**	2441.000	97.35	-12.31	54.0	43.35	AV	115.00	100	Vertical	N/A
3	3195.000	47.38	-6.81	74.0	-26.62	Peak	360.00	100	Vertical	Pass
3**	3195.000	30.44	-6.81	54.0	-23.56	AV	360.00	100	Vertical	Pass
4	4788.000	48.18	-2.76	74.0	-25.82	Peak	124.00	100	Vertical	Pass
4**	4788.000	33.97	-2.76	54.0	-20.03	AV	124.00	100	Vertical	Pass
5	11537.500	49.85	6.91	74.0	-24.15	Peak	247.00	100	Vertical	Pass
5**	11537.500	39.62	6.91	54.0	-14.38	AV	247.00	100	Vertical	Pass
6	14581.750	53.34	12.24	74.0	-20.66	Peak	19.00	100	Vertical	Pass
6**	14581.750	44.31	12.24	54.0	-9.69	AV	19.00	100	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.500	38.53	-16.28	74.0	-35.47	Peak	104.00	100	Horizontal	Pass
1**	1598.500	24.33	-16.28	54.0	-29.67	AV	104.00	100	Horizontal	Pass
2	2441.000	101.91	-12.31	74.0	27.91	Peak	133.00	100	Horizontal	N/A
2**	2441.000	96.18	-12.31	54.0	42.18	AV	133.00	100	Horizontal	N/A
3	3191.000	46.06	-7.49	74.0	-27.94	Peak	152.00	100	Horizontal	Pass
3**	3191.000	30.38	-7.49	54.0	-23.62	AV	152.00	100	Horizontal	Pass
4	6858.000	51.41	2.62	74.0	-22.59	Peak	211.00	100	Horizontal	Pass
4**	6858.000	39.90	2.62	54.0	-14.10	AV	211.00	100	Horizontal	Pass
5	11389.000	49.71	6.74	74.0	-24.29	Peak	226.00	100	Horizontal	Pass
5**	11389.000	40.72	6.74	54.0	-13.28	AV	226.00	100	Horizontal	Pass
6	14570.750	53.34	11.86	74.0	-20.66	Peak	351.00	100	Horizontal	Pass
6**	14570.750	43.36	11.86	54.0	-10.64	AV	351.00	100	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.500	39.75	-16.43	74.0	-34.25	Peak	289.00	100	Vertical	Pass
1**	1595.500	25.11	-16.43	54.0	-28.89	AV	289.00	100	Vertical	Pass
2	2480.000	98.30	-11.65	74.0	24.30	Peak	97.00	100	Vertical	N/A
2**	2480.000	92.27	-11.65	54.0	38.27	AV	97.00	100	Vertical	N/A
3	3191.000	50.63	-7.49	74.0	-23.37	Peak	343.00	100	Vertical	Pass
3**	3191.000	35.56	-7.49	54.0	-18.44	AV	343.00	100	Vertical	Pass
4	4785.000	51.57	-2.75	74.0	-22.43	Peak	108.00	100	Vertical	Pass
4**	4785.000	33.14	-2.75	54.0	-20.86	AV	108.00	100	Vertical	Pass
5	5984.000	54.01	-0.74	74.0	-19.99	Peak	11.00	100	Vertical	Pass
5**	5984.000	41.33	-0.74	54.0	-12.67	AV	11.00	100	Vertical	Pass
6	14416.750	54.98	11.02	74.0	-19.02	Peak	360.00	100	Vertical	Pass
6**	14416.750	43.42	11.02	54.0	-10.58	AV	360.00	100	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1596.000	37.70	-16.53	74.0	-36.30	Peak	98.00	100	Horizontal	Pass
1**	1596.000	24.06	-16.53	54.0	-29.94	AV	98.00	100	Horizontal	Pass
2	2480.000	100.16	-11.65	74.0	26.16	Peak	142.00	100	Horizontal	N/A
2**	2480.000	94.69	-11.65	54.0	40.69	AV	142.00	100	Horizontal	N/A
3	3200.000	48.98	-6.82	74.0	-25.02	Peak	101.00	100	Horizontal	Pass
3**	3200.000	30.80	-6.82	54.0	-23.20	AV	101.00	100	Horizontal	Pass
4	6381.000	49.67	1.33	74.0	-24.33	Peak	58.00	100	Horizontal	Pass
4**	6381.000	38.44	1.33	54.0	-15.56	AV	58.00	100	Horizontal	Pass
5	9950.750	48.12	6.10	74.0	-25.88	Peak	84.00	100	Horizontal	Pass
5**	9950.750	39.11	6.10	54.0	-14.89	AV	84.00	100	Horizontal	Pass
6	14587.250	53.88	12.38	74.0	-20.12	Peak	339.00	100	Horizontal	Pass
6**	14587.250	43.85	12.38	54.0	-10.15	AV	339.00	100	Horizontal	Pass

Hopping Mode:

GFSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1868.000	39.63	-14.84	74.0	-34.37	Peak	21.00	100	Vertical	Pass
1**	1868.000	25.85	-14.84	54.0	-28.15	AV	21.00	100	Vertical	Pass
2	2402.500	98.67	-12.07	74.0	24.67	Peak	152.00	100	Vertical	N/A
2**	2402.500	81.80	-12.07	54.0	27.80	AV	152.00	100	Vertical	N/A
3	2478.500	61.66	-11.67	74.0	-12.34	Peak	37.00	100	Vertical	N/A
3**	2478.500	89.60	-11.67	54.0	35.60	AV	37.00	100	Vertical	N/A
4	4763.000	46.98	-2.72	74.0	-27.02	Peak	219.00	100	Vertical	Pass
4**	4763.000	35.09	-2.72	54.0	-18.91	AV	219.00	100	Vertical	Pass
5	10022.250	48.77	6.56	74.0	-25.23	Peak	0.00	100	Vertical	Pass
5**	10022.250	38.60	6.56	54.0	-15.40	AV	0.00	100	Vertical	Pass
6	14612.000	53.48	12.21	74.0	-20.52	Peak	213.00	100	Vertical	Pass
6**	14612.000	43.43	12.21	54.0	-10.57	AV	213.00	100	Vertical	Pass

GFSK MODE 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1517.000	36.77	-16.13	74.0	-37.23	Peak	360.00	100	Horizontal	Pass
1**	1517.000	26.09	-16.13	54.0	-27.91	AV	360.00	100	Horizontal	Pass
2	2403.000	100.62	-12.19	74.0	26.62	Peak	360.00	100	Horizontal	N/A
2**	2403.000	95.69	-12.19	54.0	41.69	AV	360.00	100	Horizontal	N/A
3	2479.500	39.61	-11.57	74.0	-34.39	Peak	38.00	100	Horizontal	N/A
3**	2479.500	95.35	-11.57	54.0	41.35	AV	38.00	100	Horizontal	N/A
4	5761.000	50.14	-0.79	74.0	-23.86	Peak	242.00	100	Horizontal	Pass
4**	5761.000	39.62	-0.79	54.0	-14.38	AV	242.00	100	Horizontal	Pass
5	9527.250	47.04	4.83	74.0	-26.96	Peak	293.00	100	Horizontal	Pass
5**	9527.250	37.59	4.83	54.0	-16.41	AV	293.00	100	Horizontal	Pass
6	14400.250	52.82	11.78	74.0	-21.18	Peak	122.00	100	Horizontal	Pass
6**	14400.250	43.58	11.78	54.0	-10.42	AV	122.00	100	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1595.300	42.39	-17.77	74.0	-31.61	Peak	57.00	100	Vertical	Pass
1**	1595.300	32.56	-17.77	54.0	-21.44	AV	57.00	100	Vertical	Pass
2	2403.700	87.70	-12.85	74.0	13.70	Peak	268.00	100	Vertical	N/A
2**	2403.700	86.08	-12.85	54.0	32.08	AV	268.00	100	Vertical	N/A
3	2479.800	94.22	-12.62	74.0	20.22	Peak	245.00	100	Vertical	N/A
3**	2479.800	92.58	-12.62	54.0	38.58	AV	245.00	100	Vertical	N/A
4	3195.500	54.22	-7.96	74.0	-19.78	Peak	74.00	100	Vertical	Pass
4**	3195.500	43.06	-7.96	54.0	-10.94	AV	74.00	100	Vertical	Pass
5	6670.000	53.39	0.42	74.0	-20.61	Peak	195.00	100	Vertical	Pass
5**	6670.000	44.02	0.42	54.0	-9.98	AV	195.00	100	Vertical	Pass
6	13705.500	52.38	1.03	74.0	-21.62	Peak	19.00	100	Vertical	Pass
6**	13705.500	41.87	1.03	54.0	-12.13	AV	19.00	100	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1718.800	47.59	-17.66	74.0	-26.41	Peak	271.00	100	Horizontal	Pass
1**	1718.800	42.13	-17.66	54.0	-11.87	AV	271.00	100	Horizontal	Pass
2	2401.500	98.56	-12.88	74.0	24.56	Peak	154.00	100	Horizontal	N/A
2**	2401.500	94.07	-12.88	54.0	40.07	AV	154.00	100	Horizontal	N/A
3	2476.100	89.54	-12.75	74.0	15.54	Peak	332.00	100	Horizontal	N/A
3**	2476.100	87.86	-12.75	54.0	33.86	AV	332.00	100	Horizontal	N/A
4	4737.250	50.16	-1.60	74.0	-23.84	Peak	79.00	100	Horizontal	Pass
4**	4737.250	41.52	-1.60	54.0	-12.48	AV	79.00	100	Horizontal	Pass
5	9632.500	49.21	-3.06	74.0	-24.79	Peak	293.00	100	Horizontal	Pass
5**	9632.500	40.62	-3.06	54.0	-13.38	AV	293.00	100	Horizontal	Pass
6	13135.500	52.06	0.20	74.0	-21.94	Peak	360.00	100	Horizontal	Pass
6**	13135.500	41.88	0.20	54.0	-12.12	AV	360.00	100	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1466.000	36.82	-16.18	74.0	-37.18	Peak	159.00	100	Vertical	Pass
1**	1466.000	25.28	-16.18	54.0	-28.72	AV	159.00	100	Vertical	Pass
2	2404.000	91.79	-11.86	74.0	17.79	Peak	344.00	100	Vertical	N/A
2**	2404.000	85.54	-11.86	54.0	31.54	AV	344.00	100	Vertical	N/A
3	2477.500	90.29	-11.66	74.0	16.29	Peak	360.00	100	Vertical	N/A
3**	2477.500	84.91	-11.66	54.0	30.91	AV	360.00	100	Vertical	N/A
4	3189.000	46.04	-7.51	74.0	-27.96	Peak	51.00	100	Vertical	Pass
4**	3189.000	30.38	-7.51	54.0	-23.62	AV	51.00	100	Vertical	Pass
5	6624.000	51.22	2.89	74.0	-22.78	Peak	0.00	100	Vertical	Pass
5**	6624.000	38.68	2.89	54.0	-15.32	AV	0.00	100	Vertical	Pass
6	14581.750	53.22	12.24	74.0	-20.78	Peak	360.00	100	Vertical	Pass
6**	14581.750	44.59	12.24	54.0	-9.41	AV	360.00	100	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1339.000	36.26	-15.62	74.0	-37.74	Peak	214.00	100	Horizontal	Pass
1**	1339.000	25.88	-15.62	54.0	-28.12	AV	214.00	100	Horizontal	Pass
2	2404.000	99.54	-11.86	74.0	25.54	Peak	0.00	100	Horizontal	N/A
2**	2404.000	64.43	-11.86	54.0	10.43	AV	0.00	100	Horizontal	N/A
3	2477.500	59.68	-11.66	74.0	-14.32	Peak	60.00	100	Horizontal	N/A
3**	2477.500	79.68	-11.66	54.0	25.68	AV	60.00	100	Horizontal	N/A
4	4002.000	44.25	-5.04	74.0	-29.75	Peak	62.00	100	Horizontal	Pass
4**	4002.000	31.73	-5.04	54.0	-22.27	AV	62.00	100	Horizontal	Pass
5	10033.250	48.80	6.50	74.0	-25.20	Peak	0.00	100	Horizontal	Pass
5**	10033.250	38.95	6.50	54.0	-15.05	AV	0.00	100	Horizontal	Pass
6	14595.500	54.49	12.45	74.0	-19.51	Peak	196.00	100	Horizontal	Pass
6**	14595.500	44.27	12.45	54.0	-9.73	AV	196.00	100	Horizontal	Pass

A.9 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Data

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390.00	55.901	32	74	18.099	PEAK	Pass
		2390.00	43.286	32	54	10.714	AVERAGE	Pass
GFSK	HIGH	2483.50	54.866	32	74	19.134	PEAK	Pass
		2483.50	43.051	32	54	10.949	AVERAGE	Pass
π/4-DQPSK	Low	2390.00	54.397	32	74	19.603	PEAK	Pass
		2390.00	44.010	32	54	9.99	AVERAGE	Pass
π/4-DQPSK	HIGH	2483.50	56.523	32	74	17.477	PEAK	Pass
		2483.50	46.257	32	54	7.743	AVERAGE	Pass
8-DPSK	Low	2390.00	55.939	32	74	18.061	PEAK	Pass
		2390.00	43.358	32	54	10.642	AVERAGE	Pass
8-DPSK	HIGH	2483.50	55.523	32	74	18.477	PEAK	Pass
		2483.50	43.180	32	54	10.820	AVERAGE	Pass
GFSK(Hopping)	Low	2390.00	55.962	32	74	18.038	PEAK	Pass
		2390.00	43.242	32	54	10.758	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.50	55.097	32	74	18.903	PEAK	Pass
		2483.50	42.972	32	54	11.028	AVERAGE	Pass
π/4-DQPSK (Hopping)	Low	2390.00	54.440	32	74	19.560	PEAK	Pass
		2390.00	44.201	32	54	9.799	AVERAGE	Pass
π/4-DQPSK (Hopping)	HIGH	2483.50	54.851	32	74	19.149	PEAK	Pass
		2483.50	44.241	32	54	9.759	AVERAGE	Pass
8-DPSK (Hopping)	Low	2390.00	56.739	32	74	17.261	PEAK	Pass
		2390.00	43.329	32	54	10.671	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	2483.50	55.138	32	74	18.862	PEAK	Pass
		2483.50	42.995	32	54	11.005	AVERAGE	Pass

Test Plots

GFSK LOW CHANNEL, PEAK



GFSK LOW CHANNEL, AV

GFSK HIGH CHANNEL, PEAK



GFSK HIGH CHANNEL, AV

π/4-DQPSK LOW CHANNEL, PEAK

π/4-DQPSK LOW CHANNEL, AV

π/4-DQPSK HIGH CHANNEL, PEAK

π/4-DQPSK HIGH CHANNEL, AV

8-DPSK LOW CHANNEL, PEAK



8-DPSK LOW CHANNEL, AV

8-DPSK HIGH CHANNEL, PEAK

8-DPSK HIGH CHANNEL, AV



Hopping Mode:

GFSK LOW FREQUENCY BAND, PEAK



GFSK LOW FREQUENCY BAND, AV



GFSK HIGH FREQUENCY BAND, PEAK

GFSK HIGH FREQUENCY BAND, AV



π/4-DQPSK LOW FREQUENCY BAND, PEAK

π/4-DQPSK LOW FREQUENCY BAND, AV

π/4-DQPSK HIGH FREQUENCY BAND, PEAK



π/4-DQPSK HIGH FREQUENCY BAND, AV

8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, AV



8-DPSK HIGH FREQUENCY BAND, PEAK

8-DPSK HIGH FREQUENCY BAND, AV



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-EC2170804-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-EC2170804-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-EC2170804-AI.PDF”.

--END OF REPORT--