FCC TEST REPORT

Product Name:	Temperature Reading Device
Trade Mark:	weber
Model No.:	WEBER IGRILL 2
Report Number:	180601009RFC-1
Test Standards:	FCC 47 CFR Part 15 Subpart C RSS-247 Issue 2 RSS-Gen Issue 5
FCC ID:	2AHSR-V202
IC:	21267-V202
HVIN:	WEBER IGRILL 2
Test Result:	PASS
Date of Issue:	June 19, 2018

Prepared for:

Weber-Stephen Products LLC
1415 S. Roselle Road Palatine, IL 60067 USA

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park,
Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Tested by: Henry Lu
Project Engineer

Reviewed by: Kevin Liang
Assistant Manager

Approved by: Billy Li
Technical Director

Date: June 19, 2018

UnionTrust Laboratories UnionTrust * Certified *

Version

Version No.	Date	Description
V1.0	June 19, 2018	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 4
   1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 4
   1.4 OTHER INFORMATION 4
   1.5 DESCRIPTION OF SUPPORT UNITS 5
   1.6 TEST LOCATION 5
   1.7 TEST FACILITY 5
   1.8 DEVIATION FROM STANDARDS 5
   1.9 ABNORMALITIES FROM STANDARD CONDITIONS 5
   1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 6
   1.11 MEASUREMENT UNCERTAINTY 6
2. TEST SUMMARY 7
3. EQUIPMENT LIST 8
4. TEST CONFIGURATION 9
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 9
   4.2 TEST CHANNELS 9
   4.3 EUT TEST STATUS 9
   4.4 TEST SETUP 10
      4.1.1 FOR RADIATED EMISSIONS TEST SETUP 10
      4.1.2 FOR CONDUCTED RF TEST SETUP 11
   4.5 SYSTEM TEST CONFIGURATION 12
   4.6 DUTY CYCLE 13
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION 14
   5.1 REFERENCE DOCUMENTS FOR TESTING 14
   5.2 ANTENNA REQUIREMENT 14
   5.3 CONDUCTED PEAK OUTPUT POWER 15
   5.4 6 DB BANDWIDTH 16
   5.5 POWER SPECTRAL DENSITY 19
   5.6 CONDUCTED OUT OF BAND EMISSION 22
   5.7 RADIATED SPURIOUS EMISSIONS 24
   5.8 BAND EDGE MEASUREMENTS (RADIATED) 28
APPENDIX 1 PHOTOS OF TEST SETUP 31
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 31

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Weber-Stephen Products LLC
Address of Applicant:	1415 S. Roselle Road Palatine, IL 60067 USA
Manufacturer:	EWIG Industries LTD - Dong Guan Factory
Address of Manufacturer:	Yin Shan District, Fu Gang Village, Xiang Mang West Road Qing Xi, Dong Guan, China 523658

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	Temperature Reading Device	
Model No.:	WEBER IGRILL 2	
Add. Model No.:	N/A	
Trade Mark:	weber	
DUT Stage:	Identical Prototype	
EUT Supports Function:	2.4 GHz ISM Band:	Bluetooth: V4.0 (Only LE)
Sample Received Date:	June 1, 2018	
Sample Tested Date:	June 1, 2018 to June 2, 2018	

1.2.2 Description of Accessories

Colored Probe Indicator * 4	
Length:	1.20 Meter
Cable Type:	Shielded without ferrite

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Operational Frequency Band	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth V4.0 LE
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Antenna Type:	PCB Antenna
Antenna Gain:	2.4 dBi
Maximum Peak Power:	2.18 dBm
Normal Test Voltage:	3.0 V (2 x size “AA” batteries)

1.4 OTHER INFORMATION

Operation Frequency Each of Channel	
f = 2402 + 2k MHz, k = 0,…,39	
Note:	
f	is the operating frequency (MHz);
k	is the operating channel.

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
Notebook	Lenovo	E450	SL10G10780	UnionTrust

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

IC-Registration No.: 21600-1
The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013	N/A[NOTE1, 2]
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3) RSS-247 Issue 2, Section 5.4(d)	KDB 558074 D01 v04, Section 9.1.3	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2) RSS-247 Issue 2, Section 5.2(a)	KDB 558074 D01 v04, Section 8.1	PASS
Occupied Bandwidth	RSS-Gen section 6.7	RSS-Gen section 6.6	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e) RSS-247 Issue 2, Section 5.2(b)	KDB 558074 D01 v04, Section 10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d) RSS-247 Issue 2, Section 5.5	KDB 558074 D01 v04, Section 11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-Gen Issue 5, Section 6.13/8.9/8.10	KDB 558074 D01 v04, Section 12.1	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209 RSS-247 Issue 2, Section 5.5	KDB 558074 D01 v04, Section 12.1	PASS

Note:

1) N/A: In this whole report not application.
2) The EUT is powered by 2 x size “AA” batteries.

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm dd, yyyy)**	**Cal. Due date (mm dd, yyyy)**
☑	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 20, 2015	Dec. 19, 2018
☑	Receiver	R&S	ESIB26	100114	Dec. 10, 2017	Dec. 10, 2018
☑	Loop Antenna	ETS-LINDGREN	6502	00202525	Dec. 22, 2017	Dec. 22, 2018
☑	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Dec. 17, 2017	Dec. 17, 2018
☑	Preamplifier	HP	8447F	2805A02960	Dec. 10, 2017	Dec. 10, 2018
☑	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	Dec. 17, 2017	Dec. 17, 2018
☑	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Dec. 17, 2017	Dec. 17, 2018
☑	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☑	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	Jun. 21, 2017	Jun. 21, 2018
☑	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	**Equipment**	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm dd, yyyy)**	**Cal. Due date (mm dd, yyyy)**
☑	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec. 10, 2017	Dec. 10, 2018
☑	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Dec. 10, 2017	Dec. 10, 2018

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	3.0 V (2 x size "AA" batteries)	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.2 TEST CHANNELS

Type of Modulation	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
GFSK	2402 MHz to 2480 MHz	Channel 0	Channel 19	Channel 39
		2402 MHz	2440 MHz	2480 MHz

4.3 EUT TEST STATUS

Type of Modulation	Tx Function	Description
GFSK	1Tx	1. Keep the EUT in continuously transmitting with modulation test single.

Power Setting
Power Setting: not applicable, test used software default power level.

Test Software
Test software name: N/A

4.4 TEST SETUP

4.1.1 For Radiated Emissions test setup

Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz



4.1.2 For Conducted RF test setup



4.5 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.0 V (2 x size “AA” batteries). Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.6 DUTY CYCLE

Type of Modulation	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
GFSK	0.3828	0.6249	0.61	61.26	2.13	2.61	-4.26

Remark:

1) Duty cycle= On Time/ Period;
2) Duty Cycle factor = 10 * log(1/ Duty cycle);
3) Average factor = 20 $\log_{10}$ Duty Cycle.

The test plot as follows

GFSK



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
4	KDB 558074 D01 DTS Meas Guidance v04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
5	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
6	RSS-247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.247(b) (4) requirement:** The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:
Antenna in the interior of the equipment and no consideration of replacement. The gain of the antenna is 2.4 dBi.

5.3 CONDUCTED PEAK OUTPUT POWER

Test Requirement: FCC 47 CFR Part 15 Subpart C Section15.247 (b)(3)
RSS-247 Issue 2, Section 5.4(d)

Test Method: KDB 558074 D01 v04, Section 9.1.3

Limit: For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak or average output power, record the power level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Type of Modulation	Channel	Frequency (MHz)	Maximum Conducted Peak Power (dBm)	Maximum Conducted Peak Power (mW)
GFSK	0	2402	**2.18**	**1.65**
	19	2440	2.08	1.61
	39	2480	1.84	1.53

Note: The antenna gain of 2.4 dBi less than 6 dBi maximum permission antenna gain value based on 1 watt peak output power limit.

5.46 DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)
RSS-247 Issue 2, Section 5.2(a)
RSS-Gen Issue 5, Section 6.7

Test Method: KDB 558074 D01 v04, Section 8.1

Limit: For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:
a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 x RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Type of Modulation	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
GFSK	0	2402	0.7120	1.0958	> 500 kHz	Pass
	19	2440	0.7157	1.0949	> 500 kHz	Pass
	39	2480	0.7093	1.0948	> 500 kHz	Pass

The test plot as follows:

Lowest Channel



Middle Channel



Highest Channel

5.5 POWER SPECTRAL DENSITY

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247 (e)
RSS-247 Issue 2, Section 5.2(b)

Test Method: KDB 558074 D01 v04, Section 10.2

Limit: For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

Type of Modulation	Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Result (Pass / Fail)
GFSK	0	2402	-12.722	8	Pass
	19	2440	-12.269	8	Pass
	39	2480	-12.381	8	Pass

The test plot as follows:

Lowest Channel

Middle Channel

Highest Channel

5.6 CONDUCTED OUT OF BAND EMISSION

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.247(d)
RSS-247 Issue 2, Section 5.5

Test Method: KDB 558074 D01 v04, Section 11

Limit: In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

Test Procedure: Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
Use the following spectrum analyzer settings:

Step 1:Measurement Procedure REF

a) Set instrument center frequency to DTS channel center frequency.
b) Set the span to ≥ 1.5 times the DTS bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ 3 x RBW.
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.
j) Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

Step 2:Measurement Procedure OOBE

a) Set RBW = 100 kHz.
b) Set VBW ≥ 300 kHz.
c) Detector = peak.
d) Sweep = auto couple.
e) Trace Mode = max hold.
f) Allow trace to fully stabilize.
g) Use the peak marker function to determine the maximum amplitude level.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.4.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data:

The test plot as follows:

In-Band Reference Level	Out of Band Emission
Lowest Channel	
	
Middle Channel	
	
Highest Channel	
	

5.7 RADIATED SPURIOUS EMISSIONS

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: KDB 558074 D01 v04, Section 12.1

Receiver Setup:

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

Limits:

Spurious Emissions

Frequency	Field strength (microvolt/meter)	Limit (dBμV/m)	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

Remark:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

1. From 30 MHz to 1GHz test procedure as below:

1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

2. Above 1GHz test procedure as below:

1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).
2) Test the EUT in the lowest channel ,middle channel, the Highest channel

3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the Y axis positioning which it is worse case.
4) Repeat above procedures until all frequencies measured was complete.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Radiated Emission Test Data (9 KHz ~ 30 MHz):
The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

Radiated Emission Test Data (30 MHz ~ 1 GHz):
Worst-Case Configuration

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	43.233	27.26	-17.73	9.53	40.00	-30.47	QP
2*	160.885	26.86	-15.78	11.08	43.50	-32.42	QP
3	607.181	26.95	-3.47	23.48	46.00	-22.52	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	47.369	27.86	-19.20	8.66	40.00	-31.34	QP
2*	156.426	28.14	-16.20	11.94	43.50	-31.56	QP
3	488.326	27.55	-5.70	21.85	46.00	-24.15	QP

Radiated Emission Test Data (Above 1GHz):

Lowest Channel:

No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4804.00	54.16	74.00	-19.84	Peak	Horizontal
2	4804.00	34.56	54.00	-19.44	Average	Horizontal
3	7206.00	63.03	74.00	-10.97	Peak	Horizontal
4	7206.00	41.67	54.00	-12.33	Average	Horizontal
5	9608.00	47.83	74.00	-26.17	Peak	Horizontal
6	9608.00	35.06	54.00	-18.94	Average	Horizontal
7	4804.00	53.41	74.00	-20.59	Peak	Vertical
8	4804.00	33.74	54.00	-20.26	Average	Vertical
9	7206.00	62.87	74.00	-11.13	Peak	Vertical
10	7206.00	41.11	54.00	-12.89	Average	Vertical
11	9608.00	47.21	74.00	-26.79	Peak	Vertical
12	9608.00	34.62	54.00	-19.38	Average	Vertical

Middle Channel:

No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4880.00	54.40	74.00	-19.60	Peak	Horizontal
2	4880.00	35.56	54.00	-18.44	Average	Horizontal
3	7320.00	61.82	74.00	-12.18	Peak	Horizontal
4	7320.00	40.06	54.00	-13.94	Average	Horizontal
5	9760.00	47.53	74.00	-26.47	Peak	Horizontal
6	9760.00	35.06	54.00	-18.94	Average	Horizontal
7	4880.00	54.43	74.00	-19.57	Peak	Vertical
8	4880.00	35.32	54.00	-18.68	Average	Vertical
9	7320.00	61.69	74.00	-12.31	Peak	Vertical
10	7320.00	39.61	54.00	-14.39	Average	Vertical
11	9760.00	47.63	74.00	-26.37	Peak	Vertical
12	9760.00	34.62	54.00	-19.38	Average	Vertical

Highest Channel:

No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4960.00	54.24	74.00	-19.76	Peak	Horizontal
2	4960.00	34.72	54.00	-19.28	Average	Horizontal
3	7440.00	60.90	74.00	-13.10	Peak	Horizontal
4	7440.00	39.10	54.00	-14.90	Average	Horizontal
5	9920.00	47.73	74.00	-26.27	Peak	Horizontal
6	9920.00	35.06	54.00	-18.94	Average	Horizontal
7	4960.00	46.30	74.00	-27.70	Peak	Vertical
8	4960.00	29.19	54.00	-24.81	Average	Vertical
9	7440.00	58.07	74.00	-15.93	Peak	Vertical
10	7440.00	35.57	54.00	-18.43	Average	Vertical
11	9920.00	47.83	74.00	-26.17	Peak	Vertical
12	9920.00	34.62	54.00	-19.38	Average	Vertical

5.8 BAND EDGE MEASUREMENTS (RADIATED)

Test Requirement: FCC 47 CFR Part 15 Subpart C Section 15.205/15.209
RSS-Gen Issue 5, Section 6.13/8.9/8.10

Test Method: KDB 558074 D01 v04, Section 12.1

Limits:

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dBμV/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

Test Setup: Refer to section 4.4.1 for details.

Test Procedures:

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).

1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The measurement data as follows:

Test Channel:	Lowest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2389.96	62.83	74	33.96	54	Pass

Test Channel:	Lowest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2389.96	53.23	74	28.76	54	Pass

Test Channel:	Highest Channel	Ant. Polar. :	Horizontal



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.53	72.63	74	44.12	54	Pass

Test Channel:	Highest Channel	Ant. Polar. :	Vertical



Frequency (MHz)	Peak level (dBuv/m)	Peak Limit (dBuv/m)	AV level (dBuv/m)	AV Limit (dBuv/m)	Conclusion
2483.53	61.67	74	31.81	54	Pass

APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.