TEST REPORT

Product	:	L400, S400, S500, TS-400, IP400
Trade mark	:	AIPTEK/iBeamBLOCK/hp
Model/Type reference	:	L400 PAD
Serial Number	:	N/A
Report Number	:	EED32I00318001
FCC ID	:	2AHTC-IBBL4
Date of Issue	:	Jul. 14, 2017
Test Standards	:	47 CFR Part 15 Subpart C
Test result	:	PASS

Prepared for:

Global Aiptek Corporation
5F, No. 550, Xianzheng 2nd Rd., Zhubei City, Hsinchu County, Taiwan

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:	Tom- chen Tom chen (Test Project)	Compiled by:	Kevin lan Kevin lan(Project Engineer)
Reviewed by:	Kevin Yang Kevin yang (Reviewer)	Approved by:	Sheek. Luo Sheek Luo (Lab supervisor)
Date:	Jul. 14, 2017		Check No.:2402615206

CENTRE TESTING INTERNATIONAL GROUP CO.,LTD. Report Seal

2 Version

Version No.	Date	Description
00	Jul. 14, 2017	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013	PASS
20dB Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Carrier Frequencies Separation	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Hopping Channel Number	47 CFR Part 15 Subpart C Section 15.247 (b)	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15 Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:
Test according to ANSI C63.4-2014 & ANSI C63.10-2013.
The tested sample(s) and the sample information are provided by the client.

4 Content

1 COVER PAGE 1

2 VERSION 2

3 TEST SUMMARY 3

4 CONTENT 4

5 TEST REQUIREMENT 5

5.1 TEST SETUP 5
5.1.1 For Conducted test setup 5
5.1.2 For Radiated Emissions test setup 5
5.1.3 For Conducted Emissions test setup 6
5.2 TEST ENVIRONMENT 6
5.3 TEST CONDITION 6

6 GENERAL INFORMATION 7

6.1 CLIENT INFORMATION 7
6.2 GENERAL DESCRIPTION OF EUT 7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 7
6.4 DESCRIPTION OF SUPPORT UNITS 8
6.5 TEST LOCATION 8
6.6 DEVIATION FROM STANDARDS 8
6.7 ABNORMALITIES FROM STANDARD CONDITIONS 8
6.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER 8
6.9 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2) 9

7 EQUIPMENT LIST 10

8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION 12

Appendix A): 20dB Occupied Bandwidth 13
Appendix B): Carrier Frequency Separation 17
Appendix C): Dwell Time 21
Appendix D): Hopping Channel Number 25
Appendix E): Conducted Peak Output Power 27
Appendix F): Band-edge for RF Conducted Emissions 31
Appendix G): RF Conducted Spurious Emissions 36
Appendix H) Pseudorandom Frequency Hopping Sequence 43
Appendix I) Antenna Requirement 44
Appendix J) AC Power Line Conducted Emission 45
Appendix K) Restricted bands around fundamental frequency (Radiated) 48
Appendix L) Radiated Spurious Emissions 56

PHOTOGRAPHS OF TEST SETUP 64

PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS 66

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup

Conducted Emissions setup



5.2 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
GFSK / π/4DQPSK / 8DPSK(DH1,DH3,DH5)	2402MHz ~2480 MHz	Channel 1	Channel 40	Channel79
		2402MHz	2441MHz	2480MHz

Test mode:

Pre-scan under all rate at lowest channel 1

Mode	**GFSK**		
packets	**1-DH1**	**1-DH3**	**1-DH5**
Power(dBm)	3.081	3.199	3.284

Mode	π/4DQPSK		
packets	**2-DH1**	**2-DH3**	**2-DH5**
Power(dBm)	5.701	5.798	5.895
Mode	8DPSK		
packets	**3-DH1**	**3-DH3**	**3-DH5**
Power(dBm)	6.099	6.178	6.255

Through Pre-scan, 1-DH5 packet the power is the worst case of GFSK, 2-DH5 packet the power is the worst case of π/4DQPSK, 3-DH5 packet the power is the worst case of 8DPSK,

6 General Information

6.1 Client Information

Applicant:	Global Aiptek Corporation
Address of Applicant:	5F, No. 550, Xianzheng 2nd Rd., Zhubei City, Hsinchu County, Taiwan
Manufacturer:	Global Aiptek Corporation
Address of Manufacturer:	5F, No. 550, Xianzheng 2nd Rd., Zhubei City, Hsinchu County, Taiwan
Factory:	Shenzhen ACT Industrial Co., Ltd
Address of Factory:	1~8F, No. 5 Building, Beishan Industrial Park, No. 146 Beishan Avenue, Yantian District, Shenzhen City

6.2 General Description of EUT

Product Name:	L400, S400, S500, TS-400, IP400
Model No.(EUT):	L400 PAD
Trade mark:	AIPTEK/iBeamBLOCK/hp
EUT Supports Radios application:	WIFI 2.4GHz 802.11b/g/n(HT20), BT4.0 Dual mode
AC adapter:	MODEL: DSA-42PFB-12 1 120350; Input: 100-240V~50/60Hz, 1.2A; Output: 12V⎓3.5A
Sample Received Date:	Dec. 16, 2016
Sample tested Date:	Dec. 16, 2016 to Jun. 23, 2017

6.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Other than BT4.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, 8DPSK, π/4DQPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	mobile production
Test Power Grade:	N/A
Test Software of EUT:	N/A
Antenna Type:	PIFA Antenna
Antenna Gain:	-4.5dBi
Test Voltage:	AC 120V/60Hz

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz

7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

6.4 Description of Support Units

The EUT has been tested with associated equipment below

Associated equipment name		Manufacture	model	Supplied by
AE1	Projector	Global Aiptek Corporation	L400	Client
AE2	Mobile Power	Global Aiptek Corporation	PB-TS02	Client

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385
No tests were sub-contracted.

6.6 Deviation from Standards

None.

6.7 Abnormalities from Standard Conditions

None.

6.8 Other Information Requested by the Customer

None.

6.9 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.31dB (30MHz-1GHz)
		0.57dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-12.75GHz)
4	Conduction emission	3.6dB (9kHz to 150kHz)
		3.2dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	2.8%
7	DC power voltages	0.025%

7 Equipment List

RF test system					
Equipment	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. Date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
Signal Generator	Keysight	E8257D	MY53401106	03-14-2017	03-13-2018
Spectrum Analyzer	Keysight	N9010A	MY54510339	03-14-2017	03-13-2018
Signal Generator	Keysight	N5182B	MY53051549	03-14-2017	03-13-2018
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	TTF20120439	01-11-2017	01-10-2018
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	003	01-11-2017	01-10-2018
DC Power	Keysight	E3642A	MY54436035	03-14-2017	03-13-2018
power meter & power sensor	R&S	OSP120	101374	03-14-2017	03-13-2018
RF control unit	JS Tonscend	JS0806-2	158060006	03-14-2017	03-13-2018

Conducted disturbance Test					
Equipment	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
Receiver	R&S	ESCI	100009	06-14-2017	06-13-2018
Temperature/ Humidity Indicator	TAYLOR	1451	1905	05-08-2017	05-07-2018
LISN	R&S	ENV216	100098	06-13-2017	06-12-2018
LISN	schwarzbeck	NNLK8121	8121-529	06-13-2017	06-12-2018
Current Probe	R&S	EZ17	100106	06-13-2017	06-12-2018
ISN	TESEQ GmbH	ISN T800	30297	02-23-2017	02-22-2018

3M Semi/full-anechoic Chamber					
Equipment	**Manufacturer**	**Model No.**	**Serial Number**	**Cal. date (mm-dd-yyyy)**	**Cal. Due date (mm-dd-yyyy)**
3M Chamber & Accessory Equipment	TDK	SAC-3	TTE20130797	06-05-2016	06-05-2019
TRILOG Broadband Antenna	SCHWARZBECK	VULB9163	9163-484	05-23-2017	05-22-2018
Microwave Preamplifier	Agilent	8449B	3008A02425	02-16-2017	02-15-2018
Horn Antenna	ETS-LINDGREN	3117	00057407	07-20-2015	07-18-2018
Loop Antenna	ETS	6502	00071730	07-30-2015	07-28-2017
Microwave Preamplifier	A.H.SYSTEMS	PAP-1840-60	6041.6042	06-30-2015	06-28-2018
Horn Antenna	A.H.SYSTEMS	SAS-574 374	374	06-30-2015	06-28-2018
Spectrum Analyzer	R&S	FSP40	100416	06-13-2017	06-12-2018
Receiver	R&S	ESCI	100435	06-14-2017	06-13-2018
LISN	schwarzbeck	NNBM8125	81251547	06-13-2017	06-12-2018
LISN	schwarzbeck	NNBM8125	81251548	06-13-2017	06-12-2018
Signal Generator	Agilent	E4438C	MY45095744	03-14-2017	03-13-2018
Signal Generator	Keysight	E8257D	MY53401106	03-14-2017	03-13-2018
Temperature/ Humidity Indicator	TAYLOR	1451	1905	05-08-2017	05-07-2018
Cable line	Fulai(7M)	SF106	5219/6A	01-11-2017	01-10-2018
Cable line	Fulai(6M)	SF106	5220/6A	01-11-2017	01-10-2018
Cable line	Fulai(3M)	SF106	5216/6A	01-11-2017	01-10-2018
Cable line	Fulai(3M)	SF106	5217/6A	01-11-2017	01-10-2018
Communication test set	R&S	CMW500	152394	03-14-2017	03-13-2018
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	TTF20120439	01-11-2017	01-10-2018
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	003	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX01CA09 CL12-0395-001	TTF20120434	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX01CA08 CL12-0393-001	TTF20120435	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX02CA04 CL12-0396-002	TTF20120436	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX02CA03 CL12-0394-001	TTF20120437	01-11-2017	01-10-2018

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices

Test Results List:

Test requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (a)(1)	ANSI 63.10	20dB Occupied Bandwidth	PASS	Appendix A)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Carrier Frequencies Separation	PASS	Appendix B)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Dwell Time	PASS	Appendix C)
Part15C Section 15.247 (b)	ANSI 63.10	Hopping Channel Number	PASS	Appendix D)
Part15C Section 15.247 (b)(1)	ANSI 63.10	Conducted Peak Output Power	PASS	Appendix E)
Part15C Section 15.247(d)	ANSI 63.10	Band-edge for RF Conducted Emissions	PASS	Appendix F)
Part15C Section 15.247(d)	ANSI 63.10	RF Conducted Spurious Emissions	PASS	Appendix G)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Pseudorandom Frequency Hopping Sequence	PASS	Appendix H)
Part15C Section 15.203/15.247 (c)	ANSI 63.10	Antenna Requirement	PASS	Appendix I)
Part15C Section 15.207	ANSI 63.10	AC Power Line Conducted Emission	PASS	Appendix J)
Part15C Section 15.205/15.209	ANSI 63.10	Restricted bands around fundamental frequency (Radiated) Emission)	PASS	Appendix K)
Part15C Section 15.205/15.209	ANSI 63.10	Radiated Spurious Emissions	PASS	Appendix L)

Appendix A): 20dB Occupied Bandwidth

Test Result

Mode	Channel.	20dB Bandwidth [MHz]	99% OBW [MHz]	Verdict	Remark
GFSK	LCH	1.012	0.91853	PASS	Peak detector
GFSK	MCH	1.009	0.91593	PASS	
GFSK	HCH	1.003	0.91856	PASS	
π/4DQPSK	LCH	1.358	1.2041	PASS	
π/4DQPSK	MCH	1.360	1.2232	PASS	
π/4DQPSK	HCH	1.359	1.2110	PASS	
8DPSK	LCH	1.315	1.2172	PASS	
8DPSK	MCH	1.320	1.2331	PASS	
8DPSK	HCH	1.321	1.2246	PASS	

Test Graph

Graphs			
GFSK/LCH			
GFSK/MCH			
GFSK/HCH			

π/4DQPSK/LCH			
π/4DQPSK/MCH			
π/4DQPSK/HCH			

8DPSK/LCH			
8DPSK/MCH			
8DPSK/HCH			

Appendix B): Carrier Frequency Separation

Result Table

Mode	Channel.	Carrier Frequency Separation [MHz]	Verdict
GFSK	LCH	0.972	PASS
GFSK	MCH	1.002	PASS
GFSK	HCH	1.052	PASS
π/4DQPSK	LCH	1.014	PASS
π/4DQPSK	MCH	1.016	PASS
π/4DQPSK	HCH	0.990	PASS
8DPSK	LCH	1.000	PASS
8DPSK	MCH	0.940	PASS
8DPSK	HCH	1.020	PASS

Test Graph

Graphs			
GFSK/LCH			
GFSK/MCH			
GFSK/HCH			

π/4DQPSK/LCH			
π/4DQPSK/MCH			
π/4DQPSK/HCH			

8DPSK/LCH			
8DPSK/MCH			
8DPSK/HCH			

Appendix C): Dwell Time

Result Table

Mode	Packet	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Verdict
GFSK	DH1	LCH	0.381267	320	0.122	PASS
GFSK	DH1	MCH	0.38126	320	0.122	PASS
GFSK	DH1	HCH	0.38127	320	0.122	PASS
GFSK	DH3	LCH	1.637803	160	0.262	PASS
GFSK	DH3	MCH	1.6378	160	0.262	PASS
GFSK	DH3	HCH	1.6378	160	0.262	PASS
GFSK	DH5	LCH	2.88547	106.7	0.308	PASS
GFSK	DH5	MCH	2.88547	106.7	0.308	PASS
GFSK	DH5	HCH	2.885467	106.7	0.308	PASS

Test Graph

Graphs			
GFSK_DH1/LCH			
GFSK_DH1/MCH			
GFSK_DH1/HCH			

GFSK_DH3/LCH			
GFSK_DH3/MCH			
GFSK_DH3/HCH			

GFSK_DH5/LCH			
GFSK_DH5/MCH			
GFSK_DH5/HCH			

Appendix D): Hopping Channel Number

Result Table

Mode	Channel.	Number of Hopping Channel	Verdict
GFSK	Hop	79	PASS
π/4DQPSK	Hop	79	PASS
8DPSK	Hop	79	PASS

Test Graph

Graphs			
GFSK/Hop			
π/4DQPSK/Hop			
8DPSK/Hop			

Appendix E): Conducted Peak Output Power

Result Table

Mode	Channel.	Maximum Peak Output Power [dBm]	Verdict
GFSK	LCH	3.284	PASS
GFSK	MCH	4.978	PASS
GFSK	HCH	4.224	PASS
π/4DQPSK	LCH	5.895	PASS
π/4DQPSK	MCH	6.973	PASS
π/4DQPSK	HCH	5.283	PASS
8DPSK	LCH	6.255	PASS
8DPSK	MCH	7.186	PASS
8DPSK	HCH	5.595	PASS

Test Graph

Graphs		
GFSK/LCH		
GFSK/MCH		
GFSK/HCH		

π/4DQPSK/LCH			
π/4DQPSK/MCH			
π/4DQPSK/HCH			

8DPSK/LCH			
8DPSK/MCH			
8DPSK/HCH			

Appendix F): Band-edge for RF Conducted Emissions

Result Table

Mode	Channel	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max Spurious Level [dBm]	Limit [dBm]	Verdict
GFSK	LCH	2402	2.531	Off	-60.507	-17.47	PASS
			2.633	On	-59.282	-17.37	PASS
GFSK	HCH	2480	3.996	Off	-58.886	-16.00	PASS
			3.951	On	-58.150	-16.05	PASS
π/4DQPSK	LCH	2402	3.540	Off	-59.705	-16.46	PASS
			3.288	On	-60.085	-16.71	PASS
π/4DQPSK	HCH	2480	3.139	Off	-58.018	-16.86	PASS
			2.815	On	-58.951	-17.19	PASS
8DPSK	LCH	2402	3.564	Off	-60.527	-16.44	PASS
			1.727	On	-60.720	-18.27	PASS
8DPSK	HCH	2480	3.251	Off	-56.369	-16.75	PASS
			3.072	On	-59.232	-16.93	PASS

Test Graph

Graphs			
GFSK/LCH/No Hop			
GFSK/LCH/Hop			
GFSK/HCH/No Hop			

GFSK/HCH/Hop			
π/4DQPSK/LCH/No Hop			
π/4DQPSK/LCH/Hop			

π/4DQPSK/HCH/No Hop			
π/4DQPSK/HCH/Hop			
8DPSK/LCH/No Hop			

8DPSK/LCH/Hop			
8DPSK/HCH/No Hop			
8DPSK/HCH/Hop			

Appendix G): RF Conducted Spurious Emissions

Result Table

Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
GFSK	LCH	2.534	<Limit	PASS
GFSK	MCH	4.883	<Limit	PASS
GFSK	HCH	3.923	<Limit	PASS
π/4DQPSK	LCH	3.37	<Limit	PASS
π/4DQPSK	MCH	4.974	<Limit	PASS
π/4DQPSK	HCH	3.108	<Limit	PASS
8DPSK	LCH	3.471	<Limit	PASS
8DPSK	MCH	5.037	<Limit	PASS
8DPSK	HCH	3.144	<Limit	PASS

Test Graph

GFSK_LCH_Graphs		
Pref		
Puw		

GFSK_MCH_Graphs		
Pref		

Puw	

GFSK_HCH_Graphs		
Pref		
Puw		

π/4DQPSK_LCH_Graphs			
Pref			
Puw			

π/4DQPSK_MCH_Graphs			
Pref			

Puw	

π/4DQPSK_HCH_Graphs	
Pref	
Puw	

8DPSK_LCH_Graphs	
Pref	
Puw	

8DPSK_MCH_Graphs	
Pref	

Puw	

8DPSK_HCH_Graphs	
Pref	
Puw	

Appendix H) Pseudorandom Frequency Hopping Sequence

Test Requirement:	47 CFR Part 15**C Section 15.247 (a)(1) requirement:**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2^9 -1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.