

MODEL PLATE (JWM22)


69.00 mm



DESIGNED TO MOVE [YOU]™

MODEL:JWM22
JENSEN 2-ZONE WALL STEREO

+12V DC NEGATIVE. GROUND
Power Input: DC 12V, ---10A
USB Output: DC 5V, ---1A(max)
FCC ID: 2AHU2JWM22



PIN	COLOR	FUNCTION
1	GREY	RIGHT(A) SPEAKER +
2	GREY/BLACK	RIGHT(A) SPEAKER -
3	WHITE	LEFT(A) SPEAKER +
4	WHITE/BLACK	LEFT(A) SPEAKER -
5	GND(BLACK)	---
6	BLUE JACK	GREY SUBWOOFER
7	GND(BLACK)	GREY LINE OUT R
8	RED JACK	---
9	GND(BLACK)	GREY LINE OUT L
10	WHITE JACK	---
11	PURPLE	RIGHT(B) SPEAKER +
12	PURPLE/BLACK	RIGHT(B) SPEAKER -
13	GREEN	LEFT(B) SPEAKER +
14	GREEN/BLACK	LEFT(B) SPEAKER -
15	RED	+12V DC SWITCHED
16	BLACK	---
17	GND(BLACK)	---
18	RED JACK	YELLOW REAR AUX IN R
19	GND(BLACK)	YELLOW REAR AUX IN L
20	WHITE JACK	---

*REPLACE FUSE WITH DC 32V 10AMP ATO TYPE FUSE
IMPORTANT: DO NOT BRIDGE (COMBINE) SPEAKER OUTPUTS
FAILURE TO WIRE CORRECTLY MAY CAUSE DAMAGE TO UNIT

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
(2) THIS DEVICE MUST ACCERT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIED OPERATION.

THIS PRODUCT COMPLIES WITH DHHS RULES 21 CFR SUBCHAPTER J AT DATE OF MANUFACTURE




www.asaelectronics.com
 MADE IN MALAYSIA

66.00 mm




产品顶部



DESIGNED TO MOVE [YOU]™

MODEL:JWM22
JENSEN 2-ZONE WALL STEREO

+12V DC NEGATIVE. GROUND
Power Input: DC 12V, ---10A
USB Output: DC 5V, ---1A(max)
FCC ID: 2AHU2JWM22



PIN	COLOR	FUNCTION
1	GREY	RIGHT(A) SPEAKER +
2	GREY/BLACK	RIGHT(A) SPEAKER -
3	WHITE	LEFT(A) SPEAKER +
4	WHITE/BLACK	LEFT(A) SPEAKER -
5	GND(BLACK)	---
6	BLUE JACK	GREY SUBWOOFER
7	GND(BLACK)	GREY LINE OUT R
8	RED JACK	---
9	GND(BLACK)	GREY LINE OUT L
10	WHITE JACK	---
11	PURPLE	RIGHT(B) SPEAKER +
12	PURPLE/BLACK	RIGHT(B) SPEAKER -
13	GREEN	LEFT(B) SPEAKER +
14	GREEN/BLACK	LEFT(B) SPEAKER -
15	RED	+12V DC SWITCHED
16	BLACK	---
17	GND(BLACK)	---
18	RED JACK	YELLOW REAR AUX IN R
19	GND(BLACK)	YELLOW REAR AUX IN L
20	WHITE JACK	---

*REPLACE FUSE WITH DC 32V 10AMP ATO TYPE FUSE
IMPORTANT: DO NOT BRIDGE (COMBINE) SPEAKER OUTPUTS
FAILURE TO WIRE CORRECTLY MAY CAUSE DAMAGE TO UNIT

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
(2) THIS DEVICE MUST ACCERT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIED OPERATION.

THIS PRODUCT COMPLIES WITH DHHS RULES 21 CFR SUBCHAPTER J AT DATE OF MANUFACTURE




www.asaelectronics.com
 MADE IN MALAYSIA