

Chassis Label_XMH1

45 mm

Marine Hide-Away
Audio Source Unit

+12V DC NEGATIVE GROUND
Power Input: DC 12V, ≍ 10A
USB Output: DC 5V, ≍ 1A(max)

FCC ID: 2AHU2XMH1

asa

ELECTRONICS

www.asaelectronics.com

4

3

2

1

4

3

2

1

5

6

7

8

4

3

2

1

SHOWN FROM PIN VIEW

PIN	WIRE COLOR	DESCRIPTION
1	RED	+12V SWITCHED
2	BLACK	GROUND
3	LIGHT BLUE	PWR ANTENNA 12V/300mA
4	DARK BLUE	AMP REMOTE 12V/500mA

SHOWN FROM PIN VIEW

PIN	WIRE COLOR	DESCRIPTION	REMARK
1	WHITE/BLACK	ZONE 1 LEFT -	CH1-
2	GRAY/BLACK	ZONE 1 RIGHT -	CH2-
3	GREEN/BLACK	ZONE 2 LEFT -	CH3-
4	VIOLET/BLACK	ZONE 2 RIGHT -	CH4-
5	VIOLET	ZONE 2 RIGHT +	CH4+
6	GREEN	ZONE 2 LEFT +	CH3+
7	GRAY	ZONE 1 RIGHT +	CH2+
8	WHITE	ZONE 1 LEFT +	CH1+

*REPLACE FUSE WITH 15 AMP ATO TYPE FUSE
IMPORTANT: DO NOT BRIDGE (COMBINE) SPEAKER OUTPUTS
FAILURE TO WIRE CORRECTLY MAY CAUSE DAMAGE TO UNIT

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS:
(1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
(2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.

THIS PRODUCT COMPLIES WITH DHHS RULES 21 CFR SUBCHAPTER J AT DATE OF MANUFACTURE.

MADE IN MALAYSIA

80 mm

SCALE 1:1

2026/03/09