

Analysis Report

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Drone Unit) for a RC Controller operated at 2440MHz for pairing with Controller only. The EUT is powered by 1 X 3.7V rechargeable battery. After switch on the EUT and paired with RC controller, the EUT can be controlled to move forward, backward, turning left/right direction by the controller. The EUT is equipped with a charging port for charging by controller or computer.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Nominal rated field strength: 92.5dB μ V/m at 3m

Maximum allowed field strength of production tolerance: +/- 3dB

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 95.5dB μ V/m at 3m in frequency 2.4GHz, thus;

The EIRP = $[(FS \cdot D)^2 \cdot 1000 / 30] = 1.064\text{mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain

So;

Conducted Power = 1.064mW.

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 \cdot 5 / \sqrt{2.440} \text{ mW}$

= 9.60 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.