

S

T

S

L

A

B



RADIO TESTREPORT

Report No: STS1604021F01

Issued for

TONOCH ELECTRONICS LIMITED

No.1111, JINHAI ROAD, CIXI COASTAL DEVELOPMENT
DISTRICT, NINGBO, CHINA

Product Name:	ACTIVE SPEAKER
Brand Name:	N/A
Model Name:	E-F15
Series Model:	TN15D,TK15D,TX15D,TN15AU, TK15AU,TX15AU
FCC ID:	2AHUWFX-1215
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail: sts@stsapp.com



**TEST RESULT CERTIFICATION**

Applicant's name..... TONOUCH ELECTRONICS LIMITED
Address No.1111, JINHAI ROAD, CIXI COASTAL DEVELOPMENT DISTRICT, NINGBO, CHINA
Manufacture's Name TONOUCH ELECTRONICS LIMITED
Address No.1111, JINHAI ROAD, CIXI COASTAL DEVELOPMENT DISTRICT, NINGBO, CHINA

Product description

Product name..... ACTIVE SPEAKER

Brand name..... N/A

Model and/or type reference .. E-F15

Standards..... FCC Part15.247

Test procedure..... ANSI C63.10-2013 and ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test.....

Date (s) of performance of tests.. 06 Apr 2016 ~12 Apr 2016

Date of Issue 13 Apr 2016

Test Result Pass

Testing Engineer :

(JinMing)

Technical Manager :

(Vita Li)

Authorized Signatory :

(Bovey Yang)





Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	10
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF SUPPORT UNITS	12
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 TEST SETUP	15
3.1.4 EUT OPERATING CONDITIONS	15
3.1.5 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TESTSETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS	21
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	32
4.1 REQUIREMENT	32
4.2 TEST PROCEDURE	32
4.3 TEST SETUP	32
4.4 EUT OPERATION CONDITIONS	32
4.5 TEST RESULTS	33
5. NUMBER OF HOPPING CHANNEL	45
5.1 APPLIED PROCEDURES / LIMIT	45
5.2 TEST PROCEDURE	45
5.3 TEST SETUP	45
5.4 EUT OPERATION CONDITIONS	45



Table of Contents	Page
5.5 TEST RESULTS	46
6. AVERAGE TIME OF OCCUPANCY	47
6.1 APPLIED PROCEDURES / LIMIT	47
6.2 TEST PROCEDURE	47
6.3 TEST SETUP	47
6.4 EUT OPERATION CONDITIONS	47
6.5 TEST RESULTS	48
7. HOPPING CHANNEL SEPARATION MEASUREMEN	54
7.1 APPLIED PROCEDURES / LIMIT	54
7.2 TEST PROCEDURE	54
7.3 TEST SETUP	54
7.4 EUT OPERATION CONDITIONS	54
7.5 TEST RESULTS	55
8. BANDWIDTH TEST	61
8.1 APPLIED PROCEDURES / LIMIT	61
8.2 TEST PROCEDURE	61
8.3 TEST SETUP	61
8.4 EUT OPERATION CONDITIONS	61
8.5 TEST RESULTS	62
9. OUTPUT POWER TEST	68
9.1 APPLIED PROCEDURES / LIMIT	68
9.2 TEST PROCEDURE	68
9.3 TEST SETUP	68
9.4 EUT OPERATION CONDITIONS	68
9.5 TEST RESULTS	69
10. ANTENNA REQUIREMENT	70
10.1 STANDARD REQUIREMENT	70
10.2 EUT ANTENNA	70

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	13 Apr 2016	STS1604021F01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

(1)KDB DA 00-705

(2)KDB 558074 D01 DTS Meas Guidance v03r04

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247(a)(1)	Hopping Channel Separation	PASS	--
15.247 (a)(1)&(b)(1)	Output Power	PASS	--
15.247(c)	Radiated Spurious Emission	PASS	--
15.247(d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247(a)(iii)	Number of Hopping Frequency	PASS	--
15.247(a)(iii)	Dwell Time	PASS	--
15.247(a)(1)	Bandwidth	PASS	--
15.205	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) all tests are according to ANSI C63.10-2013 and ANSI C63.4-2014



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<30M)(9KHz-30MHz)	$\pm 2.45\text{dB}$
6	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
7	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
8	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	ACTIVE SPEAKER
Trade Name	N/A
Model Name	E-F15
Series Model	TN15D,TK15D,TX15D,TN15AU, TK15AU,TX15AU
Model Difference	Only different in model name
Channel List	Please refer to the Note 2.
Bluetooth	Frequency:2402 – 2480 MHz Modulation: GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8-DPSK(3Mbps)
Adapter	Input: AC120V ,500mA, 60 Hz
Hardware version number	N/A
Software version number	N/A
Connecting I/O Port(s)	Please refer to the User's Manual

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	E-F15	PCB Antenna	N/A	0.5	BT Antenna

The EUT antenna is PCB Antenna. no antenna other than that furnished by the responsible party shall be used with the device.



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	Data Rate/Modulation
Mode 1	TX CH00	1Mbps/GFSK
Mode 2	TX CH39	1Mbps/GFSK
Mode 3	TX CH78	1Mbps/GFSK
Mode 4	TX CH00	2 Mbps/ π /4-DQPSK
Mode 5	TX CH39	2 Mbps/ π /4-DQPSK
Mode 6	TX CH78	2 Mbps/ π /4-DQPSK
Mode7	TX CH00	3 Mbps/8-DPSK
Mode 8	TX CH39	3 Mbps/8-DPSK
Mode 9	TX CH78	3 Mbps/8-DPSK

Note:

- (1) All above mode have been measurement, only worst data was reported.
- (2) We have been tested for all available U.S. voltage and frequencies (For 120V, 60Hz) for which the device is capable of operation.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 10 : Keeping BT TX

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Bluetooth		
Frequency	2402 MHz	2441 MHz	2480 MHz
CSR (Power control software) Parameters(1/2/3Mbps)	Power class: 1 M rate:4:27 2 M rate:11:183 3 M rate:15:339	Power class: 1 M rate:4:27 2 M rate:11:183 3 M rate:15:339	Power class: 1 M rate:4:27 2 M rate:11:183 3 M rate:15:339


2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Radiated Spurious EmissionTest



Conducted Emission Test





2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	ACTIVE SPEAKER	N/A	E-F15	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C01	AC Line	N/A	1.5M	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2016.03.06	2017.03.05
Horn Antenna	Schwarzbeck	BBHA 9170	9170-0741	2016.03.06	2017.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.03.06	2017.03.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07
Preamplifier	Agilent	8449B	60538	2015.11.05	2016.11.05
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBECK	AK9515H	SN-96286/96287	N/A	N/A

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Signal Analyzer	Agilent	N9020A	MY49100060	2015.11.18	2016.11.17



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.107(a)&207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 10 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULTS


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Mode:	Mode 10		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.2243	39.77	9.98	49.75	62.66	-12.91	QP
0.2243	35.74	9.98	45.72	52.66	-6.94	AVG
0.2878	32.33	9.91	42.24	60.59	-18.35	QP
0.2878	33.04	9.91	42.95	50.59	-7.64	AVG
0.4711	30.84	9.99	40.83	56.49	-15.66	QP
0.4711	30.54	9.99	40.53	46.49	-5.96	AVG
0.6620	32.76	9.98	42.74	56.00	-13.26	QP
0.6620	31.60	9.98	41.58	46.00	-4.42	AVG
1.0420	33.77	9.90	43.67	56.00	-12.33	QP
1.0420	29.51	9.90	39.41	46.00	-6.59	AVG
17.7340	37.61	10.57	48.18	60.00	-11.82	QP
17.7340	34.95	10.57	45.52	50.00	-4.48	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV




Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Mode:	Mode 10		

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB)	(dBuV)	(dBuV)	(dB)	
0.2162	39.70	9.98	49.68	62.96	-13.28	QP
0.2162	35.74	9.98	45.72	52.96	-7.24	AVG
0.2878	32.33	9.91	42.24	60.59	-18.35	QP
0.2878	33.04	9.91	42.95	50.59	-7.64	AVG
0.6620	32.76	9.98	42.74	56.00	-13.26	QP
0.6620	31.60	9.98	41.58	46.00	-4.42	AVG
1.0420	33.77	9.90	43.67	56.00	-12.33	QP
1.0420	29.51	9.90	39.41	46.00	-6.59	AVG
1.6140	33.66	9.96	43.62	56.00	-12.38	QP
1.6140	29.55	9.96	39.51	46.00	-6.49	AVG
15.3380	37.94	10.33	48.27	60.00	-11.73	QP
15.3380	36.05	10.33	46.38	50.00	-3.62	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part15.205(a)&209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1GHz-25 GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1MHz / 1MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz, AV=1 MHz /10 Hz



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.1 meters(above 1GHz is 0.1 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.1 m(above 1GHz is 0.1 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TESTSETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS

(9KHz-30MHz)

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Test Mode:	TX Mode
Test Voltage:	AC 120V 60Hz		

Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



(30MHz-1000MHz)


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	AC 120V	Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
59.8588	60.02	-27.54	32.48	40.00	-7.52	QP
119.8555	54.14	-20.57	33.57	43.50	-9.93	QP
180.0165	53.40	-21.80	31.60	43.50	-11.90	QP
300.3672	56.05	-16.96	39.09	46.00	-6.91	QP
420.5803	51.47	-13.81	37.66	46.00	-8.34	QP
539.4773	50.83	-11.53	39.30	46.00	-6.70	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m






Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	AC 120V	Test Mode:	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
46.1780	52.24	-22.99	29.25	40.00	-10.75	QP
129.9225	51.84	-20.43	31.41	43.50	-12.09	QP
180.0165	54.22	-21.80	32.42	43.50	-11.08	QP
300.3672	55.16	-16.96	38.20	46.00	-7.80	QP
420.5803	53.92	-13.81	40.11	46.00	-5.89	QP
539.4773	53.57	-12.21	41.36	46.00	-4.64	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.





(1GHz~25GHz)

GFSK Low Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.15	44.57	-9.80	34.77	74.00	-39.23	Pk	Vertical
3265.11	34.97	-9.80	25.17	54.00	-28.83	AV	Vertical
3265.10	44.67	-9.80	34.87	74.00	-39.13	Pk	Horizontal
3265.12	35.14	-9.80	25.34	54.00	-28.66	AV	Horizontal
3334.71	42.91	-9.75	33.16	74.00	-40.84	Pk	Vertical
3334.93	32.84	-9.75	23.09	54.00	-30.91	AV	Vertical
3334.67	42.55	-9.75	32.80	74.00	-41.20	Pk	Horizontal
3334.93	32.38	-9.75	22.63	54.00	-31.37	AV	Horizontal
3349.74	42.46	-9.75	32.71	74.00	-41.29	Pk	Vertical
3349.84	32.72	-9.75	22.97	54.00	-31.03	AV	Vertical
3349.74	42.77	-9.75	33.02	74.00	-40.98	Pk	Horizontal
3349.81	32.35	-9.75	22.60	54.00	-31.40	AV	Horizontal
4000.04	39.77	-6.60	33.17	74.00	-40.83	Pk	Vertical
3999.99	29.73	-6.60	23.13	54.00	-30.87	AV	Vertical
4000.08	40.35	-6.60	33.75	74.00	-40.25	Pk	Horizontal
3999.95	29.68	-6.60	23.08	54.00	-30.92	AV	Horizontal
4803.84	38.51	-3.56	34.95	74.00	-39.05	Pk	Vertical
4803.82	29.13	-3.56	25.57	54.00	-28.43	AV	Vertical
4804.85	39.43	-3.56	35.87	74.00	-38.13	Pk	Horizontal
4803.83	28.76	-3.56	25.20	54.00	-28.80	AV	Horizontal
5360.09	38.42	-2.34	36.08	74.00	-37.92	Pk	Vertical
5359.96	28.49	-2.34	26.15	54.00	-27.85	AV	Vertical
5360.12	37.85	-2.34	35.51	74.00	-38.49	Pk	Horizontal
5360.01	28.35	-2.34	26.01	54.00	-27.99	AV	Horizontal
7206.17	37.77	3.40	41.17	74.00	-32.83	Pk	Vertical
7206.21	28.21	3.40	31.61	54.00	-22.39	AV	Vertical
7206.19	37.19	3.40	40.59	74.00	-33.41	Pk	Horizontal
7236.23	27.58	3.40	30.98	54.00	-23.02	AV	Horizontal
8124.23	35.54	4.80	40.34	74.00	-33.66	Pk	Vertical
8124.30	26.36	4.80	31.16	54.00	-22.84	AV	Vertical
8124.29	35.98	4.80	40.78	74.00	-33.22	Pk	Horizontal
8124.36	25.81	4.80	30.61	54.00	-23.39	AV	Horizontal
9104.96	34.52	5.00	39.52	74.00	-34.48	Pk	Vertical



9105.07	24.70	5.00	29.70	54.00	-24.30	AV	Vertical
9105.00	34.68	5.00	39.68	74.00	-34.32	Pk	Horizontal
9105.04	24.46	5.00	29.46	54.00	-24.54	AV	Horizontal
11036.20	33.49	10.20	43.69	74.00	-30.31	Pk	Vertical
11036.35	24.02	10.20	34.22	54.00	-19.78	AV	Vertical
11036.23	34.08	10.20	44.28	74.00	-29.72	Pk	Horizontal
11036.42	23.13	10.20	33.33	54.00	-20.67	AV	Horizontal
13299.70	32.35	12.20	44.55	74.00	-29.45	Pk	Vertical
13299.71	22.54	12.20	34.74	54.00	-19.26	AV	Vertical
13299.76	33.04	12.20	45.24	74.00	-28.76	Pk	Horizontal
13299.77	22.45	12.20	34.65	54.00	-19.35	AV	Horizontal
14480.15	31.61	13.40	45.01	74.00	-28.99	Pk	Vertical
14480.28	21.85	13.40	35.25	54.00	-18.75	AV	Vertical
14480.07	31.77	13.40	45.17	74.00	-28.83	Pk	Horizontal
14480.21	21.45	13.40	34.85	54.00	-19.15	AV	Horizontal
16000.13	30.44	12.40	42.84	74.00	-31.16	Pk	Vertical
16000.18	20.75	12.40	33.15	54.00	-20.85	AV	Vertical
16000.09	30.57	12.40	42.97	74.00	-31.03	Pk	Horizontal
16000.21	20.95	12.40	33.35	54.00	-20.65	AV	Horizontal
17998.15	27.79	23.10	50.89	74.00	-23.11	Pk	Vertical
17998.07	17.99	23.10	41.09	54.00	-12.91	AV	Vertical
17998.06	27.79	23.10	50.89	74.00	-23.11	Pk	Horizontal
17997.92	18.22	23.10	41.32	54.00	-12.68	AV	Horizontal



GFSK Mid Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.21	44.66	-9.80	34.86	74.00	-39.14	Pk	Vertical
3265.16	34.40	-9.80	24.60	54.00	-29.40	AV	Vertical
3265.22	44.75	-9.80	34.95	74.00	-39.05	Pk	Horizontal
3265.16	34.63	-9.80	24.83	54.00	-29.17	AV	Horizontal
3334.81	42.08	-9.75	32.33	74.00	-41.67	Pk	Vertical
3334.94	33.99	-9.75	24.24	54.00	-29.76	AV	Vertical
3334.71	42.30	-9.75	32.55	74.00	-41.45	Pk	Horizontal
3335.02	33.99	-9.75	24.24	54.00	-29.76	AV	Horizontal
3349.83	42.75	-9.75	33.00	74.00	-41.00	Pk	Vertical
3349.95	33.33	-9.75	23.58	54.00	-30.42	AV	Vertical
3349.84	42.30	-9.75	32.55	74.00	-41.45	Pk	Horizontal
3349.91	33.69	-9.75	23.94	54.00	-30.06	AV	Horizontal
4000.15	39.38	-6.60	32.78	74.00	-41.22	Pk	Vertical
4000.00	30.22	-6.60	23.62	54.00	-30.38	AV	Vertical
4000.12	39.57	-6.60	32.97	74.00	-41.03	Pk	Horizontal
3999.97	29.39	-6.60	22.79	54.00	-31.21	AV	Horizontal
4882.87	39.06	-3.56	35.50	74.00	-38.50	Pk	Vertical
4882.94	29.15	-3.56	25.59	54.00	-28.41	AV	Vertical
4882.90	39.92	-3.56	36.36	74.00	-37.64	Pk	Horizontal
4882.89	28.80	-3.56	25.24	54.00	-28.76	AV	Horizontal
5360.14	38.32	-2.34	35.98	74.00	-38.02	Pk	Vertical
5360.06	28.40	-2.34	26.06	54.00	-27.94	AV	Vertical
5360.18	38.59	-2.34	36.25	74.00	-37.75	Pk	Horizontal
5360.03	28.41	-2.34	26.07	54.00	-27.93	AV	Horizontal
7323.20	37.82	3.40	41.22	74.00	-32.78	Pk	Vertical
7323.17	28.36	3.40	31.76	54.00	-22.24	AV	Vertical
7323.22	37.92	3.40	41.32	74.00	-32.68	Pk	Horizontal
7323.28	27.82	3.40	31.22	54.00	-22.78	AV	Horizontal
8124.39	35.64	4.80	40.44	74.00	-33.56	Pk	Vertical
8124.34	25.90	4.80	30.70	54.00	-23.30	AV	Vertical
8124.34	35.94	4.80	40.74	74.00	-33.26	Pk	Horizontal
8124.37	26.29	4.80	31.09	54.00	-22.91	AV	Horizontal
9105.11	34.92	5.00	39.92	74.00	-34.08	Pk	Vertical
9105.16	24.63	5.00	29.63	54.00	-24.37	AV	Vertical



9105.10	35.13	5.00	40.13	74.00	-33.87	Pk	Horizontal
9105.15	24.39	5.00	29.39	54.00	-24.61	AV	Horizontal
11036.27	33.57	10.20	43.77	74.00	-30.23	Pk	Vertical
11036.47	23.85	10.20	34.05	54.00	-19.95	AV	Vertical
11036.37	33.99	10.20	44.19	74.00	-29.81	Pk	Horizontal
11036.46	23.92	10.20	34.12	54.00	-19.88	AV	Horizontal
13299.80	33.00	12.20	45.20	74.00	-28.80	Pk	Vertical
13299.78	24.04	12.20	36.24	54.00	-17.76	AV	Vertical
13299.76	32.28	12.20	44.48	74.00	-29.52	Pk	Horizontal
13299.88	24.84	12.20	37.04	54.00	-16.96	AV	Horizontal
14480.24	31.18	13.40	44.58	74.00	-29.42	Pk	Vertical
14480.28	20.89	13.40	34.29	54.00	-19.71	AV	Vertical
14480.18	30.96	13.40	44.36	74.00	-29.64	Pk	Horizontal
14480.35	20.34	13.40	33.74	54.00	-20.26	AV	Horizontal
16000.21	30.66	12.40	43.06	74.00	-30.94	Pk	Vertical
16000.24	20.71	12.40	33.11	54.00	-20.89	AV	Vertical
16000.12	30.85	12.40	43.25	74.00	-30.75	Pk	Horizontal
16000.23	20.99	12.40	33.39	54.00	-20.61	AV	Horizontal
17998.28	27.91	23.10	51.01	74.00	-22.99	Pk	Vertical
17998.20	17.27	23.10	40.37	54.00	-13.63	AV	Vertical
17998.17	27.71	23.10	50.81	74.00	-23.19	Pk	Horizontal
17998.04	18.27	23.10	41.37	54.00	-12.63	AV	Horizontal



GFSK High Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.11	45.04	-9.80	35.24	74.00	-38.76	Pk	Vertical
3264.99	35.20	-9.80	25.40	54.00	-28.60	AV	Vertical
3265.00	45.24	-9.80	35.44	74.00	-38.56	Pk	Horizontal
3265.04	34.56	-9.80	24.76	54.00	-29.24	AV	Horizontal
3334.61	42.84	-9.75	33.09	74.00	-40.91	Pk	Vertical
3334.85	32.56	-9.75	22.81	54.00	-31.19	AV	Vertical
3334.62	43.11	-9.75	33.36	74.00	-40.64	Pk	Horizontal
3334.84	32.24	-9.75	22.49	54.00	-31.51	AV	Horizontal
3349.59	42.26	-9.75	32.51	74.00	-41.49	Pk	Vertical
3349.73	32.01	-9.75	22.26	54.00	-31.74	AV	Vertical
3349.67	42.14	-9.75	32.39	74.00	-41.61	Pk	Horizontal
3349.74	32.16	-9.75	22.41	54.00	-31.59	AV	Horizontal
4000.01	39.26	-6.60	32.66	74.00	-41.34	Pk	Vertical
3999.92	29.94	-6.60	23.34	54.00	-30.66	AV	Vertical
3999.94	39.20	-6.60	32.60	74.00	-41.40	Pk	Horizontal
3999.84	29.32	-6.60	22.72	54.00	-31.28	AV	Horizontal
4960.78	39.14	-3.56	35.58	74.00	-38.42	Pk	Vertical
4960.75	29.06	-3.56	25.50	54.00	-28.50	AV	Vertical
4960.70	39.53	-3.56	35.97	74.00	-38.03	Pk	Horizontal
4960.81	29.24	-3.56	25.68	54.00	-28.32	AV	Horizontal
5360.03	37.68	-2.34	35.34	74.00	-38.66	Pk	Vertical
5359.91	28.14	-2.34	25.80	54.00	-28.20	AV	Vertical
5359.98	37.69	-2.34	35.35	74.00	-38.65	Pk	Horizontal
5359.99	27.94	-2.34	25.60	54.00	-28.40	AV	Horizontal
7440.07	37.80	3.40	41.20	74.00	-32.80	Pk	Vertical
7440.12	27.35	3.40	30.75	54.00	-23.25	AV	Vertical
7440.13	37.55	3.40	40.95	74.00	-33.05	Pk	Horizontal
7440.11	27.13	3.40	30.53	54.00	-23.47	AV	Horizontal
8124.19	36.38	4.80	41.18	74.00	-32.82	Pk	Vertical
8124.21	25.96	4.80	30.76	54.00	-23.24	AV	Vertical
8124.22	35.81	4.80	40.61	74.00	-33.39	Pk	Horizontal
8124.26	26.14	4.80	30.94	54.00	-23.06	AV	Horizontal
9104.93	34.70	5.00	39.70	74.00	-34.30	Pk	Vertical
9105.00	24.39	5.00	29.39	54.00	-24.61	AV	Vertical



9104.88	34.65	5.00	39.65	74.00	-34.35	Pk	Horizontal
9104.99	24.35	5.00	29.35	54.00	-24.65	AV	Horizontal
11036.16	33.25	10.20	43.45	74.00	-30.55	Pk	Vertical
11036.38	24.15	10.20	34.35	54.00	-19.65	AV	Vertical
11036.19	34.40	10.20	44.60	74.00	-29.40	Pk	Horizontal
11036.29	23.62	10.20	33.82	54.00	-20.18	AV	Horizontal
13299.70	32.03	12.20	44.23	74.00	-29.77	Pk	Vertical
13299.67	22.23	12.20	34.43	54.00	-19.57	AV	Vertical
13299.72	32.67	12.20	44.87	74.00	-29.13	Pk	Horizontal
13299.69	22.14	12.20	34.34	54.00	-19.66	AV	Horizontal
14479.97	31.19	13.40	44.59	74.00	-29.41	Pk	Vertical
14480.12	21.19	13.40	34.59	54.00	-19.41	AV	Vertical
14479.95	30.99	13.40	44.39	74.00	-29.61	Pk	Horizontal
14480.23	21.24	13.40	34.64	54.00	-19.36	AV	Horizontal
16000.10	30.50	12.40	42.90	74.00	-31.10	Pk	Vertical
16000.07	19.87	12.40	32.27	54.00	-21.73	AV	Vertical
15999.96	30.66	12.40	43.06	74.00	-30.94	Pk	Horizontal
16000.08	20.47	12.40	32.87	54.00	-21.13	AV	Horizontal
17998.14	27.30	23.10	50.40	74.00	-23.60	Pk	Vertical
17998.02	17.38	23.10	40.48	54.00	-13.52	AV	Vertical
17998.06	27.92	23.10	51.02	74.00	-22.98	Pk	Horizontal
17997.91	17.45	23.10	40.55	54.00	-13.45	AV	Horizontal

Note:

- 1) Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK, the worst case is GFSK Mode
- 2) Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Meter Reading + Factor
Margin = Limit - Emission Level
- 3) Above did not show the frequency of the emission peaks form is at least 20 decibel limits, transmitting frequency noise mainly comes from the environment.



Band edge

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK							
2400.0	68.72	-12.99	55.73	74	-18.27	PK	Vertical
2400.0	54.51	-12.99	41.52	54	-12.48	AV	Vertical
2400.0	68.74	-12.99	55.75	74	-18.25	PK	Horizontal
2400.0	52.76	-12.99	39.77	54	-14.23	AV	Horizontal
2483.5	70.86	-12.78	58.08	74	-15.92	PK	Vertical
2483.5	53.59	-12.78	40.81	54	-13.19	AV	Vertical
2483.5	68.82	-12.78	56.04	74	-17.96	PK	Horizontal
2483.5	51.48	-12.78	38.70	54	-15.30	AV	Horizontal
π/4-DQPSK							
2400.0	70.44	-12.99	57.45	74	-16.55	PK	Vertical
2400.0	52.88	-12.99	39.89	54	-14.11	AV	Vertical
2400.0	68.21	-12.99	55.22	74	-18.78	PK	Horizontal
2400.0	52.65	-12.99	39.66	54	-14.34	AV	Horizontal
2483.5	71.27	-12.78	58.49	74	-15.51	PK	Vertical
2483.5	54.01	-12.78	41.23	54	-12.77	AV	Vertical
2483.5	70.21	-12.78	57.43	74	-16.57	PK	Horizontal
2483.5	52.54	-12.78	39.76	54	-14.24	AV	Horizontal
8DPSK							
2400.0	70.12	-12.99	57.13	74	-16.87	PK	Vertical
2400.0	52.29	-12.99	39.30	54	-14.70	AV	Vertical
2400.0	69.11	-12.99	56.12	74	-17.88	PK	Horizontal
2400.0	52.59	-12.99	39.60	54	-14.40	AV	Horizontal
2483.5	69.48	-12.78	56.70	74	-17.30	PK	Vertical
2483.5	55.42	-12.78	42.64	54	-11.36	AV	Vertical
2483.5	68.27	-12.78	55.49	74	-18.51	PK	Horizontal
2483.5	53.14	-12.78	40.36	54	-13.64	AV	Horizontal

Low measurement frequencies is range from 2310 to 2400 MHz,high measurement frequencies is range from 2483.5 to 2500 MHz.

Only showthe worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.



Hopping(Band edge)

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK							
2400.0	68.14	-12.99	55.15	74	-18.85	PK	Vertical
2400.0	53.73	-12.99	40.74	54	-13.26	AV	Vertical
2400.0	66.34	-12.99	53.35	74	-20.65	PK	Horizontal
2400.0	52.39	-12.99	39.40	54	-14.60	AV	Horizontal
2483.5	64.73	-12.78	51.95	74	-22.05	PK	Vertical
2483.5	54.95	-12.78	42.17	54	-11.83	AV	Vertical
2483.5	67.12	-12.78	54.34	74	-19.66	PK	Horizontal
2483.5	53.33	-12.78	40.55	54	-13.45	AV	Horizontal
π/4-DQPSK							
2400.0	68.54	-12.99	55.55	74	-18.45	PK	Vertical
2400.0	54.47	-12.99	41.48	54	-12.52	AV	Vertical
2400.0	65.51	-12.99	52.52	74	-21.48	PK	Horizontal
2400.0	51.68	-12.99	38.69	54	-15.31	AV	Horizontal
2483.5	67.12	-12.78	54.34	74	-19.66	PK	Vertical
2483.5	52.51	-12.78	39.73	54	-14.27	AV	Vertical
2483.5	67.81	-12.78	55.03	74	-18.97	PK	Horizontal
2483.5	52.44	-12.78	39.66	54	-14.34	AV	Horizontal
8DPSK							
2400.0	67.89	-12.99	54.90	74	-19.10	PK	Vertical
2400.0	53.74	-12.99	40.75	54	-13.25	AV	Vertical
2400.0	66.16	-12.99	53.17	74	-20.83	PK	Horizontal
2400.0	53.39	-12.99	40.40	54	-13.60	AV	Horizontal
2483.5	67.85	-12.78	55.07	74	-18.93	PK	Vertical
2483.5	52.73	-12.78	39.95	54	-14.05	AV	Vertical
2483.5	66.29	-12.78	53.51	74	-20.49	PK	Horizontal
2483.5	53.17	-12.78	40.39	54	-13.61	AV	Horizontal

Low measurement frequencies is range from 2310 to 2400 MHz,high measurement frequencies is range from 2483.5 to 2500 MHz.

Only showthe worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 REQUIREMENT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE


Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 – 2404 MHz Upper Band Edge: 2478 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

Remark : Hopping on and Hopping off mode all have been tested, only worst case hopping off is reported.

4.3 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




4.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	GFSK(1Mbps)-00/39/78 CH		

00 CH




39 CH






78 CH






For Band edge

00 CH




78 CH






For Hopping Band edge

00 CH




78 CH






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	$\pi/4$ -DQPSK(2Mbps) -00/39/78 CH		

00 CH




39 CH






78 CH






For Band edge

00 CH




78 CH






For Hopping Band edge

00 CH




78 CH






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	8-DPSK(3Mbps) -00/39/78 CH		

00 CH




39 CH






78 CH






For Band edge

00 CH




78 CH






For Hopping Band edge

00 CH



78 CH





5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	100KHz
VB	100KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100K, VBW=100K, Sweep time = Auto.

5.3 TEST SETUP



5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.5 TEST RESULTS

EUT :	ACTIVE SPEAKER	Model Name :	E-F15
Temperature :	25℃	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	Hopping Mode		

Number of Hopping Channel

79

Hopping channel





6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

6.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW =1MHz/VBW =3MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds.
- DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
- DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot RX, 1 time slot TX). So the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.5 TEST RESULTS


Temperature :	25℃	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	GFSK(1Mbps)-DH1/DH3/DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits(s)
DH1	2441 MHz	0.370	0.118	0.4
DH3	2441 MHz	1.630	0.261	0.4
DH5	2441 MHz	2.880	0.307	0.4







CH39-DH1



CH39-DH3



CH39-DH5






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	$\pi/4$ -DQPSK(2Mbps) –2DH1/2DH3/2DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits(s)
2DH1	2441 MHz	0.380	0.122	0.4
2DH3	2441 MHz	1.640	0.262	0.4
2DH5	2441 MHz	2.880	0.307	0.4







CH39-2DH1



CH39-2DH3



CH39-2DH5






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	8DPSK(3Mbps) –3DH1/3DH3/3DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits(s)
3DH1	2441 MHz	0.380	0.122	0.4
3DH3	2441 MHz	1.640	0.262	0.4
3DH5	2441 MHz	2.890	0.308	0.4







CH39-3DH1



CH39-3DH3



CH39-3DH5



7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT


Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.2 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for 20 dB bandwidth measurement.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.




7.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	CH00 / CH39 /CH78 (GFSK(1Mbps) Mode)		

Frequency	Ch. Separation (MHz)	Limit	Result
2402 MHz	1.000	0.887	Complies
2441 MHz	1.000	0.896	Complies
2480 MHz	1.000	0.888	Complies


For GFSK: Ch. Separation Limits: >20dB bandwidth

CH00 -1Mbps






CH39 -1Mbps



CH78 -1Mbps






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	CH00 / CH39 /CH78 ($\pi/4$ -DQPSK(2Mbps) Mode)		

Frequency	Ch. Separation (MHz)	Limit	Result
2402 MHz	1.000	0.743	Complies
2441 MHz	1.000	0.551	Complies
2480 MHz	1.000	0.551	Complies


For $\pi/4$ -DQPSK(2Mbps): Ch. Separation Limits: > two-thirds 20dB bandwidth

CH00 -2Mbps






CH39 -2Mbps



CH78 -2Mbps






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	CH00 / CH39 /CH78 (8-DPSK(3Mbps)Mode)		

Frequency	Ch. Separation (MHz)	Limit	Result
2402 MHz	1.000	0.773	Complies
2441 MHz	1.005	0.774	Complies
2480 MHz	1.000	0.774	Complies


For 8-DPSK(3Mbps):Ch. Separation Limits: > two-thirds 20dB bandwidth

CH00 -3Mbps






CH39 -3Mbps



CH78 -3Mbps





8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C

Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




8.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	GFSK(1Mbps)CH00 / CH39 /C78		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	0.887	PASS
2441 MHz	0.896	PASS
2480 MHz	0.888	PASS

CH00 -1Mbps






CH39 -1Mbps




CH78 -1Mbps






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	$\pi/4$ -DQPSK(2Mbps)CH00 / CH39 /C78		

Frequency	20dB Bandwidth(MHz)	Result
2402 MHz	1.114	PASS
2441 MHz	0.826	PASS
2480 MHz	0.827	PASS


CH00 -2Mbps



CH39 -2Mbps



CH78 -2Mbps






Temperature :	25°C	Relative Humidity :	50%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz
Test Mode :	8DPSK(3Mbps)CH00 / CH39 /C78		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.160	PASS
2441 MHz	1.161	PASS
2480 MHz	1.161	PASS

CH00 -3Mbps






CH39 -3Mbps



CH78 -3Mbps





9. OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)&(b)(1)	Output Power	1 W or 0.125W	2400-2483.5	PASS
		Or if channel separation > 2/3 bandwidth provided the systems operate with an output power no greater than 125 mW (20.96dBm)		

9.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor+PC

9.3 TEST SETUP



9.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



9.5 TEST RESULTS

Temperature :	25℃	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V 60Hz

GFSK(1Mbps)				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak (dBm)	AVG (dBm)	dBm
CH00	2402	1.177	-4.052	30
CH39	2441	1.185	-4.044	30
CH78	2480	1.228	-4.001	30

Note : the channel separation > bandwidth

$\pi/4$ QPSK(2Mbps)				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak (dBm)	AVG (dBm)	dBm
CH00	2402	-0.913	-6.142	20.96
CH39	2441	-0.285	-5.514	20.96
CH78	2480	-0.343	-5.572	20.96

Note : the channel separation >2/3 bandwidth

8-DPSK(3Mbps)				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak (dBm)	AVG (dBm)	dBm
CH00	2402	-0.450	-5.679	20.96
CH39	2441	-0.062	-5.291	20.96
CH78	2480	-0.471	-5.700	20.96

Note : the channel separation >2/3 bandwidth



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


10.2 EUT ANTENNA

The EUT antenna is PCB Antenna. It comply with the standard requirement.



APPENDIX-PHOTOS OF TEST SETUP

Radiated Measurement Photos



Conducted Measurement Photos



※※※※※END OF THE REPORT※※※※※