
FCC Test Report

Report No.: AGC06446160301FE03

FCC ID : 2AHUYBM01
APPLICATION PURPOSE : Original Equipment
PRODUCT DESIGNATION : BLE module
BRAND NAME : N/A
MODEL NAME : RTBTM01
CLIENT : RFCOM Technologies Pte. Ltd.
DATE OF ISSUE : Mar.30,2016
STANDARD(S) : FCC Part 15 Rules
TEST PROCEDURE(S)
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar.30,2016	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY..... 5

2. GENERAL INFORMATION..... 6

2.1. PRODUCT DESCRIPTION..... 6

2.2. TABLE OF CARRIER FREQUENCYS 6

3. MEASUREMENT UNCERTAINTY 7

4. DESCRIPTION OF TEST MODES 7

5. SYSTEM TEST CONFIGURATION..... 8

5.1. CONFIGURATION OF EUT SYSTEM..... 8

5.2. EQUIPMENT USED IN EUT SYSTEM 8

5.3. SUMMARY OF TEST RESULTS..... 8

6. TEST FACILITY..... 9

7 TEST METHODOLOGY..... 9

8. ALL TEST EQUIPMENT LIST 9

9. RADIATED EMISSION..... 11

9.1TEST LIMIT 11

9.2. MEASUREMENT PROCEDURE 12

9.3. TEST SETUP 14

9.4. TEST RESULT 16

10. BAND EDGE EMISSION 29

10.1. MEASUREMENT PROCEDURE 29

10.2 TEST SETUP 29

10.3 RADIATED TEST RESULT 30

11. 20DB BANDWIDTH 34

11.1. MEASUREMENT PROCEDURE 34

11.2. TEST SET-UP 34

11.3. LIMITS AND MEASUREMENT RESULTS 34

12. FCC LINE CONDUCTED EMISSION TEST37

12.1. LIMITS OF LINE CONDUCTED EMISSION TEST..... 37

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 37

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST..... 38

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 38

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 38

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 39

APPENDIX B: PHOTOGRAPHS OF EUT 40

1. VERIFICATION OF CONFORMITY

Applicant	RFCOM Technologies Pte. Ltd.
Address	20 Sin Ming Lane,#06-68 Midview City Singapore
Manufacturer	RFCOM Technologies Pte. Ltd.
Address	20 Sin Ming Lane,#06-68 Midview City Singapore
Product Designation	BLE module
Brand Name	N/A
Test Model	RTBTM01
Date of test	Mar.17,2016 to Mar.21,2016
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By 
Time Huang (Huang Nanhui) Mar.30,2016

Reviewed By 
Forrest Lei(Lei Yonggang) Mar.30,2016

Approved By 
Solger Zhang(Zhang Hongyi)
Authorized Officer Mar.30,2016

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	3.2dBm(Max)
Bluetooth Version	V4.1
Modulation	GFSK
Number of channels	40
Hardware Version	1.0
Software Version	1.10
Antenna Designation	Ceramic Antenna (Met 15.203 Antenna requirement)
Antenna Gain	-2.4dBi
Power Supply	DC3V

2.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	19	2440 MHZ
	20	2442 MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$


4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Normal operation
Note: 1. only the result of the worst case was recorded in the report, if no other cases. 2. For Radiated Emission, 3 axis were chosen for testing for each applicable mode.	


5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	BLE module	RFCOM	RTBTM01	EUT
2	Control box	N/A	N/A	A.E
3	PC	SONY	E1412AYCW	A.E
6	Temporary Antenna Connector	T10	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	N/A
§15.215	BANDWIDTH	Compliant

Note: N/A means not applicable.

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan,Guangdong, China
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.10:2013.

7 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013

8. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	1Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6,2015	June 5,2016
Conduction Cable	MXT	SE1	S003	June 6,2015	June 5,2016

9. RADIATED EMISSION

9.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

9.2. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5m meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW for peak reading. Then 1 MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz RBW/3MHz VBW for Peak, 1MHz RBW /10Hz VBW for Average


Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

9.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



9.4. TEST RESULT


(Worst modulation: GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 23.3

Limit: FCC Class B 3M Radiation

Power:

Humidity: 55.1 %

EUT: BLE module

Distance:

M/N: RTBTM01

Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		39.7000	21.19	8.51	29.70	40.00	-10.30	peak			
2	*	156.1000	21.27	15.30	36.57	43.50	-6.93	peak			
3		211.0667	23.71	10.08	33.79	43.50	-9.71	peak			
4		324.2333	14.95	17.02	31.97	46.00	-14.03	peak			
5		479.4333	11.47	20.91	32.38	46.00	-13.62	peak			
6		820.5500	4.88	27.32	32.20	46.00	-13.80	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: Conduction

Limit: FCC Class B 3M Radiation

EUT: BLE module

M/N: RTBTM01

Mode: Middle Channel TX

Note:

Polarization: *Horizontal*

Power:

Distance:


Temperature: 23.3

Humidity: 55.1 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		99.5167	20.00	10.00	30.00	43.50	-13.50	peak			
2		191.6667	17.84	11.61	29.45	43.50	-14.05	peak			
3		324.2333	15.06	17.02	32.08	46.00	-13.92	peak			
4	*	500.4500	16.17	21.14	37.31	46.00	-8.69	peak			
5		699.3000	6.21	25.17	31.38	46.00	-14.62	peak			
6		846.4167	5.85	27.31	33.16	46.00	-12.84	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: Conduction Polarization: **Vertical** Temperature: 23.3
Limit: FCC Class B 3M Radiation Power: Humidity: 55.1 %
EUT: BLE module Distance:
M/N: RTBTM01
Mode: Middle Channel TX
Note:


No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	157.7167	20.74	15.32	36.06	43.50	-7.44	peak			
2		211.0667	24.81	10.08	34.89	43.50	-8.61	peak			
3		324.2333	15.95	17.02	32.97	46.00	-13.03	peak			
4		479.4333	13.35	20.91	34.26	46.00	-11.74	peak			
5		820.5500	4.60	27.32	31.92	46.00	-14.08	peak			
6		957.9667	3.78	29.92	33.70	46.00	-12.30	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 23.3
Limit: FCC Class B 3M Radiation	Power:	Humidity: 55.1 %
EUT: BLE module	Distance:	
M/N: RTBTM01		
Mode: High Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	99.5167	21.61	10.00	31.61	43.50	-11.89	peak			
2		162.5667	19.52	10.42	29.94	43.50	-13.56	peak			
3		324.2333	13.62	17.02	30.64	46.00	-15.36	peak			
4		479.4333	12.86	20.91	33.77	46.00	-12.23	peak			
5		595.8333	10.22	23.63	33.85	46.00	-12.15	peak			
6		839.9500	5.48	27.31	32.79	46.00	-13.21	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL




Site: Conduction Polarization: **Vertical** Temperature: 23.3
Limit: FCC Class B 3M Radiation Power: Humidity: 55.1 %
EUT: BLE module Distance:
M/N: RTBTM01
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	157.7167	21.15	15.32	36.47	43.50	-7.03	peak			
2		211.0667	23.21	10.08	33.29	43.50	-10.21	peak			
3		324.2333	15.06	17.02	32.08	46.00	-13.92	peak			
4		479.4333	12.82	20.91	33.73	46.00	-12.27	peak			
5		613.6167	7.76	23.04	30.80	46.00	-15.20	peak			
6		957.9667	3.54	29.92	33.46	46.00	-12.54	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ**RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL**

Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: BLE module

Distance: 3m

M/N: RTBTM01


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	105.26	-9.68	95.58	114.00	-18.42	peak			
2		4100.000	49.60	-4.47	45.13	74.00	-28.87	peak			
3		4525.000	48.34	-3.04	45.30	74.00	-28.70	peak			
4	*	2402.000	92.47	-9.68	82.79	94.00	-11.21	AVG	100	227	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHz(PK)-

Power:

Humidity: 60 %

EUT: BLE module

Distance: 3m

M/N: RTBTM01


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	105.71	-9.68	96.03	114.00	-17.97	peak			
2		3391.667	52.85	-7.99	44.86	74.00	-29.14	peak			
3		4991.667	46.45	-1.82	44.63	74.00	-29.37	peak			
4	*	2402.000	93.79	-9.68	84.11	94.00	-9.89	AVG	100	169	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: Conduction Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: BLE module Distance: 3m
M/N: RTBTM01
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	105.27	-9.64	95.63	114.00	-18.37	peak			
2		3283.333	52.93	-8.09	44.84	74.00	-29.16	peak			
3		4150.000	48.55	-4.30	44.25	74.00	-29.75	peak			
4	*	2440.000	92.72	-9.64	83.08	94.00	-10.92	AVG	100	231	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: Conduction

Polarization: **Vertical**

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: BLE module

Distance: 3m

M/N: RTBTM01


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	105.12	-9.64	95.48	114.00	-18.52	peak			
2		4241.667	48.65	-3.99	44.66	74.00	-29.34	peak			
3		5316.667	46.39	-1.81	44.58	74.00	-29.42	peak			
4	*	2440.000	92.81	-9.64	83.17	94.00	-10.83	AVG	100	171	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: Conduction

Polarization: Horizontal

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: BLE module

Distance: 3m

M/N: RTBTM01


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	104.84	-9.59	95.25	114.00	-18.75	peak			
2		3508.333	52.32	-7.84	44.48	74.00	-29.52	peak			
3		4633.333	46.23	-2.76	43.47	74.00	-30.53	peak			
4	*	2480.000	92.26	-9.59	82.67	94.00	-11.33	AVG	100	225	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: NLE module

Distance: 3m

M/N: RTBTM01

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	104.88	-9.59	95.29	114.00	-18.71	peak			
2		3550.000	52.71	-7.58	45.13	74.00	-28.87	peak			
3		4183.333	49.23	-4.19	45.04	74.00	-28.96	peak			
4	*	2480.000	92.84	-9.59	83.25	94.00	-10.75	AVG	100	166	

RESULT: PASS

Note: 1. 6~25GHz at least have 20dB margin. No recording in the test report.

2. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

3. The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	105.26	-9.68	95.58	114	-18.42	Horizontal
2402	105.71	-9.68	96.03	114	-17.97	Vertical
2440	105.27	-9.64	95.63	114	-18.37	Horizontal
2440	105.12	-9.64	95.48	114	-18.52	Vertical
2480	104.84	-9.59	95.25	114	-18.75	Horizontal
2480	104.88	-9.59	95.29	114	-18.71	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	92.47	-9.68	82.79	94	-11.21	Horizontal
2402	93.79	-9.68	84.11	94	-9.89	Vertical
2440	92.72	-9.64	83.08	94	-10.92	Horizontal
2440	92.81	-9.64	83.17	94	-10.83	Vertical
2480	92.26	-9.59	82.67	94	-11.33	Horizontal
2480	92.84	-9.59	83.25	94	-10.75	Vertical


10. BAND EDGE EMISSION

10.1. MEASUREMENT PROCEDURE

1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Max hold the trace of the setp 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
(a) PEAK: RBW=VBW=1.5MHz / Sweep=AUTO
(b) AVERAGE: RBW=1.5MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

10.2 TEST SETUP


RADIATED EMISSION TEST SETUP



10.3 RADIATED TEST RESULT

(Worst modulation: GFSK)


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: Conduction	Polarization: <i>Horizontal</i>	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: BLE module	Distance:	
M/N: RTBTM01		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2282.000	31.48	10.19	41.67	74.00	-32.33	peak			
2		2390.000	30.12	10.31	40.43	74.00	-33.57	peak			
3	*	2402.000	85.41	10.32	95.73	74.00	21.73	peak			


TEST PLOT OF BAND EDGE FOR LOW CHANNEL –Vertical



Site: Conduction	Polarization: Vertical	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: BLE module	Distance:	
M/N: RTBTM01		
Mode: Low Channel TX		
Note:		

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2262.183	31.70	10.17	41.87	74.00	-32.13	peak			
2		2390.000	30.35	10.31	40.66	74.00	-33.34	peak			
3	*	2402.000	85.76	10.32	96.08	74.00	22.08	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: Conduction

Polarization: *Horizontal*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: BLE module

Distance:


M/N: RTBTM01

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	84.96	10.41	95.37	74.00	21.37	peak			
2		2483.500	29.75	10.41	40.16	74.00	-33.84	peak			
3		2492.043	30.46	10.42	40.88	74.00	-33.12	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: Conduction

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)

Power:

Humidity: 60 %

EUT: BLE module

Distance:

M/N: RTBTM01

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	84.85	10.41	95.26	74.00	21.26	peak			
2		2483.500	28.87	10.41	39.28	74.00	-34.72	peak			
3		2490.100	30.26	10.42	40.68	74.00	-33.32	peak			

RESULT: PASS**Note:** 1. The other modes radiation emission have enough 20dB margin.

2. Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

3. The "Factor" value can be calculated automatically by software of measurement system.


11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

11.3. LIMITS AND MEASUREMENT RESULTS

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.218	PASS
	Middle Channel	1.224	PASS
	High Channel	1.215	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST



1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Owing to the EUT power supply by DC source, so it's not applicable for the item


APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP




APPENDIX B: PHOTOGRAPHS OF EUT


TOP VIEW OF EUT




BOTTOM VIEW OF EUT




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2





----END OF REPORT----