

RF Exposure Evaluation
For
BLAZE AUTOMATION INC
B.One Hub
Test Model: Edge 2.1

Prepared for : BLAZE AUTOMATION INC
Address : 125 village, Boulevard suite 320, Princeton, New Jersey 08540, United States

Prepared by : Guangzhou LCS Compliance Testing Laboratory Ltd.
Address : No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China

Tel : (+86) 020-39166689
Fax : (+86) 020-39166619
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 07, 2025
Number of tested samples : 2
Sample No. : C251110003-1, C251110003-2
Serial number : Prototype
Date of Test : November 07, 2025 ~ December 03, 2025
Date of Report : December 04, 2025

RF Exposure Evaluation	
Report Reference No.	LCSC11065015EG
Date of Issue	December 04, 2025
Testing Laboratory Name	Guangzhou LCS Compliance Testing Laboratory Ltd.
Address	No.44-1, Qianfeng North Road, Shiqi, Panyu District, Guangzhou, Guangdong, China
Testing Location/ Procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's Name	BLAZE AUTOMATION INC
Address	125 village, Boulevard suite 320, Princeton, New Jersey 08540, United States
Test Specification	
Standard	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-215 A/0
TRF Originator	Guangzhou LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Guangzhou LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Guangzhou LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Guangzhou LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description	B.One Hub
Trade Mark	 (B.one)
Test Model	Edge 2.1
Ratings	Please Refer to Page 6
Result	Pass

Compiled by:



Lifeng Le / Administrators

Supervised by:


Justin Zhu/ Technique
Director

Approved by:



Gavin Liang/ Manager

RF Exposure Evaluation

Test Report No. : LCSC11065015EG	<u>December 04, 2025</u> Date of issue
---	---

EUT.....	: B.One Hub
Test Model.....	: Edge 2.1
Applicant.....	: BLAZE AUTOMATION INC
Address.....	: 125 village, Boulevard suite 320, Princeton, New Jersey 08540, United States
Manufacturer.....	: BLAZE AUTOMATION INC
Address.....	: 125 village, Boulevard suite 320, Princeton, New Jersey 08540, United States

Test Result	Pass
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	December 04, 2025	Initial Issue	---

TABLE OF CONTENTS

Description	Page
1. Product Information.....	6
2. Evaluation Method	7
3. Limit	7
4. MPE Calculation Method	8
5. Antenna Information.....	8
6. Conducted Power.....	8
7. Manufacturing Tolerance	9
8. Measurement Results	11
9. Conclusion.....	12
10. Description of Test Facility	12
11. Measurement Uncertainty.....	12

1. Product Information

EUT	: B.One Hub
Test Model	: Edge 2.1
Ratings	: Input: 5.0V $\Rightarrow$ 3.0A For AC Adapter Input: 100-240V~, 50/60Hz, 0.4A Adapter Output: 5.0V $\Rightarrow$ 3.0A, 15.0W
Hardware Version	: V2.XX
Software Version	: WiFi: V7.45.XX BLE: 5.XX Zigbee: 6.7.XX Zwave: 2.15.XX
Bluetooth	
Frequency Range	: 2402MHz-2480MHz
Bluetooth Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Bluetooth Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Bluetooth Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: PCB Antenna With UFL Connector and Cable, 3.0dBi (Max.)
WIFI (2.4G Band)	
Frequency Range	: 2412MHz-2462MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz)
Channel Spacing	: 5MHz
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: PCB Antenna With UFL Connector and Cable, 3.0dBi(Max.)
Z-Wave	
Frequency Range	: 908.4MHz, 908.42MHz, 916MHz
Channel Number	: 3 Channels
Modulation Type	: (908.4MHz, 908.42MHz) FSK (916MHz) GFSK
Antenna Description	: PCB Trace Antenna, 1.19dBi (Max)
Z-Wave	
Frequency Range	: 912MHz, 920MHz
Channel Number	: 2 Channels
Modulation Type	: OQPSK
Antenna Description	: PCB Trace Antenna, 1.19dBi (Max)
Zigbee	
Frequency Range	: 2405MHz-2480MHz
Channel Spacing	: 5MHz
Channel Number	: 16 Channels
Modulation Type	: O-QPSK
Antenna Description	: Chip Antenna, 1.86dBi(Max.)
LTE	
LTE Bands	: LTE band 2/4/5/12/13/14/66/71
Modulation Type	: QPSK, 16QAM
Antenna Description	: Mount Monopole Antenna

Antenna Gain	: 4.43 dBi at 1920-2170MHz 3.99 dBi at 1710-1880MHz 3.37 dBi at 824-960MHz 2.65 dBi at 698-824MHz 2.44 dBi at 617-698MHz
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device
Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.	

2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0 – 30	614	1.63	(100) *	6
30 – 300	1842/f	4.89/f	(900/f ²) *	6
300 – 1500	61.4	0.163	1.0	6
1500 – 100,000	/	/	f/300	6
	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0 – 30	614	1.63	(100) *	30
30 – 300	824/f	2.19/f	(180/f ²)*	30
300 – 1500	27.5	0.073	0.2	30
1500 – 100,000	/	/	f/1500	30
	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Antenna 0	FPC Antenna	2400MHz ~ 2500MHz	3.0 dBi	WLAN/BT
Antenna 1	PCB Antenna	860 – 930 MHz	1.19 dBi	Z-wave
Antenna 2	Chip Antenna	2400 – 2500 MHz	1.86 dBi	ZigBee
Antenna 3	Mount Monopole Antenna	617 – 698 MHz	2.44 dBi	LTE
		698 – 824 MHz	2.65 dBi	
		824 – 960 MHz	3.37 dBi	
		1710 – 1880 MHz	3.99 dBi	
		1920 – 2170 MHz	4.43 dBi	

6. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
1-DH5	0	2402	8.52
	39	2441	8.51
	78	2480	9.86
2-DH5	0	2402	10.23
	39	2441	8.43
	78	2480	9.93
3-DH5	0	2402	10.11
	19	2441	8.35
	39	2480	9.82

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE 1M	0	2402	8.53
	19	2440	9.5
	39	2480	9.98

[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
IEEE 802.11b	1	2412	18
	6	2437	18.21
	11	2462	18.42
IEEE 802.11g	1	2412	18.6
	6	2437	18.65
	11	2462	18.94
IEEE 802.11n HT20	1	2412	18.91
	6	2437	18.53
	11	2462	18.8

[Z-wave]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
O-QPSK	1	912	12.19
	2	920	12.09

Z-wave ((908.4MHz, 908.42MHz) FSK/ (916MHz) GFSK:

TX frequency (the Worst):908.4MHz

Max. Field Strength: 83.37dBuV/m @3m

EIRP=E-104.8+20logD=83.37-104.8+20log3=-11.89dBm

Maximum Conducted Output Power: -11.89dBm

Turn-up: -11±1

< Zigbee Max Conducted Power >

Mode	Channel	Frequency (MHz)	Max Conducted Power (dBm)
O-QPSK	0	2405	10.27
	7	2440	10.52
	15	2480	10.73

7. Manufacturing Tolerance**[BT]**

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8.0	8.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0
π/4-DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	10.0	8.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	10.0	8.0	9.0
Tolerance ±(dB)	1.0	1.0	1.0

[BLE 1M]

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	8.0	9.0	9.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI]

IEEE 802.11b (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	18.0	18.0	18.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[Z-wave]

O-QPSK (Peak)		
Channel	Channel 1	Channel 2
Target (dBm)	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0

<Zigbee>

O-QPSK (Peak)			
Channel	Channel 0	Channel 7	Channel 15
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

LTE modular EG915Q-NA (FCC ID: XMR2023EG915QNA) from Test Report No. SEWA2212000096RG03).

Operation Bands	Maximum Conducted Output Power including Tune up Tolerance (dBm)
LTE band 2	25.00
LTE band 4	25.00
LTE band 5	25.00
LTE band 12	25.00
LTE band 13	25.00
LTE band 14	25.00
LTE band 66	25.00
LTE band 71	25.00

8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
GFSK	10.0	10.0000	3	1.9953	0.0040	1.0000	0.0040
$\pi/4$ -DQPSK	11.0	12.5893	3	1.9953	0.0050	1.0000	0.0050
8-DPSK	11.0	12.5893	3	1.9953	0.0050	1.0000	0.0050

[BLE 1M]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
GFSK	10.0	10.0000	3	1.9953	0.0040	1.0000	0.0040

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
IEEE 802.11b	19.0	79.4328	3	1.9953	0.0315	1.0000	0.0315
IEEE 802.11g	19.0	79.4328	3	1.9953	0.0315	1.0000	0.0315
IEEE 802.11n HT20	19.0	79.4328	3	1.9953	0.0315	1.0000	0.0315

[Z-wave]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
O-QPSK	13.0	19.9526	1.19	1.3152	0.0052	1.0000	0.0052

[Z-wave]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
FSK	-10.0	0.1000	1.19	1.3152	0.00003	1.0000	0.00003

<Zigbee>

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
O-QPSK	11.0	12.5893	1.86	1.5346	0.0038	1.0000	0.0038

<LTE>

Band/Mode	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio
	dBm	mW					
LTE band 2	25.00	316.2278	4.43	2.7733	0.1746	1.0000	0.1746
LTE band 4	25.00	316.2278	3.99	2.5061	0.1577	1.0000	0.1577
LTE band 5	25.00	316.2278	3.37	2.1727	0.1368	0.5948	0.2299
LTE band 12	25.00	316.2278	2.65	1.8408	0.1159	0.4665	0.2484
LTE band 13	25.00	316.2278	2.65	1.8408	0.1159	0.5197	0.2229
LTE band 14	25.00	316.2278	2.65	1.8408	0.1159	0.5270	0.2199
LTE band 66	25.00	316.2278	3.99	2.5061	0.1577	1.0000	0.1577
LTE band 71	25.00	316.2278	2.44	1.7539	0.1104	0.4437	0.2488

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The EUT equipped with one Bluetooth/2.4GWIFI antenna, one Z-wave antenna, one Zigbee antenna. so need consider simultaneous transmission;
According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

Simultaneous Transmission						
2.4GWIFI Antenna Max MPE ratios	Z-wave Antenna Max MPE ratios	Zigbee Antenna Max MPE ratios	LTE Antenna Max MPE ratios	Σ MPE ratios	Limit	Results
0.0315	0.0052	0.0038	0.2488	0.2893	1.0	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

CNAS Registration Number is L11555
A2LA Certificate Number: 5099.01
FCC Designation Number is CN1379
Test Firm Registration Number: 729882

11. Measurement Uncertainty

BT/BLE/2.4GWIFI/Z-wave/Zigbee:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----