



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

CLASS B INDUSTRIAL BOOSTER

FCC PART 90 TEST REPORT

Applicant	RADIO SOLUTIONS, INC.
Address	55 ACCORD PARK DRIVE NORWELL, MA. 02061 USA
FCC ID	2AHVPSB400M2A
Model Number	SB400M2A
Product Description	UHF SIGNAL BOOSTER
Date Sample Received	9/21/2017
Date Tested	11/27/2017
Tested By	Franklin Rose
Approved By	Sid Sanders
Test Results	☒ PASS ☐ FAIL

Report Number	Version Number	Description	Issue Date
1702AUT17TestReport	Rev1	Initial Issue	11/27/2017
1702AUT17TestReport	Rev2	Updated Input Vs Output Plots	12/4/2017

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**

TABLE OF CONTENTS

GENERAL REMARKS	5
EUT DESCRIPTION	6
TEST RESULTS SUMMARY.....	7
RF POWER OUTPUT and AMPLIFIER GAIN. §4.5.....	8
Test Data: Power Output Measurement Table	8
AGC THRESHOLD §4.2	9
Test Data: AGC Table.....	9
OUT-OF-BAND REJECTION § 4.3	10
Test Data: Downlink 450.00 MHz	10
Test Data: Downlink 470.00 MHz	11
Test Data: Uplink 462.00 MHz	12
Test Data: Uplink 490.00 MHz	13
INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, DOWNLINK 450 MHz	14
Test Data: Downlink 450.025 MHz – 6.25 kHz Test Signal	15
Test Data: Downlink 450.025 MHz – 6.25 kHz Below AGC Threshold.....	16
Test Data: Downlink 450.025 MHz – 6.25 kHz +3 dBm Above AGC Threshold	17
Test Data: Downlink 450.025 MHz – 12.5 kHz Test Signal	18
Test Data: Downlink 450.025 MHz – 12.5 kHz Below AGC Threshold.....	19
Test Data: Downlink 450.025 MHz – 12.5 kHz +3 dBm Above AGC Threshold	20
Test Data: Downlink 450.025 MHz – 25 kHz Test Signal.....	21
Test Data: Downlink 450.025 MHz – 25 kHz Below AGC Threshold	22
Test Data: Downlink 450.025 MHz – 25 kHz +3 dBm Above AGC Threshold	23
Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM Test Signal.....	24
Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM Below AGC Threshold	25
Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold ..	26
Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM Test Signal	27
Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM Below AGC Threshold.....	28
Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold	29
INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, DOWNLINK 470 MHz	30
Test Data: Downlink 470.00 MHz – 6.25 kHz Test Signal	30
Test Data: Downlink 470.00 MHz – 6.25 kHz Below AGC Threshold	31
Test Data: Downlink 470.00 MHz – 6.25 kHz +3 dBm Above AGC Threshold.....	32
Test Data: Downlink 470.00 MHz – 12.5 kHz Test Signal	33
Test Data: Downlink 470.00 MHz – 12.5 kHz Below AGC Threshold	34
Test Data: Downlink 470.00 MHz – 12.5 kHz +3 dBm Above AGC Threshold.....	35
Test Data: Downlink 470.00 MHz – 25 kHz Test Signal.....	36
Test Data: Downlink 470.00 MHz – 25 kHz Below AGC Threshold	37
Test Data: Downlink 470.00 MHz – 25 kHz +3 dBm Above AGC Threshold.....	38
Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM Test Signal.....	39
Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM Below AGC Threshold	40
Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold ...	41
Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM Test Signal	42
Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM Below AGC Threshold	43



Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold ..	44
INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, UPLINK 462 MHz	45
Test Data: Uplink 462.00 MHz – 6.25 kHz Test Signal	45
Test Data: Uplink 462.00 MHz – 6.25 kHz Below AGC Threshold	46
Test Data: Uplink 462.00 MHz – 6.25 kHz +3 dBm Above AGC Threshold	47
Test Data: Uplink 462.00 MHz – 12.5 kHz Test Signal	48
Test Data: Uplink 462.00 MHz – 12.5 kHz Below AGC Threshold	49
Test Data: Uplink 462.00 MHz – 12.5 kHz +3 dBm Above AGC Threshold	50
Test Data: Uplink 462.00 MHz – 25 kHz Test Signal	51
Test Data: Uplink 462.00 MHz – 25 kHz Below AGC Threshold	52
Test Data: Uplink 462.00 MHz – 25 kHz +3 dBm Above AGC Threshold	53
Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM Test Signal	54
Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM Below AGC Threshold	55
Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold	56
Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM Test Signal	57
Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM Below AGC Threshold	58
Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold	59
INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, UPLINK 490 MHz	60
Test Data: Uplink 489.975 MHz – 6.25 kHz Test Signal	60
Test Data: Uplink 489.975 MHz – 6.25 kHz Below AGC Threshold	61
Test Data: Uplink 489.975 MHz – 6.25 kHz +3 dBm Above AGC Threshold	62
Test Data: Uplink 489.975 MHz – 12.5 kHz Test Signal	63
Test Data: Uplink 489.975 MHz – 12.5 kHz Below AGC Threshold	64
Test Data: Uplink 489.975 MHz – 12.5 kHz +3 dBm Above AGC Threshold	65
Test Data: Uplink 489.975 MHz – 25 kHz Test Signal	66
Test Data: Uplink 489.975 MHz – 25 kHz Below AGC Threshold	67
Test Data: Uplink 489.975 MHz – 25 kHz +3 dBm Above AGC Threshold	68
Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM Test Signal	69
Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM Below AGC Threshold	70
Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold	71
Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM Test Signal	72
Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM Below AGC Threshold	73
Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold	74
NOISE FIGURE §4.6	75
Test Data: Noise Measurement Table	75
OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, DOWNLINK 450 MHz	77
Test Data: 6.25 kHz Intermodulation without AGC	78
Test Data: 6.25 kHz Intermodulation AGC +3 dB	79
Test Data: 12.5 kHz Intermodulation without AGC	80
Test Data: 12.5 kHz Intermodulation AGC +3 dB	81
Test Data: 25 kHz Intermodulation without AGC	82
Test Data: 25 kHz Intermodulation AGC +3 dB	83



OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, DOWNLINK 470 MHz	84
Test Data: 6.25 kHz Intermodulation without AGC	85
Test Data: 6.25 kHz Intermodulation AGC +3 dB	86
Test Data: 12.5 kHz Intermodulation without AGC	87
Test Data: 12.5 kHz Intermodulation AGC +3 dB	88
Test Data: 25 kHz Intermodulation without AGC	89
Test Data: 25 kHz Intermodulation AGC +3 dB	90
OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, UPLINK 462 MHz	91
Test Data: 6.25 kHz Intermodulation without AGC	92
Test Data: 6.25 kHz Intermodulation AGC +3 dB	93
Test Data: 12.5 kHz Intermodulation without AGC	94
Test Data: 12.5 kHz Intermodulation AGC +3 dB	95
Test Data: 25 kHz Intermodulation without AGC	96
Test Data: 25 kHz Intermodulation AGC +3 dB	97
OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, UPLINK 490 MHz	98
Test Data: 6.25 kHz Intermodulation without AGC	99
Test Data: 6.25 kHz Intermodulation AGC +3 dB	100
Test Data: 12.5 kHz Intermodulation without AGC	101
Test Data: 12.5 kHz Intermodulation AGC +3 dB	102
Test Data: 25 kHz Intermodulation without AGC	103
Test Data: 25 kHz Intermodulation AGC +3 dB	104
ANTENNA CONDUCTED EMISSIONS §4.7	105
Test Data: Downlink 450.025 MHz	106
Test Data: Downlink 470.00 MHz	107
Test Data: Uplink 462.00 MHz	108
Test Data: Uplink 490.00 MHz	109
FREQUENCY STABILITY MEASUREMENTS §4.8	110
FIELD STRENGTH OF SPURIOUS RADIATION EMISSIONS §4.9	111
Test Data: Downlink 450.00 MHz Radiated Emission Table	111
Test Data: Downlink 470.00 MHz Radiated Emission Table	111
Test Data: Uplink 462.00 MHz Radiated Emission Table	112
Test Data: Uplink 490.00 MHz Radiated Emission Table	112
EQUIPMENT LIST	113
STATEMENT OF MEASUREMENT UNCERTAINTY	114

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

Summary

The device under test does:

- ☒ Fulfill the general approval requirements as identified in this test report and was selected by the customer.
- ☐ Not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025 requirements.

I attest that the necessary measurements were made at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669



Tested by:

Name and Title: Franklin Rose, Testing Technician/Project Manager

Date: 11/27/2017



Reviewed and approved by:

Name and Title: Sid Sanders , Engineer

Date: 11/28/2017

EUT DESCRIPTION

EUT Description	UHF SIGNAL BOOSTER
FCC ID	2AHVPSB400M2A
Model Number	SB400M2A
Operating Frequency	450.00, 462.00, 470.00, 490.00 MHz
Type of Emission	16K0F3E, 11K3F3E, 8K10F1E, 8K10F1W, 4K00F1E
EUT Power Source	☒ 110–120Vac/50– 60Hz
	☐ DC Power 27V
	☐ Battery Operated Exclusively
Test Item	☐ Prototype
	☒ Pre-Production
	☐ Production
Type of Equipment	☒ Fixed
	☐ Mobile
	☐ Portable
Test Conditions	The temperature was 26°C with a relative humidity of 50%.
Revision History to the EUT	None
Test Exercise	The EUT was operated in a normal mode.
Applicable Standards	FCC CFR 47 Part 90.219, KDB 935210 D05 v01r01, 971168 D01 v02r02
Test Facility	Timco Engineering Inc. at 849 NW State Road 45 Newberry, FL 32669 USA.

EUT Notes: The EUT is pre-programmed with discreet frequencies from the factory which cannot be altered by the user. In the case of this testing, the EUT was pre-programmed with Downlinks 450 and 470 MHz, and Uplinks 462 and 490 MHz.

TEST RESULTS SUMMARY

FCC RULE PART	Limit	TEST DESCRIPTION	RESULT PASS/FAIL
47CFR90.219(e)(1) AND KDB 935210-D05 v01r01 §4.5	Reporting Only	Input/output power	PASS
KDB 935210-D05 v01r01 §4.2	Reporting Only	AGC Threshold	PASS
KDB 935210-D05 v01r01 §4.3	Reporting Only	Out-Of-band rejection	PASS
47CFR90.219(e)(4) AND KDB 935210-D05 v01r01 §4.4	Reporting Only	Input-versus-output signal comparison	PASS
47CFR90.219(e)(2) AND KDB 935210-D05 v01r01 §4.6	9 dB	Noise Figure	PASS
47CFR90.210 AND KDB 935210-D05 v01r01 §4.7.2	-13 dBm	Out-of-band/out-of- block Intermodulation	PASS
47CFR90.219(e)(3) AND KDB 935210-D05 v01r01 §4.7.3	-13 dBm	Spurious Emissions Conducted	PASS
47CFR90.213 AND KDB 935210-D05 v01r01 §4.8	Refer to Table	Frequency Stability	NOT REQUIRED
47CFR90.210 AND KDB 935210-D05 v01r01 §4.9	-13 dBm	Spurious emissions radiated	PASS

RF POWER OUTPUT and AMPLIFIER GAIN. §4.5

Rule Part No.: Part 2.1046(a), Part 90.219 (e) (1)

Requirements: 5.0Watts ERP

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
 § 4.5.1 General
 § 4.5.2 Determining Amplifier/Booster Gain
 § 4.5.4 Power Measurement Method 2: Using a power meter

The Input and Output power levels were recorded and the gain calculated using the following formula:

$$\text{Gain}_{\text{dB}} = \text{Output Power}_{\text{dBm}} - \text{Input Power}_{\text{dBm}}$$

Test Data: Power Output Measurement Table

Mode	AGC	Input Freq (MHz)	Input Power (dBm)	Output Power (dBm)	Limit (dBm)	Margin (dB)	Gain (dB)
CW	Below	450.00	-20.90	32.05	36.99	4.94	52.95
CW	+3 dB	450.00	-17.90	32.21	36.99	4.78	50.11
CW	Below	462.00	-20.90	31.22	36.99	5.77	52.12
CW	+3 dB	462.00	-17.90	31.52	36.99	5.47	49.42
CW	Below	470.00	-20.90	31.81	36.99	5.18	52.71
CW	+3 dB	470.00	-17.90	32.04	36.99	4.95	49.94
CW	Below	490.00	-20.90	32.03	36.99	4.96	52.93
CW	+3 dB	490.00	-17.90	32.26	36.99	4.73	50.16

Part 2.1033 (C) (8) DC Input into the final amplifier

INPUT POWER: (110 VAC) (2.1 A) = **231 Watts Maximum**

AGC THRESHOLD §4.2

Rule Part No.: KDB935210 § 4.2

Requirements: Reporting only, used to determine test input levels

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.2 Measuring AGC threshold

Test Data: AGC Table

Frequency (MHz)	Input Level (dBm)	Booster Output (dBm)
470	-22.9	-9.23
470	-21.9	-8.24
470	-20.9	-7.64
470	-19.9	-7.65
470	-18.9	-7.66
470	-17.9	-7.67

Note: Yellow denotes level below AGC; green denotes AGC level +3 dB


OUT-OF-BAND REJECTION § 4.3

Rule Part No.: KDB 935210 §4.3 Out of band rejection

Requirements: Reporting Only

Procedure: KDB 935210 §4.3 Out of band rejection


Test Data: Downlink 450.00 MHz



Date: 6.OCT.2017 13:53:27

Out-of-Band Rejection §4.3


Test Data: Downlink 470.00 MHz



Date: 6.OCT.2017 14:17:23

Out-of-Band Rejection §4.3


Test Data: Uplink 462.00 MHz



Date: 22.NOV.2017 15:49:34

Out-of-Band Rejection §4.3

Test Data: Uplink 490.00 MHz



Date: 6.OCT.2017 14:42:42

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, DOWNLINK 450 MHz

Rule Part No.: 47CFR90.219(e)(4)
KDB 935210-D05 v01r01 §4.4

Requirements: A signal booster must be designed such that all signals that it retransmits meet the following requirements:

The signals are retransmitted on the same channels as received. Minor departures from the exact provider or reference frequencies of the input signals are allowed, provided that the retransmitted signals meet the requirements of §90.213.

There is no change in the occupied bandwidth of the retransmitted signals.


The retransmitted signals continue to meet the unwanted emissions limits of §90.210 applicable to the corresponding received signals (assuming that these received signals meet the applicable unwanted emissions limits by a reasonable margin).

Procedure: KDB935210 § 4.4 Input versus output signal comparison

The EUT was test for this requirement at 3 places in the band and the data below represents the worst case.

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 6.25 kHz Test Signal



Date: 29.NOV.2017 09:44:20

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 6.25 kHz Below AGC Threshold



Date: 29.NOV.2017 09:32:43

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 6.25 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:34:23

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 12.5 kHz Test Signal



Date: 29.NOV.2017 10:20:45

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 12.5 kHz Below AGC Threshold



Date: 29.NOV.2017 09:50:19

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 12.5 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:54:32

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 25 kHz Test Signal



Date: 29.NOV.2017 11:29:16

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 25 kHz Below AGC Threshold



Date: 29.NOV.2017 11:21:16

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – 25 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 11:27:19

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM Test Signal



Date: 29.NOV.2017 10:24:12

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM Below AGC Threshold



Date: 29.NOV.2017 10:36:28

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold



Date: 29.NOV.2017 10:43:46

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM Test Signal



Date: 29.NOV.2017 10:25:34

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM Below AGC Threshold



Date: 29.NOV.2017 10:48:10

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

Test Data: Downlink 450.025 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold




Date: 29.NOV.2017 10:48:10

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, DOWNLINK 470 MHz


Test Data: Downlink 470.00 MHz – 6.25 kHz Test Signal



Date: 29.NOV.2017 09:44:20

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 6.25 kHz Below AGC Threshold



Date: 29.NOV.2017 09:35:30

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 6.25 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:36:19

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 12.5 kHz Test Signal



Date: 29.NOV.2017 10:20:45

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 12.5 kHz Below AGC Threshold



Date: 29.NOV.2017 09:55:49

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 12.5 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:56:49

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 25 kHz Test Signal



Date: 29.NOV.2017 11:29:16

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 25 kHz Below AGC Threshold



Date: 22.NOV.2017 12:14:21

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – 25 kHz +3 dBm Above AGC Threshold



Date: 22.NOV.2017 12:14:46

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM Test Signal



Date: 29.NOV.2017 10:24:12

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM Below AGC Threshold



Date: 29.NOV.2017 10:53:17

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold



Date: 29.NOV.2017 10:57:13

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM Test Signal



Date: 29.NOV.2017 10:25:34

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM Below AGC Threshold



Date: 29.NOV.2017 10:54:18

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

Test Data: Downlink 470.00 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold




Date: 29.NOV.2017 10:58:18

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, UPLINK 462 MHz


Test Data: Uplink 462.00 MHz – 6.25 kHz Test Signal



Date: 29.NOV.2017 09:44:20

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 6.25 kHz Below AGC Threshold



Date: 29.NOV.2017 09:39:21

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 6.25 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:38:36

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 12.5 kHz Test Signal



Date: 29.NOV.2017 10:20:45

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 12.5 kHz Below AGC Threshold



Date: 29.NOV.2017 09:59:48

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 12.5 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 09:58:59

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 25 kHz Test Signal



Date: 29.NOV.2017 11:29:16

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 25 kHz Below AGC Threshold



Date: 22.NOV.2017 12:02:40

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – 25 kHz +3 dBm Above AGC Threshold



Date: 22.NOV.2017 12:03:15

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM Test Signal



Date: 29.NOV.2017 10:24:12

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM Below AGC Threshold



Date: 29.NOV.2017 11:06:58

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold



Date: 29.NOV.2017 11:03:05

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM Test Signal



Date: 29.NOV.2017 10:25:34

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM Below AGC Threshold



Date: 29.NOV.2017 11:08:03

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

Test Data: Uplink 462.00 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold




Date: 29.NOV.2017 11:03:53

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4, UPLINK 490 MHz


Test Data: Uplink 489.975 MHz – 6.25 kHz Test Signal



Date: 29.NOV.2017 09:44:20

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 6.25 kHz Below AGC Threshold



Date: 29.NOV.2017 09:40:13


INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

Test Data: Uplink 489.975 MHz – 6.25 kHz +3 dBm Above AGC Threshold



INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 12.5 kHz Test Signal



Date: 29.NOV.2017 10:20:45

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 12.5 kHz Below AGC Threshold



Date: 29.NOV.2017 10:01:23

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 12.5 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 10:02:22

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 25 kHz Test Signal



Date: 29.NOV.2017 11:29:16

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 25 kHz Below AGC Threshold



Date: 29.NOV.2017 11:31:26

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – 25 kHz +3 dBm Above AGC Threshold



Date: 29.NOV.2017 11:32:17

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM Test Signal



Date: 29.NOV.2017 10:24:12

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM Below AGC Threshold



Date: 29.NOV.2017 11:11:36

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – P25 Phase 1 C4FM +3 dBm Above AGC Threshold



Date: 29.NOV.2017 11:16:04

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM Test Signal



Date: 29.NOV.2017 10:25:34

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4


Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM Below AGC Threshold



Date: 29.NOV.2017 11:12:31

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

Test Data: Uplink 489.975 MHz – P25 Phase 2 H-CPM +3 dBm Above AGC Threshold



Date: 29.NOV.2017 11:17:02

INPUT-VERSUS-OUTPUT SIGNAL COMPARISON §4.4

NOISE FIGURE §4.6


Rule Part No.: 47CFR90.219(e)(2)
KDB 935210-D05 v01r01 §4.6

Requirements: 9 dB

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.6 Noise Figure Measurements

1MA178_2e R&S Application Note the Y Factor Technique Noise Figure
§ 2 Background Theory and Equations
§ 3 Detailed Measurement Steps

Setup Diagram:



Test Data: Noise Measurement Table

$T_{ON\ source} (K)$	$T_{OFF\ source} (K)$	Source ENR (dB)
9545.45978	290	15.04

Step 1 Calibration of Noise Source with ESU 40								
F_c	$N_{SA\ off}$		$N_{SA\ on}$		Y_{SA}	T_{SA}	NF_{SA}	
MHz	dBm	fW	dBm	fW	Linear	Analyzer	dB	
490	-114.41	3.62	-107.01	19.91	5.50	1768.87	8.51	

Step 2 Noise Measurement with EUT								
F_c	$N_{EUT\ \&\ SA\ off}$		$N_{EUT\ \&\ SA\ on}$		$Y_{EUT\ \&\ SA}$	$T_{EUT\ \&\ SA}$	NF	
MHz	dBm	fW	dBm	fW	Linear	Cascade	dB	
490	-13.39	45814188671.45	-5.28	296483138952.43	6.47	1401.60	7.66	

Step 3 Noise Figure Calculation for EUT						
F_c	Gain	Gain	T_{EUT}	NF	Limit	Margin
MHz	Num	dB	EUT	dB	≤dB	dB
490	15393286654	101.87	1401.60	7.66	9.00	1.34

Results Meet Requirements

OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, DOWNLINK 450 MHz


Rule Part No.: 47CFR90.210
KDB 935210-D05 v01r01 §4.7.2

Requirements: -13 dBm

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.7.2 Out of Band/ Out of block emissions conducted measurements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz


Test Data: 6.25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:43:37

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz

Test Data: 6.25 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:44:11

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz


Test Data: 12.5 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:45:23

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz

Test Data: 12.5 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:46:15

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz


Test Data: 25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:47:32

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 450.00 MHz

Test Data: 25 kHz Intermodulation AGC +3 dB



Date: 22.NOV.2017 09:47:59

Results Meet Requirements

OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, DOWNLINK 470 MHz


Rule Part No.: 47CFR90.210
KDB 935210-D05 v01r01 §4.7.2

Requirements: -13 dBm

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.7.2 Out of Band/ Out of block emissions conducted measurements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz


Test Data: 6.25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:50:48

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz

Test Data: 6.25 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:51:26

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz


Test Data: 12.5 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:52:37

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz

Test Data: 12.5 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:53:15

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz


Test Data: 25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:54:14

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Downlink 470.00 MHz

Test Data: 25 kHz Intermodulation AGC +3 dB



Date: 22.NOV.2017 09:56:09

Results Meet Requirements

OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, UPLINK 462 MHz


Rule Part No.: 47CFR90.210
KDB 935210-D05 v01r01 §4.7.2

Requirements: -13 dBm

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.7.2 Out of Band/ Out of block emissions conducted measurements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, UPLINK 462 MHz


Test Data: 6.25 kHz Intermodulation without AGC



Date: 22.NOV.2017 15:36:04

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 462.00 MHz

Test Data: 6.25 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 15:36:59

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 462.00 MHz


Test Data: 12.5 kHz Intermodulation without AGC



Date: 22.NOV.2017 15:38:07

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 462.00 MHz

Test Data: 12.5 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 15:39:06

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 462.00 MHz


Test Data: 25 kHz Intermodulation without AGC



Date: 22.NOV.2017 15:40:10

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 462.00 MHz

Test Data: 25 kHz Intermodulation AGC +3 dB



Date: 22.NOV.2017 15:40:39

Results Meet Requirements

OUT OF BAND / OUT OF BLOCK EMISSIONS §4.7, UPLINK 490 MHz


Rule Part No.: 47CFR90.210
KDB 935210-D05 v01r01 §4.7.2

Requirements: -13 dBm

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.7.2 Out of Band/ Out of block emissions conducted measurements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz


Test Data: 6.25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:33:25

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz

Test Data: 6.25 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:34:20

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz


Test Data: 12.5 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:35:59

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz

Test Data: 12.5 kHz Intermodulation AGC +3 dB




Date: 22.NOV.2017 09:36:52

Results Meet Requirements

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz


Test Data: 25 kHz Intermodulation without AGC



Date: 22.NOV.2017 09:39:23

Out-of-band / out-of-block Emissions (Intermodulation) §4.7.2, Uplink 490.00 MHz

Test Data: 25 kHz Intermodulation AGC +3 dB



Date: 22.NOV.2017 09:40:18

Results Meet Requirements


ANTENNA CONDUCTED EMISSIONS §4.7

Rule Part No.: 47CFR90.219(e)(3)
KDB 935210-D05 v01r01 §4.7.3

Requirements: -13 dBm in any 100 kHz bandwidth


Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.7.3 EUT Spurious emissions conducted measurements

Test Setup Diagram:



ANTENNA CONDUCTED EMISSIONS §4.7

Test Data: Downlink 450.025 MHz



Date: 6.OCT.2017 13:58:16


Results Meet Requirements

APPLICANT: RADIO SOLUTIONS, INC.
 FCC ID: 2AHVPSB400M2A
 REPORT #: 1702AUT17TestReportRev2

[TABLE OF CONTENTS](#)

ANTENNA CONDUCTED EMISSIONS §4.7

Test Data: Downlink 470.00 MHz



Date: 6.OCT.2017 14:22:13


Results Meet Requirements

APPLICANT: RADIO SOLUTIONS, INC.
 FCC ID: 2AHVPSB400M2A
 REPORT #: 1702AUT17TestReportRev2

[TABLE OF CONTENTS](#)

ANTENNA CONDUCTED EMISSIONS §4.7

Test Data: Uplink 462.00 MHz




Date: 22.NOV.2017 11:09:04

Results Meet Requirements

ANTENNA CONDUCTED EMISSIONS §4.7

Test Data: Uplink 490.00 MHz



Date: 6.OCT.2017 14:47:32

Results Meet Requirements

APPLICANT: RADIO SOLUTIONS, INC.
 FCC ID: 2AHVPSB400M2A
 REPORT #: 1702AUT17TestReportRev2

[TABLE OF CONTENTS](#)

FREQUENCY STABILITY MEASUREMENTS §4.8

Rule Part No.: FCC 90.219(e)(4)(i), FCC 90.213
KDB 935210-D05 v01r01 §4.9

Requirements: Reporting Only

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.8 Frequency Stability Measurements

Section 90.219(e)(4)(i) requires that a signal being retransmitted by an amplifier, repeater, or industrial booster meets the frequency stability requirements of Section 90.213. However, this requirement presumes that the EUT processes an input signal in ways that can influence the output signal frequency/frequencies; however, most signal boosters do not incorporate an oscillator). If the amplifier, booster, or repeater does not alter the input signal in any way, then a frequency stability test may not be required.

Result: Not required.

FIELD STRENGTH OF SPURIOUS RADIATION EMISSIONS §4.9

Rule Part No.: 47CFR90.210
KDB 935210-D05 v01r01 §4.9

Requirements: -13 dBm in any 100 kHz bandwidth

Procedure: KDB935210 Measurement Guidance for Industrial Boosters
§ 4.7.1 General
§ 4.9 Spurious emissions radiated measurements

The tabulated data shows the results of the radiated field strength emissions test. The spectrum was scanned from 9 KHz to at least the tenth harmonic of the fundamental. The EUT was oriented in the worst-case polarity, and was scanned in the worst-case emission range as determined in prior testing. Measurements were made at the test site of **TIMCO ENGINEERING, INC. located at 849 NW State Road 45, Newberry, FL 32669.**

Test Data: Downlink 450.00 MHz Radiated Emission Table

Tuned Frequency (MHz)					
Downlink - 450.00 MHz					
Emission Frequency (MHz)	Antenna Polarity	Field Strength (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dBm)
4500.00	V	59.660	-37.717	-13.000	-24.717
4500.00	H	59.450	-37.927	-13.000	-24.927
4050.00	V	59.285	-38.092	-13.000	-25.092
4050.00	H	58.595	-38.782	-13.000	-25.782
3600.00	V	57.810	-39.567	-13.000	-26.567
3600.00	H	56.860	-40.517	-13.000	-27.517

NOTE: The highest six (6) emissions are tabulated above. Emissions under 20 dB within the applicable limit(s) are not required to be shown.

Test Data: Downlink 470.00 MHz Radiated Emission Table

Tuned Frequency (MHz)					
Downlink - 470.00 MHz					
Emission Frequency (MHz)	Antenna Polarity	Field Strength (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dBm)
4700.00	V	59.940	-37.437	-13.000	-24.437
4700.00	H	59.690	-37.687	-13.000	-24.687
4230.00	H	58.557	-38.820	-13.000	-25.820
4230.00	V	58.527	-38.850	-13.000	-25.850
3760.00	V	57.562	-39.815	-13.000	-26.815
3760.00	H	57.362	-40.015	-13.000	-27.015

NOTE: The highest six (6) emissions are tabulated above. Emissions under 20 dB within the applicable limit(s) are not required to be shown.

FIELD STRENGTH OF SPURIOUS RADIATION EMISSIONS §4.9

Test Data: Uplink 462.00 MHz Radiated Emission Table

Tuned Frequency (MHz)					
Uplink - 462.00 MHz					
Emission Frequency (MHz)	Antenna Polarity	Field Strength (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dBm)
4620.00	H	59.604	-37.773	-13.000	-24.773
4620.00	V	59.474	-37.903	-13.000	-24.903
4158.00	H	59.062	-38.315	-13.000	-25.315
4158.00	V	58.672	-38.705	-13.000	-25.705
3696.00	V	58.287	-39.090	-13.000	-26.090
3696.00	H	57.757	-39.620	-13.000	-26.620

NOTE: The highest six (6) emissions are tabulated above. Emissions under 20 dB within the applicable limit(s) are not required to be shown.

Test Data: Uplink 490.00 MHz Radiated Emission Table

Tuned Frequency (MHz)					
Uplink - 490.00 MHz					
Emission Frequency (MHz)	Antenna Polarity	Field Strength (dBuV/m)	ERP (dBm)	Limit (dBm)	Margin (dBm)
4410.00	H	59.810	-37.567	-13.000	-24.567
4900.00	V	59.460	-37.917	-13.000	-24.917
4410.00	V	59.430	-37.947	-13.000	-24.947
4900.00	H	58.970	-38.407	-13.000	-25.407
3920.00	V	58.506	-38.871	-13.000	-25.871
3920.00	H	58.206	-39.171	-13.000	-26.171

NOTE: The highest six (6) emissions are tabulated above. Emissions under 20 dB within the applicable limit(s) are not required to be shown.

Results meet requirements

EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal / Char Date	Due Date
Coaxial Cable - BMBM-0065-01 Black DC-2G	Belden		BMBM-0065-01	07/18/16	07/18/18
Antenna: Biconical 1096	Eaton	94455-1	1096	08/01/17	08/01/19
Antenna: Log- Periodic 1243	Eaton	96005	1243	02/09/16	02/09/18
Coaxial Cable - Chamber 3 cable set (backup)	Micro-Coax	Chamber 3 cable set (backup)	KMKM-0244-02 ; KMKM-0670- 01; KFKF-0197- 00	N/A	N/A
CHAMBER	Panashield	3M	N/A	04/25/16	12/31/17
HP Signal Generator	HP	8648C	3847A04696	04/05/2017	04/05/2019
Antenna: Double- Ridged Horn/ETS Horn 2	ETS-Lindgren	3117	00041534	03/01/17	03/01/19
EMI Test Receiver R & S ESIB 40 Screen Room	Rohde & Schwarz	ESIB 40	100274	08/16/16	08/16/18
Software: Field Strength Program	Timco	N/A	Version 4.10.7.0	N/A	N/A
Antenna: Active Loop	ETS-Lindgren	6502	00062529	11/18/15	12/18/17
EMI Test Receiver R & S ESU 40 Chamber	Rohde & Schwarz	ESU 40	100320	04/01/16	04/01/18
Coaxial Cable - BMBM-0130-00 Black	Alpha Wire		BMBM-0130-00	05/24/16	05/24/18
Coaxial Cable - BMBM-0155-01 Black	BELDEN		BMBM-0155-01	06/01/16	06/01/18
Coaxial Cable - BMBM-0065-00 Black	Belden		BMBM-0065-00	06/08/16	06/08/18
Coaxial Cable - BMBM-0155-00 Black	MIYAZAKI		BMBM-0155-00	05/24/16	05/24/18
Splitter 1-1000MHz	Mini-Circuits	ZFSC-4-1- BNC+	U115700825	N/A	N/A
Signal Generator R & S SMU 200A	Rohde & Schwarz	SMU200A	103195	02/29/16	02/28/18
Non Radiating 50 OHM Load	Sierra Elec	160B-600X	1038	09/13/16	09/13/18
Attenuator N 20dB 2W DC-13G	Narda	757C	30201	05/24/17	05/24/19
Attenuator N 20dB 2W DC-13G	Narda	777C	36124	05/24/17	05/23/19
Bore-sight Antenna Positioning Tower	Sunol Sciences	TLT2	N/A	N/A	N/A
Noise Source 10MHz - 18GHz	Agilent	346B	MY44421884	N/A	N/A

*EMI RECEIVER SOFTWARE VERSION

The receiver firmware used was version 4.43 Service Pack 3

STATEMENT OF MEASUREMENT UNCERTAINTY

The data and results referenced in this document are true and accurate. The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16-4 or ENTR 100-028 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: “Uncertainty in EMC Measurements” and is documented in the Timco Engineering, Inc. quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Timco Engineering, Inc. is reported:

Test Items	Measurement Uncertainty	Notes
RF Frequency Accuracy	± 49.5 Hz	(1)
RF Conducted Power	± 0.93 dB	(1)
Conducted spurious emission of transmitter valid up to 40GHz	± 1.86 dB	
Occupied Bandwidth	± 2.65 %	
Audio Frequency Response	± 1.86 dB	
Modulation limiting	± 1.88 %	
Radiated RF Power	± 1.4 dB	
Maximum frequency deviation: Within 300 Hz and 6kHz of audio freq.	± 1.88 %	
Within 6kHz and 25kHz of audio Freq.	± 2.04 %	
Rad Emissions Sub Meth up to 26.5GHz	± 2.14 dB	
Rad Emissions Sub Meth up to 18-40 GHz	± 2.04 %	
Adjacent channel power	± 1.47 dB	(1)
Transient Frequency Response	± 1.88 %	
Temperature	$\pm 1.0^{\circ}$ C	(1)
Humidity	± 5.0 %	

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

END OF REPORT