



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



RF EXPOSURE EVALUATION REPORT

Applicant: Guilin Feiyu Technology Incorporated Company

Address: Feiyu Intelligent Industry Park, No.2, Chuangyou Road, Information Industry Park, Qixing District, Guilin, Guangxi, 541004, China.

FCC ID: 2AHW7-FEIYUPT4

Product Name: Feiyu Pocket 4 Handheld Gimbal Camera

Standard(s): 47 CFR §1.1307, 47 CFR §2.1093

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2603R48538E-RF-00E

Date Of Issue: 2026/6/4

Reviewed By: Calvin Chen

Title: RF Test Supervisor

Reviewed By: Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town, Dongguan City, Guangdong, China.

Tel: +86-769-83085888

www.ccttt.com.cn

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the Room 101 & 201, Building 2, 256 Pingdong Road, Dalang Town, Dongguan City, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY.....	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
2. RF EXPOSURE EVALUATION	6
2.1 RF EXPOSURE EVALUATION	6

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2603R48538E-RF-00E	Original Report	2026/6/4

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Feiyu Pocket 4 Handheld Gimbal Camera
EUT Model:	FeiyuPT4
Rated Input Voltage:	DC 5V/9V from USB or DC 7.4V from battery
EUT Received Date:	2026/3/24
EUT Received Status:	Good

2. RF EXPOSURE EVALUATION

2.1 RF Exposure Evaluation

2.1.1 Applicable Standard

According to §15.247(i), §15.407(f) and §1.1307, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.1.2 Measurement Result

Radio	Frequency (MHz)	Conducted Output Power Including Tolerance [▲]		Distance (mm)	Calculated value	Threshold (10-g)	SAR Test Exclusion
		(dBm)	(mW)				
BDR/EDR	2402-2480	5	3.16	5	1	7.5	YES
BLE	2402-2480	7	5.01	5	1.6	7.5	YES
2.4G Wi-Fi	2412-2462	11	12.59	5	4	7.5	YES
5.2G Wi-Fi	5180-5240	11	12.59	5	5.8	7.5	YES
5.8G Wi-Fi	5745-5825	10	10	5	4.8	7.5	YES

Note:

1. The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.
2. Bluetooth and Wi-Fi can not transmit simultaneously

Result: Compliant. The stand-alone SAR test is not necessary.

===== END OF REPORT =====