RF Exposure Evaluation Report

Product	:	Battery Grip
Trade mark	:	FeiyuTech
Model/Type reference	:	FeiyuPT4A
Serial Number	:	N/A
Report Number	:	EED32S823117
FCC ID	:	2AHW7-FEIYUPT4AG
Date of Issue	:	October 8, 2026
Test Standards	:	47 CFR Part 1.1307 47 CFR Part 1.1310 47 CFR Part 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01
Test result	:	PASS

Prepared for:

Guilin Feiyu Technology Incorporated Company
Feiyu Intelligent Industry Park, No.2, Chuangyou Road, Information Industry Park, Qixing District, Guilin, Guangxi, 541004, China.

Prepared by:

Centre Testing International Group Co., Ltd.
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by: Frazer Li

Reviewed by: Tom Chen

Approved by: Aaron Ma

Date: October 8, 2026

Check No.: 8043310826

1 Contents

Page

1 CONTENTS 2

2 GENERAL INFORMATION 3

2.1 CLIENT INFORMATION 3
2.2 GENERAL DESCRIPTION OF EUT 3
2.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 3
2.4 TEST LOCATION 4
2.5 DEVIATION FROM STANDARDS 4
2.6 ABNORMALITIES FROM STANDARD CONDITIONS 4
2.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER 4

3 SAR EVALUATION 5

3.1 RF EXPOSURE COMPLIANCE REQUIREMENT 5
3.1.1 Limits 5
3.1.2 Test Procedure 5
3.1.3 EUT RF Exposure Evaluation 6

2 General Information

2.1 Client Information

Applicant:	Guilin Feiyu Technology Incorporated Company
Address of Applicant:	Feiyu Intelligent Industry Park, No.2, Chuangyou Road, Information Industry Park, Qixing District, Guilin, Guangxi, 541004, China.
Manufacturer:	Guilin Feiyu Technology Incorporated Company
Address of Manufacturer:	Feiyu Intelligent Industry Park, No.2, Chuangyou Road, Information Industry Park, Qixing District, Guilin, Guangxi, 541004, China.
Factory:	Guilin Feiyu Technology Incorporated Company
Address of Factory:	Feiyu Intelligent Industry Park, No.2, Chuangyou Road, Information Industry Park, Qixing District, Guilin, Guangxi, 541004, China.

2.2 General Description of EUT

Product Name:	Battery Grip
Model No.:	FeiyuPT4A
Test Model No.:	FeiyuPT4A
Model difference:	N/A
Trade Mark:	FeiyuTech

2.3 Product Specification subjective to this standard

Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Test Software of EUT:	BT_Tool.exe	
Antenna Type:	Ceramic antenna	
Antenna Gain:	2.64 dBi	
Power Supply:	Adapter:	Model No.: N/A Input: N/A Output: N/A
	Battery:	Handle:DC 3.7V
	USB Port:	N/A
Sample Received Date:	Sep. 23, 2026	
Sample tested Date:	Sep. 23, 2026 to Sep. 29, 2026	

2.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd
Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China
Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385
No tests were sub-contracted.
FCC Designation No.: CN1164, Test Firm Registration No.: 260439

2.5 Deviation from Standards

None.

2.6 Abnormalities from Standard Conditions

None.

2.7 Other Information Requested by the Customer

None.

3 SAR Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).
This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{\text{th}}\,(\text{mW}) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \le 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \le 40\text{ cm} \end{cases}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\text{ cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{\text{th}}\,(\text{mW}) = ERP_{20\text{ cm}}\,(\text{mW}) = \begin{cases} 2040f & 0.3\text{ GHz} \le f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \le f \le 6\text{ GHz} \end{cases} \qquad \text{(B.1)}$$

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.1.3 EUT RF Exposure Evaluation

For Stand alone:

Band	Freq. (MHz)	Estimation distance (cm)	Max. Conducted Output power (dBm)	Antenna Gain (dBi)	ERP (dBm)	ERP (mW)	Limit (mW)	MPE ratio	Result
2.4G	2480	0.5	2.02	2.64	2.51	1.78	2.717	0.6560	Pass

Note：

①EIRP=conducted power+antenna gain；

②ERP=EIRP-2.15;

③EIRP(dBm) = Field strength of the fundamental signal(dBuV/m@3m) – 95.23;

④ERP(mW) = 10^(ERP (dBm)/10);

⑤The estimation distance is 0.5cm;

⑥The test data please refer to the report of EED32S823118 and only the worst case data was recorded in the report.

Statement

1. This report is considered invalid without approved signature, special seal and the seal on the perforation;

2. The Company Name shown on Report and Address, the sample(s) and sample information was/were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified;

3. The result(s) shown in this report refer(s) only to the sample(s) tested;

4. Unless otherwise stated,the decision rule for conformity reporting is based on Binary Statement for Simple Acceptance Rule stated in ILAC-G8:09/2019/CNAS-GL015:2022;

5. Without written approval of CTI, this report can't be reproduced except in full;

*** End of Report ***