



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15, CISPR PUB. 22

Applicant	: Lily Robotics, Inc.
Address	: 374 Harriet Street, San Francisco, California, United States 94103.
Equipment	: Lily Camera; Tracker
Model No.	: Lily Camera; Tracker
Brand name	: Lily
FCC ID	: Lily Camera (FCC ID: 2AHWSLILY01) Tracker (FCC ID: 2AHWSLILY00)

I HEREBY CERTIFY THAT :

The sample was received on Nov 07, 2016 and the testing was carried out on Nov 15, 2016 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Ray Chou
EMC/RF B.U. Assistant Manager



FCC TEST REPORT

Issued by:

Cerpass Technology Co.,Ltd

No.10, Lane 2, Lianfu Street, Luzhu Township, Taoyuan County 33848, Taiwan(R.O.C.)

Tel: 886-3-322-6888

Fax: 886-3-322-6881

The test record, data evaluation & Equipment. Under Test configurations represented herein are true and accurate accounts of the measurements of the samples EMC characteristics under the conditions specified in this report.

Laboratory Accreditation:

☒ Cerpass Technology Corporation Test Laboratory

NVLAP LAB Code:	200954-0
TAF LAB Code:	1439



Contents

1. Summary of Test Procedure and Test Result.....	5
1.1. Applicable Standards	5
2. Test Configuration of Equipment under Test	6
2.1. Feature of Equipment under Test.....	6
2.2. Test Manner	6
2.3. Description of Support Unit	7
2.4. Connection Diagram of Test System.....	8
2.5. General Information of Test.....	10
2.6. Measurement Uncertainty	10
3. Test of Conducted Emission.....	11
3.1. Test Limit	11
3.2. Test Procedures	11
3.3. Typical test Setup.....	12
3.4. Measurement Equipment.....	12
3.5. Test Result and Data.....	13
4. Test of Radiated Emission	15
4.1. Test Limit	15
4.2. Test Procedures	16
4.3. Typical test Setup.....	17
4.4. Measurement Equipment.....	18
4.5. Test Result and Data (30MHz~1GHz).....	19
4.6. Test Result and Data (1GHz ~ 18GHz).....	25



History of this test report

☐ ORIGINAL.

☒ Additional attachment as following record:

Report No	Version	Date	Description
SEFD1604229	Rev 01	Jun 04, 2016	Initial Issue
SEFD1604229-A	Rev 02	Nov 16, 2016	First Issue(Update the product design)



1. Summary of Test Procedure and Test Result

1.1. Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in ANSI C63.4 – 2014 and the energy emitted by this equipment was passed Part 2, Part 15, CISPR PUB. 22.

The energy emitted by this equipment was passed both Radiated and Conducted Emissions Class B limits.

Test Item	Normative References	Test Result	Remarks
Conducted Emission	ANSI C63.4-2014 FCC Part 15 Subpart B	PASS	Meets Class B Limit Minimum passing margin(AV) is -8.16dB at 0.3339MHz
Radiated Emission	ANSI C63.4-2014 FCC Part 15 Subpart B	PASS	Meets Class B Limit Minimum passing margin(QP) is -2.74dB at 575.9900MHz



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Lily Camera	Model No.:	Lily Camera	
Tracker	Model No.:	Tracker	
Power Supply	Model No.:	A15-105P1A	
	AC/DC COMBO ADAPTER	INPUT:	100-240V~2.5A 50-60Hz
		OUTPUT:	12.6V,7.5A
		USB OUTPUT:	5V,2A
	DC POWER ADAPTER	INPUT:	10-15V~5A MAX
		OUTPUT:	12.6V,2.5A MAX
		USB OUTPUT:	5V,2A
	AC Power Code	Non-Shielded,1.5 m	
	DC Power Cable	Non-Shielded,1.0 m	
Car Charger	INPUT:	DC:12V	
	OUTPUT:	DC:12V	
	Shielded,1.5M		
USB Cable	Non-Shielded,1.0 m		

2.2. Test Manner

- During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- The complete test system included EUT for EMI test.
- During the test, setup up the EUT and all system, turn on the power of all Equipments.
- Make the EUT at the test mode and it is normal operation, and then test.

The pre-test modes for CE:

Mode 1 Normal Operation in Charging Mode(From AC Power)

The pre-test modes for RE:

Mode 1 Normal Operation(EUT Only)

Mode 2 Normal Operation in Charging Mode(From AC Power)

Mode 3 Normal Operation in Charging Mode(From DC Power)

The final modes for CE:

Mode 1 Normal Operation in Charging Mode(From AC Power)

The final modes for RE:

Mode 1 Normal Operation(EUT Only)

Mode 2 Normal Operation in Charging Mode(From AC Power)

Mode 3 Normal Operation in Charging Mode(From DC Power)


**2.3. Description of Support Unit**

No.	Device	Manufacturer	Model No.	Description
N/A	N/A	N/A	N/A	N/A




2.4. Connection Diagram of Test System

Mode 1




Mode 2



No.	Cable	Quantity	Description
A	DC Cable	1	Non-Shielded, 1.0m
B	USB Cable	1	Non-Shielded, 1.0m



Mode 3



No.	Cable	Quantity	Description
A	DC Cable	1	Non-Shielded, 1.0m
B	USB Cable	1	Non-Shielded, 1.0m
C	DC Cable	1	Shielded, 1.5m



2.5. General Information of Test

Test Site :	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel:+886-3-3226-888 Fax:+886-3-3226-881 Address: No.68-1, Shihbachongsi, Shihding Township, New Taipei City 223, Taiwan, R.O.C. Tel: +886-2-2663-8582
FCC Registration Number :	TW1079, TW1061,390316, 228391, 641184
IC Registration Number :	4934B-1, 4934E-1, 4934E-2
VCCI	T-2205 for Telecommunication Test C-4663 for Conducted emission test R-3428, R-4218 for Radiated emission test G-812, G-813 for radiated disturbance above 1GHz
Frequency Range Investigated :	Conducted Emission Test: from 150 kHz to 30 MHz Radiated Emission Test: from 30 MHz to 18,000 MHz
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 3 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.

2.6. Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE / NEUTRAL	3.25 dB
Radiated Emission	30 MHz ~ 1,000 MHz	Vertical / Horizontal	3.93 dB
	1,000 MHz ~ 18,000 MHz	Vertical / Horizontal	5.18 dB

The measurement uncertainty will be considered, when test result margin to the limit.



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2009 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Conducted Emission Limits:


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



3.3. Typical test Setup




3.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2016.07.07	2017.07.06
AMN	R&S	ESH2-Z5	100182	2016.08.31	2017.08.30
Two-Line V-Network	R&S	ENV216	100325	/	/
ISN	FCC	FCC-TLISN-T2-02	20379	2016.03.26	2017.03.25
ISN	FCC	FCC-TLISN-T4-02	20380	2016.06.24	2017.06.24
ISN	FCC	FCC-TLISN-T8-02	20381	2016.03.26	2017.03.25
ISN	TESEQ	ISN ST08	30175	2016.03.26	2017.03.25
Current Probe	R&S	EZ-17	100303	2016.03.26	2017.03.25
Passive Voltage Probe	R&S	ESH2-Z3	100026	2016.03.26	2017.03.25
Pulse Limiter	R&S	ESH3-Z2	100529	2016.03.26	2017.03.25
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2016.03.29	2017.03.28
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A



3.5. Test Result and Data

Test Mode :	Mode 1: Normal Operation in Charging Mode(From AC Power)					
AC Power :	AC 120V/60Hz	Phase :	LINE			
Temperature :	24°C	Humidity :	52%			
Pressure(mbar) :	1002	Date:	2016/11/15			




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	10.13	41.59	51.72	63.20	-11.48	QP
2	0.2100	10.13	32.60	42.73	53.20	-10.47	AVG
3	0.3338	10.14	38.41	48.55	59.35	-10.80	QP
4	0.3338	10.14	34.26	44.40	59.35	-14.95	QP
5	0.5493	10.15	29.60	39.75	56.00	-16.25	QP
6	0.5493	10.15	24.12	34.27	46.00	-11.73	AVG
7	0.7669	10.16	24.82	34.98	56.00	-21.02	QP
8	0.7669	10.16	10.46	20.62	46.00	-25.38	AVG
9	8.6540	10.27	11.09	21.36	60.00	-38.64	QP
10	8.6540	10.27	2.78	13.05	50.00	-36.95	AVG
11	10.3422	10.28	27.43	37.71	50.00	-12.29	AVG
12	10.3422	10.28	29.81	40.09	50.00	-9.91	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode : Mode 1: Normal Operation in Charging Mode(From AC Power)
AC Power : AC 120V/60Hz Phase : NEUTRAL
Temperature : 24°C Humidity : 52%
Pressure(mbar) : 1002 Date: 2016/11/15



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2100	10.13	41.39	51.52	63.20	-11.68	QP
2	0.2100	10.13	32.56	42.69	53.20	-10.51	AVG
3	0.3339	10.14	39.87	50.01	59.35	-9.34	QP
4	0.3339	10.14	31.05	41.19	49.35	-8.16	AVG
5	0.5209	10.15	31.23	41.38	56.00	-14.62	QP
6	0.5209	10.15	15.78	25.93	46.00	-20.07	AVG
7	0.7274	10.16	25.49	35.65	56.00	-20.35	QP
8	0.7274	10.16	12.01	22.17	46.00	-23.83	AVG
9	8.6739	10.27	17.63	27.90	60.00	-32.10	QP
10	8.6739	10.27	15.48	25.75	50.00	-24.25	AVG
11	10.4059	10.28	9.81	20.09	60.00	-39.91	QP
12	10.4059	10.28	7.15	17.43	50.00	-32.57	AVG

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Dian



4. Test of Radiated Emission

4.1. Test Limit

Below 1GHz (for digital device)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

FREQUENCY (MHz)	dBuV/m (At 10m)	
	Class A	Class B
30 ~ 230	40	30
230 ~ 1000	47	37

Limit tables for non-digital device:

Class A Radiated Emission limit at 10m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	90	39
88 - 216	150	43.5
216 – 960	210	46.4
Above 960	300	49.5

Class B Radiated Emission limit at 3m (for others)

Frequency (MHz)	Field Strength Limit (uV/m)Q.P.	Field Strength Limit (dBuV/m)Q.P.
30 - 88	100	40
88 - 216	150	43.5
216 – 960	200	46
Above 960	500	54

Above 1GHz(for all device)

Frequency (MHz)	Class A (dBuV/m) (At 10m)		Class B (dBuV/m) (At 3m)	
	Average	Peak	Average	Peak
Above 1000	49.5	69.5	54	74

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).

(3) The measurement above 1GHz is at close-in distances 3m, and determine the limit L2 corresponding to the close-in distance d2 by applying the following relation: $L2 = L1 (d1/d2)$, where L1 is the specified limit in microvolts per metre (uV/m) at the distance d1 (10m), L2 is the new limit for distance d2 (3m).

So the new Class A limit above 1GHz at 3m is as following table:



Frequency (MHZ)	Class A (dBuV/m) (At 3m)	
	Average	Peak
Above 1000	60	80

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.75	30
1.75-108	1000
108-500	2000
500-1000	5000
Above 1000	5 th harmonic of the highest frequency or 40GHz, whichever is lower

4.2. Test Procedures

Procedure of Preliminary Test

- The equipment was set up as per the test configuration to simulate typical usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane. When the EUT is a floor standing equipment, it is placed on the ground plane which has a 15 cm non-conductive covering to insulate the EUT from the ground plane.
- Support equipment, if needed, was placed as per ANSI C63.4.
- All I/O cables were positioned to simulate typical usage as per ANSI C63.4.
- The EUT received AC 120VAC/60Hz power source from the outlet socket under the turntable. All support equipment power received from another socket under the turntable.
- The antenna was placed at 3 or 10 meter away from the EUT as stated in ANSI C63.4. The antenna connected to the Spectrum Analyzer via a cable and at times a pre-amplifier would be used.
- The Analyzer / Receiver quickly scanned from 30MHz to 40GHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.




- Set the spectrum analyzer/ Receiver in the following setting as:
Below 1GHz:
RBW=120KHz / VBW=300KHz / Sweep=AUTO
Above 1GHz:
Peak: RBW=1MHz, VBW=3MHz / Sweep=AUTO
Average: RBW=1MHz / VBW=1Hz / Sweep=AUTO
- The worst configuration of EUT and cable of the above highest emission level were recorded for reference of the final test.

Procedure of Final Test

- EUT and support equipment were set up on the turntable as per the configuration with highest emission level in the preliminary test.
- The Analyzer / Receiver scanned from 30MHz to 40GHz. Emissions were scanned and measured rotating the EUT to 360 degrees, varying cable placement and positioning the antenna 1 or 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- Recording at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. Below 1GHz the Q.P. reading and above 1GHz the Peak and Average reading are presented.
- The test data of the worst-case condition(s) was recorded.


4.3. Typical test Setup

Below 1GHz Test Setup





Above 1GHz Test Setup




4.4. Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI	101183	2016.06.29	2017.06.28
Preamplifier	songyi	EM330	60618	2016.03.26	2017.03.25
Preamplifier	Agilent	8449B	3008A02342	2016.03.26	2017.03.25
Bilog Antenna	Sunol Science	JB1	A072414-1	2016.04.16	2017.04.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-618	2016.04.16	2017.04.15
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	9170-347	2016.04.16	2017.04.15
Preamplifier	COM-POWER	PA-840	711885	2016.03.26	2017.03.25
Spectrum Analyzer	R&S	FSP40	100324	2016.08.02	2017.08.01
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2016.03.29	2017.03.28
EZ-EMC	Fala	Ver CT3A1	N/A	N/A	N/A



4.5. Test Result and Data (30MHz~1GHz)

Test Mode :	Mode 1: Normal Operation(EUT Only)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Temp :	25℃	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	32.9099	-3.58	29.14	25.56	40.00	-14.44	peak	200	200
2	64.9200	-13.15	39.04	25.89	40.00	-14.11	peak	200	171
3	150.2800	-7.65	39.86	32.21	43.50	-11.29	peak	200	34
4	191.0200	-10.29	42.11	31.82	43.50	-11.68	peak	200	36
5	220.1200	-12.19	47.38	35.19	46.00	-10.81	peak	100	0
6	320.0299	-6.24	34.94	28.70	46.00	-17.30	peak	100	98

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Normal Operation(EUT Only)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	45.5200	-8.86	46.04	37.18	40.00	-2.82	peak	100	95
2	46.4199	-9.29	43.62	34.33	40.00	-5.67	QP	100	192
3	141.5500	-7.80	35.54	27.74	43.50	-15.76	peak	200	45
4	193.9299	-10.98	35.78	24.80	43.50	-18.70	peak	100	163
5	350.1000	-6.72	31.12	24.40	46.00	-21.60	peak	100	321
6	431.5799	-4.51	29.83	25.32	46.00	-20.68	peak	100	29
7	716.7599	1.34	29.27	30.61	46.00	-15.39	peak	200	154

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 2: Normal Operation in Charging Mode(From AC Power)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	159.9798	-7.48	44.91	37.43	43.50	-6.07	peak	200	354
2	384.0500	-6.75	43.99	37.24	46.00	-8.76	peak	100	306
3	480.0799	-6.19	42.57	36.38	46.00	-9.62	peak	100	285
4	575.9900	-2.73	45.99	43.26	46.00	-2.74	QP	200	40
5	576.1100	-2.73	47.92	45.19	46.00	-0.81	peak	200	157
6	768.1699	0.93	39.73	40.66	46.00	-5.34	peak	100	50
7	960.2300	2.55	42.85	45.40	54.00	-8.60	peak	100	280

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 2: Normal Operation in Charging Mode(From AC Power)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	49.4000	-10.70	45.63	34.93	40.00	-5.07	peak	200	211
2	159.9800	-7.48	37.12	29.64	43.50	-13.86	peak	200	360
3	335.5500	-6.50	39.68	33.18	46.00	-12.82	peak	200	198
4	600.3600	-1.94	34.60	32.66	46.00	-13.34	peak	100	211
5	711.9099	1.28	31.11	32.39	46.00	-13.61	peak	102	0
6	900.0900	2.24	29.48	31.72	46.00	-14.28	peak	122	0

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 3: Normal Operation in Charging Mode(From DC Power)		
DC Power :	DC 12V	Ant. Polarization:	Horizontal
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	157.0699	-7.53	44.64	37.11	43.50	-6.39	peak	100	241
2	480.0799	-6.19	45.07	38.88	46.00	-7.12	peak	200	18
3	576.1100	-2.73	46.42	43.69	46.00	-2.31	peak	100	51
4	577.3000	-2.69	42.56	39.87	46.00	-6.13	QP	200	18
5	616.8500	-1.42	40.33	38.91	46.00	-7.09	peak	100	297
6	672.1399	-1.49	39.38	37.89	46.00	-8.11	peak	200	360
7	768.1698	0.93	39.23	40.16	46.00	-5.84	peak	100	360

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 3: Normal Operation in Charging Mode(From DC Power)		
DC Power :	DC 12V	Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	49.3998	-10.70	46.13	35.43	40.00	-4.57	peak	200	187
2	159.9798	-7.48	41.12	33.64	43.50	-9.86	peak	200	43
3	335.5500	-6.50	40.68	34.18	46.00	-11.82	peak	100	16
4	503.3600	-4.79	35.63	30.84	46.00	-15.16	peak	200	0
5	600.3600	-1.94	35.60	33.66	46.00	-12.34	peak	200	299
6	702.2100	1.16	35.21	36.37	46.00	-9.63	peak	100	351

Note: Measurement Level = Reading Level + Correct Factor



4.6. Test Result and Data (1GHz ~ 18GHz)

Test Mode :	Mode 1: Normal Operation(EUT Only)		
AC Power :		Ant. Polarization:	Horizontal
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1578.000	-5.45	44.98	39.53	74.00	-34.47	peak	100	75
2	2088.000	-3.37	45.04	41.67	74.00	-32.33	peak	100	96
3	2683.000	-1.37	44.71	43.34	74.00	-30.66	peak	200	173
4	3839.000	2.84	44.65	47.49	74.00	-26.51	peak	100	35
5	5658.000	5.27	42.46	47.73	74.00	-26.27	peak	100	274
6	7290.000	8.25	40.51	48.76	74.00	-25.24	peak	100	261

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 1: Normal Operation(EUT Only)		
AC Power :		Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1731.000	-4.81	44.75	39.94	74.00	-34.06	peak	100	132
2	3125.000	-0.03	47.04	47.01	74.00	-26.99	peak	200	282
3	4179.000	3.18	44.37	47.55	74.00	-26.45	peak	200	44
4	5743.000	5.30	43.30	48.60	74.00	-25.40	peak	100	359
5	6525.000	6.68	42.94	49.62	74.00	-24.38	peak	200	130
6	8242.000	9.11	40.87	49.98	74.00	-24.02	peak	200	33

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 2: Normal Operation in Charging Mode(From AC Power)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	2020.000	-3.63	45.90	42.27	74.00	-31.73	peak	200	110
2	2445.000	-2.04	45.10	43.06	74.00	-30.94	peak	100	194
3	3958.000	3.30	45.30	48.60	74.00	-25.40	peak	101	360
4	5556.000	5.22	43.88	49.10	74.00	-24.90	peak	185	360
5	6304.000	6.14	43.70	49.84	74.00	-24.16	peak	200	93
6	7035.000	8.07	41.46	49.53	74.00	-24.47	peak	100	360

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 2: Normal Operation in Charging Mode(From AC Power)		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	2649.000	-1.45	44.63	43.18	74.00	-30.82	peak	100	324
2	3788.000	2.65	46.75	49.40	74.00	-24.60	peak	200	127
3	5607.000	5.24	42.35	47.59	74.00	-26.41	peak	200	247
4	6287.000	6.10	42.92	49.02	74.00	-24.98	peak	200	9
5	6967.000	7.95	41.84	49.79	74.00	-24.21	peak	100	258
6	8531.000	9.02	39.91	48.93	74.00	-25.07	peak	200	54

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 3: Normal Operation in Charging Mode(From DC Power)		
DC Power :	DC 12V	Ant. Polarization:	Horizontal
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	2105.000	-3.31	48.42	45.11	74.00	-28.89	peak	100	254
2	3941.000	3.23	44.25	47.48	74.00	-26.52	peak	100	220
3	5590.000	5.24	42.60	47.84	74.00	-26.16	peak	103	360
4	6814.000	7.51	41.93	49.44	74.00	-24.56	peak	100	115
5	8276.000	9.10	41.31	50.41	74.00	-23.59	peak	100	0
6	10316.000	11.55	38.19	49.74	74.00	-24.26	peak	200	121

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Mode 3: Normal Operation in Charging Mode(From DC Power)		
DC Power :	DC 12V	Ant. Polarization:	Vertical
Temp :	25°C	Humidity :	50%
Pressure(mbar) :	1002	Date :	2016/11/08



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1901.000	-4.11	50.38	46.27	74.00	-27.73	peak	100	10
2	2428.000	-2.10	45.41	43.31	74.00	-30.69	peak	200	0
3	2768.000	-1.15	44.55	43.40	74.00	-30.60	peak	194	360
4	3941.000	3.23	44.72	47.95	74.00	-26.05	peak	173	360
5	5692.000	5.28	43.02	48.30	74.00	-25.70	peak	200	316
6	6967.000	7.95	42.65	50.60	74.00	-23.40	peak	200	85

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Dian

The end