

Prüfbericht-Nr.: Test report no.:	CN24WI2U 001	Auftrags-Nr.: Order no.:	168456347	Page 1 of 25 Seite 1 von 25
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2023-12-11	
Auftraggeber: Client:	Trek Bicycle Corporation 801 West Madison Street, Waterloo, Wisconsin, 53594, United States			
Prüfgegenstand: Test item:	BellBeats			
Bezeichnung / Typ-Nr.: Identification / Type no.:	5304359 (Trademark: TREK)			
Auftrags-Inhalt: Order content:	Type test			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 RSS-247-Issue 3 August 2023 CFR47 FCC Part 15: Subpart C Section 15.207 RSS-Gen Issue 5 March 2019 CFR47 FCC Part 15: Subpart C Section 15.209			
Wareneingangsdatum: Date of sample receipt:	2024-03-14	Refer to photos document		
Prüfmuster-Nr.: Test sample no.:	A003674402-004			
Prüfzeitraum: Testing period:	2024-03-14 – 2024-03-28			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2024-05-10	Ausstellungsdatum: Issue date:		2024-05-10
Stellung / Position: Project Manager		Stellung / Position: Reviewer		
Sonstiges / Other:	FCC ID: 2AHXD-5304359 IC: 21334-5304359 HVIN: 5304359			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet * Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

V05

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Page 2 of 25
Seite 2 von 25

Remarks
Anmerkungen

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request. <i>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.</i> <i>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</i>
2	As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. <i>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben.</i>
3	Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report. <i>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</i>
4	The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019. <i>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</i>

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 3 von 25
Page 3 of 25

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 99% BANDWIDTH

RESULT: Pass

5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.5 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.6 20dB BANDWIDTH

RESULT: Pass

5.1.7 CARRIER FREQUENCY SEPARATION

RESULT: Pass

5.1.8 FREQUENCY STABILITY

RESULT: Pass

5.1.9 NUMBER OF HOPPING FREQUENCY

RESULT: Pass

5.1.10 TIME OF OCCUPANCY

RESULT: Pass

5.1.11 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 4 von 25
Page 4 of 25

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES.....	5
2.1	TEST FACILITIES.....	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY	7
2.6	LOCATION OF ORIGINAL DATA	7
2.7	STATUS OF FACILITY USED FOR TESTING	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	10
3.5	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE	11
4.5	TEST SETUP DIAGRAM	12
5	TEST RESULTS.....	14
5.1	TRANSMITTER REQUIREMENT & TEST SUITES.....	14
5.1.1	<i>Antenna Requirement.....</i>	<i>14</i>
5.1.2	<i>Maximum Conducted Output Power</i>	<i>15</i>
5.1.3	<i>99% Bandwidth</i>	<i>16</i>
5.1.4	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>17</i>
5.1.5	<i>Radiated Spurious Emission.....</i>	<i>18</i>
5.1.6	<i>20dB Bandwidth</i>	<i>19</i>
5.1.7	<i>Carrier Frequency Separation.....</i>	<i>20</i>
5.1.8	<i>Frequency stability</i>	<i>21</i>
5.1.9	<i>Number of Hopping Frequency.....</i>	<i>22</i>
5.1.10	<i>Time of Occupancy</i>	<i>23</i>
5.1.11	<i>Conducted Emission on AC Mains.....</i>	<i>24</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	25
7	LIST OF TABLES	25

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 5 von 25
Page 5 of 25

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of Classical Bluetooth.

Appendix B: Photographs of the Test Set-up.

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District,
Shenzhen, Guangdong, China/518110

FCC Registration No.: 694916

IC Registration No.: 25069 and the CAB identifier is CN0078.

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 6 von 25
Page 6 of 25

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY60241175	21.09.2024
MXG X-Series RF Vector Signal Generator	Keysight	N5182B	MY61250137	21.09.2024
EXG X-Series Microwave Analog Signal Generator	Keysight	N5173B	MY61250141	21.09.2024
DC Power Supply	Keysight	E3642A	MY61276100	21.09.2024
Wireless Connectivity Tester	R&S	CMW270	102505	21.09.2024
Power Control Unit	Tonscend	JS0806-4ADC	N/A	21.09.2024
Automation Control Unit	Tonscend	JS0806-2	21C8060396	21.09.2024
Test Software	Tonscend	JS1120-3	N/A	N/A
Control PC	Lenovo	TianYi510S-071MB	Y LX23JMF	N/A
Unwanted Emission Testing (TS9975)				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	25.07.2024
Signal Analyzer	R&S	FSV 40	101439	25.07.2024
System Controller Interface	R&S	SCI-100	S10010038	N/A
Filterbank	R&S	Wlan	100759	25.07.2024
OSP	R&S	OSP 120	102040	N/A
Pre-amplifier	R&S	SCU08F1	08320031	25.07.2024
Amplifier	R&S	SCU-18F	180070	25.07.2024
Amplifier	R&S	SCU40A	100475	25.07.2024
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	06.08.2024
Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	06.08.2024
Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	27.08.2024
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	06.08.2024
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	22.06.2024
Conducted Emission on AC Mains				
Equipment	Manufacturer	Model	Serial No.	Cal. until
EMI Test Receiver	R&S	ESR3	102428	31.07.2024
Artificial Mains Network	R&S	ENV216	102333	01.08.2024
Impedance Stabilisation Network	R&S	ENY81-CA6	101810	01.08.2024
EMC32 test software	R&S	EMC32(Ver.10.50.00)	N/A	N/A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:Seite 7 von 25
Page 7 of 25

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Parameter	Uncertainty (k=2)
Occupied Channel Bandwidth	$\pm 2.08 \%$
RF output power, conducted	$\pm 0.99 \text{ dB}$
RF power density, conducted	$\pm 0.99 \text{ dB}$
Unwanted Emissions, conducted	$\pm 0.89 \text{ dB}$
All emissions, radiated	$\pm 4.17 \text{ dB}$
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	$\pm 3.70 \text{ dB} / \pm 3.30 \text{ dB}$

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No.362, Huanguan Middle Road, Songyuansha Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China/518110 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a BellBeats digital bell, which supports Bluetooth dual mode technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	BellBeats
Type Designation	5304359
Trademark	TREK
FCC ID	2AHXD-5304359
IC	21334-5304359
HVIN	5304359
Extreme Temperature Range	-10°C to +60°C
Operating Voltage	DC 3.7V, 650mAh via built-in lithium-ion battery DC 5V, 1A via Type-C port
Technical Specification of Classical Bluetooth	
Bluetooth Core Version	Bluetooth 5.3
Operating Frequency band	2402 ~ 2480 MHz
Channel Number	79 channels
Channel separation	1MHz
Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type	PCB Antenna
Antenna Gain	1.97 dBi (Provided by the Client)
Technical Specification of Bluetooth Low Energy	
Bluetooth Core Version	Bluetooth 5.3
Operating Frequency band	2402 ~ 2480 MHz
Channel Number	40 channels
Channel separation	2MHz
Data rate	1Mbps, 2Mbps
Modulation	GFSK
Antenna Type	PCB Antenna
Antenna Gain	1.97 dBi (Provided by the Client)

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 9 von 25
Page 9 of 25

Table 3: RF Channel and Frequency of Classic Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	78	2480.00
19	2421.00	39	2441.00	59	2461.00	--	--

Table 4: RF Channel and Frequency of Bluetooth Low Energy

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	2402.00	10	2422.00	20	2442.00	30	2462.00
01	2404.00	11	2424.00	21	2444.00	31	2464.00
02	2406.00	12	2426.00	22	2446.00	32	2466.00
03	2408.00	13	2428.00	23	2448.00	33	2468.00
04	2410.00	14	2430.00	24	2450.00	34	2470.00
05	2412.00	15	2432.00	25	2452.00	35	2472.00
06	2414.00	16	2434.00	26	2454.00	36	2474.00
07	2416.00	17	2436.00	27	2456.00	37	2476.00
08	2418.00	18	2438.00	28	2458.00	38	2478.00
09	2420.00	19	2440.00	29	2460.00	39	2480.00

3.3 Independent Operation Modes

The basic operation modes are:

- A. On
 - 1. Bluetooth transmitting mode (BR & EDR mode)
 - a) Low Channel
 - b) Middle Channel
 - c) High Channel
- B. On, Transmitting on Hopping channel
- C. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - FCC/IC Label and Location Info |
| - Block Diagram | - Photo Document |
| - Schematics | - User Manual |
| - Technical Description | |

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 11 von 25
Page 11 of 25

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all test items were applied on model 5304359.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N or Rating
Laptop	Lenovo	T480	PF-16A6N8

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 30MHz)




Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Conducted Transmitter Measurement





Diagram of Measurement Configuration for Mains Conduction Measurement



Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 14 von 25
Page 14 of 25

5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 8.3

According to the manufacturer declared, the EUT has one PCB antenna, the directional gain of antennas is 1.97 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 15 von 25
Page 15 of 25

5.1.2 Maximum Conducted Output Power

RESULT:
Pass
Test Specification

Test standard	FCC Part 15.247(b)(1) RSS-247 Clause 5.4(b)
Basic standard	ANSI C63.10: 2013
Limits	FHSS<0.125W(Maximum peak conducted output power) < 4 W (e.i.r.p.)
Kind of test site	Shielded Room

Test Setup

Date of testing	2024-03-14 to 2024-03-28
Input voltage	DC 3.7V
Operation mode	A.1
Test channel	Low / Middle / High
Ambient temperature	24.5 °C
Relative humidity	50.4 %
Atmospheric pressure	101 kPa

Table 6: Test Result of Maximum Conducted Output Power

Test Mode	Channel Frequency (MHz)	Measured Peak Output Power		Limit (W)
		(dBm)	(W)	
BR	2402	5.83	0.00383	< 0.125
	2441	6.42	0.00439	
	2480	6.38	0.00435	
EDR	2402	6.12	0.00409	< 0.125
	2441	6.69	0.00467	
	2480	6.61	0.00458	

Note: The cable loss is taken into account in results and the maximum e.i.r.p. is 8.66 dBm less than 4W(36dBm).

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 16 von 25
Page 16 of 25

5.1.3 99% Bandwidth

RESULT:

Pass

Test Specification

Test standard : RSS-Gen Clause 6.7
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : A.1
Test channel : Low / Middle / High
Ambient temperature : 24.5 °C
Relative humidity : 50.4 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:Seite 17 von 25
Page 17 of 25

5.1.4 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT: Pass**Test Specification**

Test standard : FCC Part 15.247(d)
RSS-247 Clause 5.5

Basic standard : ANSI C63.10: 2013

Limits : 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);

Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28

Input voltage : DC 3.7V

Operation mode : A.1

Test channel : Low / Middle / High

Ambient temperature : 24.5 °C

Relative humidity : 50.4 %

Atmospheric pressure : 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 18 von 25
Page 18 of 25

5.1.5 Radiated Spurious Emission

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(d) & FCC Part 15.205
RSS-247 Clause 3.3
Basic standard : ANSI C63.10: 2013
Limits : Refer to 15.209(a) of FCC part 15.247(d)
RSS-Gen Table 6 & Table 7
Kind of test site : 3m Semi-anechoic Chamber

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : A.1
Test channel : Low / Middle / High
Ambient temperature : Refer to test result
Relative humidity : Refer to test result
Atmospheric pressure : 101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 19 von 25
Page 19 of 25

5.1.6 20dB Bandwidth

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(a)(1)
RSS-247 Clause 5.1(a)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : A.1
Test channel : Low / Middle / High
Ambient temperature : 24.5 °C
Relative humidity : 50.4 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 20 von 25
Page 20 of 25

5.1.7 Carrier Frequency Separation

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(a)(1)
RSS-247 Clause 5.1(b)
Basic standard : ANSI C63.10: 2013
Limits : $\geq 25\text{kHz}$ or $2/3$ of 20dB bandwidth, whichever is greater
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : B
Test channel : Low / Middle / High
Ambient temperature : $24.5\text{ }^{\circ}\text{C}$
Relative humidity : $50.4\text{ }\%$
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 21 von 25
Page 21 of 25

5.1.8 Frequency stability

RESULT:

Pass

Test Specification

Test standard : RSS-247 Clause 8.11
Basic standard : ANSI C63.10: 2013
Limits : within at least the central 80% of its permitted operating frequency band (2400-2483.5MHz)
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : B
Ambient temperature : 24.5 °C
Relative humidity : 50.4 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 22 von 25
Page 22 of 25

5.1.9 Number of Hopping Frequency

RESULT:

Pass

Test Specification

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(d)
Basic standard : ANSI C63.10: 2013
Limits : ≥ 15 non-overlapping channels
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : B
Ambient temperature : 24.5 °C
Relative humidity : 50.4 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 23 von 25
Page 23 of 25

5.1.10 Time of Occupancy

RESULT:

Pass

Test Specification

Test standard : FCC part 15.247(a)(1)(iii)
RSS-247 Clause 5.1(d)
Basic standard : ANSI C63.10: 2013
Limits : < 0.4s
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 3.7V
Operation mode : B
Test channel : Low / Middle / High
Ambient temperature : 24.5 °C
Relative humidity : 50.4 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

Prüfbericht-Nr.: CN24WI2U 001
Test report no.:

Seite 24 von 25
Page 24 of 25

5.1.11 Conducted Emission on AC Mains

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.207(a)
RSS-Gen Clause 8.8
Basic standard : ANSI C63.10: 2013
Frequency range : 0.15 – 30MHz
Limits : FCC Part 15.207(a)
RSS-Gen Table 4
Kind of test site : Shielded Room

Test Setup

Date of testing : 2024-03-14 to 2024-03-28
Input voltage : DC 5V via Type-C interface
Operation mode : B
Earthing : Not connected
Ambient temperature : Refer to test result
Relative humidity : Refer to test result
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	8
Table 3: RF Channel and Frequency of Classic Bluetooth.....	9
Table 4: RF Channel and Frequency of Bluetooth Low Energy.....	9
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Conducted Output Power.....	15


Appendix A: Test Results of Classical Bluetooth

APPENDIX A: TEST RESULTS OF CLASSICAL BLUETOOTH	1
APPENDIX A.1: TEST RESULTS OF 99% BANDWIDTH	2
APPENDIX A.2: TEST RESULTS OF 20dB BANDWIDTH	5
APPENDIX A.3: TEST RESULTS OF FREQUENCY STABILITY	8
APPENDIX A.4: TEST RESULTS OF CARRIER FREQUENCY SEPARATION	10
APPENDIX A.5: TEST RESULTS OF NUMBER OF HOPPING FREQUENCY	11
APPENDIX A.6: TEST RESULTS OF TIME OF OCCUPANCY	12
APPENDIX A.7: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 kHz BANDWIDTH	17
Conducted measurements	17
Band edge measurements	24
APPENDIX A.8: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	28
30MHz - 1GHz	28
1GHz - 18GHz	30
APPENDIX A.9: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	42
APPENDIX A.10: TEST RESULTS OF CONDUCTED EMISSIONS ON AC MAINS	46

Appendix A.1: Test Results of 99% Bandwidth

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.86758	2401.5336	2402.4011	---	---
		2441	0.84955	2440.5422	2441.3918	---	---
		2480	0.85304	2479.5387	2480.3918	---	---
3DH5	Ant1	2402	1.1963	2401.3665	2402.5628	---	---
		2441	1.2076	2440.3583	2441.5659	---	---
		2480	1.1945	2479.3644	2480.5589	---	---







Appendix A.2: Test Results of 20dB Bandwidth

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.930	2401.511	2402.441	---	---
		2441	0.864	2440.514	2441.378	---	---
		2480	0.888	2479.511	2480.399	---	---
3DH5	Ant1	2402	1.272	2401.325	2402.597	---	---
		2441	1.275	2440.322	2441.597	---	---
		2480	1.260	2479.328	2480.588	---	---







Appendix A.3: Test Results of Frequency stability

Test Channel (MHz)	2402
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.7V	2401.991	-9	-3.75	10
DC 3.3V	2401.991	-9	-3.75	
DC 4.07V	2401.991	-9	-3.75	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2401.989	-11	-4.58	10
-20	2401.989	-11	-4.58	
-10	2401.990	-10	-4.16	
0	2401.990	-10	-4.16	
10	2401.991	-9	-3.75	
20	2401.991	-9	-3.75	
30	2401.991	-9	-3.75	
40	2401.991	-9	-3.75	
50	2401.992	-8	-3.33	
55	2401.993	-7	-2.91	

Test Channel (MHz)	2441
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.7V	2440.994	-6	-2.46	10
DC 3.3V	2440.994	-6	-2.46	
DC 4.07V	2440.994	-6	-2.46	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2440.992	-8	-3.28	10
-20	2440.992	-8	-3.28	
-10	2440.992	-8	-3.28	
0	2440.992	-8	-3.28	
10	2440.993	-7	-2.87	
20	2440.994	-6	-2.46	
30	2440.994	-6	-2.46	
40	2440.994	-6	-2.46	
50	2440.995	-5	-2.05	
55	2440.994	-6	-2.46	

Test Channel (MHz)	2480
-----------------------	------

Test result of frequency tolerance of voltage variation

Voltage	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
DC 3.7V	2479.988	-12	-4.84	10
DC 3.3V	2479.988	-12	-4.84	
DC 4.07V	2479.988	-12	-4.84	

Test result of frequency tolerance of temperature variation

Temperature (°C)	Test result (MHz)	Deviation Frequency (KHz)	Test result (ppm)	Limit (ppm)
-30	2479.986	-14	-5.65	10
-20	2479.986	-14	-5.65	
-10	2479.986	-14	-5.65	
0	2479.987	-13	-5.24	
10	2479.987	-13	-5.24	
20	2479.988	-12	-4.84	
30	2479.988	-12	-4.84	
40	2479.987	-13	-5.24	
50	2479.985	-15	-6.05	
55	2479.984	-16	-6.45	



Appendix A.4: Test Results of Carrier Frequency Separation

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	1.022	≥ 0.630	PASS
3DH5	Ant1	Hop	0.992	≥ 0.862	PASS




Appendix A.5: Test Results of Number of Hopping Frequency


TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS





Appendix A.6: Test Results of Time of Occupancy

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.375	317	0.119	≤0.4	PASS
DH3	Ant1	Hop	1.631	154	0.251	≤0.4	PASS
DH5	Ant1	Hop	2.878	106	0.305	≤0.4	PASS
3DH1	Ant1	Hop	0.385	316	0.122	≤0.4	PASS
3DH3	Ant1	Hop	1.637	161	0.264	≤0.4	PASS
3DH5	Ant1	Hop	2.887	114	0.329	≤0.4	PASS














Appendix A.7: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

Conducted measurements


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	4.45	4.45	---	PASS
			30~1000	4.45	-46.58	≤-15.55	PASS
			1000~26500	4.45	-36.92	≤-15.55	PASS
		2441	Reference	5.31	5.31	---	PASS
			30~1000	5.31	-47.12	≤-14.69	PASS
			1000~26500	5.31	-38.1	≤-14.69	PASS
		2480	Reference	4.90	4.90	---	PASS
			30~1000	4.90	-46.84	≤-15.1	PASS
			1000~26500	4.90	-38.09	≤-15.1	PASS
3DH5	Ant1	2402	Reference	3.24	3.24	---	PASS
			30~1000	3.24	-47.37	≤-16.76	PASS
			1000~26500	3.24	-38.11	≤-16.76	PASS
		2441	Reference	4.87	4.87	---	PASS
			30~1000	4.87	-47.18	≤-15.13	PASS
			1000~26500	4.87	-38.05	≤-15.13	PASS
		2480	Reference	2.64	2.64	---	PASS
			30~1000	2.64	-47.32	≤-17.36	PASS
			1000~26500	2.64	-37.92	≤-17.36	PASS














Band edge measurements

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	4.804	-46.78	≤-15.2	PASS
		High	2480	5.359	-50.73	≤-14.64	PASS
3DH5	Ant1	Low	2402	4.841	-40.11	≤-15.16	PASS
		High	2480	5.232	-48.39	≤-14.77	PASS
DH5	Ant1	Hopping	2402	4.688	-48.64	≤-15.31	PASS
		Hopping	2480	3.713	-48.61	≤-16.29	PASS
3DH5	Ant1	Hopping	2402	0.6126	-46.18	≤-19.39	PASS
		Hopping	2480	1.688	-48.48	≤-18.31	PASS


DH5_Ant1_Low_2402



DH5_Ant1_High_2480










Appendix A.8: Test Results of Radiated Spurious Emissions

Note: 1. Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported. 2. This testing was carried out on different modulations, but only the worst case (GFSK) was presented in this report.

30MHz - 1GHz

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Mid channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
56.712308	27.50	40.00	12.50	100.0	H	295.0	-18.9
80.514615	27.56	40.00	12.44	100.0	H	222.0	-23.6
128.753462	30.77	43.50	12.73	100.0	H	254.0	-22.0
252.353846	29.66	46.00	16.34	100.0	H	278.0	-17.6
383.751539	26.55	46.00	19.45	100.0	H	230.0	-14.5
937.546923	30.04	46.00	15.96	100.0	H	68.0	-5.0

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Mid channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.482692	32.35	40.00	7.65	100.0	V	120.0	-19.1
55.182692	24.78	40.00	15.22	100.0	V	237.0	-18.8
115.621154	18.49	43.50	25.01	100.0	V	211.0	-20.2
455.456923	18.02	46.00	27.98	100.0	V	253.0	-13.2
814.506154	24.23	46.00	21.77	100.0	V	211.0	-6.5

1GHz - 18GHz

Note: The highest waveform in the figure is Bluetooth Fundamental.

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Low channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1331.000000	45.10	---	74.00	28.90	150.0	H	106.0	2.1
1338.500000	---	34.22	54.00	19.78	150.0	H	14.0	2.1
3198.000000	---	42.01	54.00	11.99	150.0	H	92.0	8.6
3206.500000	52.64	---	74.00	21.36	150.0	H	150.0	8.6
5170.000000	51.89	---	74.00	22.11	150.0	H	187.0	12.5
5175.500000	---	41.35	54.00	12.65	150.0	H	298.0	12.5

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_Low channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1368.000000	45.14	---	74.00	28.86	150.0	V	99.0	2.0
1374.000000	---	33.30	54.00	20.70	150.0	V	161.0	1.9
3524.500000	53.38	---	74.00	20.62	150.0	V	55.0	9.1
3550.000000	---	42.47	54.00	11.53	150.0	V	9.0	9.2
5178.500000	56.37	---	74.00	17.63	150.0	V	191.0	12.6
5219.000000	---	45.60	54.00	8.40	150.0	V	203.0	12.7

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_Low channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9607.250000	---	36.76	54.00	17.24	150.0	H	215.0	10.4
9774.416667	44.57	---	74.00	29.43	150.0	H	22.0	10.4
13181.175000	49.98	---	74.00	24.02	150.0	H	153.0	15.4
13225.916667	---	41.61	54.00	12.39	150.0	H	34.0	15.5

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Low channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9517.275000	---	35.22	54.00	18.78	150.0	V	238.0	10.0
9598.400000	44.97	---	74.00	29.03	150.0	V	94.0	10.4
13235.750000	---	41.17	54.00	12.83	150.0	V	334.0	15.5
13365.550000	51.09	---	74.00	22.91	150.0	V	334.0	15.5

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_Mid channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1613.000000	45.14	---	74.00	28.86	150.0	H	102.0	2.2
1619.000000	---	33.95	54.00	20.05	150.0	H	102.0	2.3
3432.500000	---	41.94	54.00	12.06	150.0	H	211.0	8.8
3473.000000	53.34	---	74.00	20.66	150.0	H	136.0	8.9
5206.500000	---	43.96	54.00	10.04	150.0	H	83.0	12.7
5259.000000	53.14	---	74.00	20.86	150.0	H	0.0	12.9

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_Mid channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1312.000000	---	35.22	54.00	18.78	150.0	V	114.0	2.0
1312.500000	44.10	---	74.00	29.90	150.0	V	107.0	2.0
3463.500000	52.93	---	74.00	21.07	150.0	V	183.0	8.8
3595.500000	---	43.02	54.00	10.98	150.0	V	303.0	9.3
5238.500000	54.59	---	74.00	19.41	150.0	V	359.0	12.8
5238.500000	---	45.18	54.00	8.82	150.0	V	359.0	12.8

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Mid channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9763.108333	45.41	---	74.00	28.59	150.0	H	207.0	10.4
9763.600000	---	39.29	54.00	14.71	150.0	H	76.0	10.4
13662.025000	50.78	---	74.00	23.22	150.0	H	195.0	15.2
13680.216667	---	41.61	54.00	12.39	150.0	H	207.0	15.3

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Mid channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9763.108333	44.96	---	74.00	29.04	150.0	V	226.0	10.4
9763.600000	---	35.95	54.00	18.05	150.0	V	226.0	10.4
14364.616667	52.87	---	74.00	21.13	150.0	V	0.0	16.8
14398.050000	---	43.65	54.00	10.35	150.0	V	167.0	16.9

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_High channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1240.000000	---	33.70	54.00	20.30	150.0	H	295.0	1.7
1267.000000	44.17	---	74.00	29.83	150.0	H	217.0	1.9
3097.500000	---	41.16	54.00	12.84	150.0	H	191.0	8.7
3098.500000	52.47	---	74.00	21.53	150.0	H	0.0	8.7
5233.000000	---	43.46	54.00	10.54	150.0	H	353.0	12.8
5233.000000	54.12	---	74.00	19.88	150.0	H	353.0	12.8

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_High channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1312.500000	---	37.74	54.00	16.26	150.0	V	263.0	2.0
1385.500000	44.29	---	74.00	29.71	150.0	V	218.0	1.8
3144.000000	51.92	---	74.00	22.08	150.0	V	39.0	8.6
3361.500000	---	41.68	54.00	12.32	150.0	V	145.0	8.6
5186.000000	---	42.79	54.00	11.21	150.0	V	212.0	12.6
5219.500000	53.22	---	74.00	20.78	150.0	V	49.0	12.7

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_High channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9917.491667	41.26	---	74.00	32.74	150.0	H	0.0	10.8
9919.458333	46.19	---	74.00	27.81	150.0	H	197.0	10.8
13188.550000	---	41.29	54.00	12.71	150.0	H	185.0	15.4
13212.641667	50.84	---	74.00	23.16	150.0	H	51.0	15.5

EUT Information

EUT Name: BellBeats
Model: 5304359
Test Mode: BR_DH5_High channel
Order No/Sample No: 168456347/A003674402-004
Test Voltage:: Battery
Remark: Temp 23 Humi:56%
Test Standard: FCC 15.247
Tested By: Lich Chen
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9918.966667	---	36.84	54.00	17.16	150.0	V	254.0	10.8
10005.991667	45.46	---	74.00	28.54	150.0	V	95.0	11.1
12624.116667	50.71	---	74.00	23.29	150.0	V	155.0	14.9
12635.425000	---	40.76	54.00	13.24	150.0	V	71.0	15.0

Appendix A.9: Test Results of Radiated Emissions in Restricted Bands

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Low channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2377.132353	49.61	---	74.00	24.39	150.0	H	162.0	6.9
2377.926471	---	40.08	54.00	13.92	150.0	H	322.0	6.9

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_Low channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2353.941177	---	42.73	54.00	11.27	150.0	V	176.0	6.9
2354.044118	50.57	---	74.00	23.43	150.0	V	318.0	6.9

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_High channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.725882	53.43	---	74.00	20.57	150.0	H	74.0	7.4
2483.891765	---	40.46	54.00	13.54	150.0	H	149.0	7.4

EUT Information

EUT Name:	BellBeats
Model:	5304359
Test Mode:	BR_DH5_High channel
Order No/Sample No:	168456347/A003674402-004
Test Voltage::	Battery
Remark:	Temp 23 Humi:56%
Test Standard:	FCC 15.247
Tested By:	Lich Chen
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.514118	---	42.36	54.00	11.64	150.0	V	284.0	7.4
2483.810588	59.94	---	74.00	14.06	150.0	V	299.0	7.4

Appendix A.10: Test Results of Conducted Emissions on AC Mains

EUT Information

EUT Name:	BellBeats
Order Number:	168456347
Model:	5304359
Test Mode:	Bluetooth playing with charging
Test Voltage:	120V/50Hz
Test Standard:	FCC Part 15C
Test By:/Review By:	Dawn Shen/ Gary Chen
Tem./Hum./Pressure:	24.3°C/52.2%/101kPa
Remark:	SR2



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.706000	---	31.39	46.00	14.61	L1	10.0
0.706000	34.01	---	56.00	21.99	L1	10.0
2.118000	---	31.39	46.00	14.61	L1	10.1
2.118000	34.87	---	56.00	21.13	L1	10.1
3.529500	35.59	---	56.00	20.41	L1	10.2
3.529500	---	31.93	46.00	14.07	L1	10.2
4.942000	---	32.05	46.00	13.95	L1	10.2
4.942000	37.24	---	56.00	18.76	L1	10.2
7.766000	---	30.20	50.00	19.80	L1	10.3
7.766000	37.97	---	60.00	22.03	L1	10.3
9.178000	---	31.12	50.00	18.88	L1	10.3
9.178000	37.98	---	60.00	22.02	L1	10.3

Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
3.529500	---	30.78	46.00	15.22	1000.0	9.000	L1	10.2
3.529500	33.40	---	56.00	22.60	1000.0	9.000	L1	10.2

EUT Information

EUT Name: BellBeats
Order Number: 168456347
Model: 5304359
Test Mode: Bluetooth playing with charging
Test Voltage: 120V/50Hz
Test Standard: FCC Part 15C
Test By:/Review By: Dawn Shen/ Gary Chen
Tem./Hum./Pressure: 24.3°C/52.2%/101kPa
Remark: SR2



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.706000	---	31.13	46.00	14.87	N	9.8
0.706000	33.79	---	56.00	22.21	N	9.8
2.118000	---	32.15	46.00	13.85	N	9.9
2.118000	34.55	---	56.00	21.45	N	9.9
4.941500	38.16	---	56.00	17.84	N	9.9
4.941500	---	35.41	46.00	10.59	N	9.9
9.174000	---	35.07	50.00	14.93	N	10.0
9.174000	42.11	---	60.00	17.89	N	10.0
10.590000	---	34.56	50.00	15.45	N	10.0
10.590000	43.04	---	60.00	16.96	N	10.0
14.826000	---	26.31	50.00	23.69	N	10.1
14.826000	38.32	---	60.00	21.68	N	10.1

Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
4.941500	---	32.63	46.00	13.37	1000.0	9.000	N	9.9
4.941500	36.15	---	56.00	19.85	1000.0	9.000	N	9.9