

SHENZHEN GIEC DIGITAL CO., LTD

TEST REPORT

SCOPE OF WORK

FCC TESTING—GL-W08PBQ03C, GL-W08PBQ60B,
GL-W06PBQ60C, GL-W05PBQ60C, GL-W08PBQ02C,
GL-W06PBQ02C, GL-W05PBQ02C, GL-W08PBQ02B,
GL-W08PBQ60C, GL-W06PBQ03C, GL-W05PBQ03C,
GL-W08PBQ03B

REPORT NUMBER

190703006SZN-001

ISSUE DATE

30 August 2019

[REVISED DATE]

[-----]

PAGES

61

DOCUMENT CONTROL NUMBER

FCC ID 247_b

© 2017 INTERTEK



SHENZHEN GIEC DIGITAL CO., LTD

Application
For
Certification

FCC ID: 2AHYK-W08PBQ60**SMART LED BULB**

Model: GL-W08PBQ03C, GL-W08PBQ60B, GL-W06PBQ60C, GL-W05PBQ60C, GL-W08PBQ02C, GL-W06PBQ02C, GL-W05PBQ02C, GL-W08PBQ02B, GL-W06PBQ03C, GL-W05PBQ03C, GL-W08PBQ03B, GL-W08PBQ60C

2.4GHz Wi-Fi Transceiver

Report No.: 190703006SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-18]

Prepared and Checked by:

Rode Liu
Engineer

Approved by:

Kidd Yang
Technical Supervisor
Date: 30 August 2019

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

MEASUREMENT/TECHNICAL REPORT

This report concerns (check one) Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (Wi-Fi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until : _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-18] Edition] provision.

Report prepared by:

Rode Liu
Intertek Testing Services Shenzhen Ltd. Longhua Branch
101, 201, Building B, No. 308 Wuhe Avenue,
Zhangkengjing Community, GuanHu Subdistrict, LongHua
District, Shenzhen, P.R. China.
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6661

Table of Contents

1.0	<u>Summary of Test results</u>	4
2.0	<u>General Description</u>	5
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	6
3.0	<u>System Test Configuration</u>	7
3.1	Justification	7
3.2	EUT Exercising Software	7
3.3	Special Accessories	7
3.4	Measurement Uncertainty	8
3.5	Equipment Modification	8
3.6	Support Equipment List and Description	8
4.0	<u>Measurement Results</u>	9
4.1	Maximum Conducted Output Power at Antenna Terminals	9
4.2	Minimum 6 dB RF Bandwidth	10
4.3	Maximum Power Density Reading	16
4.4	Out of Band Conducted Emissions	22
4.5	Out of Band Radiated Emissions	40
4.6	Transmitter Radiated Emissions in Restricted Bands	41
4.7	Field Strength Calculation	42
4.8	Radiated Spurious Emission	43
4.9	Conducted Emission	55
4.10	Radiated Emissions from Digital Section of Transceiver	58
4.11	Transmitter Duty Cycle Calculation and Measurements	59
5.0	<u>Equipment Photographs</u>	60
6.0	<u>Product Labelling</u>	60
7.0	<u>Technical Specifications</u>	60
8.0	<u>Instruction Manual</u>	60
9.0	<u>Confidentiality Request</u>	60
10.0	<u>Discussion of Pulse Desensitization</u>	60
11.0	<u>Test Equipment List</u>	61

1.0 Summary of Test results

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Applicant Address: 1st&3rd Building, No.26 Puzai Road, Pingdi, Longgang District, Shenzhen, China

Manufacturer: SHENZHEN GIEC DIGITAL CO., LTD

Manufacturer Address: 1st&3rd Building, No.26 Puzai Road, Pingdi, Longgang District, Shenzhen, China

Model: GL-W08PBQ03C
FCC ID: 2AHYK-W08PBQ60

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

2.0 General Description

2.1 Product Description

The Equipment Under Test (EUT) is a SMART LED BULB with Wi-Fi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing. The EUT is powered by AC 120V, 60Hz. For more detailed features description, please refer to the user's manual.

Type of Modulation: CCK, BPSK, QPSK, 16QAM, 64QAM, DQPSK, DBPSK.

Antenna Type: Integral Antenna

Antenna Gain: 2.5dBi

All models have similar mechanical and electrical constructions. The differences are the lampbase type, appearance and LED module for marketing purpose.

Models: GL-W08PBQ60C, GL-W06PBQ02C, GL-W05PBQ60C are identical except wattage and LED module.

Models: GL-W08PBQ02C, GL-W06PBQ02C, GL-W05PBQ02C are identical except wattage and LED module.

Models: GL-W08PBQ03C, GL-W06PBQ03C, GL-W05PBQ03C are identical except wattage and LED module.

Models: GL-W08PBQ60B, GL-W08PBQ02B, GL-W08PBQ03B, GL-W08PBQ02C and GL-W08PBQ03C are identical as GL-W08PBQ60C except lampbase type.

Models: GL-W06PBQ03C and GL-W06PBQ02C are identical as GL-W06PBQ02C except lampbase type.

Models: GL-W05PBQ03C and GL-W05PBQ02C are identical as GL-W05PBQ60C except lampbase type.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz Wi-Fi transmitter portion).

Remaining portions are subject to the following procedures:

1. Receiver portion of WiFi: exempt from technical requirement of this Part.
2. Other Digital Functions were reported in the SDOC report: 190703006SZN-002.

2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

2.4 Test Facility

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by AC 120V/60Hz input during the test.

On 802.11b/g/n-HT20 mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report. Models: GL-W08PBQ03C, GL-W06PBQ02C, GL-W05PBQ60C are selected for testing, only worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The rear of unit shall be flushed with the rear of the table.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test Software: ESP Series Modules Test Tool V2.2.2

3.3 Special Accessories

N/A.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

3.5 Equipment Modification

Any modifications installed previous to testing by SHENZHEN GIEC DIGITAL CO., LTD will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

3.6 Support Equipment List and Description

Description	Manufacturer	Model No.
Lamp holder	NA	NA

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.0 Measurement Results

4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

IEEE 802.11b (Antenna Gain = 2.5dBi) (CCK, 1Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	18.72	74.47
Middle Channel: 2437	18.11	64.71
High Channel: 2462	17.13	51.64

IEEE 802.11g (Antenna Gain = 2.5dBi) (16QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	21.12	129.42
Middle Channel: 2437	20.70	117.49
High Channel: 2462	20.06	101.39

IEEE 802.11n-HT20 (Antenna Gain = 2.5dBi) (64QAM, 6Mbps)		
Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2412	21.22	132.43
Middle Channel: 2437	20.67	116.68
High Channel: 2462	20.13	103.04

Cable loss: 0.5 dB External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 21.22dBm

EUT max. E.I.R.P = 21.22dBm + 2.5dBi = 23.72dBm = 235.50mW

For RF Exposure, the information is saved with filename: RF exposure.pdf.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.



IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	8.987
2437	8.944
2462	9.030


IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	16.368
2437	16.368
2462	16.151

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	6 dB Bandwidth (MHz)
2412	17.540
2437	17.583
2462	16.975


The test plots are attached as below.



802.11b








802.11g





802.11n-HT20





Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.



IEEE 802.11b (CCK, 1Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-8.34
2437	-8.96
2462	-9.43


IEEE 802.11g (16QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-12.24
2437	-13.11
2462	-14.15

IEEE 802.11n-HT20 (64QAM, 6Mbps)	
Frequency (MHz)	Power Density with RBW 3KHz
2412	-13.37
2437	-14.23
2462	-15.24


The test plots are attached as below.



802.11b








802.11g





802.11n-HT20





Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.



Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b and 6Mbps for 802.11g and 6Mbps for 802.11n-HT20 and 13.5Mbps.



The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.



802.11b


Channel 01 (2412MHz) Reference Level: 5.98dBm








Channel 06 (2437MHz) Reference Level: 5.69dBm






Channel 11 (2462MHz) Reference Level: 5.26dBm











802.11g


Channel 01 (2412MHz) Reference Level: 3.55dBm













Channel 06 (2437MHz) Reference Level: 2.60dBm







Channel 11 (2462MHz) Reference Level: 1.49dBm









802.11n-HT20


Channel 01 (2412MHz) Reference Level: 3.49dBm








Channel 06 (2437MHz) Reference Level: 2.46dBm






Channel 11 (2462MHz) Reference Level: 1.37dBm







Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ PD &= 0 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission (802.11b-Channel 01)
at 479.984625MHz
is passed by 3.2dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019


Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11b-Channel 01)

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
150.765000	35.4	1000.0	120.000	0.0	H	10.5	8.1	43.5
186.170000	36.2	1000.0	120.000	0.0	H	12.1	7.3	43.5
480.080000	36.9	1000.0	120.000	0.0	H	20.8	9.1	46.0
720.155000	38.6	1000.0	120.000	0.0	H	25.5	7.4	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019


Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11b-Channel 01)

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
150.765000	38.3	1000.0	120.000	0.0	V	10.5	5.2	43.5
479.984625	42.8	1000.0	120.000	0.0	V	20.8	3.2	46.0
560.105000	42.2	1000.0	120.000	0.0	V	22.4	3.8	46.0
639.948125	41.4	1000.0	120.000	0.0	V	24.1	4.6	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line(dBμV/m) – Level (dBμV/m)

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11b-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	55.9	36.8	33.5	52.6	74.0	-21.4
Horizontal	*2390.000	68.5	36.4	29.1	61.2	74.0	-12.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	46.1	36.8	33.5	42.8	54.0	-11.2
Horizontal	*2390.000	55.4	36.4	29.1	48.1	54.0	-5.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11b-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	54.6	36.7	33.4	51.3	74.0	-22.7
Horizontal	*7311.000	52.2	36.6	35.8	51.4	74.0	-22.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	43.1	36.7	33.4	39.8	54.0	-14.2
Horizontal	*7311.000	44.2	36.6	35.8	43.4	54.0	-10.6

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11b-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	56.6	36.8	33.3	53.1	74.0	-20.9
Horizontal	*2484.500	64.4	36.5	29.3	57.2	74.0	-16.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	46.6	36.8	33.3	43.1	54.0	-10.9
Horizontal	*2484.500	53.5	36.5	29.3	46.3	54.0	-7.7

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11g-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	50.4	36.8	33.5	47.1	74.0	-26.9
Horizontal	*2390.000	73.8	36.4	29.1	66.5	74.0	-7.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	40.5	36.8	33.5	37.2	54.0	-16.8
Horizontal	*2390.000	57.4	36.4	29.1	50.1	54.0	-3.9

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11g-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	50.6	36.7	33.4	47.3	74.0	-26.7
Horizontal	*7311.000	53.4	36.6	35.8	52.6	74.0	-21.4

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	40.8	36.7	33.4	37.5	54.0	-16.5
Horizontal	*7311.000	43.6	36.6	35.8	42.8	54.0	-11.2

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11g-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	50.3	36.8	33.3	46.8	74.0	-27.2
Horizontal	*2484.500	70.9	36.5	29.3	63.7	74.0	-10.3

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	40.3	36.8	33.3	36.8	54.0	-17.2
Horizontal	*2484.500	54.4	36.5	29.3	47.2	54.0	-6.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11n20-Channel 01)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	48.1	36.8	33.5	44.8	74.0	-29.2
Horizontal	*2390.000	77.5	36.4	29.1	70.2	74.0	-3.8

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4824.000	39.6	36.8	33.5	36.3	54.0	-17.7
Horizontal	*2390.000	57.7	36.4	29.1	50.4	54.0	-3.6

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11n20-Channel 06)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	47.8	36.7	33.4	44.5	74.0	-29.5
Horizontal	*7311.000	51.6	36.6	35.8	50.8	74.0	-23.2

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4874.000	40.1	36.7	33.4	36.8	54.0	-17.2
Horizontal	*7311.000	43.3	36.6	35.8	42.5	54.0	-11.5

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Worst Case Operating Mode:

Model: GL-W08PBQ03C

Transmitting (802.11n20-Channel 11)

Radiated Emissions (above 1GHz)

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	47.7	36.8	33.3	44.2	74.0	-29.8
Horizontal	*2484.500	75.3	36.5	29.3	68.1	74.0	-5.9

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
Horizontal	*4924.000	39.0	36.8	33.3	35.5	54.0	-18.5
Horizontal	*2484.500	56.4	36.5	29.3	49.2	54.0	-4.8

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
 2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
 3. Negative value in the margin column shows emission below limit.
 4. Horn antenna used for the emission over 1000MHz.
- * Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.9 Conducted Emission

Worst Case Conducted Emission (802.11b-Channel 01)
at 0.166MHz
is passed by 15.7dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019


Model: GL-W08PBQ03C

Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Phase: Live

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.159000	47.6	9.000	L1	9.7	17.9	65.5
0.204000	46.7	9.000	L1	9.7	16.7	63.4
0.411000	33.3	9.000	L1	9.8	24.3	57.6
0.789000	26.6	9.000	L1	9.8	29.4	56.0
1.653000	16.6	9.000	L1	9.8	39.4	56.0
2.098500	26.2	9.000	L1	9.8	29.8	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.159000	31.6	9.000	L1	9.7	23.9	55.5
0.204000	34.3	9.000	L1	9.7	19.1	53.4
0.411000	20.0	9.000	L1	9.8	27.6	47.6
0.789000	18.9	9.000	L1	9.8	27.1	46.0
1.653000	8.7	9.000	L1	9.8	37.3	46.0
2.098500	13.8	9.000	L1	9.8	32.2	46.0

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019


Model: GL-W08PBQ03C

Worst Case Operating Mode: Transmitting (802.11b-Channel 01)

Phase: Neutral

Graphic / Data Table

Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.166000	49.5	9.000	N	9.7	15.7	65.2
0.298000	39.7	9.000	N	9.7	20.6	60.3
0.406000	36.3	9.000	N	9.8	21.4	57.7
0.538000	37.9	9.000	N	9.8	18.1	56.0
0.834000	27.5	9.000	N	9.8	28.5	56.0
2.058000	27.0	9.000	N	9.8	29.0	56.0

Limit and Margin AV

Frequency (MHz)	Average (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.166000	33.0	9.000	N	9.7	22.2	55.2
0.298000	23.0	9.000	N	9.7	27.3	50.3
0.406000	17.7	9.000	N	9.8	30.0	47.7
0.538000	17.8	9.000	N	9.8	28.2	46.0
0.834000	15.7	9.000	N	9.8	30.3	46.0
2.058000	15.3	9.000	N	9.8	30.7	46.0

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

Applicant: SHENZHEN GIEC DIGITAL CO., LTD

Date of Test: July 11, 2019

Model: GL-W08PBQ03C

4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

9.0 Confidentiality Request

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

10.0 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

11.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	28-May-2019	28-May-2020
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	28-May-2019	28-May-2020
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	14-Sep-2018	14-Sep-2019
SZ185-01	EMI Receiver	R&S	ESCI	100547	4-Jan-2019	4-Jan-2020
SZ061-08	Horn Antenna	ETS	3115	00092346	14-Sep-2018	14-Sep-2019
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	24-May-2019	24-May-2020
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	28-May-2019	28-May-2020
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	28-May-2019	28-May-2020
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	5-Jul-2019	5-Jul-2020
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	15-Dec-2018	15-Dec-2020
SZ062-02	RF Cable	RADIAL	RG 213U	--	19-Jun-2019	19-Dec-2019
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	23-Feb-2019	23-Aug-2019
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	23-Feb-2019	23-Aug-2019
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	28-May-2019	28-May-2020
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	26-Oct-2018	26-Oct-2019
SZ187-01	Two-Line V-Network	R&S	ENV216	100072	26-Oct-2018	26-Oct-2019
SZ188-03	Shielding Room	ETS	RFD-100	4100	16-Jan-2017	16-Jan-2020

***** End of Report*****