

FCC RF EXPOSURE REPORT

FCC ID: 2AHZL-CT001

Project No. : 1603203
Equipment : Cubic Trigger
Model : Ct001
Applicant : FoneTrend Technology Co., Ltd
**Address : 6-15, No. 181, Sec.2, Taiwan Blvd., West Dist.,
Taichung City 400**
**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

B T L I N C .

B1, No.37, Lane 365, Yang Guang St.,
Nei-Hu District, Taipei City 114, Taiwan.
TEL:+886-2-2657-3299 FAX: +886-2- 2657-3331

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	printed	N/A	4.44

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
-1.66	0.7	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 0.7mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold