



FCC AND ISCED CERTIFICATION TEST REPORT

Applicant	:	Klein Tools Inc.
Address of Applicant	:	450 Bond Street Lincolnshire IL, 60069 USA
Manufacturer	:	Klein Tools Inc.
Address of Manufacturer	:	450 Bond Street Lincolnshire IL, 60069 USA
Equipment under Test	:	Hardhat Bluetooth Speaker
Model No.	:	AEPHS1
FCC ID	:	2AI28-AEPHS1
IC	:	21655-AEPHS1
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 3 August 2023, ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)
Report No.	:	DDT-RE24053007-1E02
Issue Date	:	2024/07/19
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	9
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result	14
4.5.	Test graphs	15
5.	99% Bandwidth	17
5.1.	Block diagram of test setup	17
5.2.	Limits	17
5.3.	Test procedure	17
5.4.	Test result	18
5.5.	Test graphs	19
6.	Maximum Peak Output Power.....	21
6.1.	Block diagram of test setup	21
6.2.	Limits	21
6.3.	Test procedure	21
6.4.	Test result	22
6.5.	Test graphs	23
7.	Power Spectral Density	25
7.1.	Block diagram of test setup	25
7.2.	Limits	25
7.3.	Test procedure	25
7.4.	Test result	26
7.5.	Test graphs	27
8.	Band Edge Compliance (Conducted Method)	29

8.1.	Block diagram of test setup	29
8.2.	Limits	29
8.3.	Test procedure	29
8.4.	Test result	30
8.5.	Test graphs	31
9.	RF Conducted Spurious Emissions.....	33
9.1.	Block diagram of test setup	33
9.2.	Limits.....	33
9.3.	Test procedure	33
9.4.	Test result	34
9.5.	Test graphs	35
10.	Duty Cycle.....	41
10.1.	Block diagram of test setup	41
10.2.	Limit.....	41
10.3.	Test procedure	41
10.4.	Test result	42
10.5.	Test graphs	43
11.	Antenna Requirements.....	45
11.1.	Limit.....	45
11.2.	Result	45
12.	Radiated Emission	46
12.1.	Test equipment.....	46
12.2.	Block diagram of test setup	47
12.3.	Limits.....	48
12.4.	Assistant equipment used for test	50
12.5.	Test procedure	50
12.6.	Test result	51
12.7.	Test data	52
13.	Band Edge Compliance.....	68
13.1.	Test equipment.....	68
13.2.	Block diagram of test setup	69
13.3.	Limits.....	69
13.4.	Assistant equipment used for test	69
13.5.	Test procedure	69
13.6.	Test result	69
13.7.	Test data	70
14.	Power Line Conducted Emissions.....	78
14.1.	Test equipment.....	78

14.2. Block diagram of test setup78

14.3. Limits.....78

14.4. Assistant equipment used for test78

14.5. Test procedure79

14.6. Test result79

14.7. Test data80

15. Test Setup Photograph82

16. Photos of the EUT85

Test Report Declare

Applicant	:	Klein Tools Inc.
Address of Applicant	:	450 Bond Street Lincolnshire IL, 60069 USA
Equipment under Test	:	Hardhat Bluetooth Speaker
Model No.	:	AEPHS1
Manufacturer	:	Klein Tools Inc.
Address of Manufacturer	:	450 Bond Street Lincolnshire IL, 60069 USA

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
RSS-247 Issue 3 August 2023,
ANSI C63.10:2013,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24053007-1E02		
Date of Receipt:	2024/06/17	Date of Test:	2024/06/17~2024/07/19

Prepared By:

Ziqin Chen
Ziqin Chen/Engineer

Approved By:


Damon Hu
Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/07/19	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247(a)(2), RSS-247 Issue 3 clause 5.2(a), RSS-Gen Issue 5 clause 6.7	/	Pass
2	Peak Output Power	FCC Part 15: 15.247(b)(3), RSS-247 Issue 3 clause 5.4(d)	/	Pass
3	Power Spectral Density	FCC Part 15:15.247(e), RSS-247 Issue 3 clause 5.2(b)	/	Pass
4	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5	/	Pass
5	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
6	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
7	Power Line Conducted Emissions	FCC Part 15: 15.207(a), RSS-Gen Issue 5 clause 8.8	/	Pass
8	Antenna Requirement	FCC Part 15: 15.203, RSS-Gen Issue 5 clause 6.8	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Hardhat Bluetooth Speaker
Model Number	: AEPHS1
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: Input: 5V = 1A (via type-C port) Internal Li-ion Polymer battery: 3.8Vdc, 250mAh, 0.95Wh
Hardware Version	: V1.3
Software Version	: V1.0.0.7

Note: This EUT support Bluetooth BR/EDR/LE, this report only for Bluetooth LE.

Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz-2480 MHz
Modulation	: GFSK

Antenna information	
Antenna Type	: Chip Antenna
Max Antenna Gain(dBi)	: 1.24

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		


Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: BK32xx RF Test_V1.8.2.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK 1M	1	CH0	2402
	1	CH19	2440
	1	CH39	2480

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15℃ to +35 ℃
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2025/03/31
Wideband Radio Communication Tester	R&S	CMW500	168801	2025/03/31
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2025/03/31
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2024/09/05
RF Control Unit	Tonsend	JS0806-2	21I8060485	2025/03/31
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.


4.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Right side	2402	0.78	2401.63	2402.41	0.5	PASS
	Left side	2402	0.78	2401.62	2402.40	0.5	PASS
	Right side	2440	0.78	2439.63	2440.41	0.5	PASS
	Left side	2440	0.78	2439.62	2440.40	0.5	PASS
	Right side	2480	0.78	2479.63	2480.41	0.5	PASS
	Left side	2480	0.78	2479.62	2480.40	0.5	PASS

4.5. Test graphs






BLE_1M_Right side_2480




BLE_1M_Left side_2480



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:


RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Right side	2402	1.12	2401.4723	2402.5926	---	---
	Left side	2402	1.129	2401.4637	2402.5925	---	---
	Right side	2440	1.118	2439.4727	2440.5909	---	---
	Left side	2440	1.13	2439.4621	2440.5920	---	---
	Right side	2480	1.117	2479.4729	2480.5900	---	---
	Left side	2480	1.129	2479.4630	2480.5916	---	---

5.5. Test graphs






BLE_1M_Right side_2480




BLE_1M_Left side_2480



6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.


6.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Right side	2402	0.72	≤30	1.96	≤36	PASS
	Left side	2402	-1.93	≤30	-0.69	≤36	PASS
	Right side	2440	0.33	≤30	1.57	≤36	PASS
	Left side	2440	-1.15	≤30	0.09	≤36	PASS
	Right side	2480	0.33	≤30	1.57	≤36	PASS
	Left side	2480	-0.62	≤30	0.62	≤36	PASS

6.5. Test graphs






BLE_1M_Right side_2480




BLE_1M_Left side_2480



7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10-2013 clause 11.10.2.
 - (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
 - (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
 - (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:


Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
 - (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Right side	2402	-11.34	≤8.00	PASS
	Left side	2402	-13.28	≤8.00	PASS
	Right side	2440	-10.84	≤8.00	PASS
	Left side	2440	-12.51	≤8.00	PASS
	Right side	2480	-10.58	≤8.00	PASS
	Left side	2480	-12.00	≤8.00	PASS

7.5. Test graphs






BLE_1M_Right side_2480




BLE_1M_Left side_2480



8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001

EUT Set Mode	CH or Frequency	Measured Range	Verdict
GFSK 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass


8.5. Test graphs





9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


9.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Mode	Freq. (MHz)	Verdict
GFSK 1M	2402	Pass
	2440	Pass
	2480	Pass

9.5. Test graphs







BLE_1M_Left side_2402_30~1000




BLE_1M_Left side_2402_1000~26500




BLE_1M_Right side_2440_0~Reference




BLE_1M_Right side_2440_30~1000




BLE_1M_Right side_2440_1000~26500




BLE_1M_Left side_2440_0~Reference




BLE_1M_Left side_2440_30~1000




BLE_1M_Left side_2440_1000~26500




BLE_1M_Right side_2480_0~Reference




BLE_1M_Right side_2480_30~1000




BLE_1M_Right side_2480_1000~26500




BLE_1M_Left side_2480_0~Reference



BLE_1M_Left side_2480_30~1000




BLE_1M_Left side_2480_1000~26500



10. Duty Cycle

10.1. Block diagram of test setup



10.2. Limit

Just for Report.

10.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.
set the Spectrum Analyzer as below:
 - Centre Frequency: The centre frequency of the middle hopping channel.
 - Resolution BW: 10 MHz.
 - Video BW: 10 MHz.
 - Span: Zero span.
 - Detector: Peak.
 - Trace Mode: Clear Write.
 - Sweep: Video Trigger
- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.
- (3) Calculate dwell time follow below formula:
Duty cycle= Pulse's on time / Burst cycle


10.4. Test result

Test Engineer:	Zoe	Test Site:	RF Measurement System 4#
Ambient Condition:	25.6-26.1℃,41.8-45.3%RH	Test Date:	2024.06.25-2024.06.26
Test Power Supply:	Battery	Sample Number:	S24053007-001


Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Right side	2402	0.28	1.25	22.40	6.50
	Left side	2402	0.28	1.25	22.40	6.50
	Right side	2440	0.28	1.25	22.40	6.50
	Left side	2440	0.28	1.25	22.40	6.50
	Right side	2480	0.28	1.25	22.40	6.50
	Left side	2480	0.28	1.25	22.40	6.50

10.5. Test graphs






BLE_1M_Right side_2480



BLE_1M_Left side_2480



11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

11.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


12.Radiated Emission

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/07/08
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	²
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT through three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24053007-1E\FCC BELOW1G\20240702-005437_H

Memo:

Left side Sample Number:S24053007-003 Power Setting:1



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	50.051	23.45	12.95	3.88	-30.70	9.58	40.00	30.42	QP	Horizontal
2	119.991	27.5	10.00	4.33	-30.84	10.99	43.50	32.51	QP	Horizontal
3	393.270	41.76	15.34	5.59	-30.11	32.58	46.00	13.42	QP	Horizontal
4	442.435	41.07	15.95	5.78	-30.02	32.78	46.00	13.22	QP	Horizontal
5	540.680	34.53	17.17	6.15	-29.90	27.95	46.00	18.05	QP	Horizontal
6	835.102	37.21	20.20	7.04	-29.58	34.87	46.00	11.13	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24053007-1E\FCC BELOW1G\20240702-005525_V

Memo:

Left side Sample Number:S24053007-003 Power Setting:1



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	49.841	25.51	12.95	3.88	-30.70	11.64	40.00	28.36	QP	Vertical
2	71.971	30.46	9.60	4.03	-30.55	13.54	40.00	26.46	QP	Vertical
3	80.009	30.56	8.70	4.09	-30.50	12.85	40.00	27.15	QP	Vertical
4	300.229	22	13.70	5.22	-30.30	10.62	46.00	35.38	QP	Vertical
5	442.125	33.06	15.97	5.78	-30.02	24.79	46.00	21.21	QP	Vertical
6	850.466	24.26	21.19	7.08	-29.45	23.08	46.00	22.92	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24053007-1E\FCC BELOW1G\20240702-005656_H

Memo:

Right side Sample Number:S24053007-005 Power Setting:1



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	33.468	28.6	11.20	3.78	-30.95	12.63	40.00	27.37	QP	Horizontal
2	60.019	23.81	12.79	3.96	-30.63	9.93	40.00	30.07	QP	Horizontal
3	112.022	24.64	11.69	4.28	-30.86	9.75	43.50	33.75	QP	Horizontal
4	442.125	30.66	15.97	5.78	-30.02	22.39	46.00	23.61	QP	Horizontal
5	638.874	33.6	18.52	6.49	-29.90	28.71	46.00	17.29	QP	Horizontal
6	835.102	32.24	20.20	7.04	-29.58	29.90	46.00	16.10	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24053007-1E\FCC BELOW1G\20240702-005738_V

Memo:

Right side Sample Number:S24053007-005 Power Setting:1



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	43.778	25.12	12.96	3.84	-30.79	11.13	40.00	28.87	QP	Vertical
2	71.971	31.29	9.60	4.03	-30.55	14.37	40.00	25.63	QP	Vertical
3	80.009	32.62	8.70	4.09	-30.50	14.91	40.00	25.09	QP	Vertical
4	119.991	26.32	10.00	4.33	-30.84	9.81	43.50	33.69	QP	Vertical
5	451.523	24.82	15.86	5.82	-30.00	16.50	46.00	29.50	QP	Vertical
6	905.865	25.42	21.81	7.22	-28.95	25.50	46.00	20.50	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\11

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3837.300	46.56	30.85	5.08	-40.35	42.14	74.00	31.86	PK	Horizontal
2	4804.600	48.00	32.62	5.53	-40.15	46.00	74.00	28.00	PK	Horizontal
3	7373.300	42.97	36.75	6.64	-41.63	44.73	74.00	29.27	PK	Horizontal
4	9188.900	41.76	38.58	7.36	-38.78	48.92	74.00	25.08	PK	Horizontal
5	11470.300	41.55	39.23	8.43	-39.31	49.90	74.00	24.10	PK	Horizontal
6	15781.500	39.70	38.34	10.00	-39.23	48.81	74.00	25.19	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\12

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3915.500	47.02	31.17	5.06	-40.40	42.85	74.00	31.15	PK	Vertical
2	4804.600	47.57	32.62	5.53	-40.15	45.57	74.00	28.43	PK	Vertical
3	7417.500	42.85	36.67	6.66	-41.74	44.44	74.00	29.56	PK	Vertical
4	9350.400	41.82	38.70	7.42	-38.77	49.17	74.00	24.83	PK	Vertical
5	11456.700	42.03	39.24	8.42	-39.30	50.39	74.00	23.61	PK	Vertical
6	15776.400	39.91	38.35	10.00	-39.23	49.03	74.00	24.97	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\13

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4879.400	47.12	33.33	5.58	-40.12	45.91	74.00	28.09	PK	Horizontal
2	7318.900	49.45	36.86	6.61	-41.50	51.42	74.00	22.58	PK	Horizontal
3	9163.400	42.92	38.53	7.35	-38.78	50.02	74.00	23.98	PK	Horizontal
4	11310.500	41.79	39.21	8.33	-39.24	50.09	74.00	23.91	PK	Horizontal
5	12002.400	41.72	39.20	8.76	-39.56	50.12	74.00	23.88	PK	Horizontal
6	15681.200	39.97	38.52	9.94	-39.17	49.26	74.00	24.74	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\14

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3980.100	47.14	30.98	5.05	-40.44	42.73	74.00	31.27	PK	Vertical
2	4881.100	44.56	33.30	5.58	-40.12	43.32	74.00	30.68	PK	Vertical
3	7318.900	47.40	36.86	6.61	-41.50	49.37	74.00	24.63	PK	Vertical
4	9144.700	42.74	38.50	7.35	-38.78	49.81	74.00	24.19	PK	Vertical
5	11256.100	42.30	39.20	8.29	-39.21	50.58	74.00	23.42	PK	Vertical
6	12325.400	41.27	39.30	8.93	-39.69	49.81	74.00	24.19	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\15

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4959.300	47.41	33.12	5.63	-40.10	46.06	74.00	27.94	PK	Horizontal
2	7439.600	50.82	36.62	6.67	-41.80	52.31	74.00	21.69	PK	Horizontal
3	9017.200	42.32	38.33	7.31	-38.79	49.17	74.00	24.83	PK	Horizontal
4	10858.300	41.69	39.34	8.06	-39.04	50.05	74.00	23.95	PK	Horizontal
5	11902.100	42.86	38.91	8.70	-39.51	50.96	74.00	23.04	PK	Horizontal
6	15761.100	39.51	38.38	9.99	-39.22	48.66	74.00	25.34	PK	Horizontal

Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	7439.550	46.92	36.62	6.67	-41.80	48.41	54.0	5.59	AV	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\16

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	4959.300	46.34	33.12	5.63	-40.10	44.99	74.00	29.01	PK	Vertical
2	7439.600	48.37	36.62	6.67	-41.80	49.86	74.00	24.14	PK	Vertical
3	9032.500	42.53	38.37	7.31	-38.79	49.42	74.00	24.58	PK	Vertical
4	10936.500	41.52	39.30	8.10	-39.07	49.85	74.00	24.15	PK	Vertical
5	12024.500	41.80	39.22	8.77	-39.57	50.22	74.00	23.78	PK	Vertical
6	16170.800	40.75	37.83	10.19	-39.50	49.27	74.00	24.73	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\43

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3740.400	46.46	30.48	5.09	-40.29	41.74	74.00	32.26	PK	Horizontal
2	4802.900	50.34	32.58	5.53	-40.15	48.30	74.00	25.70	PK	Horizontal
3	7454.900	43.82	36.59	6.68	-41.84	45.25	74.00	28.75	PK	Horizontal
4	10701.900	41.19	39.40	7.98	-38.98	49.59	74.00	24.41	PK	Horizontal
5	12050.000	41.59	39.25	8.79	-39.58	50.05	74.00	23.95	PK	Horizontal
6	15757.700	40.13	38.38	9.99	-39.21	49.29	74.00	24.71	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\44

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3788.000	47.72	30.65	5.09	-40.32	43.14	74.00	30.86	PK	Vertical
2	4804.600	47.35	32.62	5.53	-40.15	45.35	74.00	28.65	PK	Vertical
3	7456.600	43.67	36.59	6.68	-41.84	45.10	74.00	28.90	PK	Vertical
4	9420.100	42.11	38.70	7.44	-38.76	49.49	74.00	24.51	PK	Vertical
5	11172.800	41.82	39.23	8.24	-39.17	50.12	74.00	23.88	PK	Vertical
6	12301.600	41.93	39.30	8.91	-39.68	50.46	74.00	23.54	PK	Vertical

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\45

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4241.900	46.43	31.37	5.20	-40.36	42.64	74.00	31.36	PK	Horizontal
2	4879.400	47.70	33.33	5.58	-40.12	46.49	74.00	27.51	PK	Horizontal
3	7318.900	46.44	36.86	6.61	-41.50	48.41	74.00	25.59	PK	Horizontal
4	10912.700	42.39	39.30	8.09	-39.06	50.72	74.00	23.28	PK	Horizontal
5	12056.800	41.80	39.26	8.79	-39.58	50.27	74.00	23.73	PK	Horizontal
6	16175.900	40.41	37.82	10.19	-39.50	48.92	74.00	25.08	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2440MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\46

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4381.300	47.10	31.66	5.28	-40.31	43.73	74.00	30.27	PK	Vertical
2	4887.900	45.64	33.19	5.58	-40.12	44.29	74.00	29.71	PK	Vertical
3	7320.600	50.86	36.86	6.61	-41.50	52.83	74.00	21.17	PK	Vertical
4	10700.200	42.15	39.40	7.98	-38.98	50.55	74.00	23.45	PK	Vertical
5	12264.200	42.76	39.30	8.89	-39.66	51.29	74.00	22.71	PK	Vertical
6	16056.900	41.20	37.94	10.16	-39.41	49.89	74.00	24.11	PK	Vertical

Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7319.585	45.29	36.86	6.61	-41.50	47.26	54.0	6.74	AV	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\47

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3818.600	46.24	30.77	5.08	-40.34	41.75	74.00	32.25	PK	Horizontal
2	4961.000	49.08	33.12	5.63	-40.09	47.74	74.00	26.26	PK	Horizontal
3	7439.600	48.62	36.62	6.67	-41.80	50.11	74.00	23.89	PK	Horizontal
4	9341.900	41.51	38.68	7.41	-38.77	48.83	74.00	25.17	PK	Horizontal
5	11422.700	41.79	39.28	8.40	-39.29	50.18	74.00	23.82	PK	Horizontal
6	15757.700	40.21	38.38	9.99	-39.21	49.37	74.00	24.63	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\48

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	3893.400	46.43	31.16	5.07	-40.38	42.28	74.00	31.72	PK	Vertical
2	4961.000	46.21	33.12	5.63	-40.09	44.87	74.00	29.13	PK	Vertical
3	7439.600	49.35	36.62	6.67	-41.80	50.84	74.00	23.16	PK	Vertical
4	10667.900	41.29	39.34	7.96	-38.97	49.62	74.00	24.38	PK	Vertical
5	11558.700	41.99	39.08	8.48	-39.35	50.20	74.00	23.80	PK	Vertical
6	15776.400	40.35	38.35	10.00	-39.23	49.47	74.00	24.53	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13.Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2025/07/08

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.
Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\23

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2388.410	12.04	27.25	3.57	0.00	42.86	74.00	31.14	PK	Horizontal
2	2390.000	9.61	27.26	3.57	0.00	40.44	74.00	33.56	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2024-06-25

Tested By:Genliu

EUT:Hardhat Bluetooth Speaker

Model Number:AEPHS1

Test Mode:BLE1M TX 2402MHz

Power Supply:Battery


Condition:Temp:22.4°C;Humi:70.9%

Test Site:DDT 3# Chamber

File Path:d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\24

Memo:R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2389.820	14.33	27.26	3.57	0.00	45.16	74.00	28.84	PK	Vertical
2	2390.000	11.53	27.26	3.57	0.00	42.36	74.00	31.64	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\25

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBµV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Detector	Polarity
1	2483.500	9.88	27.53	3.62	0.00	41.03	74.00	32.97	PK	Horizontal
2	2488.441	13.43	27.55	3.62	0.00	44.60	74.00	29.40	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\26

Memo:

R Sample Number:S24053007-005 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	12.11	27.53	3.62	0.00	43.26	74.00	30.74	PK	Vertical
2	2486.290	12.96	27.55	3.62	0.00	44.13	74.00	29.87	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\55

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.150	13.99	27.26	3.57	0.00	44.82	74.00	29.18	PK	Horizontal
2	2390.000	9.56	27.26	3.57	0.00	40.39	74.00	33.61	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-06-25

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2402MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\56

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2389.620	14.01	27.26	3.57	0.00	44.84	74.00	29.16	PK	Vertical
2	2390.000	13.24	27.26	3.57	0.00	44.07	74.00	29.93	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\63

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	9.93	27.53	3.62	0.00	41.08	74.00	32.92	PK	Horizontal
2	2486.974	13.52	27.55	3.62	0.00	44.69	74.00	29.31	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-07-02

Tested By:

Genliu

EUT:

Hardhat Bluetooth Speaker

Model Number:

AEPHS1

Test Mode:

BLE1M TX 2480MHz

Power Supply:

Battery

Condition:

Temp:22.4°C;Humi:70.9%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24053007-1E\FCC ABOVE 1G\64

Memo:

L Sample Number:S24053007-003 Power Setting:1

Test Graph



Data List										
N O.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	10.02	27.53	3.62	0.00	41.17	74.00	32.83	PK	Vertical
2	2487.139	13.29	27.55	3.62	0.00	44.46	74.00	29.54	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14.Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
RF Cable	Yuhu Technology	Z806-NJ-NJ-6M	DDT-ZC02004	2025/07/08
Two Line V-Network	R&S	ENV216	DDT-ZC02056	/
Two Line V-Network	R&S	ENV216	DDT-ZC02059	2025/07/08
Conducted Radiated Software	Audix	E3	DDT-ZC00562	2025/07/08
EMI Test Receiver	R&S	ESCI/E3	DDT-ZC01297	2025/07/08
Pulse Limiter	SCHWARZBEC K	VTSD 9561	DDT-ZC02128	2025/03/31
Δ -shaped artificial power network	SCHWARZBEC K	PVDC 8301	DDT-ZC03939	2025/07/08
Three-phase artificial power network	SCHWARZBEC K	NSLK 8163	DDT-ZC01572	2025/07/08

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 6# Shield Room

Test Date : 2024-07-09

EUT : Hardhat Bluetooth Speaker

Power Supply : AC 120V/60Hz

Condition : Temp:21.9°C,Humi:56.2%

Memo :

D:\2024 Report Date\Q24053007-1E\0709 CE.EM6


Tested By : Gen Liu

Model Number : AEPHS1

Test Mode : BLE 1M mode

LISN : 2023 ENV 216 3#/NEUTRAL

Data: 6



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	7.61	9.81	0.10	9.94	27.46	65.91	-38.45	QP	NEUTRAL
2	0.15	-6.29	9.81	0.10	9.94	13.56	55.91	-42.35	Average	NEUTRAL
3	0.75	2.07	9.86	0.16	9.96	22.05	56.00	-33.95	QP	NEUTRAL
4	0.75	0.16	9.86	0.16	9.96	20.14	46.00	-25.86	Average	NEUTRAL
5	0.94	9.14	9.90	0.23	9.97	29.24	56.00	-26.76	QP	NEUTRAL
6	0.94	8.82	9.90	0.23	9.97	28.92	46.00	-17.08	Average	NEUTRAL
7	1.97	-2.38	9.99	0.26	9.99	17.86	56.00	-38.14	QP	NEUTRAL
8	1.97	-4.82	9.99	0.26	9.99	15.42	46.00	-30.58	Average	NEUTRAL
9	3.44	-4.80	9.58	0.27	10.01	15.06	56.00	-40.94	QP	NEUTRAL
10	3.44	-9.26	9.58	0.27	10.01	10.60	46.00	-35.40	Average	NEUTRAL
11	21.41	-6.98	9.92	0.34	10.09	13.37	60.00	-46.63	QP	NEUTRAL
12	21.41	-7.87	9.92	0.34	10.09	12.48	50.00	-37.52	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site

: DDT 6# Shield Room

Test Date

: 2024-07-09

EUT

: Hardhat Bluetooth Speaker

Power Supply

: AC 120V/60Hz

Condition

: Temp:21.9°C,Humi:56.2%

Memo

:

D:\2024 Report Date\Q24053007-1E\0709 CE.EM6

Tested By

: Gen Liu

Model Number

: AEPHS1


Test Mode

: BLE 1M mode

LISN

: 2023 ENV 216 3#/LINE

Data: 8



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	7.40	9.87	0.10	9.94	27.31	65.91	-38.60	QP	LINE
2	0.15	-6.57	9.87	0.10	9.94	13.34	55.91	-42.57	Average	LINE
3	0.75	3.46	9.79	0.16	9.96	23.37	56.00	-32.63	QP	LINE
4	0.75	0.94	9.79	0.16	9.96	20.85	46.00	-25.15	Average	LINE
5	0.94	10.70	9.69	0.23	9.97	30.59	56.00	-25.41	QP	LINE
6	0.94	9.87	9.69	0.23	9.97	29.76	46.00	-16.24	Average	LINE
7	1.77	0.62	9.69	0.26	9.99	20.56	56.00	-35.44	QP	LINE
8	1.77	-1.74	9.69	0.26	9.99	18.20	46.00	-27.80	Average	LINE
9	4.75	-1.84	9.83	0.27	10.02	18.28	56.00	-37.72	QP	LINE
10	4.75	-6.11	9.83	0.27	10.02	14.01	46.00	-31.99	Average	LINE
11	18.92	-2.44	9.80	0.33	10.08	17.77	60.00	-42.23	QP	LINE
12	18.92	-4.49	9.80	0.33	10.08	15.72	50.00	-34.28	Average	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

16. Photos of the EUT

Please refer to DDT-Q24053007-2E appendix I

-----End Report-----