

**Shenzhen Global Test Service Co.,Ltd.**

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT**FCC PART 15.247****Report Reference No.....: GTSR16110032-01****FCC ID.....: 2AI52-X5**

Compiled by

(position+printed name+signature)..: File administrators Jimmy Wang

Supervised by

(position+printed name+signature)..:

Test Engineer Peter Xiao

Approved by

(position+printed name+signature)..: Manager Sam Wang

Date of issue.....: Nov. 16, 2016

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: 1F, Building No. 13A, Zhonghaixin Science and Technology City,
No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District,
Shenzhen, Guangdong

Applicant's name.....: MAD Gaze (Shen Zhen) Limited

Address: Room 201,Building A,NO.1 Qianwan Road 1,Shenzhen and
Hongkong Cooperation Zone, Qianhai, Shenzhen, China

Test specification

Standard: **FCC Part 15.247: Operation within the bands 902-928 MHz,
2400-2483.5 MHz and 5725-5850 MHz**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description Smart Glasses

Trade Mark: MAD Gaze

Manufacturer: **MAD Gaze (Shen Zhen) Limited**

Model/Type reference.....: X5

Listed Models: G200

Operation Frequency.....: From 2412MHz to 2462MHz

Hardware Version: G200-MB-V1.1

Software Version: V1.0

Rating: DC 3.7V

Result.....: **PASS**

TEST REPORT

Test Report No. : GTSR16110032-01	Nov. 16, 2016 Date of issue
--	--------------------------------

Equipment under Test : Smart Glasses

Model /Type : X5

Listed Models : G200

Applicant : **MAD Gaze (Shen Zhen) Limited**

Address : Room 201,Building A,NO.1 Qianwan Road 1,Shenzhen and Hongkong Cooperation Zone, Qianhai, Shenzhen, China

Manufacturer : **MAD Gaze (Shen Zhen) Limited**

Address : Room 201,Building A,NO.1 Qianwan Road 1,Shenzhen and Hongkong Cooperation Zone, Qianhai, Shenzhen, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	<u>4</u>
<u>2.</u>	<u>SUMMARY</u>	<u>5</u>
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment Under Test	5
2.4.	Short description of the Equipment under Test (EUT)	5
2.5.	EUT operation mode	6
2.6.	Block Diagram of Test Setup	6
2.7.	Related Submittal(s) / Grant (s)	6
2.8.	Modifications	6
2.9.	EUT configuration	6
2.10.	NOTE	6
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
3.1.	Address of the test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	7
3.4.	Test Description	8
3.5.	Statement of the measurement uncertainty	9
3.6.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS.....</u>	<u>10</u>
4.1.	AC Power Conducted Emission	10
4.2.	Radiated Emission.....	13
4.3.	Maximum Peak Output Power.....	21
4.4.	Power Spectral Density	22
4.5.	6dB Bandwidth	25
4.6.	Band Edge Compliance of RF Emission	28
4.7.	Spurious RF Conducted Emission	33
4.8.	Antenna Requirement.....	58
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>59</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>61</u>

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 V03r05](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Oct. 31, 2016
Testing commenced on	:	Oct. 31, 2016
Testing concluded on	:	Nov. 16, 2016

2.2. Product Description

Name of EUT	Smart Glasses
Model Number	X5
Listed Models	G200
FCC ID	2AI52-X5
Power Supply	DC 3.7V from battery
Supported type:	802.11b/802.11g/802.11n HT20/802.11n HT40
Modulation:	802.11b: DSSS(CCK,DQPSK,DBPSK) 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK) 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)
Operation frequency:	802.11b:2412-2462MHz 802.11g:2412-2462MHz 802.11n HT20:2412-2462MHz 802.11n HT40:2422-2452MHz
Antenna Type	Internal Antenna
Antenna gain	0.72dBi
Remark: The products are identical in interior structure, electrical circuits and components, just model names and antenna numbers are different.	

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 3.7V

2.4. Short description of the Equipment under Test (EUT)

This is a Smart Glasses.

For more details, refer to the user's manual of the EUT.


2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AI52-X5** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

2.9. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

○ Adapter	M/N: EP08CA
	Manufacturer: Shenzhen Iruis Electrical Co.,Ltd

2.10. NOTE

	Test Standards	Reference Report
WLAN	FCC Part 15 Subpart C	GTSR16110032-01
RF Exposure evaluation	FCC Per 47 CFR 2.1093(d)	GTSR16110032-02

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

Shenzhen CTL Testing Technology Co.,Ltd.

1/F.-A, Baisha Technology Park, No.3011, Shaheji Road, Nanshan District, Shenzhen, Guangdong, China

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 964637

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 964637, Jul 24, 2015.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	802.11b	☒ Lowest ☒ Middle ☒ Highest	802.11b	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.247(e)	Power spectral density	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.247(a)(2)	Spectrum bandwidth – 6 dB bandwidth	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.247(b)(1)	Maximum output power	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒ ☒	☐	☐	☐	complies
§15.247(d)	Band edge compliance conducted	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.205	Band edge compliance radiated	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Highest	☒	☐	☐	☐	complies
§15.247(d)	TX spurious emissions conducted	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	☒ ☒	☐	☐	☐	complies
§15.247(d)	TX spurious emissions radiated	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	802.11b 802.11g 802.11n HT20 802.11n HT40	☒ Lowest ☒ Middle ☒ Highest	☒	☐	☐	☐	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	☐	☐	☒	☐	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11b	-/-	802.11b	-/-	☒	☐	☐	☐	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11b	-/-	802.11b	-/-	☒	☐	☐	☐	complies

Remark:

1. The measurement uncertainty is not included in the test result.

2. NA = Not Applicable; NP = Not Performed

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9kHz~1GHz& Radiated Emission 1GHz~10 th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/9

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2016/05/28	2017/05/27
LISN	R&S	ESH2-Z5	893606/008	2016/05/27	2017/05/26
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2016/06/02	2017/06/01
EMI Test Receiver	R&S	ESCI	101102	2016/06/26	2017/06/25
Spectrum Analyzer	Agilent	N9020A	MY48010425	2016/06/17	2017/06/16
Controller	EM Electronics	Controller EM 1000	N/A	2016/05/21	2017/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2016/05/19	2017/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2016/05/19	2017/05/18
Amplifier	Agilent	8349B	3008A02306	2016/05/19	2017/05/18
Amplifier	Agilent	8447D	2944A10176	2016/05/19	2017/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2016/05/20	2017/05/19
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	N/A	2016/05/20	2017/05/19
High-Pass Filter	K&L	41H10-1375/U12750-O/O	N/A	2016/05/20	2017/05/19
Data acquisition card	Agilent	U2531A	TW53323507	2016/05/20	2017/05/19
Power Sensor	Agilent	U2021XA	MY5365004	2016/05/20	2017/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2016/05/20	2017/05/19

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC5V power, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.


TEST RESULTS

Power supply:

DC 5V from Adapter
AC 120V/60Hz

Polarization

L

**MEASUREMENT RESULT: "GTS161114102_fin"**


11/14/2016 2:59PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.402000	36.40	9.8	58	21.4	QP	L1	GND
0.762000	47.80	9.7	56	8.2	QP	L1	GND
1.806000	40.50	9.5	56	15.5	QP	L1	GND
2.139000	39.70	9.5	56	16.3	QP	L1	GND
6.261000	37.60	9.2	60	22.4	QP	L1	GND
16.102500	25.30	7.9	60	34.7	QP	L1	GND

MEASUREMENT RESULT: "GTS161114102_fin2"

11/14/2016 2:59PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.370500	31.50	9.9	49	17.0	AV	L1	GND
0.748500	38.10	9.7	46	7.9	AV	L1	GND
1.423500	31.90	9.6	46	14.1	AV	L1	GND
2.251500	29.40	9.5	46	16.6	AV	L1	GND
6.378000	25.30	9.2	50	24.7	AV	L1	GND
16.120500	15.60	7.9	50	34.4	AV	L1	GND




4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$\text{Transd}=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: Test site: Shenzhen CTL Testing Technology Co., Ltd

For 9 KHz-30MHz

Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.54	50.54	92.96	42.42	QP	PASS
1.478	43.89	64.21	20.32	QP	PASS
20.52	44.74	69.54	24.80	QP	PASS
25.68	44.33	69.54	25.21	QP	PASS

For 30MHz-1GHz

For 1GHz to 25GHz

802.11b Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	55.48	PK	74	18.52	1.00	125	53.38	31.6	7.00	36.5	2.10
1	4824	47.51	AV	54	6.49	1.00	125	45.41	31.6	7.00	36.5	2.10
2	7236	50.12	PK	74	23.88	1.00	244	39.19	37.33	8.90	35.3	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	55.65	PK	74	18.35	1.00	135	53.55	31.60	7.00	36.50	2.10
1	4824	47.87	AV	54	6.13	1.00	135	45.77	31.60	7.00	36.50	2.10
2	7236	50.96	PK	74	23.04	1.00	220	40.03	37.33	8.90	35.30	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	56.01	PK	74.00	17.99	1.00	89	53.89	31.02	7.60	36.5	2.12
1	4874.00	48.44	AV	54.00	5.56	1.00	89	46.32	31.02	7.60	36.5	2.12
2	7311.00	51.25	PK	74.00	22.75	1.00	156	40.17	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	56.22	PK	74.00	17.78	1.00	169	54.10	31.02	7.60	36.5	2.12
1	4874.00	48.59	AV	54.00	5.41	1.00	169	46.47	31.02	7.60	36.5	2.12
2	7311.00	51.31	PK	74.00	22.69	1.00	265	40.23	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	55.14	PK	74.00	18.86	1.00	174	51.94	31.58	7.82	36.2	3.20
1	4924.00	47.58	AV	54.00	6.42	1.00	174	44.38	31.58	7.82	36.2	3.20
2	7386.00	50.23	PK	74.00	23.77	1.00	229	38.29	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	55.39	PK	74.00	18.61	1.00	144	52.19	31.58	7.82	36.2	3.20
1	4924.00	47.64	AV	54.00	6.36	1.00	144	44.44	31.58	7.82	36.2	3.20
2	7386.00	50.11	PK	74.00	23.89	1.00	235	38.17	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

802.11g Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	50.25	PK	74	23.75	1.00	59	48.15	31.6	7.00	36.5	2.10
1	4824	--	AV	54	--	--	--	--	--	--	--	--
2	7236	48.50	PK	74	25.50	1.00	169	37.57	37.33	8.90	35.3	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	50.39	PK	74	23.61	1.00	118	48.29	31.60	7.00	36.50	2.10
1	4824	--	AV	54	--	--	--	--	--	--	--	--
2	7236	48.48	PK	74	25.52	1.00	186	37.55	37.33	8.90	35.30	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	51.52	PK	74.00	22.48	1.00	144	49.40	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	49.22	PK	74.00	24.78	1.00	231	38.14	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	51.66	PK	74.00	22.34	1.00	138	49.54	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	49.37	PK	74.00	24.63	1.00	276	38.29	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	50.47	PK	74.00	23.53	1.00	105	47.27	31.58	7.82	36.2	3.20
1	4924.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7386.00	47.98	PK	74.00	26.02	1.00	89	36.04	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	50.89	PK	74.00	23.11	1.00	175	47.69	31.58	7.82	36.2	3.20
1	4924.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7386.00	48.21	PK	74.00	25.79	1.00	236	36.27	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

802.11n HT20 Mode (above 1GHz)

Frequency(MHz):				2412			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	51.22	PK	74	22.78	1.00	48	49.12	31.6	7.00	36.5	2.10
1	4824	--	AV	54	--	--	--	--	--	--	--	--
2	7236	47.58	PK	74	26.42	1.00	135	36.65	37.33	8.90	35.3	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2412			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4824	51.98	PK	74	22.02	1.00	125	49.88	31.60	7.00	36.50	2.10
1	4824	--	AV	54	--	--	--	--	--	--	--	--
2	7236	48.15	PK	74	25.85	1.00	208	37.22	37.33	8.90	35.30	10.93
2	7236	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	52.41	PK	74.00	21.59	1.00	123	50.29	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	48.44	PK	74.00	25.56	1.00	174	37.36	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	52.57	PK	74.00	21.43	1.00	98	50.45	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	48.53	PK	74.00	25.47	1.00	41	37.45	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	51.36	PK	74.00	22.64	1.00	225	48.16	31.58	7.82	36.2	3.20
1	4924.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7386.00	47.59	PK	74.00	26.41	1.00	207	35.65	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2462			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4924.00	51.44	PK	74.00	22.56	1.00	215	48.24	31.58	7.82	36.2	3.20
1	4924.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7386.00	47.59	PK	74.00	26.41	1.00	183	35.65	38.51	8.73	35.3	11.94
2	7386.00	--	AV	54.00	--	--	--	--	--	--	--	--

802.11n HT40 Mode (above 1GHz)

Frequency(MHz):				2422			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4844	50.69	PK	74	23.31	1.00	69	48.52	31.64	7.05	36.52	2.17
1	4844	--	AV	54	--	--	--	--	--	--	--	--
2	7266	47.85	PK	74	26.15	1.00	124	36.41	37.85	8.92	35.33	11.44
2	7266	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2422			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4844	50.98	PK	74	23.02	1.00	105	48.81	31.64	7.05	36.52	2.17
1	4844	--	AV	54	--	--	--	--	--	--	--	--
2	7266	48.22	PK	74	25.78	1.00	117	36.78	37.85	8.92	35.33	11.44
2	7266	--	AV	54	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	51.47	PK	74.00	22.53	1.00	241	49.35	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	49.33	PK	74.00	24.67	1.00	155	38.25	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2437			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4874.00	51.96	PK	74.00	22.04	1.00	52	49.84	31.02	7.60	36.5	2.12
1	4874.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7311.00	49.21	PK	74.00	24.79	1.00	126	38.13	37.28	8.60	34.8	11.08
2	7311.00	--	AV	54.00	--	--	--	--	--	--	--	--

Frequency(MHz):				2452			Polarity:			HORIZONTAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4904.00	50.85	PK	74.00	23.15	1.00	150	47.77	31.49	7.78	36.19	3.08
1	4904.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7356.00	47.41	PK	74.00	26.59	1.00	118	35.50	38.45	8.71	35.25	11.91
2	7356.00	--	AV	54.00	--	--	--	--	--	--	--	--


Frequency(MHz):				2452			Polarity:			VERTICAL		
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
1	4904.00	50.63	PK	74.00	23.37	1.00	208	47.55	31.49	7.78	36.19	3.08
1	4904.00	--	AV	54.00	--	--	--	--	--	--	--	--
2	7356.00	47.14	PK	74.00	26.86	1.00	163	35.23	38.45	8.71	35.25	11.91
2	7356.00	--	AV	54.00	--	--	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.

4.3. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power, 9.1.1. The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

LIMIT


The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

Type	Channel	Output power PK (dBm)	Output power AV (dBm)	Limit (dBm)	Result
802.11b	01	11.52	8.44	30.00	Pass
	06	11.56	8.45		
	11	11.45	8.33		
802.11g	01	11.58	8.10	30.00	Pass
	06	11.75	8.17		
	11	11.33	8.12		
802.11n(HT20)	01	10.25	5.91	30.00	Pass
	06	10.36	5.95		
	11	10.47	5.90		
802.11n(HT40)	03	10.26	5.56	30.00	Pass
	06	10.34	5.84		
	09	10.28	5.68		


Note: 1. The test results including the cable lose.

Duty cycle used in all test items: 100%



4.4. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 Method PKPSD (peak PSD) This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \text{ RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


TEST RESULTS

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-14.421	8.00	Pass
	06	-13.962		
	11	-15.129		
802.11g	01	-17.499	8.00	Pass
	06	-16.094		
	11	-17.114		
802.11n(HT20)	01	-17.681	8.00	Pass
	06	-16.625		
	11	-16.769		
802.11n(HT40)	03	-20.931	8.00	Pass
	06	-21.711		
	09	-21.315		


802.11b




802.11g




CH01




CH01



CH06




CH06




CH11

CH11


802.11nHT20




802.11nHT40




CH01




CH03



CH06



CH06




CH11

CH09

4.5. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz


TEST RESULTS

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	10.23	≥ 500	Pass
	06	10.25		
	11	10.25		
802.11g	01	16.54	≥ 500	Pass
	06	16.54		
	11	16.52		
802.11nHT20	01	17.81	≥ 500	Pass
	06	17.82		
	11	17.80		
802.11nHT40	03	36.43	≥ 500	Pass
	06	36.46		
	09	36.44		


802.11b




802.11g




CH01




CH01



CH06




CH06




CH11

CH11


802.11nHT20




802.11nHT40




CH01




CH03



CH06



CH06



CH11

CH09

4.6. Band Edge Compliance of RF Emission

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

According to KDB 558074 D01 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for average detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test duress until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band.

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

TEST RESULTS

Remark: Test site: Shenzhen CTL Testing Technology Co., Ltd.

4.6.1 For Radiated Bandedge Measurement**802.11b**

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	54.25	PK	74.00	19.75	1.00	85	59.56	27.49	3.32	36.12	-5.31
2390.00	45.26	AV	54.00	8.74	1.00	85	50.57	27.49	3.32	36.12	-5.31
Frequency(MHz):			2412			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	54.78	PK	74.00	19.22	1.00	125	60.09	27.49	3.32	36.12	-5.31
2390.00	45.96	AV	54.00	8.04	1.00	125	51.27	27.49	3.32	36.12	-5.31
Frequency(MHz):			2462			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.35	PK	74.00	16.65	1.00	104	63.07	27.45	3.38	36.55	-5.72
2483.50	49.22	AV	54.00	4.78	1.00	104	54.94	27.45	3.38	36.55	-5.72
Frequency(MHz):			2462			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.40	PK	74.00	16.60	1.00	158	63.12	27.45	3.38	36.55	-5.72
2483.50	49.89	AV	54.00	4.11	1.00	158	55.61	27.45	3.38	36.55	-5.72

802.11g

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	55.24	PK	74.00	18.76	1.00	135	60.55	27.49	3.32	36.12	-5.31
2390.00	46.98	AV	54.00	7.02	1.00	135	52.29	27.49	3.32	36.12	-5.31
Frequency(MHz):			2412			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	55.62	PK	74.00	18.38	1.00	114	60.93	27.49	3.32	36.12	-5.31
2390.00	47.04	AV	54.00	6.96	1.00	114	52.35	27.49	3.32	36.12	-5.31
Frequency(MHz):			2462			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.25	PK	74.00	16.75	1.00	152	62.97	27.45	3.38	36.55	-5.72
2483.50	49.36	AV	54.00	4.64	1.00	152	55.08	27.45	3.38	36.55	-5.72
Frequency(MHz):			2462			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.40	PK	74.00	16.60	1.00	98	63.12	27.45	3.38	36.55	-5.72
2483.50	49.64	AV	54.00	4.36	1.00	98	55.36	27.45	3.38	36.55	-5.72



802.11n HT20

Frequency(MHz):			2412			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	55.25	PK	74.00	18.75	1.00	165	60.56	27.49	3.32	36.12	-5.31
2390.00	47.11	AV	54.00	6.89	1.00	165	52.42	27.49	3.32	36.12	-5.31
Frequency(MHz):			2412			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	56.14	PK	74.00	17.86	1.00	241	61.45	27.49	3.32	36.12	-5.31
2390.00	48.20	AV	54.00	5.80	1.00	241	53.51	27.49	3.32	36.12	-5.31
Frequency(MHz):			2462			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.36	PK	74.00	16.64	1.00	128	63.08	27.45	3.38	36.55	-5.72
2483.50	50.12	AV	54.00	3.88	1.00	128	55.84	27.45	3.38	36.55	-5.72
Frequency(MHz):			2462			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	57.57	PK	74.00	16.43	1.00	141	63.29	27.45	3.38	36.55	-5.72
2483.50	50.33	AV	54.00	3.67	1.00	141	56.05	27.45	3.38	36.55	-5.72

802.11n HT40

Frequency(MHz):			2422			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	57.25	PK	74.00	16.75	1.00	133	62.56	27.49	3.32	36.12	-5.31
2390.00	50.26	AV	54.00	3.74	1.00	133	55.57	27.49	3.32	36.12	-5.31
Frequency(MHz):			2422			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2390.00	57.98	PK	74.00	16.02	1.00	244	63.29	27.49	3.32	36.12	-5.31
2390.00	50.64	AV	54.00	3.36	1.00	244	55.95	27.49	3.32	36.12	-5.31
Frequency(MHz):			2452			Polarity:			HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	58.98	PK	74.00	15.02	1.00	125	64.70	27.45	3.38	36.55	-5.72
2483.50	51.01	AV	54.00	2.99	1.00	125	56.73	27.45	3.38	36.55	-5.72
Frequency(MHz):			2452			Polarity:			VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier	Correction Factor (dB/m)
2483.50	59.01	PK	74.00	14.99	1.00	139	64.73	27.45	3.38	36.55	-5.72
2483.50	51.21	AV	54.00	2.79	1.00	139	56.93	27.45	3.38	36.55	-5.72

4.6.2 For Conducted Bandedge Measurement



802.11n HT20

Frequency (MHz)	Delta Peak to Band emission (dBc)	Limit (dBc)	Verdict
2400.00	-44.547	-30	PASS
2483.50	-41.067	-30	PASS

Agilent Spectrum Analyzer - Swept SA			
Center Freq 2.370000000 GHz			
Mkr4 2.385 165 GHz -51.326 dBm			
Start 2.31000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 11.7 ms (8001 pts)			
Stop 2.43000 GHz			
CF Step 12.000000 MHz			
Freq Offset 0 Hz			
2412			

Agilent Spectrum Analyzer - Swept SA			
Center Freq 2.490000000 GHz			
Mkr4 2.483 862.5 GHz -44.429 dBm			
Start 2.44000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 9.60 ms (8001 pts)			
Stop 2.54000 GHz			
CF Step 10.000000 MHz			
Freq Offset 0 Hz			
2462			

802.11n HT40


Frequency (MHz)	Delta Peak to Band emission (dBc)	Limit (dBc)	Verdict
2400.00	-44.259	-30	PASS
2483.50	-35.299	-30	PASS

Agilent Spectrum Analyzer - Swept SA			
Center Freq 2.380000000 GHz			
Mkr4 2.388 855.0 GHz -51.852 dBm			
Start 2.31000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 13.9 ms (8001 pts)			
Stop 2.45000 GHz			
CF Step 14.000000 MHz			
Freq Offset 0 Hz			
2422			

Agilent Spectrum Analyzer - Swept SA			
Center Freq 2.480000000 GHz			
Mkr4 2.484 437.5 GHz -44.120 dBm			
Start 2.43000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 9.60 ms (8001 pts)			
Stop 2.53000 GHz			
CF Step 10.000000 MHz			
Freq Offset 0 Hz			
2452			

4.7. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.

Test Mode:	802.11b	Test channel :	01								
Agilent Spectrum Analyzer - Swept SA Center Freq 2.412000000 GHz Ref Offset 1 dB Ref 20.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Span 40.00 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.27 ms (8001 pts) Mkr1 2.412 520 GHz -0.919 dBm Frequency Auto Tune Center Freq 2.412000000 GHz Start Freq 2.392000000 GHz Stop Freq 2.432000000 GHz CF Step 4.000000 MHz Auto Freq Offset 0 Hz Channel 01 <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Average/Hold Number 100 Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Start 9 kHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.867 ms (1001 pts) Mkr1 549 kHz -42.620 dBm Trace/Detector Select Trace 1 Clear Write Trace Average Max Hold Min Hold View Blank Trace On More 1 of 3 9KHz~30MHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz </td></tr> </td></tr>				Agilent Spectrum Analyzer - Swept SA Average/Hold Number 100 Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Start 9 kHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.867 ms (1001 pts) Mkr1 549 kHz -42.620 dBm Trace/Detector Select Trace 1 Clear Write Trace Average Max Hold Min Hold View Blank Trace On More 1 of 3 9KHz~30MHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz			
Agilent Spectrum Analyzer - Swept SA Average/Hold Number 100 Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Start 9 kHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.867 ms (1001 pts) Mkr1 549 kHz -42.620 dBm Trace/Detector Select Trace 1 Clear Write Trace Average Max Hold Min Hold View Blank Trace On More 1 of 3 9KHz~30MHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz							
Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Mkr1 948.59 MHz -57.503 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz 30M Hz~1GHz											

Test Mode:	802.11b	Test channel :	01								
Agilent Spectrum Analyzer - Swept SA Center Freq 4.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 1.000 GHz #Res BW 100 kHz Stop 8.000 GHz #VBW 300 kHz Sweep 669 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 5/100 Mkr1 5.650 625 GHz -55.182 dBm Frequency Auto Tune Center Freq 4.500000000 GHz Start Freq 1.000000000 GHz Stop Freq 8.000000000 GHz CF Step 700.000000 MHz Auto Man Freq Offset 0 Hz 1G Hz~8GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz Stop 16.000 GHz #VBW 300 kHz Sweep 765 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 15.359 GHz -51.979 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Man Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz </td></tr> </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz Stop 16.000 GHz #VBW 300 kHz Sweep 765 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 15.359 GHz -51.979 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Man Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz Stop 16.000 GHz #VBW 300 kHz Sweep 765 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 15.359 GHz -51.979 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Man Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz							
Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz Stop 25.000 GHz #VBW 300 kHz Sweep 860 ms (8001 pts) Trig: Free Run #Atten: 30 dB #Avg Type: Pwr(RMS) AvgHold: 3/100 Mkr1 24.962 9 GHz -46.782 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Man Freq Offset 0 Hz 16Gz~25GHz											

Test Mode:	802.11b	Test channel :	06
Agilent Spectrum Analyzer - Swept SA Center Freq 2.437000000 GHz Ref Offset 1 dB Ref 20.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Span 40.00 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.27 ms (8001 pts) Mkr1 2.437 510 GHz -0.272 dBm Frequency Auto Tune Center Freq 2.437000000 GHz Start Freq 2.417000000 GHz Stop Freq 2.457000000 GHz CF Step 4.000000 MHz Auto Freq Offset 0 Hz			
Channel 06			
Agilent Spectrum Analyzer - Swept SA Marker 1 668.802000 kHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 100/100 Sweep 2.867 ms (1001 pts) Mkr1 668 kHz -45.680 dBm Peak Search Next Peak Next Pk Right Next Pk Left Marker Delta Mkr--CF Mkr--Ref Lvl More 1 of 2			
9KHz~30MHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 515.0000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) AvgHold: 29/100 Sweep 92.8 ms (8001 pts) Mkr1 948.47 MHz -56.901 dBm Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Auto Freq Offset 0 Hz			
30M Hz~1GHz			

Test Mode:	802.11b	Test channel :	06
Agilent Spectrum Analyzer - Swept SA Center Freq 4.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 1.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 8.000 GHz Sweep 669 ms (8001 pts) Mkr1 7.834 625 GHz -54.172 dBm Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) Avg/Hold: 5/100 Frequency Auto Tune Center Freq 4.500000000 GHz Start Freq 1.000000000 GHz Stop Freq 8.000000000 GHz CF Step 700.000000 MHz Auto Freq Offset 0 Hz			
1G Hz~8GHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 16.000 GHz Sweep 765 ms (8001 pts) Mkr1 15.572 GHz -50.556 dBm Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) Avg/Hold: 3/100 Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Freq Offset 0 Hz			
8GHz~16GHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Stop 25.000 GHz Sweep 860 ms (8001 pts) Mkr1 24.996 6 GHz -47.227 dBm Trig: Free Run #Att: 30 dB #Avg Type: Pwr(RMS) Avg/Hold: 3/100 Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz			
16Gz~25GHz			

Test Mode:	802.11b	Test channel :	11
------------	---------	----------------	----

Agilent Spectrum Analyzer - Swept SA

Center Freq 2.46200000 GHz

Ref Offset 1 dB

Ref 20.00 dBm

10 dB/div

Log

Mkr1 2.462 510 GHz

-1.559 dBm

Center 2.46200 GHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 4.27 ms (8001 pts)

Frequency

Auto Tune

Center Freq 2.462000000 GHz

Start Freq 2.442000000 GHz

Stop Freq 2.482000000 GHz

CF Step 4.000000 MHz

Auto

Freq Offset 0 Hz

Channel 11

Agilent Spectrum Analyzer - Swept SA

Marker 1 458.865000 kHz

Ref Offset 1 dB

Ref 21.00 dBm

10 dB/div

Log

Mkr1 459 kHz

-40.283 dBm

Start 9 kHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 2.867 ms (1001 pts)

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr--CF

Mkr--Ref Lvl

More 1 of 2

9KHz~30MHz

Agilent Spectrum Analyzer - Swept SA

Center Freq 515.000000 MHz

Ref Offset 1 dB

Ref 21.00 dBm

10 dB/div

Log

Mkr1 920.46 MHz

-58.445 dBm

Start 30.0 MHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 92.8 ms (8001 pts)

Frequency

Auto Tune

Center Freq 515.000000 MHz

Start Freq 30.000000 MHz

Stop Freq 1.000000000 GHz

CF Step 97.000000 MHz

Auto

Freq Offset 0 Hz

30M Hz~1GHz

Test Mode:	802.11b	Test channel :	11								
Agilent Spectrum Analyzer - Swept SA Center Freq 4.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 1.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 669 ms (8001 pts) Mkr1 5.274 375 GHz -54.115 dBm Frequency Auto Tune Center Freq 4.500000000 GHz Start Freq 1.000000000 GHz Stop Freq 8.000000000 GHz CF Step 700.000000 MHz Auto Freq Offset 0 Hz 1G Hz~8GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 765 ms (8001 pts) Mkr1 15.522 GHz -50.592 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz </td></tr></td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 765 ms (8001 pts) Mkr1 15.522 GHz -50.592 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 12.000000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 8.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 765 ms (8001 pts) Mkr1 15.522 GHz -50.592 dBm Frequency Auto Tune Center Freq 12.000000000 GHz Start Freq 8.000000000 GHz Stop Freq 16.000000000 GHz CF Step 800.000000 MHz Auto Freq Offset 0 Hz 8GHz~16GHz <tr><td colspan="4"> Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz </td></tr>				Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz							
Agilent Spectrum Analyzer - Swept SA Center Freq 20.500000000 GHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Start 16.000 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 860 ms (8001 pts) Mkr1 21.188 5 GHz -46.741 dBm Frequency Auto Tune Center Freq 20.500000000 GHz Start Freq 16.000000000 GHz Stop Freq 25.000000000 GHz CF Step 900.000000 MHz Auto Freq Offset 0 Hz 16Gz~25GHz											

Test Mode:	802.11g	Test channel :	01
Agilent Spectrum Analyzer - Swept SA Center Freq 2.41200000 GHz Ref Offset 1 dB Ref 20.00 dBm 10 dB/div Log Marker 1 2.414 805 GHz -3.524 dBm Start 2.41200 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 4.27 ms (8001 pts) Frequency Auto Tune Center Freq 2.412000000 GHz Start Freq 2.392000000 GHz Stop Freq 2.432000000 GHz CF Step 4.000000 MHz Man Freq Offset 0 Hz			
Channel 01			
Agilent Spectrum Analyzer - Swept SA Marker 1 578.829000 kHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Marker 1 579 kHz -44.479 dBm Start 9 kHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.867 ms (1001 pts) Trace/Detector Select Trace 1 Clear Write Trace Average Max Hold Min Hold View Blank Trace On More 1 of 3			
9KHz~30MHz			
Agilent Spectrum Analyzer - Swept SA Center Freq 515.000000 MHz Ref Offset 1 dB Ref 21.00 dBm 10 dB/div Log Marker 1 465.89 MHz -57.995 dBm Start 30.0 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 92.8 ms (8001 pts) Frequency Auto Tune Center Freq 515.000000 MHz Start Freq 30.000000 MHz Stop Freq 1.000000000 GHz CF Step 97.000000 MHz Man Freq Offset 0 Hz			
30M Hz~1GHz			