

TEST REPORT

Applicant: Joy Sky (Far East) Limited

Address of Applicant: Room 2311, 23/F, BEA Tower Millennium City 5, 418 Kwun Tong Road, Kwun Tong, Kowloon, Hong Kong, China

Manufacturer: Joy Sky (Far East) Limited

Address of Manufacturer: Room 2311, 23/F, BEA Tower Millennium City 5, 418 Kwun Tong Road, Kwun Tong, Kowloon, Hong Kong, China

Equipment Under Test (EUT)

Product Name: Table Top Electronic Drum

Model No.: RJTTED02-1

FCC ID: 2A15N-RJTTED02-1

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: March 10, 2026

Date of Test: March 10-16, 2026

Date of report issued: March 16, 2026

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 16, 2026	Original

Tested By:

Joshua Cai

Date:

March 16, 2026

Test Engineer

Prepared By:

Jason Wu

Date:

March 16, 2026

Project Engineer

Check By:

Robinson Liu

Date:

March 16, 2026

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 CONDUCTED PEAK OUTPUT POWER	14
7.4 20dB EMISSION BANDWIDTH	15
7.5 CARRIER FREQUENCIES SEPARATION	16
7.6 HOPPING CHANNEL NUMBER	17
7.7 DWELL TIME	18
7.8 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	19
7.8.1 Conducted Emission Method	19
7.8.2 Radiated Emission Method	20
8 TEST SETUP PHOTO	29
9 EUT CONSTRUCTIONAL DETAILS	29

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)(iii)	Pass
Dwell Time	15.247 (a)(1)(iii)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2020
3. N/A: Not applicable.

Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	Table Top Electronic Drum
Model No.:	RJTTE02-1
Test sample(s) ID:	GTS2026030115-1
Sample(s) Status:	Engineer sample
S/N:	N/A
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK
Antenna Type:	Inverted F Antenna
Antenna gain:	-0.68dBi
Power supply:	MODEL:BSG18W-0902000A INPUT:AC 100-240V, 0.5A, 50/60H OUTPUT:DC 9.0V, 2.0A Or DC 7.4V, 4000mAh for INR 18650-2S29

Disclaimer statement:

1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● ISED—Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).
--

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional Instructions

Test Software	FCC_assist_1.0.2.2
Power level setup	10

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 11, 2025	Jul 10, 2026
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.22, 2025	Nov.21, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV-Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 10, 2026	Mar. 09, 2027
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 24, 2025	Nov. 23, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 11, 2025	Jul. 10, 2026
17	RE cable 2	GTS	N/A	GTS676	Jul. 11, 2025	Jul. 10, 2026
18	RE cable 3	GTS	N/A	GTS677	Jul. 11, 2025	Jul. 10, 2026
19	RE cable 4	GTS	N/A	GTS678	Jul. 11, 2025	Jul. 10, 2026
20	RE cable 5	GTS	N/A	GTS679	Jul. 11, 2025	Jul. 10, 2026
21	RE cable 6	GTS	N/A	GTS680	Jul. 11, 2025	Jul. 10, 2026
22	RE cable 7	GTS	N/A	GTS681	Jul. 11, 2025	Jul. 10, 2026
23	RE cable 8	GTS	N/A	GTS682	Jul. 11, 2025	Jul. 10, 2026
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	Jul. 12, 2022	Jul. 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	Apr. 11, 2025	Apr. 10, 2026
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	Thermo meter	JINCHUANG	GSP-8A	GTS642	Apr. 15, 2025	Apr. 14, 2026
6	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	Apr. 12, 2025	Apr. 11, 2026
7	ISN	SCHWARZBECK	NTFM 8158	GTS565	Apr. 11, 2025	Apr. 10, 2026
8	High voltage probe	SCHWARZBECK	TK9420	GTS537	Apr. 11, 2025	Apr. 10, 2026
9	Antenna end assembly	Weinschel	1870A	GTS560	Apr. 11, 2025	Apr. 10, 2026
10	EMI Test Software	AUDIX	E3-6.100622	GTS726	N/A	N/A
11	Current probe	CYBERTEK	EM5011	GTS698	Jan. 27, 2026	Jan. 26, 2027

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Wireless Connectivity Test Set	Anritsu	MT8862A	SN6272327180	2025-08-26	2026-08-25
2	Bluetooth Test Set	Anritsu	MT8852B	SN6262097212	2025-08-26	2026-08-25
3	EXA Signal Analyzer	Keysight	N9010B	MY60241168	2025-08-26	2026-08-25
4	Vector Signal Generator	Keysight	N5182B	MY61250192	2025-04-17	2026-4-16
5	Analog Signal Generator	Keysight	N5171B	MY61252573	2025-08-26	2026-08-25
6	RF Control Unit and Power Test Unit	Tonscend	JS0806-2	SN21F8060437	2025-04-17	2026-4-16
7	Power Control Unit	Tonscend	JS0806-4ADC	SN21C8060386	N/A	N/A
8	Wideband Radio Communication Tester	R&S	CWM500	GTS569	2025-08-26	2026-08-25
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026
11	Test Software	Tonscend	JS1120-3 V3.5.39	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 16, 2025	Jul. 15, 2026

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna: The antenna is Inverted F Antenna, reference to the appendix II for details.	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207																			
Test Method:	ANSI C63.10:2020																			
Test Frequency Range:	150KHz to 30MHz																			
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																			
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.						Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																			
	Quasi-peak	Average																		
0.15-0.5	66 to 56*	56 to 46*																		
0.5-5	56	46																		
5-30	60	50																		
Test setup:	Reference Plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m																			
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.																			
Test Instruments:	Refer to section 6.0 for details																			
Test mode:	Refer to section 5.2 for details																			
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar														
Test voltage:	AC 120V, 60Hz																			
Test results:	Pass																			

Measurement data:


Pre-scan all test modes, found worst case at GFSK 2402MHz, and so only show the test result of it
Line:



Freq	Reading level	Correct Factor	Final level	Limit level	Over limit	Remark
MHz	dBuV	dB	dBuV	level	dBuV	
0.21	15.61	19.60	35.21	63.18	-27.97	QP
0.21	10.22	19.60	29.82	53.18	-23.36	Average
0.33	13.65	19.60	33.25	59.44	-26.19	QP
0.33	6.82	19.60	26.42	49.44	-23.02	Average
0.77	3.50	19.61	23.11	56.00	-32.89	QP
0.77	-1.74	19.61	17.87	46.00	-28.13	Average
2.40	1.93	19.66	21.59	56.00	-34.41	QP
2.40	-5.69	19.66	13.97	46.00	-32.03	Average
3.60	2.39	19.67	22.06	56.00	-33.94	QP
3.60	-4.42	19.67	15.25	46.00	-30.75	Average
8.02	5.75	19.71	25.46	60.00	-34.54	QP
8.02	-1.67	19.71	18.04	50.00	-31.96	Average

Note: Correct Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
Final level (dBuV) = Reading level (dBuV) + Correct Factor (dB)

Neutral:




Freq	Reading	Correct	Final	Limit	Over	Remark
MHz	dBuV	dB	dBuV	level	dBuV	
0.22	17.80	19.60	37.40	62.70	-25.30	QP
0.22	6.46	19.60	26.06	52.70	-26.64	Average
0.30	10.78	19.60	30.38	60.24	-29.86	QP
0.30	3.04	19.60	22.64	50.24	-27.60	Average
0.97	6.19	19.62	25.81	56.00	-30.19	QP
0.97	-1.56	19.62	18.06	46.00	-27.94	Average
2.96	4.95	19.67	24.62	56.00	-31.38	QP
2.96	-1.13	19.67	18.54	46.00	-27.46	Average
5.80	4.09	19.70	23.79	60.00	-36.21	QP
5.80	-2.23	19.70	17.47	50.00	-32.53	Average
9.25	5.52	19.72	25.24	60.00	-34.76	QP
9.25	0.00	19.72	19.72	50.00	-30.28	Average

Note: Correct Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
 Final level (dBuV) = Reading level (dBuV) + Correct Factor (dB)

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	ANSI C63.10:2020
Limit:	GFSK: 30dBm $\pi/4$ -DQPSK, 8-DPSK: 20.97dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.5 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=300KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data: The detailed test data see Appendix for BT EDR.

7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.


7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.

7.8 Spurious Emission in Non-restricted & restricted Bands



7.8.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2020
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data: The detailed test data see Appendix for BT EDR.

7.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209																																					
Test Method:	ANSI C63.10:2020																																					
Test Frequency Range:	9kHz to 25GHz																																					
Test site:	Measurement Distance: 3m																																					
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Value</td></tr><tr><td>9KHz-150KHz</td><td>Quasi-peak</td><td>200Hz</td><td>600Hz</td><td>Quasi-peak</td></tr><tr><td>150KHz-30MHz</td><td>Quasi-peak</td><td>9KHz</td><td>30KHz</td><td>Quasi-peak</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>120KHz</td><td>300KHz</td><td>Quasi-peak</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak</td></tr><tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average</td></tr></table> Note: For Duty cycle $\geq 98\%$, average detector set as above For Duty cycle $< 98\%$, average detector set as below: $VBW \geq 1 / T$					Frequency	Detector	RBW	VBW	Value	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak	Above 1GHz	Peak	1MHz	3MHz	Peak	Peak	1MHz	10Hz	Average				
Frequency	Detector	RBW	VBW	Value																																		
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak																																		
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak																																		
30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak																																		
Above 1GHz	Peak	1MHz	3MHz	Peak																																		
	Peak	1MHz	10Hz	Average																																		
Limit:	<table><tr><td>Frequency</td><td>Limit (uV/m)</td><td>Value</td><td>Measurement Distance</td></tr><tr><td>0.009MHz-0.490MHz</td><td>2400/F(KHz)</td><td>PK/QP/AV</td><td>300m</td></tr><tr><td>0.490MHz-1.705MHz</td><td>24000/F(KHz)</td><td>QP</td><td>30m</td></tr><tr><td>1.705MHz-30MHz</td><td>30</td><td>QP</td><td>30m</td></tr><tr><td>30MHz-88MHz</td><td>100</td><td>QP</td><td rowspan="5">3m</td></tr><tr><td>88MHz-216MHz</td><td>150</td><td>QP</td></tr><tr><td>216MHz-960MHz</td><td>200</td><td>QP</td></tr><tr><td>960MHz-1GHz</td><td>500</td><td>QP</td></tr><tr><td rowspan="2">Above 1GHz</td><td>500</td><td>Average</td></tr><tr><td>5000</td><td>Peak</td></tr></table>				Frequency	Limit (uV/m)	Value	Measurement Distance	0.009MHz-0.490MHz	2400/F(KHz)	PK/QP/AV	300m	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	1.705MHz-30MHz	30	QP	30m	30MHz-88MHz	100	QP	3m	88MHz-216MHz	150	QP	216MHz-960MHz	200	QP	960MHz-1GHz	500	QP	Above 1GHz	500	Average	5000	Peak
Frequency	Limit (uV/m)	Value	Measurement Distance																																			
0.009MHz-0.490MHz	2400/F(KHz)	PK/QP/AV	300m																																			
0.490MHz-1.705MHz	24000/F(KHz)	QP	30m																																			
1.705MHz-30MHz	30	QP	30m																																			
30MHz-88MHz	100	QP	3m																																			
88MHz-216MHz	150	QP																																				
216MHz-960MHz	200	QP																																				
960MHz-1GHz	500	QP																																				
Above 1GHz	500	Average																																				
	5000	Peak																																				
Test setup:	For radiated emissions from 9kHz to 30MHz																																					

	For radiated emissions from 30MHz to1GHz  For radiated emissions above 1GHz 						
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test environment:	<table><tr><td>Temp.:</td><td>25 °C</td><td>Humid.:</td><td>52%</td><td>Press.:</td><td>1012mbar</td></tr></table>	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar		

Test voltage:	AC 120V, 60Hz
Test results:	Pass

Measurement data:

Remarks:


1. During the test, pre-scan the GFSK, $\pi/4$ -DQPSK modulation, and found the GFSK modulation which it is worse case.
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ 9kHz~30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at GFSK 2402MHz, and so only show the test result of it
Horizontal:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
191.745	55.30	10.60	2.74	33.41	35.23	43.50	-8.27	QP
205.675	53.15	10.17	2.84	33.39	32.77	43.50	-10.73	QP
228.490	50.77	9.54	3.04	33.33	30.02	46.00	-15.98	QP
400.432	44.69	14.72	4.14	33.03	30.52	46.00	-15.48	QP
468.876	43.87	16.28	4.45	32.94	31.66	46.00	-14.34	QP
605.659	37.82	19.11	5.11	32.61	29.43	46.00	-16.57	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
134.088	44.77	13.39	2.31	33.52	26.95	43.50	-16.55	QP
150.011	42.46	14.70	2.45	33.48	26.13	43.50	-17.37	QP
191.745	53.77	10.60	2.74	33.41	33.70	43.50	-9.80	QP
228.490	45.46	9.54	3.04	33.33	24.71	46.00	-21.29	QP
350.477	39.06	13.71	3.87	33.11	23.53	46.00	-22.47	QP
468.876	42.07	16.28	4.45	32.94	29.86	46.00	-16.14	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

- Above 1GHz
- Unwanted Emissions in Non-restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	35.27	31.06	16.91	38.36	44.88	74.00	-29.12	Vertical
7206.00	30.48	35.91	23.33	38.96	50.76	74.00	-23.24	Vertical
9608.00	30.27	37.91	30.16	39.68	58.66	74.00	-15.34	Vertical
4804.00	39.15	31.06	16.91	38.36	48.76	74.00	-25.24	Horizontal
7206.00	32.06	35.91	23.33	38.96	52.34	74.00	-21.66	Horizontal
9608.00	29.50	37.91	30.16	39.68	57.89	74.00	-16.11	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.47	31.06	16.91	38.36	34.08	54.00	-19.92	Vertical
7206.00	19.40	35.91	23.33	38.96	39.68	54.00	-14.32	Vertical
9608.00	18.60	37.91	30.16	39.68	46.99	54.00	-7.01	Vertical
4804.00	28.48	31.06	16.91	38.36	38.09	54.00	-15.91	Horizontal
7206.00	21.44	35.91	23.33	38.96	41.72	54.00	-12.28	Horizontal
9608.00	18.16	37.91	30.16	39.68	46.55	54.00	-7.45	Horizontal

Test channel:	Middle channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	35.65	31.28	17.16	38.38	45.71	74.00	-28.29	Vertical
7323.00	30.73	36.16	24.06	39.00	51.95	74.00	-22.05	Vertical
9764.00	30.49	38.06	30.51	39.72	59.34	74.00	-14.66	Vertical
4882.00	39.60	31.28	17.16	38.38	49.66	74.00	-24.34	Horizontal
7323.00	32.34	36.16	24.06	39.00	53.56	74.00	-20.44	Horizontal
9764.00	29.76	38.06	30.51	39.72	58.61	74.00	-15.39	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4882.00	24.78	31.28	17.16	38.38	34.84	54.00	-19.16	Vertical
7323.00	19.61	36.16	24.06	39.00	40.83	54.00	-13.17	Vertical
9764.00	18.79	38.06	30.51	39.72	47.64	54.00	-6.36	Vertical
4882.00	28.83	31.28	17.16	38.38	38.89	54.00	-15.11	Horizontal
7323.00	21.67	36.16	24.06	39.00	42.89	54.00	-11.11	Horizontal
9764.00	18.38	38.06	30.51	39.72	47.23	54.00	-6.77	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	35.53	31.52	17.43	38.54	45.94	74.00	-28.06	Vertical
7440.00	30.65	36.34	24.43	39.23	52.19	74.00	-21.81	Vertical
9920.00	30.42	38.32	30.75	39.96	59.53	74.00	-14.47	Vertical
4960.00	39.45	31.52	17.43	38.54	49.86	74.00	-24.14	Horizontal
7440.00	32.25	36.34	24.43	39.23	53.79	74.00	-20.21	Horizontal
9920.00	29.67	38.32	30.75	39.96	58.78	74.00	-15.22	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	24.71	31.52	17.43	38.54	35.12	54.00	-18.88	Vertical
7440.00	19.56	36.34	24.43	39.23	41.10	54.00	-12.90	Vertical
9920.00	18.75	38.32	30.75	39.96	47.86	54.00	-6.14	Vertical
4960.00	28.75	31.52	17.43	38.54	39.16	54.00	-14.84	Horizontal
7440.00	21.62	36.34	24.43	39.23	43.16	54.00	-10.84	Horizontal
9920.00	18.33	38.32	30.75	39.96	47.44	54.00	-6.56	Horizontal

Remarks:

1. Final Level (dBuV/m) = Reading level (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Factor (dB)
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	41.96	27.17	4.60	38.52	35.21	74.00	-38.79	Horizontal
2390.00	43.38	27.27	4.65	38.56	36.74	74.00	-37.26	Horizontal
2310.00	42.84	27.17	4.60	38.52	36.09	74.00	-37.91	Vertical
2390.00	43.97	27.27	4.65	38.56	37.33	74.00	-36.67	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	32.56	27.17	4.60	38.52	25.81	54.00	-28.19	Horizontal
2390.00	33.81	27.27	4.65	38.56	27.17	54.00	-26.83	Horizontal
2310.00	33.11	27.17	4.60	38.52	26.36	54.00	-27.64	Vertical
2390.00	33.79	27.27	4.65	38.56	27.15	54.00	-26.85	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.54	27.38	4.52	38.59	38.85	74.00	-35.15	Horizontal
2500.00	44.62	27.40	4.49	38.60	37.91	74.00	-36.09	Horizontal
2483.50	46.47	27.38	4.52	38.59	39.78	74.00	-34.22	Vertical
2500.00	45.66	27.40	4.49	38.60	38.95	74.00	-35.05	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.65	27.38	4.52	38.59	29.96	54.00	-24.04	Horizontal
2500.00	34.58	27.40	4.49	38.60	27.87	54.00	-26.13	Horizontal
2483.50	37.90	27.38	4.52	38.59	31.21	54.00	-22.79	Vertical
2500.00	34.54	27.40	4.49	38.60	27.83	54.00	-26.17	Vertical

Remarks:

- Final Level (dBuV/m) = Reading level (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier Factor (dB)
- The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----