



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 1 of 36

Applicant : Radiance Instruments Ltd.
Flat 2002, 20/F, CEO Tower, 77 Wing Hong Street Lai Chi Kok,
Kowloon, Hong Kong, China.

Supplier / Manufacturer : Radiance Instruments Ltd.
Da Jing Village, Si Jiao Lou, Luo Yang Town, Hui Zhou City, China

Description of Sample(s) : Submitted sample(s) said to be
Product: SCALE
Brand Name: N/A
Model No.: TX-5800A
FCC ID: 2AI67-5800A

Date Samples Received : 2026-04-02

Date Tested : 2026-04-03 to 2026-04-08

Investigation Requested : Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.10: 2020 for FCC Certification.

Conclusions : The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Remarks : --

Test by : Susu


Dr.CHAN Kwok Hung, Brian
Authorized Signatory





Test Report

Date : 2026-04-20
No. : HMD26030017

Page 2 of 36

CONTENT:

Cover	Page 1 of 36
Content	Page 2 of 36
<u>1.0 General Details</u>	
1.1 Equipment Under Test [EUT] Description of EUT operation	Page 3 of 36
1.2 RF Module Details	Page 3 of 36
1.3 Antenna Details	Page 3 of 36
1.4 Date of Order	Page 3 of 36
1.5 Submitted Sample(s)	Page 3 of 36
1.6 Test Duration	Page 3 of 36
1.7 Country of Origin	Page 3 of 36
1.8 Channel List	Page 4 of 36
<u>2.0 Technical Details</u>	
2.1 Investigations Requested	Page 5 of 36
2.2 Test Standards and Results Summary	Page 5 of 36
<u>3.0 Test Results</u>	
3.1 Emission	Page 6-30 of 36
<u>Appendix A</u>	
List of Measurement Equipment	Page 31 of 36
<u>Appendix B</u>	
Photograph(s) of Product	Page 32-36 of 36

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 3 of 36

1.0 General Details

1.1 Equipment Under Test [EUT] Description of Sample(s)

Product: SCALE
Manufacturer: Radiance Instruments Ltd.
Da Jing Village, Si Jiao Lou, Luo Yang Town, Hui Zhou City, China
Brand Name: N/A
Model Number: TX-5800A
Rating: Scale TX-5800A: 6.0Vd.c.("AA"size battery x4)

1.1.1 Description of EUT Operation

The Equipment Under Test (EUT) is a SCALE. It is a transceiver operating at 2410MHz~2470MHz and the RF signal was modulated by IC.

1.2 RF Module Details

Module Model Number: N/A
Module FCC ID: N/A
Modulation: GFSK
Frequency Range: 2410-2470MHz

1.3 Antenna Details

Antenna Type: PCB antenna
Antenna Gain: 0.0dBi

1.4 Date of Order

2026-03-30

1.5 Submitted Sample(s):

1 Sample

1.6 Test Duration

2026-04-02 to 2026-04-08

1.7 Country of Origin

China

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 4 of 36

1.8 Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2410	42	2441
2	2411	43	2442
3	2412	44	2443
4	2413	45	2444
5	2414	46	2445
6	2415	47	2446
7	2416	48	2447
8	2417	...	...
9	2418	67	2466
...	2419	68	2467
...	...	69	2468
33	2432	70	2469
34	2433	71	2470
35	2434		
36	2435		
37	2436		
38	2437		
39	2438		
40	2439		
41	2440		

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 5 of 36

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 Regulations and ANSI C63.10: 2020 for FCC Certification.
The device was realized by special test program

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental & Harmonics Emissions	FCC 47CFR 15.249	ANSI C63.10: 2020	N/A	☒	☐	☐
Radiated Emissions	FCC 47CFR 15.209 FCC 47CFR 15.205	ANSI C63.10: 2020	N/A	☒	☐	☐
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.10: 2020	N/A	☐	☐	☒
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	☒	☐	☐
20dB Emission bandwidth	FCC 47CFR 15.215(c)	ANSI C63.10: 2020	N/A	☒	☐	☐

Note: N/A - Not Applicable

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taiipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 6 of 36

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions

Ambient temperature 25°C

Relative humidity 57%

Test Requirement:	FCC 47CFR 15.249 & FCC 47CFR 15.209
Test Method:	ANSI C63.10:2020
Test Date:	2026-04-07
Mode of Operation:	Tx mode

Test Method:

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

- * Semi-Anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd. with Registration Number: HK0001
Test Firm Registration Number: 367672

Test Report


Date : 2026-04-20
No. : HMD26030017

Page 7 of 36

Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW:	10kHz
	VBW:	30kHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold
30MHz – 1GHz (QP)	RBW:	120kHz
	VBW:	120kHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold
Above 1GHz (Pk & Av) (Other than Fundamental Emissions)	RBW:	1MHz
	VBW:	1MHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold

Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 8 of 36

Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [microvolts/meter]	Field Strength of Harmonics Emission [microvolts/meter]
902-928	50,000 [Quasi-Peak]	500 [Average]
2400-2483.5	50,000 [Average]	500 [Average]

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz

Calculated measurement uncertainty
(9kHz-30MHz): 2.0dB
(30MHz -1GHz): 4.9dB
(1GHz -6GHz): 4.02dB
(6GHz -26.5GHz): 4.03dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 9 of 36

Results of Tx mode (Lowest Frequency Channel-2410 MHz): Pass

Field Strength of Fundamental Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2410.00	94.2	-4.8	89.4	29,342.7	500,000	Vertical
2410.00	90.6	-4.7	85.9	19,611.0	500,000	Horizontal

Field Strength of Fundamental Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2410.00	83.0	-4.8	78.2	8,137.7	50,000	Vertical
2410.00	79.1	-4.7	74.4	5,224.0	50,000	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 10 of 36

Field Strength of Harmonics Emission 1-18 GHz Horizontal



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
1	4820.000	35.01	54.00	-18.99	Average	Horizontal
2	4820.000	48.76	74.00	-25.24	Peak	Horizontal
3	7230.000	43.99	54.00	-10.01	Average	Horizontal
4	7233.333	59.47	74.00	-14.53	Peak	Horizontal
5	14797.100	39.60	54.00	-14.40	Average	Horizontal
6	14797.100	53.72	74.00	-20.28	Peak	Horizontal
7	17236.230	42.07	54.00	-11.93	Average	Horizontal
8	17236.230	53.98	74.00	-20.02	Peak	Horizontal

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 11 of 36

Field Strength of Harmonics Emission 1-18GHz Vertical



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	4820.000	34.19	54.00	-19.81	Average	Vertical
2	4820.000	48.41	74.00	-25.59	Peak	Vertical
3	7230.000	44.35	54.00	-9.65	Average	Vertical
4	7230.000	59.48	74.00	-14.52	Peak	Vertical
5	15240.580	38.88	54.00	-15.12	Average	Vertical
6	15240.580	53.58	74.00	-20.42	Peak	Vertical
7	16349.280	53.99	74.00	-20.01	Peak	Vertical
8	16349.280	39.55	54.00	-14.45	Average	Vertical
9	17310.140	40.06	54.00	-13.94	Average	Vertical
10	17310.140	54.15	74.00	-19.85	Peak	Vertical

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 12 of 36

Results of Tx mode (Middle Frequency Channel- 2440MHz): Pass

Field Strength of Fundamental Emissions Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2440.00	93.5	-4.8	88.7	27,362.1	500,000	Vertical
2440.00	88.1	-4.7	83.4	14,791.1	500,000	Horizontal

Field Strength of Fundamental Emissions Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2440.00	81.9	-4.8	77.1	7,161.4	50,000	Vertical
2440.00	77.5	-4.7	72.8	4,365.2	50,000	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 13 of 36

Field Strength of Harmonics Emission 1-18GHz Horizontal



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	4880.000	35.44	54.00	-18.56	Average	Horizontal
2	4880.000	50.89	74.00	-23.11	Peak	Horizontal
3	7320.000	43.23	54.00	-10.77	Average	Horizontal
4	7320.000	57.66	74.00	-16.34	Peak	Horizontal
5	15659.420	39.85	54.00	-14.15	Average	Horizontal
6	15659.420	54.12	74.00	-19.88	Peak	Horizontal
7	17162.320	53.95	74.00	-20.05	Peak	Horizontal
8	17162.320	39.68	54.00	-14.32	Average	Horizontal

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 14 of 36

Field Strength of Harmonics Emission 1-18GHz Vertical



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over		
	MHz	dBuV/m	Line	Limit	Remark	Pol/Phase
1	4880.000	35.51	54.00	-18.49	Average	Vertical
2	4880.000	50.94	74.00	-23.06	Peak	Vertical
3	7320.000	43.39	54.00	-10.61	Average	Vertical
4	7320.000	57.60	74.00	-16.40	Peak	Vertical
5	15634.780	39.04	54.00	-14.96	Average	Vertical
6	15634.780	53.75	74.00	-20.25	Peak	Vertical
7	16866.670	53.71	74.00	-20.29	Peak	Vertical
8	16866.670	39.50	54.00	-14.50	Average	Vertical

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 15 of 36

Results of Tx mode (Highest Frequency Channel – 2470MHz): Pass

Field Strength of Fundamental Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength dB μ V/m	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2470.00	94.0	-4.8	89.2	28,906.8	500,000	Vertical
2470.00	89.3	-4.7	84.6	17,002.0	500,000	Horizontal

Field Strength of Fundamental Emissions						
Average Value						
Frequency MHz	Measured Level @3m dB μ V/m	Correction Factor dB μ V/m	Field Strength	Field Strength μ V/m	Limit @3m μ V/m	E-Field Polarity
2470.00	82.7	-4.8	77.9	7,807.3	50,000	Vertical
2470.00	77.3	-4.7	72.6	4,265.8	50,000	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 16 of 36

Field Strength of Harmonics Emission 1-18GHz Horizontal



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
1	4940.000	37.72	54.00	-16.28	Average	Horizontal
2	4940.000	51.31	74.00	-22.69	Peak	Horizontal
3	7410.000	42.44	54.00	-11.56	Average	Horizontal
4	7410.000	56.47	74.00	-17.53	Peak	Horizontal
5	15610.140	39.44	54.00	-14.56	Average	Horizontal
6	15610.140	53.68	74.00	-20.32	Peak	Horizontal
7	17113.040	39.72	54.00	-14.28	Average	Horizontal
8	17113.040	53.79	74.00	-20.21	Peak	Horizontal

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 17 of 36

Field Strength of Harmonics Emission 1-18GHz Vertical



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
1	4940.000	36.87	54.00	-17.13	Average	Vertical
2	4940.000	50.88	74.00	-23.12	Peak	Vertical
3	7410.000	42.27	54.00	-11.73	Average	Vertical
4	7410.000	56.72	74.00	-17.28	Peak	Vertical
5	15807.250	53.17	74.00	-20.83	Peak	Vertical
6	15807.250	39.28	54.00	-14.72	Average	Vertical
7	17359.420	39.86	54.00	-14.14	Average	Vertical
8	17359.420	53.63	74.00	-20.37	Peak	Vertical

Field Strength of Harmonics Emission Above 18GHz:

Emissions detected are more than 20 dB below the FCC Limits.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 18 of 36


Radiated Emissions Measurement:

Limit :

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Result: RF Radiated Emissions (Lowest)

Horizontal



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over		
	MHz	dBuV/m	Line	Limit	Remark	Pol/Phase
			dBuV/m	dB		
1	2396.283	39.97	54.00	-14.03	Average	Horizontal
2	2396.283	53.70	74.00	-20.30	Peak	Horizontal
3	2400.000	42.01	54.00	-11.99	Average	Horizontal
4	2400.000	55.39	74.00	-18.61	Peak	Horizontal

In restricted bands 2310-2390MHz, Emissions detected are more than 20 dB below the Limits.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 19 of 36

Vertical



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	2400.000	39.45	54.00	-14.55	Average	Vertical
2	2400.000	52.45	74.00	-21.55	Peak	Vertical

In restricted bands 2310-2390MHz, Emissions detected are more than 20 dB below the Limits.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 20 of 36

Result: RF Radiated Emissions (Highest)

Horizontal



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	2483.500	38.64	54.00	-15.36	Average	Horizontal
2	2483.500	52.81	74.00	-21.19	Peak	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 21 of 36

Vertical



Ambient Temperature : 24°C
Relative Humidity : 44%
Atmospheric Pressure: 101.7kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
			dBuV/m	dB		
1	2483.500	35.69	54.00	-18.31	Average	Vertical
2	2483.500	49.16	74.00	-24.84	Peak	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20

Page 22 of 36

No. : HMD26030017

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Remarks:

Calculated measurement uncertainty (9kHz-30MHz): 2.0dB / (30MHz – 1GHz): 4.9dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

Results of TX mode (9kHz – 30MHz): PASS

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report


Date : 2026-04-20

Page 23 of 36

No. : HMD26030017

Results of TX mode (30MHz – 1GHz)(2410MHz worst case): PASS

Horizontal



	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
1	31.510	29.45	40.00	-10.55	QP	Horizontal
2	36.254	26.26	40.00	-13.74	QP	Horizontal
3	224.519	23.69	46.00	-22.31	QP	Horizontal
4	325.596	27.38	46.00	-18.62	QP	Horizontal
5	401.839	30.53	46.00	-15.47	QP	Horizontal
6	719.200	36.56	46.00	-9.44	QP	Horizontal

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 24 of 36

Results of TX mode (30MHz – 1GHz) (2410MHz worst case): PASS

Vertical



	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	Line	Limit		
			dBuV/m	dB		
1	31.289	29.45	40.00	-10.55	QP	Vertical
2	39.162	24.99	40.00	-15.01	QP	Vertical
3	113.714	20.93	43.50	-22.57	QP	Vertical
4	297.224	27.00	46.00	-19.00	QP	Vertical
5	547.098	34.05	46.00	-11.95	QP	Vertical
6	694.417	36.78	46.00	-9.22	QP	Vertical

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2026-04-20
No. : HMD26030017

Page 25 of 36

3.1.2 AC Mains Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.10:2020
Test Date:	N/A
Mode of Operation:	TX mode
Test Voltage:	120V a.c. 60Hz

Ambient Temperature: 25°C Relative Humidity: 51% Atmospheric Pressure: 101 kPa


Test Method:

The test was performed in accordance with ANSI C63.10:2020, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Receiver Setting:

Bandw. = 9 kHz, Meas. Time= 10.0 ms, Step Width = 5.0kHz
 Detector = MaxPeak and CISPR AV

Test Setup:



Limits for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range [MHz]	Quasi-Peak Limits [dBμV]	Average [dBμV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Remarks:

Calculated measurement uncertainty (0.15MHz – 30MHz): 3.25dB

* Test Result: N/A



Test Report

Date : 2026-04-20

Page 26 of 36

No. : HMD26030017

3.1.3 Antenna Requirement

Ambient temperature 25°C

Relative humidity 57%

Test Requirements: § 15.203

Test Specification:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Results:

This is PCB antenna. There is no external antenna, the antenna gain =0.0dBi. User is unable to remove or changed the Antenna.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 27 of 36

3.1.4 20dB Bandwidth of Fundamental Emission

Ambient temperature 25°C

Relative humidity 57%

Test Requirement: FCC 47 CFR 15.249
Test Method: ANSI C63.10:2020
Test Date: 2026-04-03
Mode of Operation: Tx mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

The measurement bandwidth settings are RBW = 30 kHz
VBW = 100 kHz

Test Setup:

As Test Setup of clause 3.1.1 in this test report.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 28 of 36

Limits for 20dB Bandwidth of Fundamental Emission (Low Frequency Channel):

Frequency Range [MHz]	20dB Bandwidth [MHz]
2410.0	1.665



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 29 of 36

Limits for 20dB Bandwidth of Fundamental Emission (Middle Frequency Channel):

Frequency Range [MHz]	20dB Bandwidth [MHz]
2440.0	1.708



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 30 of 36

Limits for 20dB Bandwidth of Fundamental Emission (High Frequency Channel):

Frequency Range [MHz]	20dB Bandwidth [MHz]
2470.0	1.593



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



Test Report

Date : 2026-04-20
No. : HMD26030017

Page 31 of 36

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2024-04-18	2029-04-18
EM356	ANTENNA POSITIONING TOWER	ETS-LINDGREN	2171B	00150346	N/A	N/A
EM293	SPECTRUM ANALYZER	AGILENT TECHNOLOGIES	N9020A	MY50510152	2024-11-07	2026-11-07
EM363	SIGNAL ANALYZER(10HZ- 40GHZ)	R & S	FSV40	101231	2026-01-15	2028-01-15
EM299	BROADBAND HORN ANTENNA	ETS-LINDGREN	3115	00114120	2025-07-08	2028-07-08
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2025-07-14	2027-07-14
EM301	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-10	00130988	2025-07-14	2027-07-14
EM353	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2025-02-12	2027-02-12
EM355	BICONILOG ANTENNA	ETS-LINDGREN	3143B	00094856	2025-01-02	2027-01-02
EM200	DUAL CHANNEL POWER METER	R & S	NRVD	100592	2023-08-02	2026-08-02

Remarks:-

N/A Not Applicable or Not Available

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2026-04-20
No. : HMD26030017

Page 32 of 36

Appendix B

Photographs of EUT

View of the product



View of the product



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2026-04-20
No. : HMD26030017

Page 33 of 36

Photographs of EUT

View of the product



View of the product




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 34 of 36

Photographs of EUT

View of the product



View of the product




Test Report

Date : 2026-04-20
No. : HMD26030017

Page 35 of 36

Photographs of EUT

Measurement of Radiated Emission Test Set Up(9kHz – 30MHz)



Measurement of Radiated Emission Test Set Up(30MHz to 1000MHz)



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Test Report

Date : 2026-04-20
No. : HMD26030017

Page 36 of 36

Photographs of EUT

Measurement of Radiated Emission Test Set Up(Above 1000MHz)



******* End of Test Report *******

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by the Company as a result of this application for testing service (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. Subject to clause 3, the Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall be at liberty to disclose the testing-related documents and/or files anytime to any third-party accreditation and/or recognition bodies for audit or other related purposes. No liabilities whatsoever shall attach to the Company's act of disclosure.
4. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
5. The results in Report apply only to the sample as received and do not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
6. When a statement of conformity to a specification or standard is provided, the ILAC-G8 Guidance document (and/or IEC Guide 115 in the electrotechnical sector) will be adopted as a decision rule for the determination of conformity unless it is inherent in the requested specification or standard, or otherwise specified in the Report.
7. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
8. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
9. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
10. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
11. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
12. Issuance records of the Report are available on the internet at www.stc.group. Further enquiry of validity or verification of the Reports should be addressed to the Company.