



FCC Test Report (WIFI)

FCC ID : 2A16DX98PRO

Applicant : SHENZHEN AMEDIATECH TECHNOLOGY CO., LTD
3F, Tower A, Building A, Minsheng Industrial Park, Longhua Road,
Longhua New Area, Shenzhen, China.

Sample Description

Product Name : Smart TV BOX

Model No. : X98PRO

Serial No. : X98

Trademark : N/A

Receipt Date : 2016-12-05

Test Date : 2016-12-06 to 2016-12-12

Issue Date : 2016-12-13

Test Standard(s) : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Conclusions : PASSED*

*In the configuration tested, the EUT complied with the standards specified above.

Test/Witness Engineer :

Jason Deng

Approved & Authorized :

Frank Zhang

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



Contents

CONTENTS.....	2
1. GENERAL INFORMATION.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test).....	4
1.3 Description of Test Mode.....	5
1.4 Test Instruments List.....	6
1.5 Laboratory Location.....	7
2. TEST SUMMARY.....	8
3. ANTENNA REQUIREMENT.....	9
3.1. Standard Requirement.....	9
3.2. Antenna Connected Construction.....	9
4. CONDUCTED EMISSION TEST.....	10
4.1 Test Standard and Limit.....	10
4.2 Test Setup.....	10
4.3 Test Procedure.....	10
4.4 Test Data.....	11
5. PEAK OUTPUT POWER TEST.....	14
5.1. Test Standard and Limit.....	14
5.2. Test Setup.....	14
5.3. Test Procedure.....	14
5.4. Test Data.....	14
6. OCCUPY BANDWIDTH TEST.....	15
6.1. Test Standard and Limit.....	15
6.2. Test Setup.....	15
6.3. Test Procedure.....	15
6.4. Test Data.....	15
7. POWER SPECTRAL DENSITY TEST.....	22
7.1. Test Standard and Limit.....	22
7.2. Test Setup.....	22
7.3. Test Procedure.....	22
7.4. Test Data.....	22
8. BAND EDGE REQUIREMENT (CONDUCTED EMISSION METHOD).....	31
8.1. Test Standard and Limit.....	31
8.2. Test Setup.....	31
8.3. Test Procedure.....	31
8.4. Test Data.....	31
9. BAND EDGE REQUIREMENT (RADIATED EMISSION METHOD).....	34



ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 3 of 71

9.1.	Test Standard and Limit.....	34
9.2.	Test Setup.....	34
9.3.	Test Procedure.....	35
9.4.	Test Data.....	36
10.	SPURIOUS EMISSION (RADIATED EMISSION METHOD).....	52
11.1.	Test Standard and Limit.....	52
11.2.	Test Setup.....	52
11.3.	Test Procedure.....	53
11.4.	Test Data.....	53
11	SPURIOUS EMISSION (CONDUCTED METHOD).....	65
11.1	Test Standard and Limit.....	65
11.2	Test Setup.....	65
11.3	Test Procedure.....	65
11.4	Test Data.....	65



1. General Information

1.1 Client Information

Applicant	:	SHENZHEN AMEDIATECH TECHNOLOGY CO., LTD
Address	:	3F, Tower A, Building A, Minsheng Industrial Park, Longhua Road, Longhua New Area, Shenzhen, China.
Manufacturer	:	SHENZHEN AMEDIATECH TECHNOLOGY CO., LTD
Address	:	3F, Tower A, Building A, Minsheng Industrial Park, Longhua Road, Longhua New Area, Shenzhen, China.

1.2 General Description of EUT (Equipment Under Test)

Product Name	:	Smart TV BOX
Models No.	:	X98PRO, X98
Difference	:	Only differ on appearance and name
Product Description	:	Operation Frequency: 2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)/ 802.11n(H40))
	:	Transfer Rate: 802.11b: 1/ 2/ 5.5/ 11Mbps 802.11g: 6/ 9/ 12/ 18/ 24/ 36/, 48/54 Mbps 802.11n: Up to 300Mbps
	:	Number of Channel: 11 for 802.11b/802.11g/ 802.11n(H20)/ 802.11n(H40)
	:	Channel separation 5MHz
	:	Modulation Technology: 802.11b:DSSS 802.11g/ 802.11n:OFDM
	:	Antenna Type: Integral Antenna
	:	Antenna Gain: 2.0 dBi
Power Supply	:	DC 5V powered by power adapter

Note:

(1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(2) Channel List:



CH 01~CH 11 for 802.11b/ g/ n(20M)

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01		05	2432	09	2452
02		06	2437	10	
03	2422	07	2442	11	
04	2427	08	2447		

1.3 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

Test Mode	Description
Transmitting mode	Keep the EUT in continuous transmitting with modulation

Remark: The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11b	1Mbps



802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5 Mbps
Final Test Mode:	
According to ANSI C63.4 standards, the test results are both the “worst case” and “worst setup” 1Mbps for 802.11b, 6Mbps for 802.11g, 6.5Mbps for 802.11n(H20) and 13.5 Mbps for 802.11n(H40). Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.	

1.4 Test Instruments List

	Test Equipment	Manufacturer	Model No.	Cal. Date	Cal. Due date
1	Bilog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	May 22, 2016	May 21, 2017
2	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	May 27, 2016	May 26, 2017
3	Coaxial Cable	N/A	N/A	Mar. 28, 2016	Mar. 27, 2017
4	Coaxial Cable	N/A	N/A	Mar. 29, 2016	Mar. 29, 2017
5	Coaxial cable	N/A	N/A	Mar. 29, 2016	Mar. 29, 2017
6	Coaxial Cable	N/A	N/A	Mar. 29, 2016	Mar. 29, 2017
7	Coaxial Cable	N/A	N/A	Mar. 29, 2016	Mar. 29, 2017
8	Amplifier (10kHz-1.3GHz)	HP	8447D	Mar. 29, 2016	Mar. 29, 2017
9	Amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	Jun. 06, 2016	Mar. 29, 2017
10	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	Mar. 29, 2016	Mar. 29, 2017
11	Horn Antenna	ETS-LINDGREN	3160	Mar. 27, 2016	Mar. 27, 2017
12	Positioning Controller	UC	UC3000	N/A	N/A
13	Spectrum analyzer 9kHz-30GHz	Rohde & Schwarz	FSP	May 26, 2016	May 27, 2017
14	EMI Test Receiver	Rohde & Schwarz	ESPI	Mar. 29, 2016	Mar. 30, 2017
15	Loop antenna	Laplace instrument	RF300	May 22,, 2016	May 23, 2017



ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 7 of 71

16	Universal radio communication tester	Rhode & Schwarz	CMU200	May 26, 2016	May 27, 2017
17	Signal Analyzer	Rohde & Schwarz	FSIQ3	May 26, 2016	May 27, 2017
18	L.I.S.N.#1	Rohde & Schwarz	NSLK8126	May 26, 2016	May 27, 2017
19	L.I.S.N.#2	Rohde & Schwarz	ENV216	May 26, 2016	May 27, 2017
20	Power Meter	Anritsu	ML2495A	May 26, 2016	May 27, 2017
21	Power sensor	Anritsu	ML2491A	May 26, 2016	May 27, 2017

1.5 Laboratory Location

Shenzhen TOBY technology Co., Ltd

Address: 1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467,
Xixiang, Bao'an, Shenzhen, Guangdong, 518057, China

At the time of testing, the Laboratory is accredited. It is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562 7.

Tel:0086-755-26509301 Fax: 0086-755-26509195



2. Test Summary

Standard Section	Test Item	Judgment
15.203/15.247(c)	Antenna Requirement	PASSED
15.207	Conducted Emission	PASSED
15.247(b)(3)	Conducted Peak Output Power	PASSED
15.247(a)(2)	99% OBW and 6dB Emission Bandwidth	PASSED
15.247(e)	Power Spectral Density	PASSED
15.247(d)	Band Edge	PASSED
15.205/15.209	Spurious Emission	PASSED



3. Antenna Requirement

3.1. Standard Requirement

3.1.1 Test standard

FCC Part15 Section 15.203 /247(c)

3.1.2 Requirement

1) 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

2) 15.247(c) (1)(i) requirement:

Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2. Antenna Connected Construction

The antenna is an integral antenna which permanently attached, and the best case gain of the antenna is 2.0dBi. It complies with the standard requirement.

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part15 Section 15.207


4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequencies.

4.2 Test Setup



4.3 Test Procedure

- 1) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50 \Omega / 50 \mu\text{H} + 5 \Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.

The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal



ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

4.4 Test Data

Please refer to the following pages




ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 12 of 71

Conducted Emission Test Data

EUT: Smart TV BOX M/N: X98PRO
Operating Condition: WIFI mode
Test Site: Shielded room
Operator: Jason
Test Specification: AC 120V/60Hz
Polarization: Line
Note: Tem:25°C Hum:50%



Item	Freq MHz	Read Level dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.166	44.58	0.03	-9.52	0.10	54.24	65.16	-10.92	QP
2	0.166	37.33	0.03	-9.52	0.10	46.98	55.16	-8.18	Average
3	0.213	41.80	0.03	-9.52	0.10	51.45	63.10	-11.65	QP
4	0.213	33.66	0.03	-9.52	0.10	43.31	53.10	-9.79	Average
5	0.280	39.56	0.03	-9.56	0.10	49.25	60.81	-11.56	Peak
6	0.535	36.87	0.03	-9.58	0.10	46.58	56.00	-9.42	QP
7	0.535	30.61	0.03	-9.58	0.10	40.32	46.00	-5.68	Average
8	0.871	34.32	0.04	-9.62	0.10	44.08	56.00	-11.92	Peak
9	2.622	32.33	0.06	-9.76	0.11	42.26	56.00	-13.74	Peak

Remark: Level = Read Level + LISN Factor - Preamp Factor + Cable Loss




ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 13 of 71

Conducted Emission Test Data

EUT: Smart TV BOX M/N: X98PRO
Operating Condition: WIFI mode
Test Site: Shielded room
Operator: Jason
Test Specification: AC 120V/60Hz
Polarization: Neutral
Note: Tem:25°C Hum:50%



Item	Freq MHz	Read Level dBuV	LISN Factor dB	Preamp Factor dB	Cable Loss dB	Level dBuV	Limit dBuV	Margin dBuV	Remark
1	0.159	45.41	0.03	-9.52	0.10	55.06	65.52	-10.46	QP
2	0.159	36.33	0.03	-9.52	0.10	45.98	55.52	-9.54	Average
3	0.214	41.55	0.03	-9.52	0.10	51.20	63.05	-11.85	QP
4	0.214	34.52	0.03	-9.52	0.10	44.17	53.05	-8.88	Average
5	0.538	38.62	0.03	-9.58	0.10	48.33	56.00	-7.67	QP
6	0.538	27.53	0.03	-9.58	0.10	37.24	46.00	-8.76	Average
7	0.871	33.34	0.04	-9.62	0.10	43.10	56.00	-12.90	Peak
8	2.894	32.23	0.06	-9.76	0.11	42.16	56.00	-13.84	Peak
9	17.475	26.96	0.28	-9.82	0.30	37.36	60.00	-22.64	Peak

Remark: Level = Read Level + LISN Factor - Preamp Factor + Cable Loss



5. Peak Output Power Test

5.1. Test Standard and Limit


5.1.1 Test Standard

FCC Part15 C Section 15.247 (b)(3)

5.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

5.2. Test Setup



5.3. Test Procedure

- (1) The EUT was directly connected to peak power meter and antenna output port as show in the block diagram above.
- (2) Measure out each mode and each bands peak output power of EUT.
- (3) The EUT was set to continuously transmitting in the max power during the test.

5.4. Test Data

Test CH	Maximum Conducted Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	12.51	11.25	11.43	10.24	30.00dBm	PASSED
Middle	12.46	11.42	11.25	10.21		PASSED
Highest	12.33	11.37	11.19	10.32		PASSED
Remark: Test plot as follows						



6. Occupy Bandwidth Test

6.1. Test Standard and Limit


6.1.1 Test Standard

FCC Part15 C Section 15.247 (a)(2)

6.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range
Bandwidth	>500 kHz (6dB bandwidth)	2400~2483.5(MHz)

6.2. Test Setup



6.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (3) Spectrum Setting:

Bandwidth: RBW=100 kHz, VBW=300 kHz, detector= Peak

6.4. Test Data

Test CH	6dB Occupy Bandwidth (MHz)				Limit (kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	10.11	16.39	17.60	35.83	>=500 kHz	PASSED
Middle	10.08	16.41	17.62	35.76		PASSED
Highest	10.08	16.41	17.61	36.08		PASSED


Remark: Test plot as follows



ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 16 of 71







ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 17 of 71






ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 18 of 71






ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 19 of 71







ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 20 of 71






ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 21 of 71





7. Power Spectral Density Test

7.1. Test Standard and Limit


7.1.1 Test Standard

FCC Part15 C Section 15.247 (e)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

7.2. Test Setup



7.3. Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Measure the spectral power density the spectrum analyzer was set to Resolution Bandwidth=100 kHz, and Video Bandwidth≥300 kHz, Detector: Peak, Span to 5%~30% greater than EBW, Sweep time auto.
- (3) Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a BWCF=-15.2 dB.

7.4. Test Data

Test CH	Power Spectral Density (dBm)				Limit (dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	-24.041	-24.400	-22.864	-28.143	8	Passed
Middle	-22.533	-24.709	-26.029	-28.103		Passed
Highest	-22.831	-24.302	-24.020	-28.750		Passed


Remark: Test plot as follows



ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 23 of 71





ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 24 of 71






ATA Testing Technology Service Co., Ltd.


Report No.: ATA161212012F

Page: 25 of 71





Page: 26 of 71






ATA Testing Technology Service Co., Ltd.


Report No.: ATA161212012F

Page: 27 of 71





Page: 28 of 71






ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 29 of 71





ATA Testing Technology Service Co., Ltd.

Report No.: ATA161212012F

Page: 30 of 71

