Prüfbericht-Nr.: *Test report No.:*	**50055846 002**	**Auftrags-Nr.:** *Order No.:*	164069063	Seite 1 von 31 *Page 1 of 31*
Kunden-Referenz-Nr.: *Client reference No.:*	N/A	**Auftragsdatum:** *Order date.:*	14.07.2016	
Auftraggeber: *Client:*	**ContextMedia LLC** 330 N. Wabash Ave STE 2500, Chicago, Illinois United States.			
Prüfgegenstand: *Test item:*	13.3" Tablet			
Bezeichnung / Typ-Nr.: *Identification / Type No.:*	P-TAB-104-ELC-XX (XX equals to 00, 01, 02, 03...99) (ContextMedia Health)			
Auftrags-Inhalt: *Order content:*	FCC and IC approval			
Prüfgrundlage: *Test specification:*	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart C Section 15.207 CFR47 FCC Part 15: Subpart C Section 15.209 RSS-247 Issue 1 May 2015 RSS-Gen Issue 4 November 2014			

Wareneingangsdatum: *Date of receipt:*	21.07.2016	Please refer to photo documents
Prüfmuster-Nr.: *Test sample No.:*	A000399543-002	
Prüfzeitraum: *Testing period:*	27.07.2016 - 31.08.2016	
Ort der Prüfung: *Place of testing:*	Accurate Technology Co., Ltd.	
Prüflaboratorium: *Testing laboratory:*	TÜV Rheinland (Shenzhen) Co., Ltd.	
Prüfergebnis*: *Test result*:*	Pass	

geprüft von / *tested by:*			**kontrolliert von** / *reviewed by:*		
18.09.2016	Andy Yan / Project Manager		18.09.2016	Owen Tian / Technical Certifier	
Datum *Date*	**Name/Stellung** *Name/Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name/Stellung** *Name/Position*	**Unterschrift** *Signature*

Sonstiges / *Other:*

FCC ID: 2AI6X-PTABELC
IC: 21722-PTABELC HVIN: P-TAB-104-ELC-01, P-TAB-104-ELC-02, P-TAB-104-ELC-03
All the Identification no. are identical in the hardware and electronic aspects with each other.
All the HVIN no. are identical in the hardware and electronic aspects with each other, the difference is only color apperance.

Zustand des Prüfgegenstandes bei Anlieferung: *Condition of the test item at delivery:*	Prüfmuster vollständig und unbeschädigt *Test item complete and undamaged:*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	1 = very good	2 = good	3 = satisfactory	4 = sufficient	5 = poor
	P(ass) = passed a.m. test specifications(s)		F(ail) = failed a.m. test specifications(s)	N/A = not applicable	N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

Test Summary

5.1.1 ANTENNA REQUIREMENT
RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER
RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY
RESULT: Pass

5.1.4 6DB BANDWIDTH
RESULT: Pass

5.1.5 99% BANDWIDTH
RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH
RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION
RESULT: Pass

5.1.8 20DB BANDWIDTH
RESULT: Pass

5.1.9 CARRIER FREQUENCY SEPARATION
RESULT: Pass

5.1.10 NUMBER OF HOPPING FREQUENCY
RESULT: Pass

5.1.11 TIME OF OCCUPANCY
RESULT: Pass

5.1.12 CONDUCTED EMISSION ON AC MAINS
RESULT: Pass

Contents

1 GENERAL REMARKS 4
1.1 COMPLEMENTARY MATERIALS 4
2 TEST SITES 4
2.1 TEST FACILITIES 4
2.2 LIST OF TEST AND MEASUREMENT INSTRUMENTS 5
2.3 TRACEABILITY 6
2.4 CALIBRATION 6
2.5 MEASUREMENT UNCERTAINTY 6
2.6 LOCATION OF ORIGINAL DATA 6
2.7 STATUS OF FACILITY USED FOR TESTING 6
3 GENERAL PRODUCT INFORMATION 7
3.1 PRODUCT FUNCTION AND INTENDED USE 7
3.2 RATINGS AND SYSTEM DETAILS 7
3.3 INDEPENDENT OPERATION MODES 10
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 10
3.5 SUBMITTED DOCUMENTS 10
4 TEST SET-UP AND OPERATION MODES 11
4.1 PRINCIPLE OF CONFIGURATION SELECTION 11
4.2 TEST OPERATION AND TEST SOFTWARE 11
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 11
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 11
4.5 TEST SETUP DIAGRAM 12
5 TEST RESULTS 14
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 14
5.1.1 Antenna Requirement 14
5.1.2 Maximum Peak Conducted Output Power 15
5.1.3 Conducted Power Spectral Density 16
5.1.4 6dB Bandwidth 17
5.1.5 99% Bandwidth 18
5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth 19
5.1.7 Radiated Spurious Emission 20
5.1.8 20dB Bandwidth 21
5.1.9 Carrier Frequency Separation 22
5.1.10 Number of Hopping Frequency 23
5.1.11 Time of Occupancy 24
5.1.12 Conducted Emission on AC Mains 26
6 SAFETY HUMAN EXPOSURE 27
6.1 RADIO FREQUENCY EXPOSURE COMPLIANCE 27
6.1.1 Electromagnetic Fields 27
7 PHOTOGRAPHS OF THE TEST SET-UP 28
8 LIST OF TABLES 31
9 LIST OF PHOTOGRAPHS 31

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix B: Test Results of Bluetooth 4.1 (Dual mode) of Conducted Testing

Appendix C: Test Results of Bluetooth 4.1 (Dual mode) of AC Conducted and Radiated Emission

2 Test Sites

2.1 Test Facilities

Accurate Technology Co., Ltd.
F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan Shenzhen, 518057, P.R. China

FCC Registration No.: 752051

Test site Industry Canada No.: 5077A-2

The tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Accurate Technology Co., Ltd.

Radio Spectrum Test				
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Until**
Spectrum Analyzer	R&S	ESPI3	100396/003	09.01.2017
Spurious Emission				
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Until**
Spectrum Analyzer	R&S	FSV40	101495	09.01.2017
Test Receiver	R&S	ESCS30	100307	09.01.2017
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	14.01.2017
Loop Antenna	Schwarzbeck	FMZB1516	1516131	14.01.2017
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	14.01.2017
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	14.01.2017
RF Switching Unit+PreAMP	Compliance Direction	RSU-M2	38322	09.01.2017
Pre-Amplifier	R&S	CBLU11835 40-01	3791	09.01.2017
50 Coaxial Switch	Anritsu Corp	MP59B	6200506474	09.01.2017
RF Coaxial Cable	SUHNER	N-3m	No.8	09.01.2017
RF Coaxial Cable	RESENBERGER	N-3.5m	No.9	09.01.2017
RF Coaxial Cable	SUHNER	N-6m	No.10	09.01.2017
RF Coaxial Cable	RESENBERGER	N-12m	No.11	09.01.2017
50_ Coaxial Switch	Anritsu Corp	MP59B	6200283933	09.01.2017
Conducted Emission on AC Mains				
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Until**
Test Receiver	R&S	ESCS30	100307	09.01.2017
L.I.S.N.	R&S	NLSK8126	8126431	09.01.2017
50Ω Coaxial Switch	Anritsu	MP59B	6200283933	09.01.2017

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basics using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Item		**Extended Uncertainty**
Conducted Emission		± 3.0 dB
Radiated Emission (9kHz-30MHz)	Field strength (dBμV/m)	U=3.08dB, k=2, σ=95%
Radiated Emission (30-1000MHz)	Field strength (dBμV/m)	U=4.42dB, k=2, σ=95%
Radiated Emission (above 1000MHz)	Field strength (dBμV/m)	U=4.06dB, k=2, σ=95%
Occupied Channel Bandwidth		±5.0 %
RF Output Power, Conducted		±1.5 dB
Power Spectral Density, Conducted		±3.0 dB
Unwanted Emission, Conducted		±3.0 dB
Duty Cycle		±5.0 %

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Accurate Technology Co., Ltd. Test facility located at F1, Bldg. A, Changyuan New Material Port Keyuan Rd., Science & Industry Park, Nanshan Shenzhen, 518057, P.R. China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a 13.3" Tablet which supports Bluetooth (dual mode) and Wi-Fi 802.11 a/b/g/n/ac wireless technology. This report is only for Bluetooth function of DTS and DSS. Other functions with different technologies are reported in the related reports.

According to the declaration of the applicant, the electrical circuit design, PCB layout and components used are identical for all models, only the model No. and appearance are different.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

Technical Specification	Value
Kind of Equipment	13.3" Tablet
Type Designation	P-TAB-104-ELC-XX (XX equals to 00, 01, 02, 03...99)
Trade Mark	ContextMedia Health
FCC ID	2AI6X-PTABELC
IC	21722-PTABELC
HVIN	P-TAB-104-ELC-01, P-TAB-104-ELC-02, P-TAB-104-ELC-03
Operating Frequency	2402 - 2480 MHz
Operating Temperature Range	0 °C ~ +40 °C
Operating Voltage	DC 5.0 V from AC/DC Adapter
Testing Voltage	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
AC/DC Adapter	Model: NBS18C050250VU Input: AC 100-240V~50/60Hz, 0.6A Output: DC 5.0V~2500mA
Type of Modulation	GFSK, π/4DQPSK, 8DPSK
Channel Number	BDR & EDR mode:79 channels; Low Energy mode:40 channels
Channel Separation	BDR & EDR mode:1MHz; Low Energy mode:2MHz
Wireless Technology	Bluetooth 4.0 (Dual mode)
Antenna Type	Integral Antenna
Max. Antenna Gain	2.00 dBi

Table 3: RF Channel and Frequency of Bluetooth

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	**2402.00**	20	2422.00	40	2442.00	60	2462.00
01	2403.00	21	2423.00	41	2443.00	61	2463.00
02	2404.00	22	2424.00	42	2444.00	62	2464.00
03	2405.00	23	2425.00	43	2445.00	63	2465.00
04	2406.00	24	2426.00	44	2446.00	64	2466.00
05	2407.00	25	2427.00	45	2447.00	65	2467.00
06	2408.00	26	2428.00	46	2448.00	66	2468.00
07	2409.00	27	2429.00	47	2449.00	67	2469.00
08	2410.00	28	2430.00	48	2450.00	68	2470.00
09	2411.00	29	2431.00	49	2451.00	69	2471.00
10	2412.00	30	2432.00	50	2452.00	70	2472.00
11	2413.00	31	2433.00	51	2453.00	71	2473.00
12	2414.00	32	2434.00	52	2454.00	72	2474.00
13	2415.00	33	2435.00	53	2455.00	73	2475.00
14	2416.00	34	2436.00	54	2456.00	74	2476.00
15	2417.00	35	2437.00	55	2457.00	75	2477.00
16	2418.00	36	2438.00	56	2458.00	76	2478.00
17	2419.00	37	2439.00	57	2459.00	77	2479.00
18	2420.00	38	2440.00	58	2460.00	**78**	**2480.00**
19	2421.00	**39**	**2441.00**	59	2461.00	--	--

Table 4: RF Channel and Frequency of Bluetooth Low Energy

RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)	RF Channel	Frequency (MHz)
00	**2402.00**	10	2422.00	20	2442.00	30	2462.00
01	2404.00	11	2424.00	21	2444.00	31	2464.00
02	2406.00	12	2426.00	22	2446.00	32	2466.00
03	2408.00	13	2428.00	23	2448.00	33	2468.00
04	2410.00	14	2430.00	24	2450.00	34	2470.00
05	2412.00	15	2432.00	25	2452.00	35	2472.00
06	2414.00	16	2434.00	26	2454.00	36	2474.00
07	2416.00	17	2436.00	27	2456.00	37	2476.00
08	2418.00	18	2438.00	28	2458.00	38	2478.00
09	2420.00	**19**	**2440.00**	29	2460.00	**39**	**2480.00**

Table 5: Frequency Hopping Information

Technical Specification	Description
Hopping Range	Hereby we declare that the frequency range of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V2.1 + EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73, 07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56, 69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43, 15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings. Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

3.3 Independent Operation Modes

The basic operation modes are:

A. On
   1. Bluetooth transmitting mode (BDR & EDR mode)
      a) Low Channel
      b) Middle Channel
      c) High Channel
   2. Bluetooth transmitting mode (Low Energy mode)
      a) Low Channel
      b) Middle Channel
      c) High Channel

B. On, Transmitting on Hopping channel

C. On, Bluetooth connecting mode

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- Block Diagram
- Schematics
- Technical Description
- FCC/IC Label and Location Info
- Photo Document
- User Manual

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All testing were performed according to the procedures in ANSI C63.10: 2013.

4.3 Special Accessories and Auxiliary Equipment

Table 6: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Adapter	Mass Power	NBS18C050250VU	N/A	Input: 100-240V~, 50/60Hz, 0.6A Output: DC 5.0V, 2.5A
Notebook PC	Lenovo	ThinkPad X240	N/A	N/A
Printer	HP	HP laserjet 1015	CNFG030424	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)



Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



Diagram of Measurement Configuration for Mains Conduction Measurement



Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Pass**

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 8.3

According to the manufacturer declared, the EUT has an integral antenna, the directional gain of antenna is 2.0dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(b)(1)&(3)
		RSS-247 Clause 5.4(2)&(4)
Basic standard	:	ANSI C63.10: 2013
Limits	:	FHSS < 0.125 Watts, DSSS < 1.0 Watts
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	27.07.2016 ~ 29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.1, A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 7: Test Result of Maximum Peak Conducted Output Power

Test Mode	Channel Frequency (MHz)	Measured Peak Output Power		Limit (W)
		(dBm)	(W)	
BDR	2402	5.07	0.00321	< 0.125
	2441	8.25	0.00668	
	2480	6.17	0.00414	
EDR	2402	3.64	0.00231	< 0.125
	2441	7.29	0.00536	
	2480	4.99	0.00316	
Low Energy	2402	-1.35	0.00073	< 1.0
	2440	2.30	0.00170	
	2480	1.54	0.00143	
Maximum Measured Value		8.25	0.00668	/

Note: The cable loss 2.0 dB is taken into account in results.

This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix B.

5.1.3 Conducted Power Spectral Density

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(e)
		RSS-247 Clause 5.2(2)
Basic standard	:	ANSI C63.10: 2013
Limits	:	8 dBm/3kHz
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	27.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 8: Test Result of Power Spectral Density, Low Energy

Test Mode	Test Channel (MHz)	Power Spectrum Density(dBm/3kHz)	Limit (dBm/3kHz)
Low Energy	2402	-15.63	< 8.0
	2440	-11.97	
	2480	-12.66	
Maximum Measured Value		-11.97	

Note: The cable loss 2.0 dB is taken into account in results.

This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix B.

5.1.4 6dB Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(a)(2)
		RSS-247 Clause 5.2(1)
Basic standard	:	ANSI C63.10: 2013
Limits	:	More than 500 KHz
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	27.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 9: Test Result of 6dB Bandwidth, Low Energy

Test Mode	Test Channel (MHz)	-6dB Bandwidth (kHz)	Limit (kHz)
Low Energy	2402	738.10	> 500
	2440	738.10	
	2480	738.10	
Minimum Measured Value		738.10	

For the measurement records, refer to the appendix B.

5.1.5 99% Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	RSS-Gen Clause 6.6
Basic standard	:	ANSI C63.10: 2013
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	27.07.2016 ~ 29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.1, A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 10: Test Result of 99% Bandwidth

Test Mode	Channel Frequency (MHz)	99% Bandwidth (kHz)	Limit (kHz)
BDR	2402	994.2	/
	2441	998.6	
	2480	998.6	
EDR	2402	1228.7	/
	2441	1228.7	
	2480	1228.7	
Low Energy	2402	1081.0	/
	2440	1085.4	
	2480	1085.4	
Maximum Measured Value		1228.7	/

For the measurement records, refer to the appendix B.

5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(d)
		RSS-247 Clause 5.5
Basic standard	:	ANSI C63.10: 2013
Limits	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power);
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	27.07.2016 ~ 29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.1, A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to following test plot, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.7 Radiated Spurious Emission

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205
		RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d)
		RSS-Gen Table 4 & Table 5
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	09.08.2016 ~ 31.08.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.1, A.2
Test channel	:	Low / Middle / High
Ambient temperature	:	23 ℃
Relative humidity	:	48 %
Atmospheric pressure	:	101 kPa

Remark:
During the pretest the EUT was rotated through three orthogonal axes to determine the attitude that maximizes the emissions. After that the EUT was manually handled to find the orientation that has the maximum emission, which is the orientation shown in the test set-up photos.

Pre-test the EUT in continuous transmitting with different data packet. Compliance test in continuous transmitting mode with BDR mode (DH5) as the worst case was found.

Testing was carried out within frequency range 9kHz to the tenth harmonics.

For the measurement records, refer to the appendix C.

5.1.8 20dB Bandwidth

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(a)(1)
		RSS-247 Clause 5.1(1)
Basic standard	:	ANSI C63.10: 2013
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	A.1
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 11: Test Result of 20dB Bandwidth

Test Mode	Channel Frequency (MHz)	20dB Bandwidth (kHz)	2/3 of 20dB Bandwidth (kHz)	Limit (MHz)
BDR	2402	1037.7	691.8	Within the Frequency band 2400~2483.5MHz
	2441	1037.6	691.7	
	2480	1037.6	691.7	
EDR	2402	1328.5	885.7	
	2441	1328.5	885.7	
	2480	1328.5	885.7	
Maximum Measured Value		1328.5	885.7	

For the measurement records, refer to the appendix B.

5.1.9 Carrier Frequency Separation

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.247(a)(1)
		RSS-247 Clause 5.1(2)
Basic standard	:	ANSI C63.10: 2013
Limits	:	≥ 25kHz or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	B
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 12: Test Result of Carrier Frequency Separation

Channel	Channel Frequency (MHz)	Measured Channel Separation (KHz)	Limit (kHz)	Result
Low Channel	2402	1002.9	≥ 25kHz or 2/3 of 20dB bandwidth	Pass
Adjacency Channel	2403			
Middle Channel	2441	1002.9		Pass
Adjacency Channel	2442			
High Channel	2480	1002.9		Pass
Adjacency Channel	2479			

Note:

The limit is maximum 2/3 of the 20 dB bandwidth: 885.7 KHz.

For the measurement records, refer to the appendix B.

5.1.10 Number of Hopping Frequency

RESULT: **Pass**

Test Specification

Test standard	:	FCC part 15.247(a)(1)(iii)
		RSS-247 Clause 5.1(4)
Basic standard	:	ANSI C63.10: 2013
Limits	:	≥ 15 non-overlapping channels
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	B
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 13: Test Result of Number of Hopping Frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
2402 to 2480 MHz	79	≥15	Pass

For the measurement records, refer to the appendix B.

5.1.11 Time of Occupancy

RESULT: **Pass**

Test Specification

Test standard	:	FCC part 15.247(a)(1)(iii)
		RSS-247 Clause 5.1(4)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 0.4s
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	29.07.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	B
Test channel	:	Low / Middle / High
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Table 14: Test Result of Time of Occupancy

Test Mode	Test Channel	Data Packet	Pulse width (ms)	Measured Dwell time(s)	Limit (s)
BDR mode	2402	DH1	0.442	0.141	< 0.4s
		DH3	1.703	0.272	
		DH5	2.986	0.319	
	2441	DH1	0.442	0.141	
		DH3	1.688	0.270	
		DH5	2.964	0.316	
	2480	DH1	0.442	0.141	
		DH3	1.688	0.270	
		DH5	2.964	0.316	
EDR mode	2402	3DH1	0.442	0.141	
		3DH3	1.703	0.272	
		3DH5	2.986	0.319	
	2441	3DH1	0.442	0.141	
		3DH3	1.703	0.272	
		3DH5	2.986	0.319	
	2480	3DH1	0.442	0.141	
		3DH3	1.688	0.270	
		3DH5	2.986	0.319	
Maximum Measured Value			2.986	0.319	

Note:

Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 x 79 (channel) = 31.6 seconds

This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix B.

5.1.12 Conducted Emission on AC Mains

RESULT: **Pass**

Test Specification

Test standard	:	FCC Part 15.207(a)
		RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207(a)
		RSS-Gen Table 3
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	28.08.2016
Input voltage	:	DC 5.0 V from AC/DC Adapter with input 120V/60Hz
Operation mode	:	C
Earthing	:	Not connected
Ambient temperature	:	25 ℃
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix C.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: **Pass**

Test Specification

Test standard : CFR47 FCC Part 2.1093
RSS-102 Issue 5 March 2015

Measurement Record:
For the measurement records, refer to the sar report with report no.: 50055846 005

7 Photographs of the Test Set-Up

Photograph 1: Set-up for Radiated Spurious Emission (9kHz ~ 30MHz)



Photograph 2: Set-up for Radiated Spurious Emission (30MHz~1GHz)



Photograph 3: Set-up for Radiated Spurious Emission (1GHz ~ 18GHz)



Photograph 4: Set-up for Radiated Spurious Emission above 18GHz



Photograph 5: Set-up for Conducted Emission on AC Mains

8 List of Tables

Table 1: List of Test and Measurement Equipment 5
Table 2: Technical Specification of EUT 7
Table 3: RF Channel and Frequency of Bluetooth 8
Table 4: RF Channel and Frequency of Bluetooth Low Energy 8
Table 5: Frequency Hopping Information 9
Table 6: List of Accessories and Auxiliary Equipment 11
Table 7: Test Result of Maximum Peak Conducted Output Power 15
Table 8: Test Result of Power Spectral Density, Low Energy 16
Table 9: Test Result of 6dB Bandwidth, Low Energy 17
Table 10: Test Result of 99% Bandwidth 18
Table 11: Test Result of 20dB Bandwidth 21
Table 12: Test Result of Carrier Frequency Separation 22
Table 13: Test Result of Number of Hopping Frequency 23
Table 14: Test Result of Time of Occupancy 25

9 List of Photographs

Photograph 1: Set-up for Radiated Spurious Emission (9kHz ~ 30MHz) 28
Photograph 2: Set-up for Radiated Spurious Emission (30MHz~1GHz) 28
Photograph 3: Set-up for Radiated Spurious Emission (1GHz ~ 18GHz) 29
Photograph 4: Set-up for Radiated Spurious Emission above 18GHz 29
Photograph 5: Set-up for Conducted Emission on AC Mains 30

Appendix B

Test Results of Bluetooth 4.1 (Dual mode) of Conducted Testing

APPENDIX B 1
APPENDIX B.1: TEST PLOTS OF MAXIMUM PEAK CONDUCTED OUTPUT POWER 2
BDR Mode, DH1 2
EDR Mode, 3DH1 3
Low Energy Mode 5
APPENDIX B.2: TEST PLOTS OF CONDUCTED POWER SPECTRAL DENSITY 6
Low Energy Mode 6
APPENDIX B.3: TEST PLOTS OF 6DB BANDWIDTH 8
Low Energy Mode 8
APPENDIX B.4: TEST PLOTS OF 99% BANDWIDTH 9
BDR Mode, DH1 9
EDR Mode, 3DH1 11
Low Energy Mode 12
APPENDIX B.5: TEST PLOTS OF 20DB BANDWIDTH 14
BDR Mode, DH1 14
EDR Mode, 3DH1 15
APPENDIX B.6: TEST PLOTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH 17
BDR Mode, DH1 17
EDR Mode, 3DH1 18
Low Energy Mode 20
BDR Mode, Band Edge 21
EDR Mode, Band Edge 22
Low Energy Mode, Band Edge 23
APPENDIX B.7: TEST PLOTS OF CARRIER FREQUENCY SEPARATION 24
Hopping Mode 24
APPENDIX B.8: TEST PLOTS OF NUMBER OF HOPPING FREQUENCY 26
Hopping Mode 26
APPENDIX B.9: TEST PLOTS OF TIME OF OCCUPANCY 26
BDR Mode, DH1 26
BDR Mode, DH3 28
BDR Mode, DH5 29
EDR Mode, 3DH1 31
EDR Mode, 3DH3 32
EDR Mode, 3DH5 34

Appendix B.1: Test Plots of Maximum Peak Conducted Output Power

BDR Mode, DH1



Date: 29.JUL.2016 20:22:00



Date: 29.JUL.2016 20:22:38



Date: 29.JUL.2016 20:23:20

EDR Mode, 3DH1



Date: 29.JUL.2016 20:24:52



Date: 29.JUL.2016 20:24:22



Date: 29.JUL.2016 20:23:51

Low Energy Mode



Date: 27.JUL.2016 16:25:04



Date: 27.JUL.2016 16:25:48



Date: 27.JUL.2016 16:26:37

Appendix B.2: Test Plots of Conducted Power Spectral Density

Low Energy Mode



Date: 27.JUL.2016 16:28:33



Date: 27.JUL.2016 16:28:04



Date: 27.JUL.2016 16:27:22

Appendix B.3: Test Plots of 6dB Bandwidth

Low Energy Mode



Date: 27.JUL.2016 16:08:26



Date: 27.JUL.2016 16:09:53



Date: 27.JUL.2016 16:11:13

Appendix B.4: Test Plots of 99% Bandwidth

BDR Mode, DH1



Date: 29.JUL.2016 20:20:40



Date: 29.JUL.2016 20:19:59



Date: 29.JUL.2016 20:19:21

EDR Mode, 3DH1



Date: 29.JUL.2016 20:16:37



Date: 29.JUL.2016 20:17:12



Date: 29.JUL.2016 20:17:43

Low Energy Mode



Date: 27.JUL.2016 16:13:55



Date: 27.JUL.2016 16:13:15



Date: 27.JUL.2016 16:12:29

Appendix B.5: Test Plots of 20dB Bandwidth

BDR Mode, DH1



Date: 29.JUL.2016 20:06:44



Date: 29.JUL.2016 20:08:52



Date: 29.JUL.2016 20:10:24

EDR Mode, 3DH1



Date: 29.JUL.2016 20:15:49



Date: 29.JUL.2016 20:14:01



Date: 29.JUL.2016 20:12:15

Appendix B.6: Test Plots of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

BDR Mode, DH1



Date: 29.JUL.2016 20:31:31



Date: 29.JUL.2016 20:32:38



Date: 29.JUL.2016 20:33:42

EDR Mode, 3DH1



Date: 29.JUL.2016 20:38:01



Date: 29.JUL.2016 20:36:32



Date: 29.JUL.2016 20:35:30

Low Energy Mode



Date: 27.JUL.2016 16:23:36



Date: 27.JUL.2016 16:22:09



Date: 27.JUL.2016 16:20:48

BDR Mode, Band Edge



Date: 29.JUL.2016 20:28:58



Date: 29.JUL.2016 20:30:05

EDR Mode, Band Edge



Date: 29.JUL.2016 20:26:51



Date: 29.JUL.2016 20:28:07

Low Energy Mode, Band Edge



Date: 27.JUL.2016 16:16:34



Date: 27.JUL.2016 16:18:48

Appendix B.7: Test Plots of Carrier Frequency Separation

Hopping Mode



Date: 29.JUL.2016 20:02:02



Date: 29.JUL.2016 20:00:50



Date: 29.JUL.2016 20:02:58

Appendix B.8: Test Plots of Number of Hopping Frequency

Hopping Mode



Date: 29.JUL.2016 19:59:13

Appendix B.9: Test Plots of Time of Occupancy

BDR Mode, DH1



Date: 29.JUL.2016 20:58:23



Date: 29.JUL.2016 20:57:38



Date: 29.JUL.2016 20:57:00

BDR Mode, DH3



Date: 29.JUL.2016 20:54:36



Date: 29.JUL.2016 20:55:26



Date: 29.JUL.2016 20:56:05

BDR Mode, DH5



Date: 29.JUL.2016 20:53:26



Date: 29.JUL.2016 20:52:51



Date: 29.JUL.2016 20:51:46

EDR Mode, 3DH1



Date: 29.JUL.2016 20:46:18



Date: 29.JUL.2016 20:45:29



Date: 29.JUL.2016 20:46:58

EDR Mode, 3DH3



Date: 29.JUL.2016 20:48:58



Date: 29.JUL.2016 20:48:19



Date: 29.JUL.2016 20:47:40

EDR Mode, 3DH5



Date: 29.JUL.2016 20:49:47



Date: 29.JUL.2016 20:50:19



Date: 29.JUL.2016 20:50:56

Appendix C

Test Results of Bluetooth 4.1 (Dual mode) of Conducted and Radiated Emission Testing

APPENDIX C 1

APPENDIX C.1: TEST PLOTS OF RADIATED SPURIOUS EMISSION 2
BDR mode, 9KHz - 30MHz *2*
BDR mode, 30MHz - 1GHz *5*
BDR mode, 1GHz - 18GHz *11*
BDR mode, 18GHz - 26.5GHz *17*
Low Energy mode, 9KHz - 30MHz *23*
Low Energy mode, 30MHz - 1GHz *26*
Low Energy mode, 1GHz - 18GHz *32*
Low Energy mode, 18GHz - 26.5GHz *38*
APPENDIX C.2: TEST PLOTS OF BAND EDGE (RADIATED) 44
BDR mode, Low Channel *44*
BDR mode, High Channel *46*
Low Energy mode, Low Channel *48*
Low Energy mode, High Channel *50*
APPENDIX C.3: TEST PLOTS OF CONDUCTED EMISSION 52
C Mode *52*

Note: The measurements with active loop antenna were greater than 20dB below the limit, so Radiated Spurious Emissions (9kHz – 30MHz) tests were applied on BDR mode only.

Appendix C.1: Test Plots of Radiated Spurious Emission

BDR mode, 9KHz - 30MHz

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

```
EUT:                  ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:         ContextMedia LLC
Operating Condition:  TX 2402MHz
Test Site:            2# Chamber
Operator:             PEI
Test Specification:   AC 120V/60Hz
Comment:              X
Start of Test:        2016-8-31 /
```

SCAN TABLE: "LFRE Fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT:	ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:	ContextMedia LLC
Operating Condition:	TX 2402MHz
Test Site:	2# Chamber
Operator:	PEI
Test Specification:	AC 120V/60Hz
Comment:	Y
Start of Test:	2016-8-31 /

SCAN TABLE: "LFRE Fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT:	ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:	ContextMedia LLC
Operating Condition:	TX 2402MHz
Test Site:	2# Chamber
Operator:	PEI
Test Specification:	AC 120V/60Hz
Comment:	Z
Start of Test:	2016-8-31 /

SCAN TABLE: "LFRE Fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



BDR mode, 30MHz - 1GHz

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2809
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	362.9844	38.91	-8.58	30.33	46.00	-15.67	QP			
2	396.2412	49.72	-7.97	41.75	46.00	-4.25	QP			
3	793.3958	35.13	-1.12	34.01	46.00	-11.99	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2810
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.8293	36.04	-16.23	19.81	43.50	-23.69	QP			
2	396.2412	49.14	-7.97	41.17	46.00	-4.83	QP			
3	793.3958	33.47	-1.12	32.35	46.00	-13.65	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2811
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2441MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	144.3348	35.39	-16.23	19.16	43.50	-24.34	QP			
2	396.2412	49.17	-7.97	41.20	46.00	-4.80	QP			
3	793.3958	32.37	-1.12	31.25	46.00	-14.75	QP			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2812
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2441MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	146.8875	35.19	-16.20	18.99	43.50	-24.51	QP			
2	396.2412	49.26	-7.97	41.29	46.00	-4.71	QP			
3	793.3958	35.20	-1.12	34.08	46.00	-11.92	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2813
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	281.9945	37.80	-10.79	27.01	46.00	-18.99	QP			
2	396.2412	49.44	-7.97	41.47	46.00	-4.53	QP			
3	793.3958	35.84	-1.12	34.72	46.00	-11.28	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2814
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	144.8418	35.92	-16.23	19.69	43.50	-23.81	QP			
2	396.2412	49.44	-7.97	41.47	46.00	-4.53	QP			
3	793.3958	33.28	-1.12	32.16	46.00	-13.84	QP			

BDR mode, 1GHz - 18GHz

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2573
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	92.76	-7.45	85.31	/	/	peak			
2	16221.189	10.10	40.13	50.23	74.00	-23.77	peak			
3	16221.189	2.52	40.13	42.65	54.00	-11.35	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2574
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	93.20	-7.45	85.75	/	/	peak			
2	15577.899	10.04	40.08	50.12	74.00	-23.88	peak			
3	15577.899	1.95	40.08	42.03	54.00	-11.97	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2577
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2441MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	92.87	-7.35	85.52	/	/	peak			
2	16315.231	10.07	40.19	50.26	74.00	-23.74	peak			
3	16315.231	2.18	40.19	42.37	54.00	-11.63	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2578
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2441MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2441.000	93.24	-7.35	85.89	/	/	peak			
2	14960.120	8.51	41.22	49.73	74.00	-24.27	peak			
3	14960.120	-0.16	41.22	41.06	54.00	-12.94	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2579
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	94.37	-7.37	87.00	/	/	peak			
2	15713.564	9.95	40.06	50.01	74.00	-23.99	peak			
3	15713.564	2.25	40.06	42.31	54.00	-11.69	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2580
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	93.68	-7.37	86.31	/	/	peak			
2	15942.303	9.83	40.01	49.84	74.00	-24.16	peak			
3	15942.303	1.63	40.01	41.64	54.00	-12.36	AVG			

BDR mode, 18GHz - 26.5GHz

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2583
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26428.351	33.30	16.95	50.25	74.00	-23.75	peak			
2	26428.351	23.61	16.95	40.56	54.00	-13.44	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2584
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25892.112	33.59	16.50	50.09	74.00	-23.91	peak			
2	25892.112	23.73	16.50	40.23	54.00	-13.77	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2585
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2441MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26275.468	34.26	16.50	50.76	74.00	-23.24	peak			
2	26275.468	24.00	16.50	40.50	54.00	-13.50	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2586	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2441MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25962.307	33.38	17.26	50.64	74.00	-23.36	peak			
2	25962.307	23.11	17.26	40.37	54.00	-13.63	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2587
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26316.150	33.00	17.02	50.02	74.00	-23.98	peak			
2	26316.150	23.62	17.02	40.64	54.00	-13.36	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2588	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2480MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26123.470	34.50	16.50	51.00	74.00	-23.00	peak			
2	26123.470	24.95	16.50	41.45	54.00	-12.55	AVG			

Low Energy mode, 9KHz - 30MHz

ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

```
EUT:                    ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:           ContextMedia LLC
Operating Condition:    TX 2402MHz
Test Site:              2# Chamber
Operator:               PEI
Test Specification:     AC 120V/60Hz
Comment:                X
Start of Test:          2016-8-31 /
```

SCAN TABLE: "LFRE Fin"

```
Short Description:                    SUB STD VTERM2 1.70
Start       Stop        Step          Detector  Meas.     IF       Transducer
Frequency   Frequency   Width                   Time      Bandw.
9.0 kHz     150.0 kHz   100.0 Hz      QuasiPeak 1.0 s     200 Hz   1516M
150.0 kHz   30.0 MHz    5.0 kHz       QuasiPeak 1.0 s     9 kHz    1516M
```



ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC
Operating Condition: TX 2402MHz
Test Site: 2# Chamber
Operator: PEI
Test Specification: AC 120V/60Hz
Comment: Y
Start of Test: 2016-8-31 /

SCAN TABLE: "LFRE Fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



ACCURATE TECHNOLOGY CO.,LTD

FCC Class B 3m Radiated

EUT: ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC
Operating Condition: TX 2402MHz
Test Site: 2# Chamber
Operator: PEI
Test Specification: AC 120V/60Hz
Comment: Z
Start of Test: 2016-8-31 /

SCAN TABLE: "LFRE Fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M



Low Energy mode, 30MHz - 1GHz

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2817
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2440MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	362.9844	41.83	-8.58	33.25	46.00	-12.75	QP			
2	396.2412	49.68	-7.97	41.71	46.00	-4.29	QP			
3	793.3958	35.65	-1.12	34.53	46.00	-11.47	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2818
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2440MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	396.2412	49.18	-7.97	41.21	46.00	-4.79	QP			
2	520.8881	38.41	-5.31	33.10	46.00	-12.90	QP			
3	893.8567	34.71	0.26	34.97	46.00	-11.03	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2819
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	396.2412	49.41	-7.97	41.44	46.00	-4.56	QP			
2	595.1327	37.49	-4.02	33.47	46.00	-12.53	QP			
3	818.8341	36.83	-0.70	36.13	46.00	-9.87	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2820
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	147.9214	35.33	-16.19	19.14	43.50	-24.36	QP			
2	396.2412	49.19	-7.97	41.22	46.00	-4.78	QP			
3	818.8341	34.13	-0.70	33.43	46.00	-12.57	QP			

ATC®

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2815
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	396.2412	49.74	-7.97	41.77	46.00	-4.23	QP			
2	520.8881	36.99	-5.31	31.68	46.00	-14.32	QP			
3	893.8567	32.59	0.26	32.85	46.00	-13.15	QP			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2816
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/28/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	143.8293	35.12	-16.23	18.89	43.50	-24.61	QP			
2	396.2412	49.22	-7.97	41.25	46.00	-4.75	QP			
3	818.8341	37.42	-0.70	36.72	46.00	-9.28	QP			

Low Energy mode, 1GHz - 18GHz

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2589
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	103.73	-7.45	96.28	/	/	peak			
2	4804.025	48.37	-0.30	48.07	74.00	-25.93	peak			
3	4804.025	40.83	-0.30	40.53	54.00	-13.47	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2590
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2402.000	95.63	-7.45	88.18	/	/	peak			
2	4804.023	47.98	-0.30	47.68	74.00	-26.32	peak			
3	4804.023	39.86	-0.30	39.56	54.00	-14.44	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2593
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2440MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	104.74	-7.36	97.38	/	/	peak			
2	4880.027	48.99	0.13	49.12	74.00	-24.88	peak			
3	4880.027	41.07	0.13	41.20	54.00	-12.80	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2594
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2440MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2440.000	95.98	-7.36	88.62	/	/	peak			
2	4880.029	46.59	0.13	46.72	74.00	-27.28	peak			
3	4880.029	38.48	0.13	38.61	54.00	-15.39	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2595	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2480MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	96.23	-7.37	88.86	/	/	peak			
2	4960.026	48.25	0.52	48.77	74.00	-25.23	peak			
3	4960.026	39.71	0.52	40.23	54.00	-13.77	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2596
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2480.000	102.03	-7.37	94.66	/	/	peak			
2	4960.025	47.56	0.52	48.08	74.00	-25.92	peak			
3	4960.025	39.71	0.52	40.23	54.00	-13.77	AVG			

Low Energy mode, 18GHz - 26.5GHz

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2599
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26275.468	32.95	17.05	50.00	74.00	-24.00	peak			
2	26275.468	23.18	17.05	40.23	54.00	-13.77	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2600	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2402MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25972.351	33.76	16.50	50.26	74.00	-23.74	peak			
2	25972.351	23.95	16.50	40.45	54.00	-13.55	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2601	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2440MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26244.998	33.77	16.50	50.27	74.00	-23.73	peak			
2	26244.998	23.85	16.50	40.35	54.00	-13.65	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2602	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2440MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26244.998	33.60	17.07	50.67	74.00	-23.33	peak			
2	26244.998	23.05	17.07	40.12	54.00	-13.88	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2603	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2480MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26163.916	33.73	17.12	50.85	74.00	-23.15	peak			
2	26163.916	23.09	17.12	40.21	54.00	-13.79	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2604	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2480MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25882.099	33.72	16.50	50.22	74.00	-23.78	peak			
2	25882.099	23.77	16.50	40.27	54.00	-13.73	AVG			

Appendix C.2: Test Plots of Band Edge (Radiated)

BDR mode, Low Channel

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2575
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2376.000	48.35	-7.62	40.73	74.00	-33.27	peak			
2	2376.000	38.16	-7.62	30.54	54.00	-23.46	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2576	Polarization: Horizontal
Standard: FCC (Band Edge)	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2402MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2314.240	44.59	-7.81	36.78	74.00	-37.22	peak			
2	2314.240	34.12	-7.81	26.31	54.00	-27.69	AVG			

BDR mode, High Channel

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2581	Polarization: Horizontal
Standard: FCC (Band Edge)	Power Source: AC 120V/60Hz
Test item: Radiation Test	Date: 16/08/09/
Temp.(C)/Hum.(%) 23 C / 48 %	Time:
EUT: ContextMedia Health	Engineer Signature: PEI
Mode: TX 2480MHz	Distance: 3m
Model: P-TAB-104-ELC-01	
Manufacturer: ContextMedia LLC	

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.863	44.64	-7.38	37.26	74.00	-36.74	peak			
2	2483.863	34.84	-7.38	27.46	54.00	-26.54	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2582
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2486.189	44.76	-7.38	37.38	74.00	-36.62	peak			
2	2486.189	35.27	-7.38	27.89	54.00	-26.11	AVG			

Low Energy mode, Low Channel

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2592
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2379.280	45.07	-7.59	37.48	74.00	-36.52	peak			
2	2379.280	35.11	-7.59	27.52	54.00	-26.48	AVG			

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2591
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2402MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2375.680	47.18	-7.62	39.56	74.00	-34.44	peak			
2	2375.680	36.74	-7.62	29.12	54.00	-24.88	AVG			

Low Energy mode, High Channel

ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2598
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Vertical
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.764	44.87	-7.38	37.49	74.00	-36.51	peak			
2	2483.764	35.04	-7.38	27.66	54.00	-26.34	AVG			

ATC®
ACCURATE TECHNOLOGY CO., LTD.
F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China
Site: 2# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: PHY #2597
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: ContextMedia Health
Mode: TX 2480MHz
Model: P-TAB-104-ELC-01
Manufacturer: ContextMedia LLC

Polarization: Horizontal
Power Source: AC 120V/60Hz
Date: 16/08/09/
Time:
Engineer Signature: PEI
Distance: 3m

Note: Bluetooth 4.0



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.715	45.74	-7.37	38.37	74.00	-35.63	peak			
2	2483.715	35.93	-7.37	28.56	54.00	-25.44	AVG			

Appendix C.3: Test Plots of Conducted Emission

C Mode

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

```
EUT:                  ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:         ContextMedia LLC
Operating Condition:  On with Bluetooth
Test Site:            1#Shielding Room
Operator:             LGWADE
Test Specification:   N 120V/60Hz
Comment:              Mains Port
Start of Test:        8/28/2016 /
```

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak Average	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TUV-0828-1_fin"

8/28/2016

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.160000	52.00	10.5	66	13.5	QP	N	GND
3.440000	33.30	11.1	56	22.7	QP	N	GND
7.260000	25.80	11.2	60	34.2	QP	N	GND

MEASUREMENT RESULT: "TUV-0828-1_fin2"

8/28/2016

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.380000	32.10	10.7	48	16.2	AV	N	GND
1.145000	33.10	10.9	46	12.9	AV	N	GND
5.730000	21.70	11.2	50	28.3	AV	N	GND

ACCURATE TECHNOLOGY CO.,LTD

CONDUCTED EMISSION STANDARD FCC PART 15 B

```
EUT:                  ContextMedia Health M/N:P-TAB-104-ELC-01
Manufacturer:         ContextMedia LLC
Operating Condition:  On with Bluetooth
Test Site:            1#Shielding Room
Operator:             LGWADE
Test Specification:   L 120V/60Hz
Comment:              Mains Port
Start of Test:        8/28/2016 /
```

SCAN TABLE: "V 9K-30MHz fin"

Short Description: SUB STD VTERM2 1.70

Start Frequency	Stop Frequency	Step Width	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak Average	1.0 s	200 Hz	NSLK8126 2008
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak Average	1.0 s	9 kHz	NSLK8126 2008



MEASUREMENT RESULT: "TUV-0828-2_fin"

8/28/2016

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	54.40	10.5	66	11.6	QP	L1	GND
3.440000	34.80	11.1	56	21.2	QP	L1	GND
14.530000	31.60	11.4	60	28.4	QP	L1	GND

MEASUREMENT RESULT: "TUV-0828-2_fin2"

8/28/2016

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.380000	31.90	10.7	48	16.4	AV	L1	GND
1.145000	33.20	10.9	46	12.8	AV	L1	GND
11.470000	25.50	11.3	50	24.5	AV	L1	GND