
FCC Test Report

Report No.: AGC07445160602FE03

FCC ID : 2A18INIMAM
APPLICATION PURPOSE : Original Equipment
PRODUCT DESIGNATION : NIMA Multimedia Bluetooth Speaker
BRAND NAME : NIMA
MODEL NAME : NIMA MED
CLIENT : NIMA LLC
DATE OF ISSUE : Aug.31, 2016
STANDARD(S) : FCC Part 15 Rules
TEST PROCEDURE(S)
REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug.31, 2016	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION.....	5
2.2. TABLE OF CARRIER FREQUENCIES.....	5
3. MEASUREMENT UNCERTAINTY.....	6
4. DESCRIPTION OF TEST MODES.....	6
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM	8
5.2. EQUIPMENT USED IN EUT SYSTEM	8
5.3. SUMMARY OF TEST RESULTS	8
6. TEST FACILITY	9
TEST METHODOLOGY.....	9
7. ALL TEST EQUIPMENT LIST	9
8. RADIATED EMISSION	11
8.1TEST LIMIT.....	11
8.2. MEASUREMENT PROCEDURE	12
8.3. TEST SETUP	14
8.4. TEST RESULT	16
9. BAND EDGE EMISSION	31
9.1. MEASUREMENT PROCEDURE	31
9.2 TEST SETUP	31
9.3 RADIATED TEST RESULT	32
10. 20DB BANDWIDTH.....	36
10.1. MEASUREMENT PROCEDURE	36
10.2. TEST SET-UP	36
10.3. LIMITS AND MEASUREMENT RESULTS.....	36
11. FCC LINE CONDUCTED EMISSION TEST	43
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	43
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	43
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	44
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	44
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	47
APPENDIX B: PHOTOGRAPHS OF EUT	50

1. VERIFICATION OF CONFORMITY

Applicant	NIMA LLC
Address	8 Corporate Park, Irvine CA 92606 USA
Manufacturer	Dongguan Yejia Electronic Technology Co., Ltd.
Address	Block B No.2 Longpu Road, Longbeiling Village, Tangxia Town, Dongguan City, Guangdong Province, China
Product Designation	NIMA Multimedia Bluetooth Speaker
Brand Name	NIMA
Test Model	NIMA MED
Date of test	Aug.22, 2016 to Aug.24, 2016
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249.

Tested By 
Time Huang(Huang Nanhui) Aug.31, 2016

Reviewed By 
Forrest Lei(Lei Yonggang) Aug.31, 2016

Approved By 
Solger Zhang(Zhang Hongyi)
Authorized Officer Aug.31, 2016

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.62dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.2
Modulation	GFSK , π /4-DQPSK, 8DPSK
Number of channels	79 for BR/EDR
Hardware Version	CGBT732_2825-V1.7.pcb
Software Version	CGBT732_2825_TWS_OTA_32M_LDO_v1.03[LX_G].fw
Antenna Designation	PCB Antenna (Met 15.203 Antenna requirement)
Antenna Gain	0dBi
Power Supply	DC 7.4V by battery

Note: The USB port only used for charging and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCIES

BR/EDR channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.18\text{dB}$
2	All emissions, radiated	$\pm 3.91\text{dB}$
3	Temperature	$\pm 0.5^\circ\text{C}$
4	Humidity	$\pm 2\%$

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel $\pi/4$ -DQPSK
5	Middle channel $\pi/4$ -DQPSK
6	High channel $\pi/4$ -DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	BT Link with charging
11	BT Link

Note:

1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. The EUT used fully-charged battery when tested.

Software Setting

The screenshot shows the 'Bluetooth MP Tool' window. At the top, there's a 'Mode' section with a green '0' button and a dropdown menu set to 'BT ONLY UART'. Next to it are 'Port = 1' and 'Baudrate=115200' dropdowns, followed by 'Open' and 'Close' buttons. A logo for '炬芯 Actions' is on the right. Below this is a row of tabs: 'Non Link Mode', 'Hopping', 'RW', 'LE Test', and a checked 'DL Patch' checkbox. The main area is divided into two columns. The left column contains several input fields: 'Channel' (0), 'Packet Type' (DH1), 'Payload Type' (PRBS9), 'Tx Packet Count' (0), 'Tx Gain Index' (6), and 'Tx Gain Value' (0xCE). The right column has a 'Pkt-Tx' dropdown, 'Exec', 'Stop', and 'Clear Report' buttons, and a table showing transaction statistics.

Item	Value
Tx bits	1272240
Tx Pkt Count	5890


Below the table are 'TX Report' and 'RX Report' buttons. At the bottom, there's a 'Message' tab with a log of system messages.

```
>>Read Tx dac current value = 0x!!  
>>Enable TRX Thread Mode...!!  
>>ActionControlExcute(Pkt-Tx) Success...!!  
>>ActionControlExcute(Pkt-Tx) Stop...!!  
>>Enable TRX Thread Mode...!!  
>>ActionControlExcute(Pkt-Tx) Success...!!  
>>ActionControlExcute(Pkt-Tx) Stop...!!
```

5. SYSTEM TEST CONFIGURATION


5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, Testing will be performed while PC or adapter remove.

Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
1	NIMA Multimedia Bluetooth Speaker	NIMA	NIMA MED	EUT
2	Battery	Huan Yu Yuan	HYY 18650	Accessory
3	PC	Sony	E1412AYCW	A.E
4	Control box	DOFLY	LY-USB-TTL v2.2	A.E
5	Adapter	NIMA	SUN-1200350US	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
§15.215	Bandwidth	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2016	July 3, 2017
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2016	July 3, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2016	June 5, 2017
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2016	July 10, 2017
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2016	July 3, 2017
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2016	July 6, 2017
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2016	July 7, 2017
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2016	June 5, 2017
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2016	June 5, 2017
Radiation Cable 1	MXT	RS1	R005	June 6, 2016	June 5, 2017
Radiation Cable 2	MXT	RS1	R006	June 6, 2016	June 5, 2017

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2016	July 3, 2017
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2016	July 7, 2017
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2016	July 7, 2017
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2016	July 3, 2017
Shielded Room	CHENGYU	843	PTS-002	June 6, 2016	June 5, 2017
Conduction Cable	MXT	SE1	S003	June 6, 2016	June 5, 2017

8. RADIATED EMISSION

8.1 TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μ V)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μ V)/m (Peak) 54.0 dB(μ V)/m (Average)	

Remark: (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE


1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak&AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.4. TEST RESULT

(Worst modulation:GFSK)


FOR BR/EDR

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: NIMA Multimedia Bluetooth Speaker
M/N: NIMA MED
Mode: Low Channel TX
Note:

Polarization: **Horizontal**
Power:
Distance:

Temperature: 23.9
Humidity: 54.7 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	138.3167	22.60	14.41	37.01	43.50	-6.49	peak			
2		199.7500	24.00	11.99	35.99	43.50	-7.51	peak			
3		295.1333	18.90	14.58	33.48	46.00	-12.52	peak			
4		393.7500	18.63	19.03	37.66	46.00	-8.34	peak			
5		492.3667	6.55	21.05	27.60	46.00	-18.40	peak			
6		954.7333	2.57	29.95	32.52	46.00	-13.48	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 23.9

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.7 %

EUT: NIMA Multimedia Bluetooth Speaker

Distance:

M/N: NIMA MED

Mode: Low Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	152.8667	21.98	15.28	37.26	43.50	-6.24	peak			
2		202.9833	23.52	9.29	32.81	43.50	-10.69	peak			
3		270.8833	21.05	14.53	35.58	46.00	-10.42	peak			
4		451.9500	10.10	20.61	30.71	46.00	-15.29	peak			
5		775.2833	2.25	26.98	29.23	46.00	-16.77	peak			
6		946.6500	3.71	29.91	33.62	46.00	-12.38	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: **Horizontal** Temperature: 23.9
Limit: FCC Class B 3M Radiation Power: Humidity: 54.7 %
EUT: NIMA Multimedia Bluetooth Speaker Distance:
M/N: NIMA MED
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	138.3167	21.95	14.41	36.36	43.50	-7.14	peak			
2		199.7500	23.20	11.99	35.19	43.50	-8.31	peak			
3		295.1333	18.58	14.58	33.16	46.00	-12.84	peak			
4		393.7500	18.34	19.03	37.37	46.00	-8.63	peak			
5		807.6167	2.00	27.32	29.32	46.00	-16.68	peak			
6		946.6500	2.67	29.91	32.58	46.00	-13.42	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Polarization: **Vertical**

Temperature: 23.9

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.7 %

EUT: NIMA Multimedia Bluetooth Speaker

Distance:

M/N: NIMA MED

Mode: Middle Channel TX


Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	154.4833	21.67	15.29	36.96	43.50	-6.54	peak			
2		270.8833	22.30	14.53	36.83	46.00	-9.17	peak			
3		361.4167	9.99	18.82	28.81	46.00	-17.19	peak			
4		451.9500	6.36	20.61	26.97	46.00	-19.03	peak			
5		810.8500	2.36	27.32	29.68	46.00	-16.32	peak			
6		943.4167	2.59	29.82	32.41	46.00	-13.59	peak			

RESULT: PASS**Note:** 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Polarization: *Horizontal*

Temperature: 23.9

Limit: FCC Class B 3M Radiation

Power:

Humidity: 54.7 %

EUT: NIMA Multimedia Bluetooth Speaker

Distance:

M/N: NIMA MED


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		138.3167	17.40	14.41	31.81	43.50	-11.69	peak			
2	*	199.7500	23.51	11.99	35.50	43.50	-8.00	peak			
3		346.8667	14.47	18.53	33.00	46.00	-13.00	peak			
4		393.7500	18.48	19.03	37.51	46.00	-8.49	peak			
5		492.3667	6.58	21.05	27.63	46.00	-18.37	peak			
6		915.9333	3.92	29.05	32.97	46.00	-13.03	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: NIMA Multimedia Bluetooth Speaker
M/N: NIMA MED
Mode: High Channel TX
Note:

Polarization: **Vertical**
Power:
Distance:

Temperature: 23.9
Humidity: 54.7 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	152.8667	24.20	15.28	39.48	43.50	-4.02	peak			
2		270.8833	21.46	14.53	35.99	46.00	-10.01	peak			
3		361.4167	10.51	18.82	29.33	46.00	-16.67	peak			
4		451.9500	9.67	20.61	30.28	46.00	-15.72	peak			
5		814.0833	2.27	27.32	29.59	46.00	-16.41	peak			
6		941.8000	2.65	29.77	32.42	46.00	-13.58	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ
(Worst modulation: GFSK)
FOR BR/EDR

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHz(PK)- Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance: 3m
M/N: NIMA MED
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	103.69	-9.68	94.01	114.00	-19.99	peak			
2	*	2402.000	94.91	-9.68	85.23	94.00	-8.77	AVG	100	95	
3		4050.000	50.82	-4.64	46.18	74.00	-27.82	peak			
4		5750.000	47.76	-1.69	46.07	74.00	-27.93	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance: 3m
M/N: NIMA MED
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	103.27	-9.68	93.59	114.00	-20.41	peak			
2	*	2402.000	94.80	-9.68	85.12	94.00	-8.88	AVG	100	142	
3		4025.000	50.56	-4.72	45.84	74.00	-28.16	peak			
4		5375.000	48.06	-1.81	46.25	74.00	-27.75	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance: 3m
M/N: NIMA MED
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	105.24	-9.63	95.61	114.00	-18.39	peak			
2	*	2441.000	98.39	-9.63	88.76	94.00	-5.24	AVG	100	88	
3		3916.667	51.27	-5.32	45.95	74.00	-28.05	peak			
4		5025.000	47.92	-1.80	46.12	74.00	-27.88	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL




Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance: 3m
M/N: NIMA MED
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1216.667	61.99	-15.50	46.49	74.00	-27.51	peak			
2		2441.000	105.19	-9.63	95.56	114.00	-18.44	peak			
3	*	2441.000	97.97	-9.63	88.34	94.00	-5.66	AVG	100	164	
4		3441.667	54.59	-7.94	46.65	74.00	-27.35	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL




Site: site #1 Polarization: *Horizontal* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance: 3m
M/N: NIMA MED
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	106.41	-9.59	96.82	114.00	-17.18	peak			
2	*	2480.000	98.93	-9.59	89.34	94.00	-4.66	AVG	100	75	
3		3458.333	54.02	-7.93	46.09	74.00	-27.91	peak			
4		4591.667	48.89	-2.87	46.02	74.00	-27.98	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1

Polarization: *Vertical*

Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)-

Power:

Humidity: 60 %

EUT: NIMA Multimedia Bluetooth Speaker

Distance: 3m

M/N: NIMA MED

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	106.32	-9.59	96.73	114.00	-17.27	peak			
2	*	2480.000	98.02	-9.59	88.43	94.00	-5.57	AVG	100	167	
3		3183.333	54.09	-8.19	45.90	74.00	-28.10	peak			
4		4683.333	48.44	-2.63	45.81	74.00	-28.19	peak			

RESULT: PASS**Note:** 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	103.69	-9.68	94.01	114	-19.99	Horizontal
2402	103.27	-9.68	93.59	114	-20.41	Vertical
2441	105.24	-9.63	95.61	114	-18.39	Horizontal
2441	105.19	-9.63	95.56	114	-18.44	Vertical
2480	106.41	-9.59	96.82	114	-17.18	Horizontal
2480	106.32	-9.59	96.73	114	-17.27	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	94.91	-9.68	85.23	94	-8.77	Horizontal
2402	94.80	-9.68	85.12	94	-8.88	Vertical
2441	98.39	-9.63	88.76	94	-5.24	Horizontal
2441	97.97	-9.63	88.34	94	-5.66	Vertical
2480	98.93	-9.59	89.34	94	-4.66	Horizontal
2480	98.02	-9.59	88.43	94	-5.57	Vertical

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	103.54	-9.68	93.86	114	-20.14	Horizontal
2402	103.42	-9.68	93.74	114	-20.26	Vertical
2441	104.97	-9.68	95.29	114	-18.71	Horizontal
2441	104.84	-9.68	95.16	114	-18.84	Vertical
2480	106.04	-9.63	96.41	114	-17.59	Horizontal
2480	105.91	-9.63	96.28	114	-17.72	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	94.68	-9.63	85.05	94	-8.95	Horizontal
2402	94.52	-9.63	84.89	94	-9.11	Vertical
2441	98.18	-9.59	88.59	94	-5.41	Horizontal
2441	98.02	-9.59	88.43	94	-5.57	Vertical
2480	97.95	-9.59	88.36	94	-5.64	Horizontal
2480	97.80	-9.59	88.21	94	-5.79	Vertical

3Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	103.36	-9.68	93.68	114	-20.32	Horizontal
2402	103.25	-9.68	93.57	114	-20.43	Vertical
2441	104.70	-9.68	95.02	114	-18.98	Horizontal
2441	104.65	-9.68	94.97	114	-19.03	Vertical
2480	105.74	-9.63	96.11	114	-17.89	Horizontal
2480	105.69	-9.63	96.06	114	-17.94	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	94.38	-9.63	84.75	94	-9.25	Horizontal
2402	94.28	-9.63	84.65	94	-9.35	Vertical
2441	97.85	-9.59	88.26	94	-5.74	Horizontal
2441	97.78	-9.59	88.19	94	-5.81	Vertical
2480	97.63	-9.59	88.04	94	-5.96	Horizontal
2480	97.54	-9.59	87.95	94	-6.05	Vertical


9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

- 1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




9.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: NIMA Multimedia Bluetooth Speaker
M/N: NIMA MED
Mode: Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2326.758	32.91	10.24	43.15	74.00	-30.85	peak			
2		2390.000	35.00	10.31	45.31	74.00	-28.69	peak			
3	*	2402.000	83.22	10.32	93.54	74.00	19.54	peak			


TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: NIMA Multimedia Bluetooth Speaker Distance:
M/N: NIMA MED
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2279.608	32.98	10.19	43.17	74.00	-30.83	peak			
2		2390.000	33.21	10.31	43.52	74.00	-30.48	peak			
3	*	2402.000	83.59	10.32	93.91	74.00	19.91	peak			


TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: *Horizontal* Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
 EUT: NIMA Multimedia Bluetooth Speaker Distance:
 M/N: NIMA MED
 Mode: High Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	87.05	10.41	97.46	74.00	23.46	peak			
2		2483.500	33.19	10.41	43.60	74.00	-30.40	peak			
3		2489.000	32.14	10.42	42.56	74.00	-31.44	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: **Vertical** Temperature: 26
 Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
 EUT: NIMA Multimedia Bluetooth Speaker Distance:
 M/N: NIMA MED
 Mode: High Channel TX
 Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.82	10.41	96.23	74.00	22.23	peak			
2		2483.500	34.76	10.41	45.17	74.00	-28.83	peak			
3		2487.643	33.67	10.42	44.09	74.00	-29.91	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.


10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% of the 20 dB bandwidth, VBW $\geq$ RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

10.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	0.993	1.123	PASS
	Middle Channel	0.991	1.114	PASS
	High Channel	0.991	1.122	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.220	1.375	PASS
	Middle Channel	1.220	1.384	PASS
	High Channel	1.229	1.379	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT				
Applicable Limits	Measurement Result			
	Test Data (MHz)			Result
		99%OBW (MHz)	-20dB BW(MHz)	
N/A	Low Channel	1.222	1.376	PASS
	Middle Channel	1.222	1.372	PASS
	High Channel	1.227	1.374	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hz power by a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)

FOR BR/EDR


Line Conducted Emission Test Line 1-L



Site: Conduction Phase: **L1** Temperature: 22.5
Limit: FCC Class B Conduction(QP) Power: Humidity: 56.3 %
EUT: NIMA Multimedia Bluetooth Speaker
M/N: NIMA MED
Mode: BT Link with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	39.03		25.36	10.21	49.24		35.57	63.86	53.86	-14.62	-18.29	P	
2	0.4540	31.61		17.79	10.37	41.98		28.16	56.80	46.80	-14.82	-18.64	P	
3	1.3460	28.64		14.81	10.38	39.02		25.19	56.00	46.00	-16.98	-20.81	P	
4	4.1539	25.02		11.51	10.36	35.38		21.87	56.00	46.00	-20.62	-24.13	P	
5	7.0259	18.25		8.62	10.36	28.61		18.98	60.00	50.00	-31.39	-31.02	P	
6	15.8579	22.43		15.28	10.11	32.54		25.39	60.00	50.00	-27.46	-24.61	P	

Line Conducted Emission Test Line 2-N



Site: Conduction Phase: **N** Temperature: 23.5
Limit: FCC Class B Conduction(QP) Power: Humidity: 57.2 %
EUT: NIMA Multimedia Bluetooth Speaker
M/N: NIMA MED
Mode: BT Link with charging
Note:


No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	33.76		18.53	10.21	43.97		28.74	63.69	53.69	-19.72	-24.95	P	
2	0.4140	28.95		12.93	10.34	39.29		23.27	57.57	47.57	-18.28	-24.30	P	
3	0.6900	24.84		14.22	10.35	35.19		24.57	56.00	46.00	-20.81	-21.43	P	
4	3.3060	27.50		14.55	10.53	38.03		25.08	56.00	46.00	-17.97	-20.92	P	
5	5.6539	21.51		10.80	10.26	31.77		21.06	60.00	50.00	-28.23	-28.94	P	
6	15.6859	27.52		14.65	10.11	37.63		24.76	60.00	50.00	-22.37	-25.24	P	



APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP









APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



VIEW OF EUT (PORT)




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



VIEW OF ADAPTER(AE)



The adapter was supplied by grantee

----END OF REPORT----