NVLAP TESTING
NVLAP LAB CODE 200707-0

BACL Bay Area Compliance Labs Corp.

FCC PART 15.247
TEST REPORT

For

SHENZHEN HUATONG TECHNOLOGY CO.,LTD.

Room2088,20th Floor,CBlock,Electronic Technology Building ,Huaqiang North,Futian Area, Shenzhen China

FCC ID: 2AI97V5

Report Type:	**Product Type:**
Original Report	Flip phone

Report Number:	RSZ171110001-00B
Report Date:	2017-12-18
Reviewed By:	Rocky Kang RF Engineer
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EUT EXERCISE SOFTWARE 6
SPECIAL ACCESSORIES 6
EQUIPMENT MODIFICATIONS 6
SUPPORT EQUIPMENT LIST AND DETAILS 6
EXTERNAL I/O CABLE 6
BLOCK DIAGRAM OF TEST SETUP 7
SUMMARY OF TEST RESULTS **8**
TEST EQUIPMENT LIST **9**
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE **11**
APPLICABLE STANDARD 11
FCC §15.203 – ANTENNA REQUIREMENT **12**
APPLICABLE STANDARD 12
ANTENNA CONNECTOR CONSTRUCTION 12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **13**
APPLICABLE STANDARD 13
EUT SETUP 13
EMI TEST RECEIVER SETUP 13
TEST PROCEDURE 13
CORRECTED FACTOR & MARGIN CALCULATION 14
TEST RESULTS SUMMARY 14
TEST DATA 14
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS **17**
APPLICABLE STANDARD 17
EUT SETUP 17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 18
TEST PROCEDURE 18
CORRECTED AMPLITUDE & MARGIN CALCULATION 18
TEST RESULTS SUMMARY 18
TEST DATA 19
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST **25**
APPLICABLE STANDARD 25
TEST PROCEDURE 25
TEST DATA 25
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH **32**

APPLICABLE STANDARD 32
TEST PROCEDURE 32
TEST DATA 32
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST 38
APPLICABLE STANDARD 38
TEST PROCEDURE 38
TEST DATA 38
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME) 41
APPLICABLE STANDARD 41
TEST PROCEDURE 41
TEST DATA 41
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT 57
APPLICABLE STANDARD 57
TEST PROCEDURE 57
TEST DATA 57
FCC §15.247(d) - BAND EDGES TESTING 59
APPLICABLE STANDARD 59
TEST PROCEDURE 59
TEST DATA 59

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHENZHEN HUATONG TECHNOLOGY CO.,LTD.'s* product, model number: *V5 (FCC ID: 2AI97V5)* or the "EUT" in this report was a *Flip phone,* which was measured approximately: 103 mm (L) * 52 mm (W) * 18 mm (H), rated with input voltage: DC 3.7 V from rechargeable li-ion battery or DC 5.0V from adapter.

Adapter Information:
Model: V5
Input: 110-240V, 50/60Hz, 0.15 A
Output: 5V, 1000 mA

**All measurement and test data in this report was gathered from production sample serial number: 1702474 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-11-06.*

Objective

This test report is prepared on behalf of *SHENZHEN HUATONG TECHNOLOGY CO.,LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H/24E PCE and Part 15B JBP submissions with FCC ID: 2AI97V5.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3℃
Humidity		±6%
Supply voltages		±0.4%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS (Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP (Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

No exercise software was made to the EUT tested.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-Shielding Un-Detachable DC Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2017-08-04	2018-08-04
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-11-19	2018-05-17
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-11-12	2018-05-12
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-05-21	2018-05-21
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2014-12-17	2017-12-16
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2014-12-29	2017-12-28
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2017-08-03	2018-08-03
Sinoscite	Band Reject Filter	BSF2402-2480MN-0898-001	N/A	2017-05-21	2018-05-21

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Agilent	P-Series Power Meter	N1912A	MY5000448	2016-12-05	2017-12-05
Agilent	Wideband Power Sensor	N1921A	MY54210016	2016-12-05	2017-12-05
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-05-21	2017-11-19
WEINSCHEL	3 dB Attenuator	N/A	N/A	2017-11-19	2018-05-17
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2016-12-05	2017-12-05
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2017-12-05	2018-12-05
Ducommun technologies	RF Cable	RG-214	3	2017-05-22	2017-11-22
Ducommun technologies	RF Cable	RG-214	3	2017-11-22	2018-05-22

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
2480	9.50	8.91	5.0	2.81	3.0	**Yes**

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is -3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-29.

EUT operation mode: Transmitting

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.530110	48.7	20.2	56.0	7.3	QP
0.537870	48.0	20.2	56.0	8.0	QP
0.896710	44.4	20.1	56.0	11.6	QP
0.943990	47.3	20.1	56.0	8.7	QP
1.053950	43.5	20.1	56.0	12.5	QP
1.133110	43.5	20.1	56.0	12.5	QP
0.530110	39.8	20.2	46.0	6.2	Ave.
0.537870	39.8	20.2	46.0	6.2	Ave.
0.896710	36.7	20.1	46.0	9.3	Ave.
0.943990	38.8	20.1	46.0	7.2	Ave.
1.053950	37.2	20.1	46.0	8.8	Ave.
1.133110	34.7	20.1	46.0	11.3	Ave.

AC 120V/60 Hz, Neutral



Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.565510	46.7	20.1	56.0	9.3	QP
0.600850	44.5	20.1	56.0	11.5	QP
0.857130	44.6	20.1	56.0	11.4	QP
0.971390	44.8	20.1	56.0	11.2	QP
1.030670	43.2	20.1	56.0	12.8	QP
1.160330	41.9	20.1	56.0	14.1	QP
0.565510	39.0	20.1	46.0	7	Ave.
0.600850	36.3	20.1	46.0	9.7	Ave.
0.857130	34.6	20.1	46.0	11.4	Ave.
0.971390	36.7	20.1	46.0	9.3	Ave.
1.030670	35.6	20.1	46.0	10.4	Ave.
1.160330	35.4	20.1	46.0	10.6	Ave.

Note:
1) Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
2) Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr}, if L_m is less than L_{lim}, it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	24 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-08.

EUT operation mode: Transmitting (*Scan with GFSK, π/4-DQPSK, 8-DPSK mode, the worst case was 8-DPSK mode)*

30 MHz - 1GHz: *(8-DPSK mode, Low channel)*



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
158.966625	30.78	213.0	H	271.0	-4.9	43.50	12.72
172.852125	32.89	223.0	H	268.0	-5.8	43.50	10.61
179.668375	29.39	191.0	H	266.0	-5.5	43.50	14.11
468.011375	42.82	107.0	H	269.0	1.2	46.00	3.18
624.004750	42.35	347.0	H	81.0	3.9	46.00	3.65
931.583500	30.74	258.0	V	248.0	8.7	46.00	15.26

1 GHz – 25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Correction Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
2402.00	63.16	PK	135	2.0	H	33.92	97.08	/	/
2402.00	53.01	Ave.	135	2.0	H	33.92	86.93	/	/
2402.00	62.04	PK	46	2.1	V	33.92	95.96	/	/
2402.00	51.12	Ave.	46	2.1	V	33.92	85.04	/	/
2358.89	27.74	PK	66	1.6	H	33.92	61.66	74	12.34
2358.89	13.85	Ave.	66	1.6	H	33.92	47.77	54	6.23
2380.94	27.60	PK	237	1.2	H	33.92	61.52	74	12.48
2380.94	13.86	Ave.	237	1.2	H	33.92	47.78	54	6.22
2486.93	26.89	PK	26	1.0	H	34.08	60.97	74	13.03
2486.93	13.33	Ave.	26	1.0	H	34.08	47.41	54	6.59
4804.00	45.69	PK	91	1.9	H	5.84	51.53	74	22.47
4804.00	31.27	Ave.	91	1.9	H	5.84	37.11	54	16.89
Middle Channel (2441 MHz)									
2441.00	63.28	PK	262	2.1	H	33.92	97.20	/	/
2441.00	53.07	Ave.	262	2.1	H	33.92	86.99	/	/
2441.00	62.21	PK	163	1.3	V	33.92	96.13	/	/
2441.00	51.83	Ave.	163	1.3	V	33.92	85.75	/	/
2384.46	27.58	PK	186	1.1	H	33.92	61.50	74	12.50
2384.46	13.81	Ave.	186	1.1	H	33.92	47.73	54	6.27
2370.76	27.55	PK	52	2.3	H	33.92	61.47	74	12.53
2370.76	13.84	Ave.	52	2.3	H	33.92	47.76	54	6.24
2491.40	27.20	PK	239	1.3	H	34.08	61.28	74	12.72
2491.40	13.31	Ave.	239	1.3	H	34.08	47.39	54	6.61
4882.00	45.30	PK	80	1.6	H	6.21	51.51	74	22.49
4882.00	30.33	Ave.	80	1.6	H	6.21	36.54	54	17.46

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2480 MHz)									
2480.00	63.02	PK	178	1.9	H	34.08	97.10	/	/
2480.00	52.81	Ave.	178	1.9	H	34.08	86.89	/	/
2480.00	60.91	PK	52	1.5	V	34.08	94.99	/	/
2480.00	50.35	Ave.	52	1.5	V	34.08	84.43	/	/
2383.34	27.79	PK	165	2.1	H	33.92	61.71	74	12.29
2383.34	13.83	Ave.	165	2.1	H	33.92	47.75	54	6.25
2483.53	27.31	PK	47	2.2	H	34.08	61.39	74	12.61
2483.53	14.31	Ave.	47	2.2	H	34.08	48.39	54	5.61
2483.58	28.27	PK	265	1.1	H	34.08	62.35	74	11.65
2483.58	14.37	Ave.	265	1.1	H	34.08	48.45	54	5.55
4960.00	44.71	PK	103	2.5	H	7.82	52.53	74	21.47
4960.00	29.93	Ave.	103	2.5	H	7.82	37.75	54	16.25

Note:
Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude = Corrected Factor + Reading
Margin = Limit - Corrected. Amplitude
The other spurious emission which is 20dB to the limit was not recorded.
And for the pre-scan is performed with the 2400-2483.5MHz band filter.

Pre-scan with 2480 MHz

Horizontal





Vertical


Marker 1 [T1]
RBW 1 MHz
RF Att 0 dB
Ref Lvl
50.73 dBµV
VBW 3 MHz
97 dBµV
4.91783567 GHz
SWT 98 ms
Unit dBµV
1 [T1] 50.73 dBµV
4.91783567 GHz
D1 74 dBµV
1MAX
1MA
TDF
Start 1 GHz
1.7 GHz/
Stop 18 GHz
Date: 8.NOV.2017 13:26:09


Marker 1 [T1]
RBW 1 MHz
RF Att 0 dB
Ref Lvl
57.07 dBµV
VBW 3 MHz
97 dBµV
24.88777555 GHz
SWT 40 ms
Unit dBµV
1 [T1] 57.07 dBµV
24.88777555 GHz
D1 74 dBµV
1MAX
1MA
TDF
Start 18 GHz
700 MHz/
Stop 25 GHz
Date: 8.NOV.2017 13:57:29

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-14.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	≥Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.000	0.615	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.618	Pass
	Adjacent	2442			
	High	2480	1.000	0.618	Pass
	Adjacent	2479			
EDR (π/4-DQPSK)	Low	2402	1.000	0.867	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.860	Pass
	Adjacent	2442			
	High	2480	1.000	0.860	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.000	0.853	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.860	Pass
	Adjacent	2442			
	High	2480	1.000	0.847	Pass
	Adjacent	2479			

Note: Limit = 20 dB bandwidth *2/3

BDR (GFSK): Low Channel



Date: 14.NOV.2017 15:12:31

BDR (GFSK): Middle Channel



Date: 14.NOV.2017 15:13:09

BDR (GFSK): High Channel



Date: 14.NOV.2017 15:13:48

EDR (π/4-DQPSK): Low Channel



Date: 14.NOV.2017 15:16:49

EDR (π/4-DQPSK): Middle Channel



Date: 14.NOV.2017 15:17:31

EDR (π/4-DQPSK): High Channel



Date: 14.NOV.2017 15:18:10

EDR (8DPSK): Low Channel



Date: 14.NOV.2017 15:14:36

EDR (8DPSK): Middle Channel



Date: 14.NOV.2017 15:15:18

EDR (8DPSK): High Channel



Date: 14.NOV.2017 15:15:57

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-14.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.922
	Middle	2441	0.927
	High	2480	0.927
EDR (π/4-DQPSK)	Low	2402	1.30
	Middle	2441	1.29
	High	2480	1.29
EDR (8DPSK)	Low	2402	1.28
	Middle	2441	1.29
	High	2480	1.27

BDR (GFSK): Low Channel



Date: 14.NOV.2017 14:53:41

BDR (GFSK): Middle Channel



Date: 14.NOV.2017 14:55:05

BDR (GFSK): High Channel



Date: 14.NOV.2017 14:56:12

EDR (π/4-DQPSK): Low Channel



Date: 14.NOV.2017 14:57:26

EDR (π/4-DQPSK): Middle Channel



Date: 14.NOV.2017 14:58:54

EDR (π/4-DQPSK): High Channel



Date: 14.NOV.2017 15:00:04

EDR (8DPSK): Low Channel



Date: 14.NOV.2017 15:04:18

EDR (8DPSK): Middle Channel



Date: 14.NOV.2017 15:03:23

EDR (8DPSK): High Channel



Date: 14.NOV.2017 15:01:11

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

2. Set the EUT in hopping mode from first channel to last.

3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-14.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels



Date: 14.NOV.2017 15:44:29

EDR (π/4-DQPSK): Number of Hopping Channels



Date: 14.NOV.2017 15:47:40

EDR (8DPSK): Number of Hopping Channels



Date: 14.NOV.2017 15:55:29

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	24~25 ℃
Relative Humidity:	52~53 %
ATM Pressure:	100.6~101.0 kPa

The testing was performed by Hill He on 2017-11-14 and 2017-12-16.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH 1	Low	0.420	0.134	0.4	Pass
		Middle	0.420	0.134	0.4	Pass
		High	0.420	0.134	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	DH 3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	DH 5	Low	2.936	0.313	0.4	Pass
		Middle	2.936	0.313	0.4	Pass
		High	2.936	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR (π/4-DQPSK)	2DH 1	Low	0.412	0.132	0.4	Pass
		Middle	0.412	0.132	0.4	Pass
		High	0.412	0.132	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	2DH 3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	2DH 5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.933	0.313	0.4	Pass
		Note:2DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				
EDR (8DPSK)	3DH 1	Low	0.415	0.133	0.4	Pass
		Middle	0.415	0.133	0.4	Pass
		High	0.415	0.133	0.4	Pass
		Note: 3DH1:Dwell time = Pulse time*(1600/2/79)*31.6s				
	3DH 3	Low	1.694	0.271	0.4	Pass
		Middle	1.694	0.271	0.4	Pass
		High	1.694	0.271	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6s				
	3DH 5	Low	2.943	0.314	0.4	Pass
		Middle	2.943	0.314	0.4	Pass
		High	2.943	0.314	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6s				

BDR (GFSK):
Pulse time, Low Channel, DH1



Date: 14.NOV.2017 15:28:30

Pulse time, Middle Channel, DH1



Date: 14.NOV.2017 15:29:17

Pulse time, High Channel, DH1



Date: 14.NOV.2017 15:29:35

Pulse time, Low Channel, DH3



Date: 14.NOV.2017 15:33:43

Pulse time, Middle Channel, DH3



Date: 14.NOV.2017 15:33:57

Pulse time, High Channel, DH3



Date: 14.NOV.2017 15:33:15

Pulse time, Low Channel, DH5



Date: 14.NOV.2017 15:37:37

Pulse time, Middle Channel, DH5



Date: 14.NOV.2017 15:38:09

Pulse time, High Channel, DH5



Date: 14.NOV.2017 15:38:28

EDR (π/4-DQPSK):
Pulse time, Low Channel, 2DH1



Date: 14.NOV.2017 15:30:18

Pulse time, Middle Channel, 2DH1



Date: 14.NOV.2017 15:30:43

Pulse time, High Channel, 2DH1



Date: 14.NOV.2017 15:30:57

Pulse time, Low Channel, 2DH3



Date: 14.NOV.2017 15:34:30

Pulse time, Middle Channel, 2DH3



Date: 14.NOV.2017 15:35:09

Pulse time, High Channel, 2DH3



Date: 14.NOV.2017 15:35:30

Pulse time, Low Channel, 2DH5



Date: 14.NOV.2017 15:41:43

Pulse time, Middle Channel, 2DH5



Date: 14.NOV.2017 15:39:29

Pulse time, High Channel, 2DH5



Date: 16.DEC.2017 09:48:04

EDR (8DPSK):
Pulse time, Low Channel, 3DH1



Date: 14.NOV.2017 15:31:35

Pulse time, Middle Channel, 3DH1



Date: 14.NOV.2017 15:32:02

Pulse time, High Channel, 3DH1



Date: 14.NOV.2017 15:32:16

Pulse time, Low Channel, 3DH3



Date: 14.NOV.2017 15:36:31

Pulse time, Middle Channel, 3DH3



Date: 14.NOV.2017 15:36:15

Pulse time, High Channel, 3DH3



Date: 14.NOV.2017 15:35:58

Pulse time, Low Channel, 3DH5



Date: 14.NOV.2017 15:39:57

Pulse time, Middle Channel, 3DH5



Date: 14.NOV.2017 15:40:13

Pulse time, High Channel, 3DH5



Date: 14.NOV.2017 15:40:24

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Hill He on 2017-11-14.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following table.

Mode	Channel	Frequency (MHz)	Peak Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	7.07	5.09	1000
	Middle	2441	7.42	5.52	1000
	High	2480	7.71	5.90	1000
EDR (π/4-DQPSK)	Low	2402	8.13	6.50	1000
	Middle	2441	8.56	7.18	1000
	High	2480	8.86	7.69	1000
EDR (8DPSK)	Low	2402	8.66	7.35	1000
	Middle	2441	8.95	7.85	1000
	High	2480	9.42	8.75	1000

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	23~25 ℃
Relative Humidity:	50~52 %
ATM Pressure:	100.6~101.0 kPa

The testing was performed by Hill He on 2017-11-14 and 2017-12-16.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following plots.

BDR (GFSK): Band Edge-Left Side

Hopping



Date: 16.DEC.2017 09:28:17

Single



Date: 14.NOV.2017 15:20:25

BDR (GFSK): Band Edge-Right Side

Hopping



Date: 16.DEC.2017 09:32:17

Single



Date: 14.NOV.2017 15:21:24

EDR (π/4-DQPSK): Band Edge-Left Side

Hopping



Date: 16.DEC.2017 09:38:34

Single



Date: 14.NOV.2017 15:23:44

EDR (π/4-DQPSK): Band Edge-Right Side

Hopping



Date: 16.DEC.2017 09:34:44

Single



Date: 14.NOV.2017 15:22:42

EDR (8DPSK): Band Edge-Left Side

Hopping



Date: 16.DEC.2017 09:41:12

Single



Date: 14.NOV.2017 15:24:37

EDR (8DPSK): Band Edge-Right Side

Hopping



Date: 16.DEC.2017 09:43:47

Single



Date: 14.NOV.2017 15:25:49

******* END OF REPORT *******