

## MEASUREMENT REPORT

### FCC PART 15.407 WLAN 802.11a/n/ac/ax

---

**FCC ID:** 2A19TOAW-AP136X

**APPLICANT:** ALE USA INC.

**Application Type:** Certification

**Product:** OmniAccess Stellar

**Modole No.:** OAW-AP1361, OAW-AP1361D, OAW-AP1362

**Brand Name:** Alcatel-Lucent   
Enterprise

**FCC Classification:** Unlicensed National Information Infrastructure (NII)

**FCC Rule Part(s):** Part15 Subpart E (Section 15.407)

**Test Procedure(s):** ANSI C63.10-2013, KDB 789033 D02v02r01,  
KDB 662911 D01v02r01


**Test Procedure(s):** ANSI C63.10-2013

**Test Date:** November 05, 2019 ~ March 10, 2020

**Reviewed By:**

  
( Sunny Sun )

**Approved By:**

  
(Robin Wu)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 789033. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

## Revision History

| Report No.    | Version | Description                                    | Issue Date | Note    |
|---------------|---------|------------------------------------------------|------------|---------|
| 1912RSU073-U4 | Rev. 01 | Initial Report                                 | 03-18-2020 | Invalid |
| 1912RSU073-U4 | Rev. 02 | Updated some description<br>with TCB's comment | 03-28-2020 | Valid   |

## CONTENTS

| Description                                               | Page      |
|-----------------------------------------------------------|-----------|
| <b>General Information .....</b>                          | <b>6</b>  |
| <b>1. INTRODUCTION .....</b>                              | <b>7</b>  |
| 1.1. Scope .....                                          | 7         |
| 1.2. MRT Test Location.....                               | 7         |
| <b>2. PRODUCT INFORMATION .....</b>                       | <b>8</b>  |
| 2.1. Feature of Equipment under Test.....                 | 8         |
| 2.2. Product Specification Subjective to this Report..... | 8         |
| 2.3. Working Frequencies for this report .....            | 9         |
| 2.4. Description of Available Antenna.....                | 10        |
| 2.5. Description of Antenna RF Port.....                  | 12        |
| 2.6. Test Mode.....                                       | 12        |
| 2.7. Description of Test Software .....                   | 12        |
| 2.8. Duty Cycle .....                                     | 13        |
| 2.9. EMI Suppression Device(s)/Modifications .....        | 14        |
| 2.10. Labeling Requirements .....                         | 14        |
| <b>3. DESCRIPTION OF TEST .....</b>                       | <b>15</b> |
| 3.1. Evaluation Procedure.....                            | 15        |
| 3.2. AC Line Conducted Emissions.....                     | 15        |
| 3.3. Radiated Emissions .....                             | 16        |
| <b>4. ANTENNA REQUIREMENTS .....</b>                      | <b>17</b> |
| <b>5. TEST EQUIPMENT CALIBRATION DATE .....</b>           | <b>18</b> |
| <b>6. MEASUREMENT UNCERTAINTY .....</b>                   | <b>20</b> |
| <b>7. TEST RESULT.....</b>                                | <b>21</b> |
| 7.1. Summary .....                                        | 21        |
| 7.2. 26dB Bandwidth Measurement.....                      | 22        |
| 7.2.1. Test Limit .....                                   | 22        |
| 7.2.2. Test Procedure used .....                          | 22        |
| 7.2.3. Test Setting.....                                  | 22        |
| 7.2.4. Test Setup.....                                    | 22        |
| 7.2.5. Test Result.....                                   | 23        |
| 7.3. 6dB Bandwidth Measurement .....                      | 32        |
| 7.3.1. Test Limit .....                                   | 32        |
| 7.3.2. Test Procedure used .....                          | 32        |

|        |                                                |     |
|--------|------------------------------------------------|-----|
| 7.3.3. | Test Setting .....                             | 32  |
| 7.3.4. | Test Setup.....                                | 32  |
| 7.3.5. | Test Result .....                              | 32  |
| 7.4.   | Output Power Measurement .....                 | 33  |
| 7.4.1. | Test Limit .....                               | 33  |
| 7.4.2. | Test Procedure Used .....                      | 33  |
| 7.4.3. | Test Setting .....                             | 34  |
| 7.4.4. | Test Setup.....                                | 34  |
| 7.4.5. | Test Result .....                              | 35  |
| 7.5.   | Transmit Power Control .....                   | 48  |
| 7.5.1. | Test Limit .....                               | 48  |
| 7.5.2. | Test Procedure Used .....                      | 48  |
| 7.5.3. | Test Setting .....                             | 48  |
| 7.5.4. | Test Setup.....                                | 48  |
| 7.5.5. | Test Result .....                              | 49  |
| 7.6.   | Power Spectral Density Measurement .....       | 51  |
| 7.6.1. | Test Limit .....                               | 51  |
| 7.6.2. | Test Procedure Used .....                      | 51  |
| 7.6.3. | Test Setting .....                             | 52  |
| 7.6.4. | Test Setup.....                                | 52  |
| 7.6.5. | Test Result .....                              | 53  |
| 7.7.   | Frequency Stability Measurement.....           | 175 |
| 7.7.1. | Test Limit .....                               | 175 |
| 7.7.2. | Test Procedure Used .....                      | 175 |
| 7.7.3. | Test Setup.....                                | 176 |
| 7.7.4. | Test Result .....                              | 176 |
| 7.8.   | Radiated Spurious Emission Measurement .....   | 177 |
| 7.8.1. | Test Limit .....                               | 177 |
| 7.8.2. | Test Procedure Used .....                      | 177 |
| 7.8.3. | Test Setting .....                             | 177 |
| 7.8.4. | Test Setup.....                                | 179 |
| 7.8.5. | Test Result .....                              | 180 |
| 7.9.   | Radiated RestrictedBand Edge Measurement ..... | 329 |
| 7.9.1. | Test Limit .....                               | 329 |
| 7.9.2. | Test Procedure Used .....                      | 330 |
| 7.9.3. | Test Setting .....                             | 330 |
| 7.9.4. | Test Setup.....                                | 331 |
| 7.9.5. | Test Result .....                              | 332 |
| 7.10.  | AC Conducted Emissions Measurement.....        | 610 |

|                                                |            |
|------------------------------------------------|------------|
| 7.10.1. Test Limit .....                       | 610        |
| 7.10.2. Test Setup.....                        | 610        |
| 7.10.3. Test Result.....                       | 610        |
| <b>8. CONCLUSION.....</b>                      | <b>611</b> |
| <b>Appendix A – Test Setup Photograph.....</b> | <b>612</b> |
| <b>Appendix B – EUT Photograph .....</b>       | <b>613</b> |

## General Information

|                                |                                                                                                                                 |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Applicant:</b>              | ALE USA INC.                                                                                                                    |
| <b>Applicant Address:</b>      | 26801 WEST AGOURA ROAD, CALABASAS, CA 91301, USA                                                                                |
| <b>Manufacturer:</b>           | ALE USA INC.                                                                                                                    |
| <b>Manufacturer Address:</b>   | 26801 WEST AGOURA ROAD, CALABASAS, CA 91301, USA                                                                                |
| <b>Test Site:</b>              | MRT Technology (Suzhou) Co., Ltd                                                                                                |
| <b>Test Site Address:</b>      | D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China                                              |
| <b>Test Device Serial No.:</b> | N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering |

## Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC accredited (MRT Designation No. CN1166) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LACert. No.3628.01) in EMC, Telecommunications, Radio and SAR testing.



## 1. INTRODUCTION

### 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

### 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The measurement facility compliant with the test site requirements specified in ANSI C63.4-2014.



## 2. PRODUCT INFORMATION

### 2.1. Feature of Equipment under Test

|                          |                                                                                                                |
|--------------------------|----------------------------------------------------------------------------------------------------------------|
| Product Name:            | OmniAccess Stellar                                                                                             |
| Module No.:              | OAW-AP1361, OAW-AP1361D, OAW-AP1362                                                                            |
| Brand Name:              | Alcatel-Lucent <br>Enterprise |
| Wi-Fi Specification:     | 802.11a/b/g/n/ax                                                                                               |
| Bluetooth Specification: | v5.1 single mode                                                                                               |
| Operating Temperature:   | -40 ~ 65 °C                                                                                                    |
| Power Type:              | PoE input                                                                                                      |
| Operating Environment:   | Outdoor Use                                                                                                    |
| Accessories              |                                                                                                                |
| Adapter                  | Model No.: PD-9501GC/AC<br>Input Power: 100 - 240V ~ 50/60Hz, 1.5A<br>Output Power: 55VDC/1.1A                 |

Note 1: The difference between models is that EUT use different antennas and appearances, other hardware and software are the same.

Note 2: The adapter is not for sale together with AP.

### 2.2. Product Specification Subjective to this Report

|                     |                                                                                                                                                                                                                                                                                               |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range:    | For 802.11a/n-HT20/ac-VHT20/ax-HE20:<br>5260~5320MHz, 5500~5720MHz<br>For 802.11n-HT40/ac-VHT40/ax-HE40:<br>5270~5310MHz, 5510~5710MHz<br>For 802.11ac-VHT80/ax-HE80:<br>5290MHz, 5530MHz, 5610 MHz, 5690 MHz<br>For 802.11ac-VHT80 + 80/ax-HE80 + 80:<br>5210MHz, 5290MHz, 5530MHz, 5610 MHz |
| Type of Modulation: | 802.11a/n/ac: OFDM; 802.11ax: OFDMA                                                                                                                                                                                                                                                           |
| Data Rate:          | 802.11a: 6/9/12/18/24/36/48/54Mbps<br>802.11n: up to 300Mbps<br>802.11ac: up to 1733.3Mbps<br>802.11ax: up to 2402Mbps                                                                                                                                                                        |

Note: For other features of this EUT, test report will be issued separately.

### 2.3. Working Frequencies for this report

802.11a/n/ac-VHT20/ax-HE20

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 52      | 5260 MHz  | 56      | 5280 MHz  | 60      | 5300 MHz  |
| 64      | 5320 MHz  | 100     | 5500 MHz  | 104     | 5520 MHz  |
| 108     | 5540 MHz  | 112     | 5560 MHz  | 116     | 5580 MHz  |
| 120     | 5600 MHz  | 124     | 5620 MHz  | 128     | 5640 MHz  |
| 132     | 5660 MHz  | 136     | 5680 MHz  | 140     | 5700 MHz  |
| 144     | 5720 MHz  | --      | --        | --      | --        |

802.11n-HT40/ac-VHT40/ax-HE40

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 54      | 5270 MHz  | 62      | 5310 MHz  | 102     | 5510 MHz  |
| 110     | 5550 MHz  | 118     | 5590 MHz  | 126     | 5630 MHz  |
| 134     | 5670 MHz  | 142     | 5710 MHz  | --      | --        |

802.11ac-VHT80/ax-HE80

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 58      | 5290 MHz  | 106     | 5530 MHz  | 122     | 5610 MHz  |
| 138     | 5690 MHz  | --      | --        | --      | --        |

802.11ac-VHT80 + 80/ax-HE80 + 80

| Channel | Frequency | Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|---------|-----------|
| 42      | 5210 MHz  | 58      | 5290 MHz  | 106     | 5530 MHz  |
| 122     | 5610 MHz  | --      | --        | --      | --        |

## 2.4. Description of Available Antenna

Model No.: OAW-AP1361

| Antenna Type                                                 | Frequency Band (GHz)               | Tx Paths                           | Bandwidth (MHz) | Max Peak Gain (dBi) |       |                     |       | Directional Gain (dBi) |             |
|--------------------------------------------------------------|------------------------------------|------------------------------------|-----------------|---------------------|-------|---------------------|-------|------------------------|-------------|
|                                                              |                                    |                                    |                 | Ant 0               | Ant 1 | Ant 2               | Ant 3 | CDD                    | Beamforming |
| Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO) |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Omni Antenna                                                 | 2400 ~ 2483.5                      | 2                                  | 20, 40          | 4.72                | 4.85  | --                  | --    | 4.85                   | 7.86        |
|                                                              | 5150 ~ 5850                        | 4                                  | 20, 40, 80      | 6.48                | 6.31  | 6.26                | 6.12  | 6.48                   | 12.50       |
|                                                              | 5150 ~ 5250<br>30° elevation angle | 4                                  | 20, 40, 80      | -5.46               | -4.22 | -2.90               | -3.84 | --                     |             |
| Bluetooth Internal Antenna                                   |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     |       | Max Peak Gain (dBi) |       |                        |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     |       | 4.64                |       |                        |             |
| Scan Antenna                                                 |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     |       | Max Peak Gain (dBi) |       |                        |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     |       | 4.58                |       |                        |             |
|                                                              |                                    | 5150 ~ 5850                        |                 |                     |       | 6.00                |       |                        |             |
|                                                              |                                    | 5150 ~ 5250<br>30° elevation angle |                 |                     |       | -5.83               |       |                        |             |

Model No.: OAW-AP1361D

| Antenna Type                                                 | Frequency Band (GHz)               | Tx Paths                           | Bandwidth (MHz) | Max Peak Gain (dBi) |       |                     |       | Directional Gain (dBi) |             |
|--------------------------------------------------------------|------------------------------------|------------------------------------|-----------------|---------------------|-------|---------------------|-------|------------------------|-------------|
|                                                              |                                    |                                    |                 | Ant 0               | Ant 1 | Ant 2               | Ant 3 | CDD                    | Beamforming |
| Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO) |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Directional Antenna                                          | 2400 ~ 2483.5                      | 2                                  | 20, 40          | 7.5                 | 7.0   | --                  | --    | 7.5                    | 10.51       |
|                                                              | 5150 ~ 5850                        | 4                                  | 20, 40, 80      | 7.4                 | 7.0   | 6.9                 | 7.2   | 7.4                    | 13.42       |
|                                                              | 5150 ~ 5250<br>30° elevation angle | 4                                  | 20, 40, 80      | 3.12                | 2.98  | 3.24                | 3.65  | --                     |             |
| Bluetooth Internal Antenna                                   |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     |       | Max Peak Gain (dBi) |       |                        |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     |       | 3.30                |       |                        |             |
| Scan Antenna                                                 |                                    |                                    |                 |                     |       |                     |       |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     |       | Max Peak Gain (dBi) |       |                        |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     |       | 7.20                |       |                        |             |
|                                                              |                                    | 5150 ~ 5850                        |                 |                     |       | 9.40                |       |                        |             |
|                                                              |                                    | 5150 ~ 5250<br>30° elevation angle |                 |                     |       | 2.88                |       |                        |             |

Model No.: OAW-AP1362

| Antenna Type                                                 | Frequency Band (GHz)               | Tx Paths                           | Bandwidth (MHz) | Max Peak Gain (dBi) | Directional Gain (dBi) |             |
|--------------------------------------------------------------|------------------------------------|------------------------------------|-----------------|---------------------|------------------------|-------------|
|                                                              |                                    |                                    |                 |                     | CDD                    | Beamforming |
| Wi-Fi Internal Antenna List (2.4GHz 2*2 MIMO, 5GHz 4*4 MIMO) |                                    |                                    |                 |                     |                        |             |
| Omni Antenna                                                 | 2400 ~ 2483.5                      | 2                                  | 20, 40          | 5                   | 5                      | 8.01        |
|                                                              | 5150 ~ 5850                        | 4                                  | 20, 40, 80      | 7                   | 7                      | 13.02       |
|                                                              | 5150 ~ 5250<br>30° elevation angle | 4                                  | 20, 40, 80      | -0.3                | --                     |             |
| Bluetooth Internal Antenna                                   |                                    |                                    |                 |                     |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     | Max Peak Gain (dBi)    |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     | 4.06                   |             |
| Scan Antenna                                                 |                                    |                                    |                 |                     |                        |             |
| Antenna Type                                                 |                                    | Frequency Band (GHz)               |                 |                     | Max Peak Gain (dBi)    |             |
| Omni Antenna                                                 |                                    | 2400 ~ 2483.5                      |                 |                     | 4.58                   |             |
|                                                              |                                    | 5150 ~ 5850                        |                 |                     | 6.00                   |             |
|                                                              |                                    | 5150 ~ 5250<br>30° elevation angle |                 |                     | 2.88                   |             |

Note 1: The EUT supports Cyclic Delay Diversity (CDD) technology for 802.11a/b/g/n/ac/ax and Beam Forming technology for 802.11n/ac/ax.

Note 2: When the EUT supports Cyclic Delay Diversity (CDD) and it is correlated.

If all antennas have the same gain,  $G_{ANT}$ , Directional gain =  $G_{ANT} + \text{Array Gain}$ , where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,

$$\text{Array Gain} = 10 \log (N_{ANT} / N_{SS}) \text{ dB} = 3.01;$$

- For power measurements on IEEE 802.11 devices,


$$\text{Array Gain} = 0 \text{ dB for } N_{ANT} \leq 4;$$

If antenna gains are not equal, Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain.

Note 3: The EUT also supports Beam Forming mode, Directional gain =  $G_{ANT} + 10 \log(N_{ANT}/N_{SS})$  dBi, Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain.

## 2.5. Description of Antenna RF Port

| Antenna RF Port       |                |       |              |       |       |       |              |             |
|-----------------------|----------------|-------|--------------|-------|-------|-------|--------------|-------------|
| --                    | 2.4GHz RF Port |       | 5GHz RF Port |       |       |       | Scan RF Port | BLE RF Port |
| Software Control Port | Ant 0          | Ant 1 | Ant 0        | Ant 1 | Ant 2 | Ant 3 | Ant 0        | Ant 0       |



The photograph shows the internal components of the antenna RF port assembly. A green rectangular area is overlaid on the image, with red arrows pointing to specific ports. The labels are as follows:

- Scan RF Port 0
- BLE RF Port 0
- 2.4GHz Wi-Fi RF Port 1
- 2.4GHz Wi-Fi RF Port 0
- 5GHz Wi-Fi RF Port 3
- 5GHz Wi-Fi RF Port 2
- 5GHz Wi-Fi RF Port 1
- 5GHz Wi-Fi RF Port 0

## 2.6. Test Mode

|           |                                               |
|-----------|-----------------------------------------------|
| Test Mode | Mode 1: Transmit by 802.11a (6Mbps)           |
|           | Mode 2: Transmit by 802.11n-HT20 (MSC0)       |
|           | Mode 3: Transmit by 802.11n-HT40 (MSC0)       |
|           | Mode 4: Transmit by 802.11ax-HE20 (MSC0)      |
|           | Mode 5: Transmit by 802.11ax-HE40 (MSC0)      |
|           | Mode 6: Transmit by 802.11ax-HE80 (MSC0)      |
|           | Mode 7: Transmit by 802.11ax-HE80 + 80 (MSC0) |

## 2.7. Description of Test Software

The test utility software used during testing was “QSPR”, and the version was “v50-00170”.

## 2.8. Duty Cycle

5GHz (NII) operation is possible in 20MHz, 40MHz, 80MHz and 80 + 80 channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = average. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

| Model No.:   | Test Mode      | Duty Cycle |
|--------------|----------------|------------|
| OAW-AP1361   | 802.11a        | 92.19%     |
|              | 802.11n-HT20   | 94.76%     |
|              | 802.11n-HT40   | 91.62%     |
|              | 802.11ac-VHT20 | 95.01%     |
|              | 802.11ac-VHT40 | 93.79%     |
|              | 802.11ac-VHT80 | 90.25%     |
|              | 802.11ax-HE20  | 93.56%     |
|              | 802.11ax-HE40  | 94.76%     |
|              | 802.11ax-HE80  | 94.26%     |
| OAW-AP1361D  | 802.11a        | 92.14%     |
|              | 802.11n-HT20   | 95.80%     |
|              | 802.11n-HT40   | 93.70%     |
|              | 802.11ac-VHT20 | 94.76%     |
|              | 802.11ac-VHT40 | 93.58%     |
|              | 802.11ac-VHT80 | 90.02%     |
|              | 802.11ax-HE20  | 95.77%     |
|              | 802.11ax-HE40  | 95.41%     |
|              | 802.11ax-HE80  | 94.49%     |
| Scan Antenna | 802.11a        | 96.20%     |
| OAW-AP1362   | 802.11a        | 92.26%     |
|              | 802.11n-HT20   | 95.01%     |
|              | 802.11n-HT40   | 91.60%     |
|              | 802.11ac-VHT20 | 95.01%     |
|              | 802.11ac-VHT40 | 93.73%     |
|              | 802.11ac-VHT80 | 93.52%     |
|              | 802.11ax-HE20  | 95.03%     |
|              | 802.11ax-HE40  | 96.02%     |
|              | 802.11ax-HE80  | 94.27%     |

## **2.9. EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added and/or no modifications were made during testing.

## **2.10. Labeling Requirements**

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### **3. DESCRIPTION OF TEST**

#### **3.1. Evaluation Procedure**

The measurement procedure described in the document titled “American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices” (ANSI C63.10-2013) was used in the measurement.

#### **3.2. AC Line Conducted Emissions**

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

## **4. ANTENNA REQUIREMENTS**

### **Excerpt from §15.203 of the FCC Rules/Regulations:**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

### **Conclusion:**

The product is defined as the professional installation of equipment by the manufacturer, there is no necessary to comply with the requirement of §15.203.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions - SR2

| Instrument         | Manufacturer | Type No.    | Asset No.   | Cali. Interval | Cali. Due Date |
|--------------------|--------------|-------------|-------------|----------------|----------------|
| EMI Test Receiver  | R&S          | ESR3        | MRTSUE06185 | 1 year         | 2020/04/15     |
| Two-Line V-Network | R&S          | ENV 216     | MRTSUE06002 | 1 year         | 2020/06/13     |
| Two-Line V-Network | R&S          | ENV 216     | MRTSUE06003 | 1 year         | 2020/06/13     |
| Thermohygrometer   | Testo        | 608-H1      | MRTSUE06404 | 1 year         | 2020/08/08     |
| Shielding Room     | MIX-BEP      | Chamber-SR2 | MRTSUE06215 | N/A            | N/A            |

### Radiated Emissions - AC1

| Instrument                 | Manufacturer | Type No.    | Asset No.   | Cali. Interval | Cali. Due Date |
|----------------------------|--------------|-------------|-------------|----------------|----------------|
| EMI Test Receiver          | R&S          | ESR7        | MRTSUE06001 | 1 year         | 2020/08/01     |
| PXA Signal Analyzer        | Keysight     | 9030B       | MRTSUE06395 | 1 year         | 2020/09/03     |
| Loop Antenna               | Schwarzbeck  | FMZB 1519   | MRTSUE06025 | 1 year         | 2019/11/13     |
|                            |              |             |             | 1 year         | 2020/11/13     |
| Bilog Period Antenna       | Schwarzbeck  | VULB 9168   | MRTSUE06172 | 1 year         | 2020/03/31     |
| Broad Band Horn Antenna    | Schwarzbeck  | BBHA 9120D  | MRTSUE06023 | 1 year         | 2020/10/13     |
| Broad Band Horn Antenna    | Schwarzbeck  | BBHA 9170   | MRTSUE06024 | 1 year         | 2020/12/17     |
| Microwave System Amplifier | Agilent      | 83017A      | MRTSUE06076 | 1 year         | 2020/11/15     |
| Preamplifier               | Schwarzbeck  | BBV 9721    | MRTSUE06121 | 1 year         | 2020/06/11     |
| Thermohygrometer           | Testo        | 608-H1      | MRTSUE06403 | 1 year         | 2020/08/08     |
| Anechoic Chamber           | TDK          | Chamber-AC1 | MRTSUE06212 | 1 year         | 2020/04/30     |

### Radiated Emission - AC2

| Instrument                     | Manufacturer | Type No.    | Asset No.   | Cali. Interval | Cali. Due Date |
|--------------------------------|--------------|-------------|-------------|----------------|----------------|
| Spectrum Analyzer              | Keysight     | N9038A      | MRTSUE06125 | 1 year         | 2020/08/01     |
| Loop Antenna                   | Schwarzbeck  | FMZB 1519   | MRTSUE06025 | 1 year         | 2019/11/13     |
|                                |              |             |             | 1 year         | 2020/11/13     |
| Bilog Period Antenna           | Schwarzbeck  | VULB 9162   | MRTSUE06022 | 1 year         | 2020/10/13     |
| Horn Antenna                   | Schwarzbeck  | BBHA9120D   | MRTSUE06171 | 1 year         | 2020/10/27     |
| Broad Band Horn Antenna        | Schwarzbeck  | BBHA 9170   | MRTSUE06024 | 1 year         | 2020/12/17     |
| Broadband Coaxial Preamplifier | Schwarzbeck  | BBV 9718    | MRTSUE06176 | 1 year         | 2020/11/15     |
| Preamplifier                   | Schwarzbeck  | BBV 9721    | MRTSUE06121 | 1 year         | 2020/06/11     |
| Temperature/Humidity Meter     | Minggao      | ETH529      | MRTSUE06170 | 1 year         | 2020/12/13     |
| Anechoic Chamber               | RIKEN        | Chamber-AC2 | MRTSUE06213 | 1 year         | 2020/04/30     |

## Conducted Test Equipment - TR3

| Instrument                             | Manufacturer | Type No.    | Asset No.   | Cali. Interval | Cali. Due Date |
|----------------------------------------|--------------|-------------|-------------|----------------|----------------|
| EXA Signal Analyzer                    | Agilent      | N9020A      | MRTSUE06106 | 1 year         | 2020/04/15     |
| EXA Signal Analyzer                    | Keysight     | N9010B      | MRTSUE06452 | 1 year         | 2020/07/11     |
| Signal Analyzer                        | R&S          | FSV40       | MRTSUE06218 | 1 year         | 2020/04/15     |
| Power Meter                            | Agilent      | U2021XA     | MRTSUE06030 | 1 year         | 2020/11/18     |
| USB wideband power sensor              | Keysight     | U2021XA     | MRTSUE06446 | 1 year         | 2020/06/30     |
| USB wideband power sensor              | Keysight     | U2021XA     | MRTSUE06447 | 1 year         | 2020/06/30     |
| Bluetooth Test Set                     | Anritsu      | MT8852B-042 | MRTSUE06389 | 1 year         | 2020/06/13     |
| Audio Analyzer                         | Agilent      | U8903B      | MRTSUE06143 | 1 year         | 2020/06/13     |
| Modulation Analyzer                    | HP           | 8901A       | MRTSUE06098 | 1 year         | 2020/10/10     |
| Wideband Radio<br>Communication Tester | R&S          | CMW 500     | MRTSUE06243 | 1 year         | 2020/11/07     |
| DC Power Supply                        | GWINSTEK     | DPS-3303C   | MRTSUE06064 | N/A            | N/A            |
| Temperature & Humidity<br>Chamber      | BAOYT        | BYH-150CL   | MRTSUE06051 | 1 year         | 2020/11/07     |
| Thermohygrometer                       | testo        | 608-H1      | MRTSUE06401 | 1 year         | 2020/08/08     |

| Software     | Version | Function          |
|--------------|---------|-------------------|
| EMI Software | V3      | EMI Test Software |

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

| Conducted Emission Measurement - SR2                 |                      |
|------------------------------------------------------|----------------------|
| The maximum measurement uncertainty is evaluated as: |                      |
| 9kHz~150kHz: 3.84dB                                  |                      |
| 150kHz~30MHz: 3.46dB                                 |                      |
| Radiated Emission Measurement - AC1                  |                      |
| The maximum measurement uncertainty is evaluated as: |                      |
| Horizontal:                                          | 30MHz~300MHz: 4.07dB |
|                                                      | 300MHz~1GHz: 3.63dB  |
|                                                      | 1GHz~18GHz: 4.16dB   |
| Vertical:                                            | 30MHz~300MHz: 4.18dB |
|                                                      | 300MHz~1GHz: 3.60dB  |
|                                                      | 1GHz~18GHz: 4.76dB   |
| Radiated Emission Measurement - AC2                  |                      |
| The maximum measurement uncertainty is evaluated as: |                      |
| Horizontal:                                          | 30MHz~300MHz: 3.75dB |
|                                                      | 300MHz~1GHz: 3.53dB  |
|                                                      | 1GHz~18GHz: 4.28dB   |
| Vertical:                                            | 30MHz~300MHz: 3.86dB |
|                                                      | 300MHz~1GHz: 3.53dB  |
|                                                      | 1GHz~18GHz: 4.33dB   |

## 7. TEST RESULT

### 7.1. Summary

| FCC Section(s)                           | Test Description                                                              | Test Limit                                                                     | Test Condition | Test Result | Reference          |
|------------------------------------------|-------------------------------------------------------------------------------|--------------------------------------------------------------------------------|----------------|-------------|--------------------|
| 15.407(a)                                | 26dB Bandwidth                                                                | N/A                                                                            | Conducted      | Pass        | Section 7.2        |
| 15.407(e)                                | 6dB Bandwidth                                                                 | $\geq 500\text{kHz}$                                                           |                | N/A         | Section 7.3        |
| 15.407(a)(1)(ii), (2)                    | Maximum Conducted Output Power                                                | Refer to Section 7.5                                                           |                | Pass        | Section 7.5        |
| 15.407(h)(1)                             | Transmit Power Control                                                        | $\leq 24\text{ dBm}$                                                           |                | Pass        | Section 7.6        |
| 15.407(a)(1)(ii), (2)                    | Peak Power Spectral Density                                                   | Refer to Section 7.7                                                           |                | Pass        | Section 7.7        |
| 15.407(g)                                | Frequency Stability                                                           | $\pm 20\text{ ppm}$                                                            |                | N/A         | Section 7.8        |
| 15.407(b)(1), (2), (3)                   | Undesirable Emissions                                                         | Refer to Section 7.9 & 7.10                                                    | Radiated       | Pass        | Section 7.9 & 7.10 |
| 15.205, 15.209<br>15.407(b)(5), (6), (7) | General Field Strength Limits (Restricted Bands and Radiated Emission Limits) | Emissions in restricted bands must meet the radiated limits detailed in 15.209 |                | Pass        |                    |
| 15.207                                   | AC Conducted Emissions<br>150kHz - 30MHz                                      | $< \text{FCC } 15.207\text{ limits}$                                           | Line Conducted | Pass        | Section 7.11       |

Notes:

- 1) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 3) The difference between models is that EUT use different antennas and appearances, other hardware and software are the same, so we only use the OAW-AP1361 to perform all conducted tests. Test Items "26dB Bandwidth", "6dB Bandwidth" have been assessed MIMO transmission, and showed the worst test data in this report.
- 4) Test Item "Radiated Spurious Emission" have been showed the worst beam-forming test data in this report.
- 5) We have evaluated 802.11a/n/ac/ax mode and showed the test data of 802.11a/n/ax mode.

## 7.2. 26dB Bandwidth Measurement

### 7.2.1. Test Limit

N/A


### 7.2.2. Test Procedure used

KDB 789033 D02v02r01-Section C.1

### 7.2.3. Test Setting

1. The analyzers' automatic bandwidth measurement capability was used to perform the 26dB bandwidth measurement. The "X" dB bandwidth parameter was set to  $X = 26$ . The automatic bandwidth measurement function also has the capability of simultaneously measuring the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediated power nulls in the fundamental emission.
2. RBW = approximately 1% of the emission bandwidth.
3. VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.

### 7.2.4. Test Setup



### 7.2.5.Test Result

|               |                    |                   |                         |
|---------------|--------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar | Temperature       | 24 ~ 25°C               |
| Test Engineer | Eric Xu            | Relative Humidity | 48 ~ 56%                |
| Test Site     | TR3                | Test Date         | 2019/11/28 ~ 2019/12/13 |
| Model No.     | OAW-AP1361         | Test Item         | 26dB Bandwidth          |

| Test Mode                 | Data Rate/<br>MCS | Channel No. | Frequency<br>(MHz) | 26dB Bandwidth<br>(MHz) |
|---------------------------|-------------------|-------------|--------------------|-------------------------|
| Ant 0 / Ant 0 + 1 + 2 + 3 |                   |             |                    |                         |
| 802.11a                   | 6Mbps             | 52          | 5260               | 19.37                   |
| 802.11a                   | 6Mbps             | 60          | 5300               | 19.00                   |
| 802.11a                   | 6Mbps             | 64          | 5320               | 19.20                   |
| 802.11a                   | 6Mbps             | 100         | 5500               | 19.15                   |
| 802.11a                   | 6Mbps             | 120         | 5600               | 19.12                   |
| 802.11a                   | 6Mbps             | 140         | 5700               | 19.29                   |
| 802.11a                   | 6Mbps             | 144         | 5720               | 19.28                   |
| 802.11n-HT20              | MCS0              | 52          | 5260               | 20.33                   |
| 802.11n-HT20              | MCS0              | 60          | 5300               | 20.44                   |
| 802.11n-HT20              | MCS0              | 64          | 5320               | 20.24                   |
| 802.11n-HT20              | MCS0              | 100         | 5500               | 20.10                   |
| 802.11n-HT20              | MCS0              | 120         | 5600               | 19.96                   |
| 802.11n-HT20              | MCS0              | 140         | 5700               | 20.33                   |
| 802.11n-HT20              | MCS0              | 144         | 5720               | 20.28                   |
| 802.11n-HT40              | MCS0              | 54          | 5270               | 39.96                   |
| 802.11n-HT40              | MCS0              | 62          | 5310               | 39.98                   |
| 802.11n-HT40              | MCS0              | 102         | 5510               | 40.33                   |
| 802.11n-HT40              | MCS0              | 118         | 5590               | 40.04                   |
| 802.11n-HT40              | MCS0              | 134         | 5670               | 39.67                   |
| 802.11n-HT40              | MCS0              | 142         | 5710               | 40.10                   |
| 802.11ax-HE20             | MCS0              | 52          | 5260               | 20.87                   |
| 802.11ax-HE20             | MCS0              | 60          | 5300               | 20.79                   |
| 802.11ax-HE20             | MCS0              | 64          | 5320               | 20.83                   |
| 802.11ax-HE20             | MCS0              | 100         | 5500               | 20.92                   |
| 802.11ax-HE20             | MCS0              | 120         | 5600               | 20.75                   |
| 802.11ax-HE20             | MCS0              | 140         | 5700               | 21.32                   |
| 802.11ax-HE20             | MCS0              | 144         | 5720               | 20.50                   |


| Test Mode                 | Data Rate/<br>MCS | Channel No. | Frequency<br>(MHz) | 26dB Bandwidth<br>(MHz) |
|---------------------------|-------------------|-------------|--------------------|-------------------------|
| Ant 0 / Ant 0 + 1 + 2 + 3 |                   |             |                    |                         |
| 802.11ax-HE40             | MCS0              | 54          | 5270               | 40.45                   |
| 802.11ax-HE40             | MCS0              | 62          | 5310               | 40.80                   |
| 802.11ax-HE40             | MCS0              | 102         | 5510               | 41.05                   |
| 802.11ax-HE40             | MCS0              | 118         | 5590               | 40.41                   |
| 802.11ax-HE40             | MCS0              | 134         | 5670               | 40.40                   |
| 802.11ax-HE40             | MCS0              | 142         | 5710               | 40.44                   |
| 802.11ax-HE80             | MCS0              | 58          | 5290               | 81.22                   |
| 802.11ax-HE80             | MCS0              | 106         | 5530               | 82.22                   |
| 802.11ax-HE80             | MCS0              | 122         | 5610               | 82.19                   |
| 802.11ax-HE80             | MCS0              | 138         | 5690               | 81.72                   |
| 802.11ax-HE80 + 80        | MCS0              | 42          | 5210               | 88.24                   |
|                           |                   | 58          | 5290               | 126.0                   |
| 802.11ax-HE80 + 80        | MCS0              | 106         | 5530               | 88.59                   |
|                           |                   | 122         | 5610               | 91.41                   |

## 802.11a 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 52 (5260MHz)



## Channel 60 (5300MHz)




## Channel 64 (5320MHz)




## Channel 100 (5500MHz)




## Channel 120 (5600MHz)



## Channel 140 (5700MHz)



## Channel 144 (5720MHz)




## 802.11n-HT20 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 52 (5260MHz)



## Channel 60 (5300MHz)




## Channel 64 (5320MHz)




## Channel 100 (5500MHz)




## Channel 120 (5600MHz)



## Channel 140 (5700MHz)




## Channel 144 (5720MHz)




## 802.11n-HT40 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 54 (5270MHz)




## Channel 62 (5310MHz)




## Channel 102 (5510MHz)




## Channel 118 (5590MHz)



## Channel 134 (5670MHz)




## Channel 142 (5710MHz)




## 802.11ax-HE20 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 52 (5260MHz)




## Channel 60 (5300MHz)




## Channel 64 (5320MHz)




## Channel 100 (5500MHz)




## Channel 120 (5600MHz)



## Channel 140 (5700MHz)




## Channel 144 (5720MHz)




## 802.11ax-HE40 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 54 (5270MHz)




## Channel 62 (5310MHz)




## Channel 102 (5510MHz)




## Channel 118 (5590MHz)



## Channel 134 (5670MHz)




## Channel 142 (5710MHz)




## 802.11ax-HE80 26dB &amp; 99% Bandwidth - Ant 0 / Ant 0 + 1 + 2 + 3


## Channel 58 (5290MHz)




## Channel 106 (5530MHz)



## Channel 122 (5610MHz)




## Channel 138 (5690MHz)




## 802.11ax-HE80 + 80 26dB &amp; 99% Bandwidth

## Channel 42 (5210MHz)




## Channel 58 (5290MHz)



## Channel 106 (5530MHz)



## Channel 122 (5610MHz)



### 7.3. 6dB Bandwidth Measurement

#### 7.3.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


#### 7.3.2. Test Procedure used

KDB 789033 D02v02r01 - Section C.2

#### 7.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. VBW  $\geq 3 \times$  RBW.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 7.3.4. Test Setup



#### 7.3.5. Test Result

The test item is not required for systems operating in frequency band 5250-5350MHz & 5470-5725MHz.

## 7.4. Output Power Measurement

### 7.4.1. Test Limit

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (23.98dBm) or 11dBm +10 log (26dB BW).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

| Frequency Band<br>(MHz) | Per Chain Max Antenna Gain (dBi) |       |       |       | Directional Gain (dBi) |             | Limit (dBm) |             |
|-------------------------|----------------------------------|-------|-------|-------|------------------------|-------------|-------------|-------------|
|                         | Ant 0                            | Ant 1 | Ant 2 | Ant 3 | CDD                    | Beamforming | CDD         | Beamforming |
| OAW-AP1361              |                                  |       |       |       |                        |             |             |             |
| 5250 ~ 5725             | 6.48                             | 6.31  | 6.26  | 6.12  | 6.48                   | 12.50       | 23.50       | 17.48       |
| OAW-AP1361D             |                                  |       |       |       |                        |             |             |             |
| 5250 ~ 5725             | 7.4                              | 7.0   | 6.9   | 7.2   | 7.4                    | 13.42       | 22.58       | 16.56       |
| OAW-AP1362              |                                  |       |       |       |                        |             |             |             |
| 5250 ~ 5725             | 7                                |       |       |       | 7                      | 13.02       | 22.98       | 16.96       |


### 7.4.2. Test Procedure Used

KDB 789033D02v01r04- Section E)3)b) Method PM-G

### 7.4.3.Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### 7.4.4.Test Setup



#### 7.4.5.Test Result

Power output test was verified over all data rates of each mode shown as below table, and then choose the maximum power output (gray marker) for final test of each channel.

Output power at various data rates for Ant 0 / Ant 0 + 1 + 2 + 3 port:

| Test Mode | Bandwidth | Channel | Frequency (MHz) | Data Rate/ MCS | Average Power (dBm) |
|-----------|-----------|---------|-----------------|----------------|---------------------|
| 802.11a   | 20        | 52      | 5260            | 6Mbps          | 8.10                |
|           |           |         |                 | 24Mbps         | 7.97                |
|           |           |         |                 | 54Mbps         | 7.72                |
| 802.11n   | 20        | 52      | 5260            | MCS0           | 8.71                |
|           |           |         |                 | MCS4           | 8.55                |
|           |           |         |                 | MCS7           | 8.31                |
| 802.11n   | 40        | 54      | 5270            | MCS0           | 11.39               |
|           |           |         |                 | MCS4           | 11.20               |
|           |           |         |                 | MCS7           | 11.04               |
| 802.11ax  | 20        | 52      | 5260            | MCS0           | 8.47                |
|           |           |         |                 | MCS6           | 8.13                |
|           |           |         |                 | MCS11          | 8.02                |
| 802.11ax  | 40        | 54      | 5270            | MCS0           | 11.61               |
|           |           |         |                 | MCS6           | 11.41               |
|           |           |         |                 | MCS11          | 11.06               |
| 802.11ax  | 80        | 58      | 5290            | MCS0           | 14.16               |
|           |           |         |                 | MCS6           | 14.01               |
|           |           |         |                 | MCS11          | 13.83               |
| 802.11ax  | 80 + 80   | 106     | 5530            | MCS0           | 14.27               |
|           |           |         |                 | MCS6           | 14.06               |
|           |           |         |                 | MCS11          | 13.81               |

|               |                     |                   |                         |
|---------------|---------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar  | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu             | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                 | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1361 CDD Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11a               | 6Mbps             | 52          | 5260        | 8.10                         | 7.91                         | 7.52                         | 7.96                         | 13.90                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 60          | 5300        | 8.06                         | 8.21                         | 7.74                         | 8.09                         | 14.05                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 64          | 5320        | 7.91                         | 8.01                         | 7.41                         | 7.79                         | 13.81                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 100         | 5500        | 7.91                         | 7.90                         | 7.47                         | 7.95                         | 13.83                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 120         | 5600        | 7.15                         | 7.65                         | 7.39                         | 7.33                         | 13.40                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 140         | 5700        | 8.00                         | 8.31                         | 7.84                         | 7.47                         | 13.94                        | ≤ 23.50                   | Pass   |
| 11a               | 6Mbps             | 144         | 5720        | 7.55                         | 7.66                         | 7.91                         | 8.01                         | 13.81                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 52          | 5260        | 8.71                         | 8.45                         | 8.45                         | 8.42                         | 14.53                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.50                         | 8.79                         | 8.61                         | 8.44                         | 14.61                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.59                         | 8.69                         | 8.44                         | 8.66                         | 14.62                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 8.76                         | 8.84                         | 8.62                         | 8.89                         | 14.80                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.53                         | 8.85                         | 8.58                         | 8.53                         | 14.65                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 8.28                         | 8.65                         | 8.15                         | 7.95                         | 14.29                        | ≤ 23.50                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 8.16                         | 8.68                         | 8.63                         | 8.45                         | 14.51                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 11.39                        | 11.47                        | 11.13                        | 11.30                        | 17.34                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 10.90                        | 11.02                        | 10.72                        | 11.17                        | 16.98                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.03                        | 11.15                        | 10.85                        | 11.12                        | 17.06                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 11.16                        | 10.72                        | 11.12                        | 11.06                        | 17.04                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 10.80                        | 11.55                        | 11.41                        | 10.40                        | 17.09                        | ≤ 23.50                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 10.98                        | 11.15                        | 10.93                        | 11.02                        | 17.04                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.47                         | 8.33                         | 8.13                         | 8.22                         | 14.31                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 7.90                         | 8.27                         | 7.88                         | 8.07                         | 14.05                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 7.90                         | 8.02                         | 7.99                         | 8.00                         | 14.00                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 8.06                         | 8.34                         | 8.26                         | 8.24                         | 14.25                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 7.98                         | 8.11                         | 8.18                         | 7.59                         | 13.99                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 7.97                         | 8.58                         | 7.99                         | 7.68                         | 14.09                        | ≤ 23.50                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 7.65                         | 8.21                         | 8.15                         | 7.62                         | 13.94                        | ≤ 23.50                   | Pass   |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE40         | MCS0              | 54          | 5270        | 11.61                     | 11.90                     | 11.51                     | 11.33                     | 17.61                     | ≤ 23.50                   | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 11.22                     | 11.35                     | 10.94                     | 11.53                     | 17.29                     | ≤ 23.50                   | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 11.92                     | 12.15                     | 12.21                     | 12.07                     | 18.11                     | ≤ 23.50                   | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 11.46                     | 11.10                     | 11.53                     | 11.01                     | 17.30                     | ≤ 23.50                   | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 10.81                     | 11.57                     | 11.33                     | 10.42                     | 17.08                     | ≤ 23.50                   | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 10.98                     | 11.51                     | 11.20                     | 11.32                     | 17.28                     | ≤ 23.50                   | Pass   |
| 11ax-HE80         | MCS0              | 58          | 5290        | 14.16                     | 14.38                     | 14.19                     | 14.10                     | 20.23                     | ≤ 23.50                   | Pass   |
| 11ax-HE80         | MCS0              | 106         | 5530        | 13.97                     | 13.96                     | 14.14                     | 13.72                     | 19.97                     | ≤ 23.50                   | Pass   |
| 11ax-HE80         | MCS0              | 122         | 5610        | 13.64                     | 13.73                     | 13.73                     | 13.51                     | 19.67                     | ≤ 23.50                   | Pass   |
| 11ax-HE80         | MCS0              | 138         | 5690        | 13.49                     | 14.14                     | 13.73                     | 13.36                     | 19.71                     | ≤ 23.50                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 42          | 5210        | 14.27                     | 13.67                     |                           |                           | 16.99                     | ≤ 29.52                   | Pass   |
|                   |                   | 58          | 5290        |                           |                           | 13.95                     | 13.97                     | 16.97                     | ≤ 23.50                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 106         | 5530        | 13.47                     | 13.48                     |                           |                           | 19.83                     | ≤ 23.50                   | Pass   |
|                   |                   | 122         | 5610        |                           |                           | 14.01                     | 14.21                     |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)}\}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

|               |                              |                   |                         |
|---------------|------------------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar           | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu                      | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                          | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1361 Beam-Forming Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11n-HT20          | MCS0              | 52          | 5260        | 8.71                         | 8.45                         | 8.45                         | 8.42                         | 14.53                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.50                         | 8.79                         | 8.61                         | 8.44                         | 14.61                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.59                         | 8.69                         | 8.44                         | 8.66                         | 14.62                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 8.76                         | 8.84                         | 8.62                         | 8.89                         | 14.80                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.53                         | 8.85                         | 8.58                         | 8.53                         | 14.65                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 8.28                         | 8.65                         | 8.15                         | 7.95                         | 14.29                        | ≤ 17.48                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 8.16                         | 8.68                         | 8.63                         | 8.45                         | 14.51                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 11.39                        | 11.47                        | 11.13                        | 11.30                        | 17.34                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 10.90                        | 11.02                        | 10.72                        | 11.17                        | 16.98                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.03                        | 11.15                        | 10.85                        | 11.12                        | 17.06                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 11.16                        | 10.72                        | 11.12                        | 11.06                        | 17.04                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 10.80                        | 11.55                        | 11.41                        | 10.40                        | 17.09                        | ≤ 17.48                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 10.98                        | 11.15                        | 10.93                        | 11.02                        | 17.04                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.47                         | 8.33                         | 8.13                         | 8.22                         | 14.31                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 7.90                         | 8.27                         | 7.88                         | 8.07                         | 14.05                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 7.90                         | 8.02                         | 7.99                         | 8.00                         | 14.00                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 8.06                         | 8.34                         | 8.26                         | 8.24                         | 14.25                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 7.98                         | 8.11                         | 8.18                         | 7.59                         | 13.99                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 7.97                         | 8.58                         | 7.99                         | 7.68                         | 14.09                        | ≤ 17.48                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 7.65                         | 8.21                         | 8.15                         | 7.62                         | 13.94                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 54          | 5270        | 10.99                        | 11.08                        | 10.61                        | 10.95                        | 16.93                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 11.22                        | 11.35                        | 10.94                        | 11.53                        | 17.29                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 11.02                        | 10.84                        | 10.71                        | 10.68                        | 16.84                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 11.46                        | 11.10                        | 11.53                        | 11.01                        | 17.30                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 10.81                        | 11.57                        | 11.33                        | 10.42                        | 17.08                        | ≤ 17.48                   | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 10.98                        | 11.51                        | 11.20                        | 11.32                        | 17.28                        | ≤ 17.48                   | Pass   |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE80         | MCS0              | 58          | 5290        | 11.29                     | 11.16                     | 10.88                     | 11.35                     | 17.19                     | ≤ 17.48                   | Pass   |
| 11ax-HE80         | MCS0              | 106         | 5530        | 11.06                     | 10.84                     | 10.70                     | 10.73                     | 16.86                     | ≤ 17.48                   | Pass   |
| 11ax-HE80         | MCS0              | 122         | 5610        | 10.90                     | 11.07                     | 10.92                     | 10.85                     | 16.96                     | ≤ 17.48                   | Pass   |
| 11ax-HE80         | MCS0              | 138         | 5690        | 10.68                     | 11.19                     | 10.92                     | 10.89                     | 16.94                     | ≤ 17.48                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 42          | 5210        | 11.03                     | 10.79                     |                           |                           | 13.92                     | ≤ 23.50                   | Pass   |
|                   |                   | 58          | 5290        |                           |                           | 11.24                     | 11.52                     | 14.39                     | ≤ 17.48                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 106         | 5530        | 11.18                     | 11.15                     |                           |                           | 17.17                     | ≤ 17.48                   | Pass   |
|                   |                   | 122         | 5610        |                           |                           | 11.26                     | 11.02                     |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}\}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

|               |                      |                   |                         |
|---------------|----------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar   | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu              | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                  | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1361D CDD Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11a               | 6Mbps             | 52          | 5260        | 8.93                         | 8.91                         | 8.36                         | 8.56                         | 14.72                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 60          | 5300        | 8.28                         | 8.10                         | 7.71                         | 7.71                         | 13.98                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 64          | 5320        | 7.92                         | 8.00                         | 7.58                         | 7.59                         | 13.80                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 100         | 5500        | 9.03                         | 8.98                         | 8.91                         | 8.40                         | 14.86                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 120         | 5600        | 8.08                         | 8.54                         | 8.45                         | 8.56                         | 14.43                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 140         | 5700        | 7.61                         | 8.20                         | 8.25                         | 7.92                         | 14.02                        | ≤ 22.58                   | Pass   |
| 11a               | 6Mbps             | 144         | 5720        | 7.20                         | 7.15                         | 7.72                         | 7.63                         | 13.45                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 52          | 5260        | 9.02                         | 8.73                         | 8.51                         | 8.76                         | 14.78                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.72                         | 9.11                         | 8.56                         | 8.53                         | 14.76                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.28                         | 8.75                         | 8.37                         | 8.15                         | 14.41                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 9.25                         | 9.05                         | 8.81                         | 8.45                         | 14.92                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.51                         | 8.63                         | 8.56                         | 8.59                         | 14.59                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 8.18                         | 9.51                         | 8.98                         | 8.73                         | 14.90                        | ≤ 22.58                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 7.75                         | 8.38                         | 8.33                         | 8.17                         | 14.19                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 12.19                        | 12.46                        | 12.09                        | 12.25                        | 18.27                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 12.03                        | 12.15                        | 11.42                        | 11.75                        | 17.87                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.73                        | 11.50                        | 11.50                        | 11.40                        | 17.55                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 11.41                        | 11.38                        | 11.65                        | 11.55                        | 17.52                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 11.16                        | 11.45                        | 11.30                        | 11.11                        | 17.28                        | ≤ 22.58                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 11.10                        | 11.63                        | 11.55                        | 11.42                        | 17.45                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.93                         | 9.10                         | 8.31                         | 8.28                         | 14.69                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 9.08                         | 9.13                         | 8.55                         | 8.71                         | 14.89                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 8.77                         | 8.72                         | 8.68                         | 8.40                         | 14.67                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 8.91                         | 8.52                         | 8.46                         | 8.13                         | 14.53                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 8.12                         | 8.55                         | 8.35                         | 8.18                         | 14.32                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 7.87                         | 8.63                         | 8.73                         | 8.39                         | 14.44                        | ≤ 22.58                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 8.03                         | 8.68                         | 8.29                         | 8.36                         | 14.37                        | ≤ 22.58                   | Pass   |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE40         | MCS0              | 54          | 5270        | 11.40                     | 11.62                     | 11.41                     | 11.35                     | 17.47                     | ≤ 22.58                   | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 11.86                     | 11.81                     | 11.27                     | 11.47                     | 17.63                     | ≤ 22.58                   | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 11.51                     | 11.45                     | 11.42                     | 11.56                     | 17.51                     | ≤ 22.58                   | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 11.16                     | 11.62                     | 11.72                     | 11.83                     | 17.61                     | ≤ 22.58                   | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 11.18                     | 11.67                     | 11.48                     | 11.31                     | 17.43                     | ≤ 22.58                   | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 11.22                     | 11.95                     | 11.74                     | 11.62                     | 17.66                     | ≤ 22.58                   | Pass   |
| 11ax-HE80         | MCS0              | 58          | 5290        | 14.66                     | 14.73                     | 14.52                     | 14.54                     | 20.63                     | ≤ 22.58                   | Pass   |
| 11ax-HE80         | MCS0              | 106         | 5530        | 14.41                     | 14.24                     | 14.30                     | 14.01                     | 20.26                     | ≤ 22.58                   | Pass   |
| 11ax-HE80         | MCS0              | 122         | 5610        | 13.81                     | 14.09                     | 14.08                     | 13.98                     | 20.01                     | ≤ 22.58                   | Pass   |
| 11ax-HE80         | MCS0              | 138         | 5690        | 13.75                     | 14.42                     | 14.53                     | 14.23                     | 20.26                     | ≤ 22.58                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 42          | 5210        | 12.96                     | 12.47                     |                           |                           | 15.73                     | ≤ 28.60                   | Pass   |
|                   |                   | 58          | 5290        |                           |                           | 13.05                     | 12.44                     | 15.77                     | ≤ 22.58                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 106         | 5530        | 15.49                     | 15.02                     |                           |                           | 21.23                     | ≤ 22.58                   | Pass   |
|                   |                   | 122         | 5610        |                           |                           | 15.21                     | 15.12                     |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)}\}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

|               |                               |                   |                         |
|---------------|-------------------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar            | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu                       | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                           | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1361D Beam-Forming Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11n-HT20          | MCS0              | 52          | 5260        | 9.02                         | 8.73                         | 8.51                         | 8.76                         | 14.78                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.72                         | 9.11                         | 8.56                         | 8.53                         | 14.76                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.28                         | 8.75                         | 8.37                         | 8.15                         | 14.41                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 9.25                         | 9.05                         | 8.81                         | 8.45                         | 14.92                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.51                         | 8.63                         | 8.56                         | 8.59                         | 14.59                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 8.18                         | 9.51                         | 8.98                         | 8.73                         | 14.90                        | ≤ 16.56                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 7.75                         | 8.38                         | 8.33                         | 8.17                         | 14.19                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 9.98                         | 10.11                        | 9.83                         | 9.44                         | 15.87                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 10.13                        | 10.18                        | 9.99                         | 9.79                         | 16.05                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 10.51                        | 9.98                         | 10.23                        | 9.82                         | 16.16                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 9.87                         | 10.04                        | 10.30                        | 10.10                        | 16.10                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 9.36                         | 10.10                        | 9.80                         | 9.82                         | 15.80                        | ≤ 16.56                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 9.85                         | 10.72                        | 10.12                        | 10.09                        | 16.23                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.93                         | 9.10                         | 8.31                         | 8.28                         | 14.69                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 9.08                         | 9.13                         | 8.55                         | 8.71                         | 14.89                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 8.77                         | 8.72                         | 8.68                         | 8.40                         | 14.67                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 8.91                         | 8.52                         | 8.46                         | 8.13                         | 14.53                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 8.12                         | 8.55                         | 8.35                         | 8.18                         | 14.32                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 7.87                         | 8.63                         | 8.73                         | 8.39                         | 14.44                        | ≤ 16.56                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 8.03                         | 8.68                         | 8.29                         | 8.36                         | 14.37                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 54          | 5270        | 10.24                        | 10.32                        | 10.13                        | 9.97                         | 16.19                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 9.98                         | 9.97                         | 9.85                         | 9.59                         | 15.87                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 10.38                        | 10.03                        | 9.94                         | 9.46                         | 15.99                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 9.49                         | 9.88                         | 10.01                        | 9.91                         | 15.85                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 9.81                         | 10.37                        | 10.13                        | 10.14                        | 16.14                        | ≤ 16.56                   | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 9.32                         | 10.72                        | 9.84                         | 9.65                         | 15.93                        | ≤ 16.56                   | Pass   |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE80         | MCS0              | 58          | 5290        | 10.04                     | 9.85                      | 9.78                      | 9.44                      | 15.80                     | ≤ 16.56                   | Pass   |
| 11ax-HE80         | MCS0              | 106         | 5530        | 10.25                     | 9.75                      | 9.96                      | 9.60                      | 15.92                     | ≤ 16.56                   | Pass   |
| 11ax-HE80         | MCS0              | 122         | 5610        | 10.09                     | 10.19                     | 10.25                     | 10.07                     | 16.17                     | ≤ 16.56                   | Pass   |
| 11ax-HE80         | MCS0              | 138         | 5690        | 9.42                      | 10.56                     | 9.80                      | 9.81                      | 15.94                     | ≤ 16.56                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 42          | 5210        | 12.96                     | 12.47                     |                           |                           | 15.73                     | ≤ 22.58                   | Pass   |
|                   |                   | 58          | 5290        |                           |                           | 13.05                     | 12.44                     | 15.77                     | ≤ 16.56                   | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 106         | 5530        | 10.35                     | 10.28                     |                           |                           | 16.13                     | ≤ 16.56                   | Pass   |
|                   |                   | 122         | 5610        |                           |                           | 10.02                     | 9.76                      |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}\}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\}$ .

|               |                     |                   |                         |
|---------------|---------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar  | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu             | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                 | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1362 CDD Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11a               | 6Mbps             | 52          | 5260        | 8.65                         | 8.11                         | 7.71                         | 8.12                         | 14.18                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 60          | 5300        | 8.31                         | 8.06                         | 7.69                         | 8.59                         | 14.20                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 64          | 5320        | 7.76                         | 8.02                         | 8.23                         | 7.98                         | 14.02                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 100         | 5500        | 8.48                         | 7.33                         | 7.67                         | 8.07                         | 13.93                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 120         | 5600        | 8.18                         | 7.72                         | 7.61                         | 7.91                         | 13.88                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 140         | 5700        | 6.89                         | 7.85                         | 7.93                         | 7.82                         | 13.66                        | ≤ 22.98                   | Pass   |
| 11a               | 6Mbps             | 144         | 5720        | 7.47                         | 8.18                         | 7.99                         | 8.47                         | 14.06                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 52          | 5260        | 8.58                         | 7.93                         | 7.98                         | 8.13                         | 14.18                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.19                         | 8.03                         | 7.82                         | 8.56                         | 14.18                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.33                         | 8.28                         | 8.72                         | 8.46                         | 14.47                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 8.87                         | 7.96                         | 8.15                         | 8.68                         | 14.45                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.41                         | 8.06                         | 8.23                         | 8.21                         | 14.25                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 7.83                         | 8.86                         | 8.56                         | 8.72                         | 14.53                        | ≤ 22.98                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 7.72                         | 8.01                         | 8.25                         | 8.21                         | 14.07                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 11.76                        | 11.25                        | 11.13                        | 11.36                        | 17.40                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 11.63                        | 11.51                        | 11.42                        | 11.46                        | 17.53                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.94                        | 11.13                        | 11.23                        | 11.98                        | 17.61                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 11.16                        | 10.74                        | 10.92                        | 11.04                        | 16.99                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 10.25                        | 10.91                        | 10.56                        | 10.37                        | 16.55                        | ≤ 22.98                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 10.39                        | 10.68                        | 10.55                        | 10.98                        | 16.68                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.85                         | 8.31                         | 7.98                         | 8.46                         | 14.43                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 8.89                         | 8.34                         | 8.16                         | 8.89                         | 14.60                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 8.86                         | 8.57                         | 8.93                         | 8.76                         | 14.80                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 9.25                         | 8.11                         | 8.55                         | 9.12                         | 14.80                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 8.31                         | 8.07                         | 7.93                         | 8.13                         | 14.13                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 8.01                         | 8.68                         | 8.38                         | 8.59                         | 14.44                        | ≤ 22.98                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 7.98                         | 8.57                         | 8.08                         | 8.65                         | 14.35                        | ≤ 22.98                   | Pass   |

| Test Mode         | Data Rate/MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|---------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |               |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE40         | MCS0          | 54          | 5270        | 11.12                     | 10.66                     | 10.65                     | 10.75                     | 16.82                     | ≤ 22.98                   | Pass   |
| 11ax-HE40         | MCS0          | 62          | 5310        | 11.86                     | 11.76                     | 11.72                     | 11.81                     | 17.81                     | ≤ 22.98                   | Pass   |
| 11ax-HE40         | MCS0          | 102         | 5510        | 12.28                     | 11.41                     | 11.48                     | 12.24                     | 17.89                     | ≤ 22.98                   | Pass   |
| 11ax-HE40         | MCS0          | 118         | 5590        | 11.09                     | 10.53                     | 10.99                     | 10.89                     | 16.90                     | ≤ 22.98                   | Pass   |
| 11ax-HE40         | MCS0          | 134         | 5670        | 10.67                     | 11.20                     | 11.02                     | 10.64                     | 16.91                     | ≤ 22.98                   | Pass   |
| 11ax-HE40         | MCS0          | 142         | 5710        | 10.98                     | 11.59                     | 11.37                     | 11.56                     | 17.40                     | ≤ 22.98                   | Pass   |
| 11ax-HE80         | MCS0          | 58          | 5290        | 14.34                     | 14.09                     | 13.83                     | 14.28                     | 20.16                     | ≤ 22.98                   | Pass   |
| 11ax-HE80         | MCS0          | 106         | 5530        | 14.62                     | 13.54                     | 14.61                     | 14.51                     | 20.36                     | ≤ 22.98                   | Pass   |
| 11ax-HE80         | MCS0          | 122         | 5610        | 14.18                     | 14.09                     | 14.13                     | 14.16                     | 20.16                     | ≤ 22.98                   | Pass   |
| 11ax-HE80         | MCS0          | 138         | 5690        | 13.93                     | 14.86                     | 14.43                     | 14.36                     | 20.43                     | ≤ 22.98                   | Pass   |
| 11ax-HE80 +80     | MCS0          | 42          | 5210        | 11.16                     | 10.97                     |                           |                           | 14.08                     | ≤ 29.00                   | Pass   |
|                   |               | 58          | 5290        |                           |                           | 10.97                     | 11.05                     | 14.02                     | ≤ 22.98                   | Pass   |
| 11ax-HE80 +80     | MCS0          | 106         | 5530        | 12.63                     | 11.67                     |                           |                           | 18.20                     | ≤ 22.98                   | Pass   |
|                   |               | 122         | 5610        |                           |                           | 12.10                     | 12.28                     |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)}\}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power}/10)} + 10^{(\text{Ant 1 Average Power}/10)} + 10^{(\text{Ant 2 Average Power}/10)} + 10^{(\text{Ant 3 Average Power}/10)}\}$ .

|               |                              |                   |                         |
|---------------|------------------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar           | Temperature       | 22 ~ 25°C               |
| Test Engineer | Eric Xu                      | Relative Humidity | 45 ~ 56%                |
| Test Site     | TR3                          | Test Date         | 2019/10/20 ~ 2020/03/02 |
| Model No.     | OAW-AP1362 Beam-Forming Mode |                   |                         |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0<br>Average Power (dBm) | Ant 1<br>Average Power (dBm) | Ant 2<br>Average Power (dBm) | Ant 3<br>Average Power (dBm) | Total<br>Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|------------------------------|------------------------------|------------------------------|------------------------------|------------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                              |                              |                              |                              |                              |                           |        |
| 11n-HT20          | MCS0              | 52          | 5260        | 8.58                         | 7.93                         | 7.98                         | 8.13                         | 14.18                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 8.19                         | 8.03                         | 7.82                         | 8.56                         | 14.18                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 8.33                         | 8.28                         | 8.72                         | 8.46                         | 14.47                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 8.87                         | 7.96                         | 8.15                         | 8.68                         | 14.45                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 8.41                         | 8.06                         | 8.23                         | 8.21                         | 14.25                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 7.83                         | 8.86                         | 8.56                         | 8.72                         | 14.53                        | ≤ 16.96                   | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 7.72                         | 8.01                         | 8.25                         | 8.21                         | 14.07                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 11.02                        | 10.54                        | 10.58                        | 10.52                        | 16.69                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 10.51                        | 10.56                        | 10.68                        | 10.56                        | 16.60                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.23                        | 10.52                        | 10.66                        | 11.12                        | 16.91                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 10.58                        | 10.22                        | 10.25                        | 10.27                        | 16.35                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 10.25                        | 10.91                        | 10.56                        | 10.37                        | 16.55                        | ≤ 16.96                   | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 10.39                        | 10.68                        | 10.55                        | 10.98                        | 16.68                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 52          | 5260        | 8.85                         | 8.31                         | 7.98                         | 8.46                         | 14.43                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 8.89                         | 8.34                         | 8.16                         | 8.89                         | 14.60                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 8.86                         | 8.57                         | 8.93                         | 8.76                         | 14.80                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 9.25                         | 8.11                         | 8.55                         | 9.12                         | 14.80                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 8.31                         | 8.07                         | 7.93                         | 8.13                         | 14.13                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 8.01                         | 8.68                         | 8.38                         | 8.59                         | 14.44                        | ≤ 16.96                   | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 7.98                         | 8.57                         | 8.08                         | 8.65                         | 14.35                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 54          | 5270        | 11.12                        | 10.66                        | 10.65                        | 10.75                        | 16.82                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 10.98                        | 10.84                        | 10.62                        | 10.78                        | 16.83                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 10.98                        | 10.20                        | 10.40                        | 10.87                        | 16.65                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 11.09                        | 10.53                        | 10.99                        | 10.89                        | 16.90                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 10.67                        | 11.20                        | 11.02                        | 10.64                        | 16.91                        | ≤ 16.96                   | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 10.16                        | 10.67                        | 10.54                        | 10.62                        | 16.52                        | ≤ 16.96                   | Pass   |

| Test Mode         | Data Rate/MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total Average Power (dBm) | Average Power Limit (dBm) | Result |
|-------------------|---------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|--------|
| Ant 0 + 1 + 2 + 3 |               |             |             |                           |                           |                           |                           |                           |                           |        |
| 11ax-HE80         | MCS0          | 58          | 5290        | 10.88                     | 10.72                     | 10.48                     | 10.78                     | 16.74                     | ≤ 16.96                   | Pass   |
| 11ax-HE80         | MCS0          | 106         | 5530        | 10.86                     | 10.07                     | 10.03                     | 10.20                     | 16.32                     | ≤ 16.96                   | Pass   |
| 11ax-HE80         | MCS0          | 122         | 5610        | 10.25                     | 10.16                     | 10.39                     | 10.21                     | 16.27                     | ≤ 16.96                   | Pass   |
| 11ax-HE80         | MCS0          | 138         | 5690        | 10.14                     | 10.86                     | 10.65                     | 10.53                     | 16.57                     | ≤ 16.96                   | Pass   |
| 11ax-HE80 +80     | MCS0          | 42          | 5210        | 10.51                     | 10.42                     |                           |                           | 13.48                     | ≤ 22.98                   | Pass   |
|                   |               | 58          | 5290        |                           |                           | 10.77                     | 10.81                     | 13.80                     | ≤ 16.96                   | Pass   |
| 11ax-HE80 +80     | MCS0          | 106         | 5530        | 10.82                     | 10.16                     |                           |                           | 16.42                     | ≤ 16.96                   | Pass   |
|                   |               | 122         | 5610        |                           |                           | 10.45                     | 10.12                     |                           |                           |        |

Note 1: Total Average Power (dBm) =  $10 \cdot \log \{ 10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)} \}$ .

Note 2: For ax-HE80+80 Contiguous Mode

5210MHz fall within UNII-1: Total Average Power (dBm) =  $10 \cdot \log \{ 10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} \}$ .

5290MHz fall within UNII-2A: Total Average Power (dBm) =  $10 \cdot \log \{ 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)} \}$ .

5530MHz & 5610MHz Fall within UNII-2C: Total Average Power (dBm) =  $10 \cdot \log \{ 10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)} \}$ .

## 7.5. Transmit Power Control

### 7.5.1. Test Limit

The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30dBm.


### 7.5.2. Test Procedure Used

KDB 789033 D02v01- Section E)3)b) Method PM-G

### 7.5.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### 7.5.4. Test Setup



### 7.5.5.Test Result

|               |                    |                   |                                      |
|---------------|--------------------|-------------------|--------------------------------------|
| Product       | OmniAccess Stellar | Temperature       | 22 ~ 25°C                            |
| Test Engineer | David Lv           | Relative Humidity | 46 ~ 54%                             |
| Test Site     | TR3                | Test Date         | 2019/10/12 ~ 2020/03/02              |
| Model No.     | OAW-AP1361         | Test Item         | Transmit Power Control<br>(CDD Mode) |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total TPC EIRP (dBm) | Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|----------------------|-------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                      |             |        |
| 11a               | 6Mbps             | 52          | 5260        | 10.82                     | 10.99                     | 10.50                     | 10.25                     | 23.15                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 60          | 5300        | 11.15                     | 11.42                     | 10.97                     | 10.92                     | 23.62                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 64          | 5320        | 11.01                     | 11.25                     | 10.99                     | 10.68                     | 23.49                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 100         | 5500        | 10.34                     | 10.66                     | 10.65                     | 10.35                     | 23.00                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 120         | 5600        | 10.99                     | 11.23                     | 10.97                     | 11.25                     | 23.61                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 140         | 5700        | 11.05                     | 11.44                     | 11.19                     | 10.47                     | 23.55                | ≤ 24.00     | Pass   |
| 11a               | 6Mbps             | 144         | 5720        | 10.42                     | 11.19                     | 11.35                     | 10.57                     | 23.40                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 52          | 5260        | 10.75                     | 10.95                     | 10.44                     | 10.30                     | 23.12                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 60          | 5300        | 10.95                     | 11.25                     | 11.10                     | 10.89                     | 23.55                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 64          | 5320        | 10.83                     | 11.03                     | 10.83                     | 10.70                     | 23.35                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 100         | 5500        | 10.75                     | 10.68                     | 10.68                     | 10.26                     | 23.10                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 120         | 5600        | 11.04                     | 10.97                     | 11.30                     | 10.70                     | 23.51                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 140         | 5700        | 11.05                     | 11.38                     | 11.14                     | 10.28                     | 23.48                | ≤ 24.00     | Pass   |
| 11n-HT20          | MCS0              | 144         | 5720        | 10.66                     | 11.19                     | 11.32                     | 10.37                     | 23.40                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 54          | 5270        | 10.73                     | 11.02                     | 10.70                     | 10.43                     | 23.23                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 62          | 5310        | 11.10                     | 11.24                     | 10.89                     | 11.08                     | 23.58                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 102         | 5510        | 11.20                     | 11.27                     | 11.16                     | 10.87                     | 23.63                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 118         | 5590        | 11.14                     | 10.73                     | 11.03                     | 10.66                     | 23.40                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 134         | 5670        | 10.52                     | 11.18                     | 10.98                     | 10.17                     | 23.23                | ≤ 24.00     | Pass   |
| 11n-HT40          | MCS0              | 142         | 5710        | 11.08                     | 11.45                     | 11.10                     | 10.78                     | 23.61                | ≤ 24.00     | Pass   |

| Test Mode         | Data Rate/<br>MCS | Channel No. | Freq. (MHz) | Ant 0 Average Power (dBm) | Ant 1 Average Power (dBm) | Ant 2 Average Power (dBm) | Ant 3 Average Power (dBm) | Total TPC EIRP (dBm) | Limit (dBm) | Result |
|-------------------|-------------------|-------------|-------------|---------------------------|---------------------------|---------------------------|---------------------------|----------------------|-------------|--------|
| Ant 0 + 1 + 2 + 3 |                   |             |             |                           |                           |                           |                           |                      |             |        |
| 11ax-HE20         | MCS0              | 52          | 5260        | 11.09                     | 11.14                     | 10.73                     | 10.73                     | 23.43                | ≤ 24.00     | Pass   |
| 11ax-HE20         | MCS0              | 60          | 5300        | 11.43                     | 11.35                     | 11.28                     | 11.13                     | 23.80                | ≤ 24.00     | Pass   |
| 11ax-HE20         | MCS0              | 64          | 5320        | 11.25                     | 11.30                     | 11.03                     | 11.13                     | 23.68                | ≤ 24.00     | Pass   |
| 11ax-HE20         | MCS0              | 100         | 5500        | 10.90                     | 10.94                     | 11.06                     | 10.52                     | 23.36                | ≤ 24.00     | Pass   |
| 11ax-HE20         | MCS0              | 120         | 5600        | 11.37                     | 11.14                     | 11.37                     | 10.75                     | 23.67                | ≤ 24.00     | Pass   |
| 11ax-HE20         | MCS0              | 140         | 5700        | 11.27                     | 11.57                     | 11.41                     | 10.61                     | 23.73                | ≤ 23.98     | Pass   |
| 11ax-HE20         | MCS0              | 144         | 5720        | 10.80                     | 11.25                     | 11.46                     | 10.44                     | 23.51                | ≤ 23.98     | Pass   |
| 11ax-HE40         | MCS0              | 54          | 5270        | 11.25                     | 11.31                     | 10.99                     | 10.99                     | 23.64                | ≤ 24.00     | Pass   |
| 11ax-HE40         | MCS0              | 62          | 5310        | 11.16                     | 10.93                     | 10.68                     | 10.98                     | 23.44                | ≤ 24.00     | Pass   |
| 11ax-HE40         | MCS0              | 102         | 5510        | 11.08                     | 11.14                     | 11.13                     | 10.51                     | 23.47                | ≤ 24.00     | Pass   |
| 11ax-HE40         | MCS0              | 118         | 5590        | 10.95                     | 10.51                     | 11.01                     | 10.56                     | 23.26                | ≤ 24.00     | Pass   |
| 11ax-HE40         | MCS0              | 134         | 5670        | 10.80                     | 11.55                     | 11.31                     | 10.26                     | 23.51                | ≤ 24.00     | Pass   |
| 11ax-HE40         | MCS0              | 142         | 5710        | 10.62                     | 11.22                     | 10.84                     | 10.65                     | 23.34                | ≤ 24.00     | Pass   |
| 11ax-HE80         | MCS0              | 58          | 5290        | 11.05                     | 11.36                     | 11.25                     | 11.20                     | 23.72                | ≤ 24.00     | Pass   |
| 11ax-HE80         | MCS0              | 106         | 5530        | 11.04                     | 10.68                     | 10.90                     | 10.33                     | 23.25                | ≤ 24.00     | Pass   |
| 11ax-HE80         | MCS0              | 122         | 5610        | 10.95                     | 11.12                     | 11.05                     | 10.70                     | 23.46                | ≤ 24.00     | Pass   |
| 11ax-HE80         | MCS0              | 138         | 5690        | 10.75                     | 11.33                     | 11.14                     | 10.62                     | 23.47                | ≤ 24.00     | Pass   |
| 11ax-HE80<br>+80  | MCS0              | 42          | 5210        |                           |                           | 13.58                     | 13.46                     | 23.01                | ≤ 24.00     | Pass   |
|                   |                   | 58          | 5290        |                           |                           |                           |                           |                      |             |        |
| 11ax-HE80<br>+80  | MCS0              | 106         | 5530        | 10.58                     | 11.05                     | 10.71                     | 10.36                     | 23.01                | ≤ 24.00     | Pass   |
|                   |                   | 122         | 5610        |                           |                           |                           |                           |                      |             |        |

Note: Total TPC EIRP Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)} + 10^{(\text{Ant 2 Average Power} / 10)} + 10^{(\text{Ant 3 Average Power} / 10)}\} + \text{Antenna Gain}.$

## 7.6. Power Spectral Density Measurement

### 7.6.1. Test Limit

For the band 5.25-5.35 GHz and 5.47-5725 GHz, the power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

| Frequency Band<br>(MHz) | Per Chain Max Antenna Gain (dBi) |       |       |       | Directional Gain<br>(dBi) | Limit |
|-------------------------|----------------------------------|-------|-------|-------|---------------------------|-------|
|                         | Ant 0                            | Ant 1 | Ant 2 | Ant 3 |                           |       |
| OAW-AP1361              |                                  |       |       |       |                           |       |
| 5150 ~ 5250             | 6.48                             | 6.31  | 6.26  | 6.12  | 12.50                     | 4.50  |
| 5725 ~ 5850             | 6.48                             | 6.31  | 6.26  | 6.12  | 12.50                     |       |
| OAW-AP1361D             |                                  |       |       |       |                           |       |
| 5150 ~ 5250             | 7.4                              | 7.0   | 6.9   | 7.2   | 13.42                     | 3.58  |
| 5725 ~ 5850             | 7.4                              | 7.0   | 6.9   | 7.2   | 13.42                     |       |
| OAW-AP1362              |                                  |       |       |       |                           |       |
| 5150 ~ 5250             | 7                                |       |       |       | 13.02                     | 3.98  |
| 5725 ~ 5850             | 7                                |       |       |       | 13.02                     |       |


### 7.6.2. Test Procedure Used

KDB 789033 D02v02r01 - Section F

### 7.6.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz,  
RBW = 100 kHz
4. VBW = 3MHz
5. Number of sweep points  $\geq 2 \times (\text{span} / \text{RBW})$
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
10. Add  $10 \cdot \log(1/x)$ , where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add  $10 \cdot \log(1/0.25) = 6$  dB if the duty cycle is 25 percent.
11. When the measurement bandwidth of Maximum PSD is specified in 500 kHz, add a constant factor  $10 \cdot \log(500\text{kHz}/100\text{kHz}) = 6.99$  dB to the measured result.

### 7.6.4. Test Setup



### 7.6.5. Test Result

|               |                    |                   |                         |
|---------------|--------------------|-------------------|-------------------------|
| Product       | OmniAccess Stellar | Temperature       | 22 ~ 25°C               |
| Test Engineer | David Lv           | Relative Humidity | 46 ~ 54%                |
| Test Site     | TR3                | Test Date         | 2019/10/12 ~ 2020/03/02 |
| Model No.     | OAW-AP1361         | Test Item         | Power Spectral Density  |

| Test Mode         | Data Rate/MCS | Channel No. | Freq. (MHz) | Ant 0 PSD (dBm/MHz) | Ant 1 PSD (dBm/MHz) | Ant 2 PSD (dBm/MHz) | Ant 3 PSD (dBm/MHz) | Duty Cycle (%) | Total PSD (dBm/MHz) | PSD Limit (dBm/MHz) | Result |
|-------------------|---------------|-------------|-------------|---------------------|---------------------|---------------------|---------------------|----------------|---------------------|---------------------|--------|
| Ant 0 + 1 + 2 + 3 |               |             |             |                     |                     |                     |                     |                |                     |                     |        |
| 11a               | 6Mbps         | 52          | 5260        | -2.61               | -2.26               | -2.72               | -2.69               | 92.19          | 3.81                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 60          | 5300        | -2.48               | -2.38               | -2.03               | -2.09               | 92.19          | 4.13                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 64          | 5320        | -2.70               | -2.08               | -2.41               | -2.25               | 92.19          | 4.02                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 100         | 5500        | -2.62               | -2.39               | -2.40               | -2.23               | 92.19          | 3.97                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 120         | 5600        | -2.64               | -2.50               | -2.55               | -2.39               | 92.19          | 3.85                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 140         | 5700        | -2.78               | -2.39               | -2.49               | -2.13               | 92.19          | 3.93                | ≤ 4.50              | Pass   |
| 11a               | 6Mbps         | 144         | 5720        | -2.71               | -2.63               | -2.39               | -2.28               | 92.19          | 3.87                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 52          | 5260        | -2.17               | -2.23               | -2.86               | -2.67               | 94.76          | 3.78                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 60          | 5300        | -2.56               | -2.03               | -2.17               | -1.98               | 94.76          | 4.08                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 64          | 5320        | -2.60               | -2.26               | -2.20               | -2.22               | 94.76          | 3.94                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 100         | 5500        | -2.67               | -2.60               | -2.11               | -2.24               | 94.76          | 3.86                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 120         | 5600        | -1.98               | -2.33               | -2.18               | -2.19               | 94.76          | 4.09                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 140         | 5700        | -2.72               | -2.27               | -2.49               | -2.00               | 94.76          | 3.89                | ≤ 4.50              | Pass   |
| 11n-HT20          | MCS0          | 144         | 5720        | -2.40               | -1.71               | -2.32               | -2.17               | 94.76          | 4.11                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 54          | 5270        | -2.33               | -1.99               | -2.80               | -2.74               | 91.62          | 3.95                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 62          | 5310        | -2.13               | -2.23               | -2.32               | -2.39               | 91.62          | 4.13                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 102         | 5510        | -2.17               | -2.10               | -2.50               | -2.38               | 91.62          | 4.12                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 118         | 5590        | -2.04               | -2.85               | -2.27               | -2.35               | 91.62          | 4.03                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 134         | 5670        | -2.15               | -2.07               | -2.34               | -2.32               | 91.62          | 4.18                | ≤ 4.50              | Pass   |
| 11n-HT40          | MCS0          | 142         | 5710        | -2.40               | -2.17               | -2.05               | -2.12               | 91.62          | 4.22                | ≤ 4.50              | Pass   |

| Test Mode         | Data Rate/MCS | Channel No. | Freq. (MHz) | Ant 0 PSD (dBm/MHz) | Ant 1 PSD (dBm/MHz) | Ant 2 PSD (dBm/MHz) | Ant 3 PSD (dBm/MHz) | Duty Cycle (%) | Total PSD (dBm/MHz) | PSD Limit (dBm/MHz) | Result |
|-------------------|---------------|-------------|-------------|---------------------|---------------------|---------------------|---------------------|----------------|---------------------|---------------------|--------|
| Ant 0 + 1 + 2 + 3 |               |             |             |                     |                     |                     |                     |                |                     |                     |        |
| 11ax-HE20         | MCS0          | 52          | 5260        | -1.92               | -2.24               | -2.16               | -2.03               | 93.56          | 4.22                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 60          | 5300        | -2.67               | -2.65               | -2.62               | -2.42               | 93.56          | 3.72                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 64          | 5320        | -2.16               | -2.57               | -2.46               | -2.24               | 93.56          | 3.96                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 100         | 5500        | -2.78               | -2.42               | -2.57               | -2.11               | 93.56          | 3.85                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 120         | 5600        | -2.12               | -2.10               | -2.04               | -2.24               | 93.56          | 4.19                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 140         | 5700        | -2.31               | -2.04               | -2.60               | -2.26               | 93.56          | 4.01                | ≤ 4.50              | Pass   |
| 11ax-HE20         | MCS0          | 144         | 5720        | -2.54               | -2.32               | -2.03               | -2.22               | 93.56          | 4.04                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 54          | 5270        | -2.51               | -1.81               | -2.03               | -1.94               | 94.76          | 4.19                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 62          | 5310        | -2.14               | -2.13               | -2.61               | -2.00               | 94.76          | 4.04                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 102         | 5510        | -2.38               | -2.45               | -2.19               | -2.54               | 94.76          | 3.87                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 118         | 5590        | -2.06               | -2.55               | -2.59               | -2.66               | 94.76          | 3.80                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 134         | 5670        | -3.25               | -2.23               | -2.16               | -2.59               | 94.76          | 3.72                | ≤ 4.50              | Pass   |
| 11ax-HE40         | MCS0          | 142         | 5710        | -2.27               | -1.87               | -2.07               | -2.29               | 94.76          | 4.13                | ≤ 4.50              | Pass   |
| 11ax-HE80         | MCS0          | 58          | 5290        | -2.16               | -2.18               | -2.37               | -2.39               | 94.26          | 4.00                | ≤ 4.50              | Pass   |
| 11ax-HE80         | MCS0          | 106         | 5530        | -2.65               | -2.43               | -2.41               | -2.46               | 94.26          | 3.79                | ≤ 4.50              | Pass   |
| 11ax-HE80         | MCS0          | 122         | 5610        | -2.43               | -2.55               | -2.49               | -2.11               | 94.26          | 3.89                | ≤ 4.50              | Pass   |
| 11ax-HE80         | MCS0          | 138         | 5690        | -2.68               | -2.62               | -2.62               | -2.25               | 94.26          | 3.74                | ≤ 4.50              | Pass   |
| 11ax-HE80 + 80    | MCS0          | 42          | 5210        | -3.24               | -3.38               |                     |                     | 94.26          | -0.04               | ≤ 10.50             | Pass   |
|                   |               | 58          | 5290        |                     |                     | -1.59               | -0.73               | 94.26          | 2.13                | ≤ 4.50              | Pass   |
| 11ax-HE80 + 80    | MCS0          | 106         | 5530        | -3.90               | -3.99               |                     |                     | 94.26          | -0.68               | ≤ 4.50              | Pass   |
|                   |               | 122         | 5610        |                     |                     | -1.54               | 0.12                | 94.26          | 2.64                | ≤ 4.50              | Pass   |

Note 1: When EUT duty cycle ≥ 98%, the total PSD (dBm/MHz) =  $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)} + 10^{(\text{Ant 2 PSD}/10)} + 10^{(\text{Ant 3 PSD}/10)}\}$

Note 2: When EUT duty cycle < 98%, the total PSD (dBm/MHz) =  $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)} + 10^{(\text{Ant 2 PSD}/10)} + 10^{(\text{Ant 3 PSD}/10)}\} + 10 \cdot \log(1/\text{duty cycle})$


Note 3: For ax-HE80+80 Contiguous Mode

5210MHz and 5530MHz: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\}$ .


5290MHz and 5610MHz: Total Average Power (dBm) =  $10 \cdot \log\{10^{(\text{Ant 2 PSD}/10)} + 10^{(\text{Ant 3 PSD}/10)}\}$ .

## 802.11a Power Spectral Density - Ant 0 / Ant 0 + 1 + 2 + 3


Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 120 (5600MHz)




Channel 140 (5700MHz)






## 802.11n-HT20 Power Spectral Density - Ant 0 / Ant 0 + 1 + 2 + 3


Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 120 (5600MHz)




Channel 140 (5700MHz)






## 802.11n-HT40 Power Spectral Density - Ant 0 / Ant 0 + 1 + 2 + 3


Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)



Channel 118 (5590MHz)



Channel 134 (5670MHz)



Channel 142 (5710MHz)

