


Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5270
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5142.200	52.29	0.80	53.09	68.23	-15.14	peak		Comment

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#148

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#147

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C(Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5270

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	5149.250	52.66	0.81	53.47	68.23	-14.76	peak	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#147

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#145

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C(Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5310

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	5351.250	59.80	1.20	61.00	68.23	-7.23	peak	


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#145

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5310
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	5350.150	57.96	1.20	59.16	68.23	-9.07	peak	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#146

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#144

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C(Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5510

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5468.850	51.97	1.43	53.40	68.23	-14.83	peak		Comment

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#144

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#143 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5510
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5465.950	50.77	1.43	52.20	68.23	-16.03	peak		Comment

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#143

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#142 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5670
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	5725.650	54.33	1.92	56.25	68.23	-11.98	peak	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#142

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#139

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C B4 (Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5755

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5725.000	63.61	1.92	65.53	125.23	-59.70	peak		Comment


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#139

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C B4 (Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5755
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	*	5723.750	63.68	1.92	65.60	121.63	-56.03	peak	


*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #140

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C(Bandedge)Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5670
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5725.150	57.26	1.92	59.18	68.23	-9.05	peak		Comment

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#141

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#138

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C B4 (Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5795

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1	*	5850.500	59.73	2.16	61.89	123.79	-61.90	peak		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#138

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#137

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C B4 (Bandedge)Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5795

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5850.500	58.76	2.16	60.92	123.79	-62.87	peak		Comment

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#137

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#62

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	55.24	0.82	56.06	74.00	-17.94	peak		Comment
2	*	5150.000	36.78	0.82	37.60	54.00	-16.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#62

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#61

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	5148.700	61.21	0.81	62.02	74.00	-11.98	peak		
2		5148.700	41.09	0.81	41.90	54.00	-12.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#61

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#68

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5068.750	48.35	0.66	49.01	74.00	-24.99	peak		
2	*	5068.750	30.84	0.66	31.50	54.00	-22.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#68

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#67

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5240MHz)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		5079.800	47.05	0.69	47.74	74.00	-26.26	peak		
2	*	5079.800	30.21	0.69	30.90	54.00	-23.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#67

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#72

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5260MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5140.900	51.63	0.80	52.43	74.00	-21.57	peak		
2	*	5140.900	33.50	0.80	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#72

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#71

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5260MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5138.300	50.85	0.80	51.65	74.00	-22.35	peak		
2	*	5138.300	33.30	0.80	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#71

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#73

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5320MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4991.400	50.98	0.50	51.48	74.00	-22.52	peak		
2	*	4991.400	33.20	0.50	33.70	54.00	-20.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#73

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#74

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5320MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5107.750	51.21	0.73	51.94	74.00	-22.06	peak		
2	*	5107.750	33.87	0.73	34.60	54.00	-19.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#74

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#78

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5500MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5104.800	51.02	0.73	51.75	74.00	-22.25	peak		
2		5104.800	33.17	0.73	33.90	54.00	-20.10	AVG		
3		5429.280	50.83	1.36	52.19	74.00	-21.81	peak		
4	*	5429.280	33.24	1.36	34.60	54.00	-19.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#78

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#77

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5500MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5143.200	51.63	0.80	52.43	74.00	-21.57	peak		
2		5143.200	33.10	0.80	33.90	54.00	-20.10	AVG		
3		5444.640	51.58	1.38	52.96	74.00	-21.04	peak		
4	*	5444.640	34.72	1.38	36.10	54.00	-17.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#77

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11a(5700MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5127.840	50.81	0.77	51.58	74.00	-22.42	peak		
2		5127.840	32.83	0.77	33.60	54.00	-20.40	AVG		
3		5456.160	50.70	1.41	52.11	74.00	-21.89	peak		
4	*	5456.160	33.69	1.41	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#80

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#79

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5700MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5108.640	51.54	0.73	52.27	74.00	-21.73	peak		
2	*	5108.640	33.77	0.73	34.50	54.00	-19.50	AVG		
3		5446.560	50.69	1.39	52.08	74.00	-21.92	peak		
4		5446.560	32.31	1.39	33.70	54.00	-20.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#79

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#59

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5745MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5148.000	52.03	0.81	52.84	74.00	-21.16	peak		
2	*	5148.000	33.29	0.81	34.10	54.00	-19.90	AVG		
3		5412.960	51.15	1.33	52.48	74.00	-21.52	peak		
4		5412.960	32.57	1.33	33.90	54.00	-20.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#59

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#60

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5745MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4983.840	51.34	0.49	51.83	74.00	-22.17	peak		
2	*	4983.840	34.21	0.49	34.70	54.00	-19.30	AVG		
3		5395.680	50.57	1.28	51.85	74.00	-22.15	peak		
4		5395.680	32.42	1.28	33.70	54.00	-20.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#60

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site: 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
EUT: Tablet PC
M/N: NS-P11A8100
Mode: 11a(5825MHz)
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5148.000	52.03	0.81	52.84	74.00	-21.16	peak		
2		5148.000	33.69	0.81	34.50	54.00	-19.50	AVG		
3		5412.960	51.15	1.33	52.48	74.00	-21.52	peak		
4	*	5412.960	34.77	1.33	36.10	54.00	-17.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #58

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#57

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5825MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5068.320	52.08	0.66	52.74	74.00	-21.26	peak		
2		5068.320	33.44	0.66	34.10	54.00	-19.90	AVG		
3		5411.040	51.39	1.32	52.71	74.00	-21.29	peak		
4	*	5411.040	33.98	1.32	35.30	54.00	-18.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#57

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#54

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5745MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5101.920	52.00	0.72	52.72	74.00	-21.28	peak		
2	*	5101.920	35.38	0.72	36.10	54.00	-17.90	AVG		
3		5403.360	50.87	1.30	52.17	74.00	-21.83	peak		
4		5403.360	33.40	1.30	34.70	54.00	-19.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#54

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#53

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5745MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5099.040	51.92	0.73	52.65	74.00	-21.35	peak		
2		5099.040	33.17	0.73	33.90	54.00	-20.10	AVG		
3		5387.040	50.93	1.27	52.20	74.00	-21.80	peak		
4	*	5387.040	33.83	1.27	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#53

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#55

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5825MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5085.600	51.15	0.70	51.85	74.00	-22.15	peak		
2		5085.600	32.00	0.70	32.70	54.00	-21.30	AVG		
3		5385.120	50.84	1.27	52.11	74.00	-21.89	peak		
4	*	5385.120	32.63	1.27	33.90	54.00	-20.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#55

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#56

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5825MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5100.960	51.56	0.72	52.28	74.00	-21.72	peak		
2		5100.960	33.18	0.72	33.90	54.00	-20.10	AVG		
3		5412.960	51.41	1.33	52.74	74.00	-21.26	peak		
4	*	5412.960	33.77	1.33	35.10	54.00	-18.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#56

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT40(5755MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5099.040	52.01	0.73	52.74	74.00	-21.26	peak		
2		5099.040	33.97	0.73	34.70	54.00	-19.30	AVG		
3		5398.560	51.19	1.30	52.49	74.00	-21.51	peak		
4	*	5398.560	34.00	1.30	35.30	54.00	-18.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#51

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#52

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5755MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5100.000	52.31	0.72	53.03	74.00	-20.97	peak		
2	*	5100.000	35.98	0.72	36.70	54.00	-17.30	AVG		
3		5377.440	50.99	1.25	52.24	74.00	-21.76	peak		
4		5377.440	33.55	1.25	34.80	54.00	-19.20	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#52

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#50

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5795MHz)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		5067.360	51.24	0.66	51.90	74.00	-22.10	peak		
2		5067.360	34.34	0.66	35.00	54.00	-19.00	AVG		
3		5367.840	51.13	1.23	52.36	74.00	-21.64	peak		
4	*	5367.840	34.97	1.23	36.20	54.00	-17.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#50

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File : TUV(HUAKE) Data : #49 Date : 2017/05/06 Time :



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5795MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5111.520	52.07	0.74	52.81	74.00	-21.19	peak		
2	*	5111.520	37.16	0.74	37.90	54.00	-16.10	AVG		
3		5426.400	50.75	1.35	52.10	74.00	-21.90	peak		
4		5426.400	35.35	1.35	36.70	54.00	-17.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File : TUV(HUAKE)\Data : #49

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#104 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT20(5180MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5147.400	57.33	0.81	58.14	74.00	-15.86	peak		
2	*	5147.400	39.29	0.81	40.10	54.00	-13.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#104

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement

File :TUV(HUAKE) Data :#103 Date: 2017/05/06 Time:


 Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT20(5180MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5149.350	61.21	0.81	62.02	74.00	-11.98	peak		
2	*	5149.350	42.79	0.81	43.60	54.00	-10.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#103

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#100

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5133.750	51.69	0.78	52.47	74.00	-21.53	peak		
2	*	5133.750	33.32	0.78	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#100

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#99

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5149.350	52.69	0.81	53.50	74.00	-20.50	peak		
2	*	5149.350	34.29	0.81	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#99

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#93

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5260MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5149.350	51.43	0.81	52.24	74.00	-21.76	peak		
2	*	5149.350	33.09	0.81	33.90	54.00	-20.10	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#93

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT20(5260MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	52.74	0.82	53.56	74.00	-20.44	peak		
2	*	5150.000	34.28	0.82	35.10	54.00	-18.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#94

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT20(5320MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5112.300	51.01	0.74	51.75	74.00	-22.25	peak		
2	*	5112.300	32.76	0.74	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File : TUV(HUAKE)\Data : #92

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#91 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT20(5320MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5112.300	51.33	0.74	52.07	74.00	-21.93	peak		
2	*	5112.300	34.46	0.74	35.20	54.00	-18.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#91

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#87

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5500MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5099.040	50.92	0.73	51.65	74.00	-22.35	peak		
2		5099.040	32.47	0.73	33.20	54.00	-20.80	AVG		
3		5444.640	50.96	1.38	52.34	74.00	-21.66	peak		
4	*	5444.640	32.62	1.38	34.00	54.00	-20.00	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#87

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#88

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5500MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5134.560	50.94	0.78	51.72	74.00	-22.28	peak		
2		5134.560	32.32	0.78	33.10	54.00	-20.90	AVG		
3		5454.240	50.69	1.41	52.10	74.00	-21.90	peak		
4	*	5454.240	32.09	1.41	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#88

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#82

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT20(5700MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5100.000	50.63	0.72	51.35	74.00	-22.65	peak		
2		5100.000	32.88	0.72	33.60	54.00	-20.40	AVG		
3		5402.400	50.78	1.30	52.08	74.00	-21.92	peak		
4	*	5402.400	32.80	1.30	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#82

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#81 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT20(5700MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5113.440	51.96	0.75	52.71	74.00	-21.29	peak		
2		5113.440	33.45	0.75	34.20	54.00	-19.80	AVG		
3		5422.560	50.92	1.35	52.27	74.00	-21.73	peak		
4	*	5422.560	33.65	1.35	35.00	54.00	-19.00	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#81

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#105

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5190MHz)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		5150.000	62.45	0.82	63.27	74.00	-10.73	peak		
2	*	5150.000	45.08	0.82	45.90	54.00	-8.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#105

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#106

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5190MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	64.71	0.82	65.53	74.00	-8.47	peak		
2	*	5150.000	45.08	0.82	45.90	54.00	-8.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#106

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#112

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5230MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5077.200	51.53	0.68	52.21	74.00	-21.79	peak		
2	*	5077.200	33.42	0.68	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#112

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#111 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT40(5230MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5115.550	51.15	0.75	51.90	74.00	-22.10	peak		
2	*	5115.550	32.35	0.75	33.10	54.00	-20.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#111

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#113

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5270MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5109.700	51.51	0.73	52.24	74.00	-21.76	peak		
2	*	5109.700	33.47	0.73	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#113

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#114

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5270MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5124.000	51.24	0.77	52.01	74.00	-21.99	peak		
2	*	5124.000	32.73	0.77	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#114

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#117

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5310MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5091.500	52.13	0.71	52.84	74.00	-21.16	peak		Comment
2	*	5091.500	33.89	0.71	34.60	54.00	-19.40	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#117

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5310MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5012.850	51.45	0.56	52.01	74.00	-21.99	peak		
2	*	5012.850	33.14	0.56	33.70	54.00	-20.30	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#118

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5510MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5119.200	51.24	0.75	51.99	74.00	-22.01	peak		
2	*	5119.200	34.25	0.75	35.00	54.00	-19.00	AVG		
3		5451.360	51.27	1.40	52.67	74.00	-21.33	peak		
4		5451.360	32.90	1.40	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File: TUV(HUAKE)\Data: #86

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement

File : TUV(HUAKE) Data : #85 Date: 2017/05/06 Time:


 Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5510MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5136.480	51.02	0.79	51.81	74.00	-22.19	peak		
2		5136.480	32.71	0.79	33.50	54.00	-20.50	AVG		
3		5453.280	51.18	1.40	52.58	74.00	-21.42	peak		
4	*	5453.280	32.70	1.40	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File : TUV(HUAKE)\Data : #85

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#83

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5670MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4972.320	51.20	0.46	51.66	74.00	-22.34	peak		
2		4972.320	33.04	0.46	33.50	54.00	-20.50	AVG		
3		5415.840	50.74	1.33	52.07	74.00	-21.93	peak		
4	*	5415.840	32.87	1.33	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#83

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#84

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5670MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5126.880	51.06	0.77	51.83	74.00	-22.17	peak		
2		5126.880	32.93	0.77	33.70	54.00	-20.30	AVG		
3		5460.000	51.10	1.41	52.51	74.00	-21.49	peak		
4	*	5460.000	32.89	1.41	34.30	54.00	-19.70	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#84

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac20 5180
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5068.750	48.35	0.66	49.01	74.00	-24.99	peak		
2	*	5068.750	30.84	0.66	31.50	54.00	-22.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#154

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#153 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac20 5180
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	5079.800	47.05	0.69	47.74	74.00	-26.26	peak	
2 *	5079.800	30.21	0.69	30.90	54.00	-23.10	AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#153

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#155

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5240

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		4991.400	50.98	0.50	51.48	74.00	-22.52	peak		Comment
2	*	4991.400	33.20	0.50	33.70	54.00	-20.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#155

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement

File :TUV(HUAKE) Data :#156 Date: 2017/05/06 Time:


 Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac20 5240
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5107.750	51.21	0.73	51.94	74.00	-22.06	peak		
2	*	5107.750	33.87	0.73	34.60	54.00	-19.40	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#156

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac20 5260
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	55.45	0.82	56.27	74.00	-17.73	peak		
2	*	5150.000	39.38	0.82	40.20	54.00	-13.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#160

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac20 5260
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5149.350	57.71	0.81	58.52	74.00	-15.48	peak		
2	*	5149.350	42.19	0.81	43.00	54.00	-11.00	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#159

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#163

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5320

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5149.350	51.93	0.81	52.74	74.00	-21.26	peak		
2	*	5149.350	34.29	0.81	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#163

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#164

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5320

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	53.24	0.82	54.06	74.00	-19.94	peak		Comment
2	*	5150.000	36.08	0.82	36.90	54.00	-17.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#164

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#167

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5500

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5099.040	50.92	0.73	51.65	74.00	-22.35	peak		
2		5099.040	32.47	0.73	33.20	54.00	-20.80	AVG		
3		5444.640	50.96	1.38	52.34	74.00	-21.66	peak		
4	*	5444.640	32.62	1.38	34.00	54.00	-20.00	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#167

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File: TUV(HUAKE)

Data: #168

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11ac20 5500

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5105.760	50.77	0.73	51.50	74.00	-22.50	peak		
2		5105.760	32.37	0.73	33.10	54.00	-20.90	AVG		
3		5435.040	51.65	1.36	53.01	74.00	-20.99	peak		
4	*	5435.040	33.84	1.36	35.20	54.00	-18.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#168

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#169

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5700

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		4972.320	51.20	0.46	51.66	74.00	-22.34	peak		
2		4972.320	33.04	0.46	33.50	54.00	-20.50	AVG		
3		5415.840	50.74	1.33	52.07	74.00	-21.93	peak		
4	*	5415.840	32.87	1.33	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#169

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#170

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5700

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5126.880	51.06	0.77	51.83	74.00	-22.17	peak		
2		5126.880	32.93	0.77	33.70	54.00	-20.30	AVG		
3		5460.000	51.10	1.41	52.51	74.00	-21.49	peak		
4	*	5460.000	32.89	1.41	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#170

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#172

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5745

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5148.000	52.03	0.81	52.84	74.00	-21.16	peak		
2	*	5148.000	34.89	0.81	35.70	54.00	-18.30	AVG		
3		5412.960	51.15	1.33	52.48	74.00	-21.52	peak		
4		5412.960	32.97	1.33	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#172

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#171

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5745

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5000.160	51.27	0.53	51.80	74.00	-22.20	peak		
2		5000.160	33.37	0.53	33.90	54.00	-20.10	AVG		
3		5456.160	50.64	1.41	52.05	74.00	-21.95	peak		
4	*	5456.160	33.79	1.41	35.20	54.00	-18.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#171

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#174

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5825

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5075.040	51.48	0.68	52.16	74.00	-21.84	peak		
2		5075.040	34.32	0.68	35.00	54.00	-19.00	AVG		
3		5403.360	50.87	1.30	52.17	74.00	-21.83	peak		
4	*	5403.360	34.80	1.30	36.10	54.00	-17.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#174

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#173

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5825

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5099.040	51.92	0.73	52.65	74.00	-21.35	peak		
2		5099.040	33.17	0.73	33.90	54.00	-20.10	AVG		
3		5387.040	50.93	1.27	52.20	74.00	-21.80	peak		
4	*	5387.040	33.83	1.27	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#173

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#177

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5190

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5140.900	51.63	0.80	52.43	74.00	-21.57	peak		
2	*	5140.900	33.50	0.80	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#177

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File: TUV(HUAKE)

Data: #178

Date: 2017/05/06

Time:



Site: 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11ac40 5190

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5107.750	51.21	0.73	51.94	74.00	-22.06	peak		
2	*	5107.750	33.87	0.73	34.60	54.00	-19.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #178

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#182

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5230

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		5133.750	51.69	0.78	52.47	74.00	-21.53	peak			
2	*	5133.750	33.32	0.78	34.10	54.00	-19.90	AVG			

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#182

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#183

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5230

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5150.000	64.71	0.82	65.53	74.00	-8.47	peak		Comment
2	*	5150.000	45.08	0.82	45.90	54.00	-8.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#183

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#186

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5270

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5109.700	51.51	0.73	52.24	74.00	-21.76	peak		
2	*	5109.700	33.47	0.73	34.20	54.00	-19.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#186

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5270
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5012.850	51.45	0.56	52.01	74.00	-21.99	peak		
2	*	5020.850	33.14	0.56	33.70	54.00	-20.30	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#187

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5310
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5149.350	51.43	0.81	52.24	74.00	-21.76	peak		
2	*	5149.350	33.09	0.81	33.90	54.00	-20.10	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#191

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5310
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5112.300	51.33	0.74	52.07	74.00	-21.93	peak		
2	*	5112.300	34.46	0.74	35.20	54.00	-18.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#190

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5510
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4972.320	51.20	0.46	51.66	74.00	-22.34	peak		
2		4972.320	33.04	0.46	33.50	54.00	-20.50	AVG		
3		5415.840	50.74	1.33	52.07	74.00	-21.93	peak		
4	*	5415.840	32.87	1.33	34.20	54.00	-19.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #195

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site: 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5510
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5113.440	51.96	0.75	52.71	74.00	-21.29	peak		
2		5113.440	33.45	0.75	34.20	54.00	-19.80	AVG		
3		5422.560	50.92	1.35	52.27	74.00	-21.73	peak		
4	*	5422.560	33.65	1.35	35.00	54.00	-19.00	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #194

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5670
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5119.200	51.24	0.75	51.99	74.00	-22.01	peak		
2	*	5119.200	34.25	0.75	35.00	54.00	-19.00	AVG		
3		5451.360	51.27	1.40	52.67	74.00	-21.33	peak		
4		5451.360	32.90	1.40	34.30	54.00	-19.70	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #197

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5670
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5134.560	50.94	0.78	51.72	74.00	-22.28	peak		
2		5134.560	32.32	0.78	33.10	54.00	-20.90	AVG		
3		5454.240	50.69	1.41	52.10	74.00	-21.90	peak		
4	*	5454.240	32.09	1.41	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #196

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#199

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5755

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5127.840	50.81	0.77	51.58	74.00	-22.42	peak		
2		5127.840	32.83	0.77	33.60	54.00	-20.40	AVG		
3		5456.160	50.70	1.41	52.11	74.00	-21.89	peak		
4	*	5456.160	33.69	1.41	35.10	54.00	-18.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#199

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5755
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5143.200	51.63	0.80	52.43	74.00	-21.57	peak		
2		5143.200	33.10	0.80	33.90	54.00	-20.10	AVG		
3		5444.640	51.58	1.38	52.96	74.00	-21.04	peak		
4	*	5444.640	34.72	1.38	36.10	54.00	-17.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #198

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5795
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5101.920	52.00	0.72	52.72	74.00	-21.28	peak		
2	*	5101.920	35.38	0.72	36.10	54.00	-17.90	AVG		
3		5403.360	50.87	1.30	52.17	74.00	-21.83	peak		
4		5403.360	33.40	1.30	34.70	54.00	-19.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#201

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
EUT: Tablet PC
M/N: NS-P11A8100
Mode: 11ac40 5795
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5111.520	52.07	0.74	52.81	74.00	-21.19	peak		
2	*	5111.520	37.16	0.74	37.90	54.00	-16.10	AVG		
3		5426.400	50.75	1.35	52.10	74.00	-21.90	peak		
4		5426.400	35.35	1.35	36.70	54.00	-17.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #200

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#64

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11a(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5368.920	51.13	1.23	52.36	74.00	-21.64	peak		
2	*	5368.920	32.87	1.23	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#64

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#63

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5370.240	51.31	1.24	52.55	74.00	-21.45	peak		
2	*	5370.240	32.26	1.24	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#63

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#65

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5369.030	51.06	1.23	52.29	74.00	-21.71	peak		
2	*	5369.030	31.47	1.23	32.70	54.00	-21.30	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#65

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#66 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11a(5240MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5380.250	50.69	1.26	51.95	74.00	-22.05	peak		
2	*	5380.250	31.74	1.26	33.00	54.00	-21.00	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#66

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File : TUV(HUAKE)

Data : #70

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11a(5260MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5355.280	51.22	1.21	52.43	74.00	-21.57	peak		
2	*	5355.280	33.09	1.21	34.30	54.00	-19.70	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File : TUV(HUAKE)\Data : #70

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11a(5260MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5352.090	50.91	1.20	52.11	74.00	-21.89	peak		Comment
2	*	5352.090	34.90	1.20	36.10	54.00	-17.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#69

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#75

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5320MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5350.440	61.29	1.20	62.49	74.00	-11.51	peak	
2	*	5350.440	42.30	1.20	43.50	54.00	-10.50	AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#75

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#76

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11a(5320MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5350.440	55.71	1.20	56.91	74.00	-17.09	peak		
2	*	5350.440	38.30	1.20	39.50	54.00	-14.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#76

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#102

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5362.560	51.55	1.23	52.78	74.00	-21.22	peak		
2	*	5362.560	33.37	1.23	34.60	54.00	-19.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#102

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#101

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT20(5180MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5348.880	51.66	1.20	52.86	74.00	-21.14	peak		
2	*	5348.880	33.00	1.20	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#101

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File :TUV(HUAKE)

Data :#97

Date: 2017/05/06

Time:



Site 3m Chamber #1

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT20(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5363.420	51.80	1.23	53.03	74.00	-20.97	peak		
2	*	5363.420	32.97	1.23	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#97

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#98

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5240MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5382.230	50.53	1.26	51.79	74.00	-22.21	peak		
2	*	5382.230	31.84	1.26	33.10	54.00	-20.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#98

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT20(5260MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5364.850	50.61	1.23	51.84	74.00	-22.16	peak		
2	*	5364.850	32.37	1.23	33.60	54.00	-20.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#96

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#95

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5260MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5356.380	51.15	1.21	52.36	74.00	-21.64	peak		
2	*	5356.380	32.99	1.21	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#95

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#90

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT20(5320MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	5351.540	59.25	1.20	60.45	74.00	-13.55	peak		
2		5351.540	38.00	1.20	39.20	54.00	-14.80	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#90

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT20(5320MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.220	59.16	1.20	60.36	74.00	-13.64	peak		
2	*	5350.220	42.30	1.20	43.50	54.00	-10.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#89

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#108

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5190MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5375.850	51.40	1.25	52.65	74.00	-21.35	peak		Comment
2	*	5375.850	32.95	1.25	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#108

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#107

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5190MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5357.040	51.07	1.21	52.28	74.00	-21.72	peak		
2	*	5357.040	32.89	1.21	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#107

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#109

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5230MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5359.680	50.66	1.22	51.88	74.00	-22.12	peak		
2	*	5359.680	32.28	1.22	33.50	54.00	-20.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#109

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#110

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11nHT40(5230MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5359.900	50.98	1.22	52.20	74.00	-21.80	peak		Comment
2	*	5359.900	32.98	1.22	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#110

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#115 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11nHT40(5270MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5358.030	51.27	1.22	52.49	74.00	-21.51	peak		
2	*	5358.030	32.88	1.22	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#115

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#116

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11nHT40(5270MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5356.930	50.99	1.21	52.20	74.00	-21.80	peak		Comment
2	*	5356.930	32.69	1.21	33.90	54.00	-20.10	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#116

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5310MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5350.440	61.41	1.20	62.61	74.00	-11.39	peak		Comment
2	*	5350.440	44.70	1.20	45.90	54.00	-8.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File: TUV(HUAKE)\Data: #119

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE) Data :#120 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11nHT40(5310MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree Comment
1		5354.400	60.04	1.21	61.25	74.00	-12.75	peak		
2	*	5354.400	41.69	1.21	42.90	54.00	-11.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#120

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#176

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5180

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5350.880	50.87	1.20	52.07	74.00	-21.93	peak		
2	*	5350.880	33.40	1.20	34.60	54.00	-19.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#176

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#175

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5180

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		5355.940	50.87	1.21	52.08	74.00	-21.92	peak	
2	*	5355.940	33.89	1.21	35.10	54.00	-18.90	AVG	

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#175

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File : TUV(HUAKE)

Data : #158

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode: 11ac20 5240

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5355.280	51.22	1.21	52.43	74.00	-21.57	peak		
2	*	5355.280	33.09	1.21	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File : TUV(HUAKE)\Data : #158

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#157

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5240

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5352.090	50.91	1.20	52.11	74.00	-21.89	peak		
2	*	5352.090	34.90	1.20	36.10	54.00	-17.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#157

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#161

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5260

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5363.420	50.80	1.23	52.03	74.00	-21.97	peak		Comment
2	*	5363.420	33.87	1.23	35.10	54.00	-18.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File :TUV(HUAKE)\Data :#161

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File : TUV(HUAKE) Data : #162 Date: 2017/05/06 Time:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac20 5260
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5354.620	50.97	1.21	52.18	74.00	-21.82	peak		
2	*	5354.620	33.09	1.21	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK


File : TUV(HUAKE)\Data : #162

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement



Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
EUT: Tablet PC
M/N: NS-P11A8100
Mode: 11ac20 5320
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.330	56.85	1.20	58.05	74.00	-15.95	peak		
2	*	5350.330	41.40	1.20	42.60	54.00	-11.40	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV(HUAKE)\Data: #166

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#165

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac20 5320

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.220	59.16	1.20	60.36	74.00	-13.64	peak		
2	*	5350.220	42.70	1.20	43.90	54.00	-10.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#165

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#180

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5190

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5355.280	51.22	1.21	52.43	74.00	-21.57	peak		
2	*	5355.280	33.09	1.21	34.30	54.00	-19.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#180

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#181

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5190

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5350.440	61.29	1.20	62.49	74.00	-11.51	peak		
2	*	5350.440	42.30	1.20	43.50	54.00	-10.50	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#181

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#184

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5230

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5375.850	51.40	1.25	52.65	74.00	-21.35	peak		
2	*	5375.850	32.95	1.25	34.20	54.00	-19.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#184

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File :TUV(HUAKE)

Data :#185

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5230

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5382.230	50.53	1.26	51.79	74.00	-22.21	peak		
2	*	5382.230	31.84	1.26	33.10	54.00	-20.90	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#185

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode:11ac40 5270
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5358.030	51.27	1.22	52.49	74.00	-21.51	peak		
2	*	5358.030	32.88	1.22	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#188

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#189

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5270

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5356.930	50.99	1.21	52.20	74.00	-21.80	peak		
2	*	5356.930	32.69	1.21	33.90	54.00	-20.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#189

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Radiated Emission Measurement

File :TUV(HUAKE)

Data :#192

Date: 2017/05/06

Time:



Site 3m Chamber #1

 Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15C Peak

Power: AC 120V/60Hz

Humidity: 50 %

EUT: Tablet PC

M/N: NS-P11A8100

Mode:11ac40 5310

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		5364.850	50.61	1.23	51.84	74.00	-22.16	peak		Comment
2	*	5364.850	32.37	1.23	33.60	54.00	-20.40	AVG		


*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#192

Page: 1

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282

Radiated Emission Measurement


Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15C Peak Power: AC 120V/60Hz Humidity: 50 %
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: 11ac40 5310
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		5382.230	50.53	1.26	51.79	74.00	-22.21	peak		
2	*	5382.230	31.84	1.26	33.10	54.00	-20.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File :TUV(HUAKE)\Data :#193

Page: 1

Prüfbericht - Nr.: 50094373 003

Test Report No.

Seite 553 von 565

Page 553 of 565

5.1.8 Dynamic Frequency Selection

RESULT:**Pass**



Date of testing	:	2017-05-25
Test standard	:	FCC part 15.407(h)(2) RSS-247 clause 6.3 KDB905462 D02 v02
Basic standard	:	ANSI C63.10: 2013
Limits	:	FCC part 15.407(h)(2)(iii)
Kind of test site	:	Shield room


Test setup

Test Channel	:	All channel
Operation mode	:	B.1, C.1 (802.11ac)
Ambient temperature	:	24°C
Relative humidity	:	53%
Atmospheric pressure	:	101kPa

For details refer to following test plot.

Table 28: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5310MHz













Table 29: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5510MHz







5.1.9 Conducted emissions**RESULT:****Pass**


Date of testing	:	2017-06-14
Test standard	:	FCC Part 15.207 FCC part 15.407(b)(6) RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 120V, 60Hz
Operation Mode	:	A, B, C, D
Earthing	:	Not Connected
Ambient temperature	:	22°C
Relative humidity	:	55%
Atmospheric pressure	:	101kPa

For details refer to following test plot.

Shenzhen EMTEK Co., Ltd.
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282


Conducted Emission Measurement


Site: Conduction #1
 Limit: (CE)FCC PART 15 class B_QP
 EUT: Tablet PC
 M/N: NS-P11A8100
 Mode: WIFI+BT ON
 Note:

Phase: L1 Temperature: 22
 Power: AC 120V/60Hz Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2450	39.13	0.00	39.13	61.92	-22.79	QP	
2		0.2450	29.12	0.00	29.12	51.92	-22.80	AVG	
3		0.5250	39.18	0.00	39.18	56.00	-16.82	QP	
4		0.5250	28.49	0.00	28.49	46.00	-17.51	AVG	
5		0.8700	40.96	0.00	40.96	56.00	-15.04	QP	
6		0.8700	29.63	0.00	29.63	46.00	-16.37	AVG	
7		1.7000	39.98	0.00	39.98	56.00	-16.02	QP	
8		1.7000	25.52	0.00	25.52	46.00	-20.48	AVG	
9		3.4450	40.26	0.00	40.26	56.00	-15.74	QP	
10		3.4450	30.53	0.00	30.53	46.00	-15.47	AVG	
11		8.7500	45.86	0.00	45.86	60.00	-14.14	QP	
12	*	8.7500	39.98	0.00	39.98	50.00	-10.02	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Stan


File: TUVData: #2745

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Conducted Emission Measurement



Site Conduction #1 Phase: N Temperature: 22
Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
EUT: Tablet PC
M/N: NS-P11A8100
Mode: WIFI+BT ON
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1800	44.50	0.00	44.50	64.49	-19.99	QP	
2		0.1800	37.99	0.00	37.99	54.49	-16.50	AVG	
3		0.2550	40.47	0.00	40.47	61.59	-21.12	QP	
4		0.2550	31.55	0.00	31.55	51.59	-20.04	AVG	
5		0.5200	34.12	0.00	34.12	56.00	-21.88	QP	
6		0.5200	23.26	0.00	23.26	46.00	-22.74	AVG	
7		1.7000	34.69	0.00	34.69	56.00	-21.31	QP	
8		1.7000	21.86	0.00	21.86	46.00	-24.14	AVG	
9		3.5800	37.97	0.00	37.97	56.00	-18.03	QP	
10		3.5800	28.00	0.00	28.00	46.00	-18.00	AVG	
11		8.8800	47.81	0.00	47.81	60.00	-12.19	QP	
12	*	8.8800	42.09	0.00	42.09	50.00	-7.91	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator: Stan

File: TUVData: #2746

Page: 1

7. List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	6
Table 3: Technical Specification of EUT	8
Table 4: Technical Specification of 5GHz, 802.11a/n.....	8
Table 5: Technical Specification of 5GHz, 802.11ac.....	9
Table 6: List of WLAN Channel of 5GHz 802.11a/n/ac	9
Table 7: Test result of Peak Output Power of 802.11a.....	15
Table 8: Test result of Peak Output Power of 802.11n HT20	16
Table 9: Test result of Peak Output Power of 802.11ac VHT20	16
Table 10: Test result of Peak Output Power of 802.11n HT40	16
Table 11: Test result of Peak Output Power of 802.11ac VHT40	17
Table 12: Test result of 26dB Bandwidth Band U-NII-1.....	18
Table 13: Test result of 26dB Bandwidth of Band U-NII-2A.....	18
Table 14: Test result of 26dB Bandwidth of Band U-NII-2C	19
Table 15: Test result of 26dB Bandwidth of Band U-NII-3.....	19
Table 16: Test result of 99% Bandwidth Band U-NII-1	20
Table 17: Test result of 99% Bandwidth of Band U-NII-2A.....	20
Table 18: Test result of 99% Bandwidth of Band U-NII-2C.....	21
Table 19: Test result of 99% Bandwidth of Band U-NII-3	21
Table 20: Test result of 6dB Bandwidth Band U-NII-1.....	22
Table 21: Test result of 6dB Bandwidth of Band U-NII-2A.....	22
Table 22: Test result of 6dB Bandwidth of Band U-NII-2C	23
Table 23: Test result of 6dB Bandwidth of Band U-NII-3.....	23
Table 24: Test result of power spectral density of Band U-NII-1.....	24
Table 25: Test result of power spectral density of Band U-NII-2A	25
Table 26: Test result of power spectral density of Band U-NII-2C	25
Table 27: Test result of power spectral density of Band U-NII-3.....	25
Table 28: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5310MHz	554
Table 29: Test result of Dynamic Frequency Selection of 802.11ac VHT40, 5510MHz	556

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions for 30 - 1000MHz	562
Photograph 2: Set-up for Spurious Emissions for 1 - 18GHz	562
Photograph 3: Set-up for Spurious Emissions for 18 - 40GHz	563