




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 70
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 70
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2464.000	28.36	8.40	36.38	86.62	87.00	74.00	-13.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 75

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)


Date: 2016-07-01



Site no.	: 3m Chamber	Data no.	: 75
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 2462MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 76
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 76
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.35	11.83	35.70	30.42	39.90	54.00	14.10	Average
2	4924.000	33.35	11.83	35.70	42.86	52.34	74.00	21.66	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 77
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no.	: 3m Chamber	Data no.	: 77
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT20 2462MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 78
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 78
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4924.000	33.35	11.83	35.70	31.14	40.62	54.00	13.38	Average
2	4924.000	33.35	11.83	35.70	43.25	52.73	74.00	21.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 83
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 83
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.31	8.36	36.38	92.80	93.09	74.00	-19.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 84
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 84
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2422.000	28.31	8.36	36.38	93.56	93.85	74.00	-19.85	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 79
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no.	: 3m Chamber	Data no.	: 79
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2422MHz Tx Mode		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel: +86-755-26639495-7
Fax: +86-755-26632877
Postcode: 518057

Data: 80

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 80
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.5°C/52.4%
Engineer : zack_zhu
EUT : 11.6" windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	33.19	11.78	35.68	30.56	39.85	54.00	14.15	Average
2	4844.000	33.19	11.78	35.68	42.76	52.05	74.00	21.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 81
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no.	: 3m Chamber	Data no.	: 81
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2422MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 82
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 82
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4844.000	33.19	11.78	35.68	30.36	39.65	54.00	14.35	Average
2	4844.000	33.19	11.78	35.68	43.25	52.54	74.00	21.46	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 93

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 93
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2437MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.32	8.38	36.38	93.57	93.89	74.00	-19.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 94

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 94
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.5°C/52.4%
Engineer : zack_zhu
EUT : 11.6" windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11nHT40 2437MHz Tx Mode
M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2437.000	28.32	8.38	36.38	92.41	92.73	74.00	-18.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 89

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no.	: 3m Chamber	Data no.	: 89
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2437MHz Tx Mode		
	M/N:NS-P11W7100		




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 90

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 90
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2437MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission			
						Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	33.25	11.80	35.69	30.85	40.21	54.00	13.79	Average
2	4874.000	33.25	11.80	35.69	42.66	52.02	74.00	21.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 91

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)


Date: 2016-07-01



Site no.	: 3m Chamber	Data no.	: 91
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2437MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 92
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 92
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2437MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4874.000	33.25	11.80	35.69	30.68	40.04	54.00	13.96	Average
2	4874.000	33.25	11.80	35.69	42.92	52.28	74.00	21.72	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 99
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 99
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2452.000	28.34	8.39	36.38	93.75	94.10	74.00	-20.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 100

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 100
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2452.000	28.34	8.39	36.38	94.01	94.36	74.00	-20.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 95
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no.	: 3m Chamber	Data no.	: 95
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2452MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 96
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 96
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Cable AMP			Emission				Remark
		Factor (dB/m)	Loss (dB)	factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	
1	4904.000	33.31	11.82	35.70	30.81	40.24	54.00	13.76	Average
2	4904.000	33.31	11.82	35.70	43.15	52.58	74.00	21.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 97
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no.	: 3m Chamber	Data no.	: 97
Dis. / Ant.	: 3m 2015 3115-4877	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 23.5°C/52.4%		
Engineer	: zack_zhu		
EUT	: 11.6" windows tablet		
Power rating	: DC 5V From Adapter Input AC 120V/60Hz		
Test Mode	: IEEE802.11nHT40 2452MHz Tx Mode		
	M/N:NS-P11W7100		



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 98
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 98
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4904.000	33.31	11.82	35.70	30.82	40.25	54.00	13.75	Average
2	4904.000	33.31	11.82	35.70	43.12	52.55	74.00	21.45	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 3

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 3
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2383.025	28.26	8.32	36.39	47.32	47.51	74.00	26.49	Peak
2	2390.000	28.27	8.33	36.39	45.73	45.94	74.00	28.06	Peak
3	2396.480	28.28	8.33	36.39	50.55	50.77	74.00	23.23	Peak
4	2400.000	28.28	8.34	36.39	46.39	46.62	74.00	27.38	Peak
5	2410.855	28.29	8.35	36.39	95.89	96.14	74.00	-22.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 4

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 4
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2412MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2376.470	28.25	8.31	36.39	37.86	38.03	54.00	15.97	Average
2	2390.000	28.27	8.33	36.39	35.65	35.86	54.00	18.14	Average
3	2396.250	28.28	8.33	36.39	45.25	45.47	54.00	8.53	Average
4	2400.000	28.28	8.34	36.39	36.64	36.87	54.00	17.13	Average
5	2411.200	28.29	8.35	36.39	93.28	93.53	54.00	-39.53	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 6

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 6
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.5°C/52.4%
Engineer : zack_zhu
EUT : 11.6" windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11b 2412MHz Tx Mode
M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2376.355	28.25	8.31	36.39	47.77	47.94	74.00	26.06	Peak
2	2390.000	28.27	8.33	36.39	46.02	46.23	74.00	27.77	Peak
3	2396.250	28.28	8.33	36.39	50.64	50.86	74.00	23.14	Peak
4	2400.000	28.28	8.34	36.39	47.41	47.64	74.00	26.36	Peak
5	2410.855	28.29	8.35	36.39	97.93	98.18	74.00	-24.18	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
- Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 5 File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-06-30




Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2412MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2376.470	28.25	8.31	36.39	37.50	37.67	54.00	16.33	Average
2	2390.000	28.27	8.33	36.39	35.86	36.07	54.00	17.93	Average
3	2396.250	28.28	8.33	36.39	45.98	46.20	54.00	7.80	Average
4	2400.000	28.28	8.34	36.39	36.83	37.06	54.00	16.94	Average
5	2411.200	28.29	8.35	36.39	94.41	94.66	54.00	-40.66	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 19
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-06-30



Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.200	28.36	8.40	36.38	98.17	98.55	74.00	-24.55	Peak
2	2483.500	28.38	8.42	36.38	46.77	47.19	74.00	26.81	Peak
3	2484.080	28.38	8.42	36.38	48.70	49.12	74.00	24.88	Peak
4	2500.000	28.40	8.44	36.38	45.63	46.09	74.00	27.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 22
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-06-30


Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.220	28.35	8.40	36.38	94.98	95.35	54.00	-41.35	Average
2	2483.500	28.38	8.42	36.38	38.04	38.46	54.00	15.54	Average
3	2484.500	28.38	8.42	36.38	38.59	39.01	54.00	14.99	Average
4	2500.000	28.40	8.44	36.38	37.47	37.93	54.00	16.07	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 20

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2460.500	28.35	8.40	36.38	98.61	98.98	74.00	-24.98	Peak
2	2483.500	28.38	8.42	36.38	47.54	47.96	74.00	26.04	Peak
3	2484.320	28.38	8.42	36.38	49.78	50.20	74.00	23.80	Peak
4	2500.000	28.40	8.44	36.38	46.77	47.23	74.00	26.77	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 21

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 21
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11b 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.220	28.35	8.40	36.38	93.76	94.13	54.00	-40.13	Average
2	2483.500	28.38	8.42	36.38	38.79	39.21	54.00	14.79	Average
3	2488.700	28.39	8.43	36.38	39.35	39.79	54.00	14.21	Average
4	2500.000	28.40	8.44	36.38	36.22	36.68	54.00	17.32	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 49

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-06-30




Site no. : 3m Chamber Data no. : 49
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2412MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2384.405	28.26	8.32	36.39	50.32	50.51	74.00	23.49	Peak
2	2390.000	28.27	8.33	36.39	47.33	47.54	74.00	26.46	Peak
3	2400.000	28.28	8.34	36.39	71.86	72.09	74.00	1.91	Peak
4	2413.730	28.30	8.35	36.39	98.48	98.74	74.00	-24.74	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 50
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-06-30


Site no. : 3m Chamber Data no. : 50
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	36.37	36.58	54.00	17.42	Average
2	2400.000	28.28	8.34	36.39	53.39	53.62	54.00	0.38	Average
3	2415.570	28.30	8.35	36.39	86.80	87.06	54.00	-33.06	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 52

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 52
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2412MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2382.680	28.26	8.32	36.39	50.67	50.86	74.00	23.14	Peak
2	2390.000	28.27	8.33	36.39	47.74	47.95	74.00	26.05	Peak
3	2400.000	28.28	8.34	36.39	72.21	72.44	74.00	1.56	Peak
4	2414.995	28.30	8.35	36.39	98.46	98.72	74.00	-24.72	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 51

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-06-30



Site no. : 3m Chamber Data no. : 51
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	36.62	36.83	54.00	17.17	Average
2	2400.000	28.28	8.34	36.39	53.93	54.16	54.00	-0.16	Average
3	2409.820	28.29	8.35	36.39	87.89	88.14	54.00	-34.14	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 36

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)

Date: 2016-06-30




Site no. : 3m Chamber Data no. : 36
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2465.600	28.36	8.40	36.38	97.83	98.21	74.00	-24.21	Peak
2	2483.500	28.38	8.42	36.38	55.47	55.89	74.00	18.11	Peak
3	2500.000	28.40	8.44	36.38	47.55	48.01	74.00	25.99	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel: +86-755-26639495-7
Fax: +86-755-26632877
Postcode: 518057

Data: 35
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-06-30


Site no. : 3m Chamber Data no. : 35
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
Limit : FCC PART 15C AV
Env. / Ins. : 23.5°C/52.4%
Engineer : zack_zhu
EUT : 11.6" windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11g 2462MHz Tx Mode
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2465.900	28.36	8.41	36.38	86.71	87.10	54.00	-33.10	Average
2	2483.500	28.38	8.42	36.38	40.09	40.51	54.00	13.49	Average
3	2500.000	28.40	8.44	36.38	35.61	36.07	54.00	17.93	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 33

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)

Date: 2016-06-30




Site no. : 3m Chamber Data no. : 33
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2460.200	28.35	8.40	36.38	98.67	99.04	74.00	-25.04	Peak
2	2483.500	28.38	8.42	36.38	54.93	55.35	74.00	18.65	Peak
3	2484.080	28.38	8.42	36.38	56.51	56.93	74.00	17.07	Peak
4	2500.000	28.40	8.44	36.38	49.15	49.61	74.00	24.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 34
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-06-30


Site no. : 3m Chamber Data no. : 34
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11g 2462MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.020	28.36	8.41	36.38	87.48	87.87	54.00	-33.87	Average
2	2483.500	28.38	8.42	36.38	41.75	42.17	54.00	11.83	Average
3	2500.000	28.40	8.44	36.38	35.94	36.40	54.00	17.60	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 54

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 54
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2412MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2381.875	28.26	8.32	36.39	52.65	52.84	74.00	21.16	Peak
2	2390.000	28.27	8.33	36.39	49.69	49.90	74.00	24.10	Peak
3	2399.355	28.28	8.34	36.39	75.33	75.56	74.00	-1.56	Peak
4	2400.000	28.28	8.34	36.39	74.49	74.72	74.00	-0.72	Peak
5	2410.050	28.29	8.35	36.39	100.36	100.61	74.00	-26.61	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 55

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 55
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	38.66	38.87	54.00	15.13	Average
2	2400.000	28.28	8.34	36.39	56.99	57.22	54.00	-3.22	Average
3	2407.980	28.29	8.35	36.39	90.43	90.68	54.00	-36.68	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 53

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 53
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2389.005	28.27	8.33	36.39	56.23	56.44	74.00	17.56	Peak
2	2390.040	28.27	8.33	36.39	53.44	53.65	74.00	20.35	Peak
3	2399.355	28.28	8.34	36.39	78.75	78.98	74.00	-4.98	Peak
4	2400.000	28.28	8.34	36.39	76.49	76.72	74.00	-2.72	Peak
5	2409.245	28.29	8.35	36.39	102.21	102.46	74.00	-28.46	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 56
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 56
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2412MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	37.75	37.96	54.00	16.04	Average
2	2400.000	28.28	8.34	36.39	54.95	55.18	54.00	-1.18	Average
3	2409.475	28.29	8.35	36.39	88.61	88.86	54.00	-34.86	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
ShenZhen Science & Industry Park
Noutou, ShenZhen, GuangDong, China
Tel:+86-755-26639495-7
Fax:+86-755-26632877
Postcode:518057

Data: 73
File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 73
Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.5°C/52.4%
Engineer : zack_zhu
EUT : 11.6" windows tablet
Power rating : DC 5V From Adapter Input AC 120V/60Hz
Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2466.980	28.36	8.41	36.38	98.90	99.29	74.00	-25.29	Peak
2	2483.500	28.38	8.42	36.38	58.45	58.87	74.00	15.13	Peak
3	2485.280	28.38	8.42	36.38	59.09	59.51	74.00	14.49	Peak
4	2500.000	28.40	8.44	36.38	48.87	49.33	74.00	24.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp Factor
2. The emission levels that are 20dB below the official
limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 72

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 72
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2457.920	28.35	8.40	36.38	86.69	87.06	54.00	-33.06	Average
2	2483.500	28.38	8.42	36.38	41.04	41.46	54.00	12.54	Average
3	2500.000	28.40	8.44	36.38	35.33	35.79	54.00	18.21	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 74

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 74
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2460.380	28.35	8.40	36.38	97.18	97.55	74.00	-23.55	Peak
2	2483.500	28.38	8.42	36.38	53.89	54.31	74.00	19.69	Peak
3	2500.000	28.40	8.44	36.38	47.26	47.72	74.00	26.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 71

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)

Date: 2016-07-01



Site no. : 3m Chamber Data no. : 71
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT20 2462MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2459.120	28.35	8.40	36.38	88.03	88.40	54.00	-34.40	Average
2	2483.500	28.38	8.42	36.38	41.32	41.74	54.00	12.26	Average
3	2500.000	28.40	8.44	36.38	35.71	36.17	54.00	17.83	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 85

File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 85
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2388.820	28.27	8.33	36.39	49.96	50.17	74.00	23.83	Peak
2	2390.000	28.27	8.33	36.39	47.94	48.15	74.00	25.85	Peak
3	2400.000	28.28	8.34	36.39	66.74	66.97	74.00	7.03	Peak
4	2410.380	28.29	8.35	36.39	93.59	93.84	74.00	-19.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 86
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 86
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	36.25	36.46	54.00	17.54	Average
2	2400.000	28.28	8.34	36.39	51.60	51.83	54.00	2.17	Average
3	2410.800	28.29	8.35	36.39	81.83	82.08	54.00	-28.08	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 88
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01



Site no. : 3m Chamber Data no. : 88
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2389.100	28.27	8.33	36.39	48.61	48.82	74.00	25.18	Peak
2	2390.000	28.27	8.33	36.39	47.49	47.70	74.00	26.30	Peak
3	2400.000	28.28	8.34	36.39	67.60	67.83	74.00	6.17	Peak
4	2410.800	28.29	8.35	36.39	92.95	93.20	74.00	-19.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 87
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 87
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2422MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.27	8.33	36.39	36.26	36.47	54.00	17.53	Average
2	2400.000	28.28	8.34	36.39	51.46	51.69	54.00	2.31	Average
3	2433.200	28.32	8.37	36.38	81.38	81.69	54.00	-27.69	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 101

File: F:\2016 Report\TUV\TUV莱茵委测-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 101
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.400	28.35	8.40	36.38	93.86	94.23	74.00	-20.23	Peak
2	2483.500	28.38	8.42	36.38	54.88	55.30	74.00	18.70	Peak
3	2486.625	28.38	8.43	36.38	55.19	55.62	74.00	18.38	Peak
4	2500.000	28.40	8.44	36.38	48.81	49.27	74.00	24.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 102
File: F:\2016 Report\TUV\TUV莱茵检测-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 102
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N:NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.420	28.36	8.40	36.38	82.03	82.41	54.00	-28.41	Average
2	2483.500	28.38	8.42	36.38	42.74	43.16	54.00	10.84	Average
3	2500.000	28.40	8.44	36.38	36.22	36.68	54.00	17.32	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 104

File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)

Date: 2016-07-01




Site no. : 3m Chamber Data no. : 104
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2460.020	28.35	8.40	36.38	93.42	93.79	74.00	-19.79	Peak
2	2483.500	28.38	8.42	36.38	53.78	54.20	74.00	19.80	Peak
3	2484.500	28.38	8.42	36.38	55.54	55.96	74.00	18.04	Peak
4	2500.000	28.40	8.44	36.38	47.44	47.90	74.00	26.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 -Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Noutou, ShenZhen, GuangDong, China
 Tel: +86-755-26639495-7
 Fax: +86-755-26632877
 Postcode: 518057

Data: 103
File: F:\2016 Report\TUV\TUV莱茵测试-FCC-2.4G.EM6 (104)
Date: 2016-07-01


Site no. : 3m Chamber Data no. : 103
 Dis. / Ant. : 3m 2015 3115-4877 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.5°C/52.4%
 Engineer : zack_zhu
 EUT : 11.6" windows tablet
 Power rating : DC 5V From Adapter Input AC 120V/60Hz
 Test Mode : IEEE802.11nHT40 2452MHz Tx Mode
 M/N: NS-P11W7100

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.420	28.36	8.40	36.38	81.75	82.13	54.00	-28.13	Average
2	2483.500	28.38	8.42	36.38	41.77	42.19	54.00	11.81	Average
3	2500.000	28.40	8.44	36.38	35.86	36.32	54.00	17.68	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
 - Amp Factor
 2. The emission levels that are 20dB below the official
 limit are not reported.

5.1.7 Conducted emissions

RESULT:**Pass**

Date of testing	:	2016-07-08
Test standard	:	FCC Part 15.207 RSS-Gen Clause 8.8
Basic standard	:	ANSI C63.10: 2013
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.207
Kind of test site	:	Shield room

Test setup

Input Voltage	:	AC 120V, 60Hz
Operation Mode	:	A
Earthing	:	Not Connected
Ambient temperature	:	24.2°C
Relative humidity	:	53%
Atmospheric pressure	:	101kPa

For details refer to following test plot.




No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Nantou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057

Data: 9

File: E:\1#CE\2016 Report Data\TUV\TUV莱茵测试\EM6 (14)

Date: 2016-07-08




Site no :1# Conduction Data No :9
 Dis./Lisn :2015 ESH2-25 LINE LISN phase:
 Limit :FCC PART 15 C
 Env./Ins. :24.2°C/53% Engineer :Evan
 EUT :11.6" windows tablet M/N:NS-P11W7100
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz
 Test Mode :TX Mode WIFI 2.4G

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.02	41.78	41.92	66.00	24.08	QP
2	0.153	0.12	0.02	32.15	32.29	55.81	23.52	Average
3	0.193	0.12	0.02	31.25	31.39	53.89	22.50	Average
4	0.194	0.12	0.02	41.69	41.83	63.84	22.01	QP
5	0.352	0.17	0.02	27.47	27.66	48.92	21.26	Average
6	0.354	0.21	0.02	38.94	39.17	58.87	19.70	QP
7	0.441	0.50	0.03	27.16	27.69	47.04	19.35	Average
8	0.447	0.48	0.03	38.08	38.59	56.93	18.34	QP
9	0.583	0.14	0.04	27.16	27.34	46.00	18.66	Average
10	0.589	0.14	0.04	37.36	37.54	56.00	18.46	QP
11	0.671	0.15	0.04	28.17	28.36	46.00	17.64	Average
12	0.675	0.15	0.04	39.87	40.06	56.00	15.94	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector.
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.



No.6 Ke Feng Road,Block 52,
 ShenZhen Science & Industry Park
 Nantou,ShenZhen,GuangDong,China
 Tel:+86-755-26639495-7
 Fax:+86-755-26632877
 Postcode:518057



Site no :1# Conduction Data No :10
 Dis./Lisn :2015 ESH2-25 NEUTRAL LISN phase:
 Limit :FCC PART 15 C
 Env./Ins. :24.2°C/53% Engineer :Evan
 EUT :11.6" windows tablet M/N:NS-P11W7100
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz
 Test Mode :TX Mode WIFI 2.4G

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.153	0.12	0.02	33.47	33.61	55.81	22.20	Average
2	0.154	0.12	0.02	44.11	44.25	65.78	21.53	QP
3	0.193	0.12	0.02	30.17	30.31	53.89	23.58	Average
4	0.198	0.12	0.02	41.08	41.22	63.71	22.49	QP
5	0.346	0.13	0.02	37.84	37.99	59.05	21.06	QP
6	0.348	0.13	0.02	27.17	27.32	49.01	21.69	Average
7	0.453	0.14	0.03	26.17	26.34	46.83	20.49	Average
8	0.454	0.14	0.03	37.89	38.06	56.80	18.74	QP
9	0.603	0.15	0.04	26.56	26.75	46.00	19.25	Average
10	0.608	0.15	0.04	37.62	37.81	56.00	18.19	QP
11	0.670	0.15	0.04	28.47	28.66	46.00	17.34	Average
12	0.675	0.15	0.04	38.51	38.70	56.00	17.30	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
 2.If the average limit is met when using a quasi-peak detector.
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

7. List of Tables

Table 1: List of Test and Measurement Equipment.....	5
Table 2: Measurement Uncertainty	7
Table 3: Technical Specification of EUT	9
Table 4: Technical Specification of Wi-Fi	9
Table 5: Carrier Frequency	10
Table 6: Test result of Peak Output Power of 802.11b.....	15
Table 7: Test result of Peak Output Power of 802.11g.....	15
Table 8: Test result of Peak Output Power of 802.11n (HT20).....	15
Table 9: Test result of Peak Output Power of 802.11n (HT40).....	16
Table 10: Test result of 6dB Bandwidth & 99% Bandwidth of 802.11b.....	17
Table 11: Test result of 6dB Bandwidth & 99% Bandwidth of 802.11g.....	17
Table 12: Test result of 6dB Bandwidth & 99% Bandwidth of 802.11n (HT20).....	18
Table 13: Test result of 6dB Bandwidth & 99% Bandwidth of 802.11n (HT40).....	18
Table 14: Test result of power spectral density:	68

8. List of Photographs

Photograph 1: Set-up for Conducted Emissions	179
Photograph 2: Set-up for Spurious Emissions for 30 - 1000MHz	179
Photograph 3: Set-up for Spurious Emissions for 1 - 18GHz	180