

**RF Exposure****FCC ID: 2AICB-SCBW01****Applied procedures / limit**

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

**TEST RESULTS****2.4G wifi:**

Test Channel	Frequency	Maximum Peak Conducted Output Power (PK)	LIMIT
	(MHz)	(dBm)	dBm
TX 802.11b Mode			
CH01	2412	6.24	30
CH06	2437	6.23	30
CH11	2462	5.98	30
TX 802.11g Mode			
CH01	2412	8.84	30
CH06	2437	8.81	30
CH11	2462	7.96	30
TX 802.11n(20) Mode			
CH01	2412	8.98	30
CH06	2437	8.91	30
CH11	2462	8.00	30
TX 802.11n(40) Mode			
CH03	2422	9.38	30
CH06	2437	9.30	30
CH09	2452	8.69	30

Mode	Range	Maximum peak output power (dBm)	Output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW / cm ²)	Limit of Power Density (S) (mW / cm ²)	Result
802.11b	5~7	7	5.01	3.9(2.45)	0.0024	1	Pass
802.11g	7~9	9	7.94	3.9(2.45)	0.0039	1	Pass
802.11n-HT20	7~9	9	7.94	3.9(2.45)	0.0039	1	Pass
802.11n-HT40	8~10	10	10.00	3.9(2.45)	0.0049	1	Pass