DEKRA Testing and Certification, S.A.U.
Parque Tecnológico de Andalucía,
c/ Severo Ochoa nº 2 · 29590 Campanillas · Málaga · España
C.I.F. A29507456

DEKRA

ilac-MRA ENAC ENSAYOS Nº 51/LE147

Test report No:
NIE: 64798RRF.002

Test Report

USA FCC Part 15.247, 15.209
CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.
Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.
General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	Bluetooth connected shaver
(*) Trademark	Philips
(*) Model and /or type reference	Series 9000 Tested model: S9985 Derived models not tested: S9982, S9983, S9986, S9987, S9989
Other identification of the product	HW version: 1.0 SW (FW) version: 1346 FCC ID: 2AICSS99 IC: 21912-S99
(*) Features	Bluetooth Low Energy
Applicant	Philips Oliemolenstraat 5, 9203 ZN Drachten. The Netherlands.
Test method requested, standard	USA FCC Part 15.247 (10-1-19 Edition): Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19 Edition): Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5, Amendment 1 (March 2019). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	José Carlos Luque RF Lab. Supervisor Firmado digitalmente por 74841983Y JOSE CARLOS LUQUE (C:A29507456) Fecha: 2020.10.26 07:18:19 +01'00'
Date of issue	2020-10-23
Report template No	FDT08_22

(*) "Data provided by the client"

Index

Competences and guarantees 3
General conditions 3
Uncertainty 3
Data provided by the client 3
Usage of samples 5
Test sample description 6
Identification of the client 7
Testing period and place 7
Document history 8
Environmental conditions 8
Remarks and comments 8
Testing verdicts 10
Summary 10
Appendix A: Test results. Bluetooth Low Energy 11

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor k=2) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").

2. The sample of the Series 9000 model S9985 is a Bluetooth connected shaver (which can be connected to a mobile application/App).

3. Derived models not tested: S9982, S9983, S9986, S9987, S9989.

These models have been declared by the supplier as equivalent ones:

Drachten (the Netherlands), 9th of October 2020

DECLARATION of EQUIVALENCE

By means of this letter, we, Philips Consumer Lifestyle BV, declare that the following series of shavers are identical in electrical construction. These models have identical RF characteristics and specifications for Bluetooth Low Energy interface on the 2,4GHz band. Except for model name, type marking and cover edge/finishing of the outer body, which does not affect the Safety, EMC and Energy test results.

The devices with their differences are listed below:

Model	Differences
S9982	Colouring/finishing of the hardware/shaver body ('Ice blue')
S9983	Colouring/finishing of the hardware/shaver body ('Ash gold')
S9985	Colouring/finishing of the hardware/shaver body ('Chrome Silver')
S9986	Colouring/finishing of the hardware/shaver body ('Ink Black')
S9987	Colouring/finishing of the hardware/shaver body ('Dark Chrome')
S9989	Colouring/finishing of the hardware/shaver body ('Ultra Black')

Please feel free to contact me in case you need any more information,

Yours sincerely,

Martijn Platzer
Quality Assurance Manager
Philips Consumer Lifestyle
Oliemolenstraat 5, 9203 ZN Drachten, The Netherlands
Email: Martijn.Platzer@philips.com

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
64798/001	Bluetooth Connected Shaver	Series 9000 model S9985	--	2020/08/21

Auxiliary elements used with the Sample S/01:

Control Nº	Description	Model	Serial Nº	Date of reception
64305/001	AC/DC Adapter	AD21163HF	--	2020/07/13
64798/005	USB_DTM	V2	--	2020/09/18

Sample S/01 has undergone the following test(s): All RADIATED tests indicated in Appendix A.

- Sample S/02 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
64798/002	Bluetooth Connected Shaver	Series 9000 model S9985	--	2020/08/21

Auxiliary elements used with the Sample S/02:

Control Nº	Description	Model	Serial Nº	Date of reception
64305/001	AC/DC Adapter	AD21163HF	--	2020/07/13
64798/005	USB_DTM	V2	--	2020/09/18

Sample S/02 has undergone the following test(s): All CONDUCTED tests indicated in Appendix A.

Test sample description

<table>
<tr><td rowspan="7">Ports…… :</td><td rowspan="2">Port name and description</td><td colspan="4">Cable</td></tr>
<tr><td>Specified max length [m]</td><td>Attached during test</td><td>Shielded</td><td>Coupled to patient(3)</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td></td><td></td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td>Supplementary information to the ports…… :</td><td colspan="5"></td></tr>
<tr><td rowspan="5">Rated power supply ..... :</td><td colspan="2" rowspan="2">Voltage and Frequency</td><td colspan="4">Reference poles</td></tr>
<tr><td>L1</td><td>L2</td><td>L3</td><td>N</td><td>PE</td></tr>
<tr><td>☐</td><td>AC:</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td>☐</td><td>AC:</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td><td>☐</td></tr>
<tr><td>☒</td><td colspan="5">DC: 3.6 V</td></tr>
<tr><td></td><td>☐</td><td colspan="5">DC:</td></tr>
<tr><td>Rated Power ..... :</td><td colspan="6"></td></tr>
<tr><td>Clock frequencies ..... :</td><td colspan="6"></td></tr>
<tr><td>Other parameters..... :</td><td colspan="6"></td></tr>
<tr><td>Software version ..... :</td><td colspan="6">SW (FW) version: 1346</td></tr>
<tr><td>Hardware version..... :</td><td colspan="6">1.0</td></tr>
<tr><td>Dimensions in cm (W x H x D).... :</td><td colspan="6"></td></tr>
<tr><td rowspan="5">Mounting position..... :</td><td>☐</td><td colspan="5">Table top equipment</td></tr>
<tr><td>☐</td><td colspan="5">Wall/Ceiling mounted equipment</td></tr>
<tr><td>☐</td><td colspan="5">Floor standing equipment</td></tr>
<tr><td>☐</td><td colspan="5">Hand-held equipment</td></tr>
<tr><td>☐</td><td colspan="5">Other:</td></tr>
</table>

Modules/parts .....:	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item) .....:	Description	Type	Manufacturer
Documents as provided by the applicant.....:	Description	File name	Issue date

(3) Only for Medical Equipment

Identification of the client

PHILIPS CONSUMER LIFESTYLE BV
Oliemolenstraat 5, 9203 ZN Drachten, the Netherlands

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2020-09-18
Date (finish)	2020-09-22

Document history

Report number	Date	Description
64798RRF.002	2020-10-23	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 20 % Max. = 75 %

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 ºC Max. = 35 ºC
Relative humidity	Min. = 20 % Max. = 75 %

Remarks and comments

The tests have been performed by the technical personnel: José Manuel Jiménez, Javier Miguel Nadales, Alfonso Gutiérrez.

Used instrumentation:

Conducted Measurements:

		Last Calibration	Due Calibration
1.	Shielded Room ETS LINDGREN S101	N.A.	N.A.
2.	Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2020/03	2022/03
4.	SIGNAL GENERATOR 8kHz-6GHz model SMB100B	2019/10	2021/10
5.	VECTOR SIGNAL GENERATOR 8kHz-6GHz model SMBV100B	2019/10	2020/10
6.	SIGNAL AND SPECTRUM ANALYZER 10Hz-40GHz model FSV40	2019/09	2021/09
7.	WIRELESS CONNECTIVITY TESTER BW 160 MHz model CMW270	2019/10	2020/10
8.	OPEN SWITCH UNIT model OSP120	2019/10	2021/10
9.	OPEN SWITCH UNIT UP TO 18GHz model OSP 150	2019/09	2021/09

Radiated Measurements:

		Last Calibration	Due Calibration
1.	Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2.	Shielded Room ETS LINDGREN S101	N.A.	N.A.
3.	Biconical/Log Antenna 30MHz - 6GHz ETS LINDGREN 3142E	2017/09	2020/09
4.	Attenuator 3 dB 2W, DC-6GHz, JFW 50HN-03	2019/10	2020/10
5.	RF Preamplifier 40 dB, 10 MHz - 6 GHz BONN ELEKTRONIK BLNA 0160-01N	2020/02	2021/02
6.	EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2019/10	2021/10
7.	Low Pass Filter DC - 1 GHz TEMSTRON / TEMWELL ST-1GA3250-LS	2019/10	2020/10
8.	Digital Multimeter, FLUKE 175	2019/10	2020/10
9.	Horn Antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2018/01	2021/01
10.	Broadband Horn Antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2018/07	2021/07
11.	RF Preamplifier G>30dB, 1-18GHz BONN ELEKTRONIK BLMA 0118-3A	2019/11	2020/11
12.	Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
13.	Signal and Spectrum Analyzer 10 Hz - 40 GHz ROHDE AND SCHWARZ FSV40	2019/10	2021/10

Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

Summary

1. Bluetooth Low Energy.

FCC PART 15 PARAGRAPH/ RSS-247			
Requirement – Test case		**Verdict**	**Remark**
FCC 15.247 (a)(2) / RSS-247 5.2. (a)	6 dB Bandwidth	P	
FCC 15.247 (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	
FCC 15.247 (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	P	
FCC 15.247 (e) / RSS-247 5.2. (b)	Power spectral density	P	
FCC 15.247 (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	
Supplementary information and remarks: None.			

Appendix A: Test results. Bluetooth Low Energy

INDEX

TEST CONDITIONS....13
Occupied Bandwidth....16
FCC 15.247 (a)(2) / RSS-247 5.2. (a) 6 dB Bandwidth....18
FCC 15.247 (b) / RSS-247 5.4. (d) Maximum output power and antenna gain....20
FCC 15.247 (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)....23
FCC 15.247 (e) / RSS-247 5.2. (b) Power spectral density....25
FCC 15.247 (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)....27

TEST CONDITIONS

POWER SUPPLY (V):

V nonimal:	3.6 Vdc
Type of Power Supply:	AC/DC Adapter.

ANTENNA:

Type of Antenna:	Internal.
Maximum Declared Antenna Gain:	+2.5 dBi

TEST FREQUENCIES:

Low Channel:	2402 MHz
Middle Channel:	2440 MHz
High Channel:	2480 MHz

CONDUCTED MEASUREMENTS:

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.

RADIATED MEASUREMENTS:

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1000 MHz and 1 GHz-17 GHz Double ridge horn antenna) is situated at a distance of 3 m and a distance of 1 m for the frequency range 17 GHz-26 GHz (18 GHz-40 GHz horn antenna).

For radiated emissions in the range 17 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360º and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

A resolution bandwidth / video bandwidth of 100 kHz / 300 kHz was used for frequencies below 1 GHz and 1 MHz / 3 MHz for frequencies above 1 GHz.

Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup from 1 GHz to 17 GHz:



Radiated measurements setup f > 17 GHz:



Occupied Bandwidth

RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
99% bandwidth (MHz)	1.050000	1.055000	1.055000
Measurement uncertainty (%)	<± 2.08		

- Low Channel:



- Middle Channel:



- High Channel:



FCC 15.247 (a)(2) / RSS-247 5.2. (a) 6 dB Bandwidth

SPECIFICATION:

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS:

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
6 dB Bandwidth (MHz)	0.732674	0.732674	0.732674
Measurement uncertainty (%)	<±2.08		

Verdict: PASS

- Low Channel:



- Middle Channel:



- High Channel:



FCC 15.247 (b) / RSS-247 5.4. (d) Maximum output power and antenna gain

SPECIFICATION:

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).
The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

RESULTS:

The maximum peak conducted output power level in the fundamental emission was measured using the method according to point 11.9.1.1 ”RBW ≥ DTS bandwidth” of ANSI C.63.10-2013.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Maximum Declared Antenna Gain: +2.5 dBi

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Maximum Conducted Power (dBm)	0.3	0.6	0.7
Maximum EIRP Power (dBm)	2.8	3.1	3.2
Measurement uncertainty (dB)	<±0.99		

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

- Low Channel:



- Middle Channel:



- High Channel:



FCC 15.247 (d) / RSS-247 5.5. Band-edge emissions compliance (Transmitter)

SPECIFICATION:

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

RESULTS:

- Low Channel:



Measurement uncertainty (dB)	<±0.89

Verdict: PASS

- High Channel:

Band Edge



Measurement uncertainty (dB)	<±0.89

Verdict: PASS

FCC 15.247 (e) / RSS-247 5.2. (b) Power spectral density

SPECIFICATION:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS:

The maximum power spectral density level in the fundamental emission was measured using the method according to FCC title 47 part 15 §15.247(a)(e), KDB 558074 D01 DTS Meas Guidance v05 F and ANSI C.63.10-2013.

	Low Channel 2402 MHz	Middle Channel 2440 MHz	High Channel 2480 MHz
Power Spectral Density (dBm)	-9.600	-9.357	-9.335
Measurement uncertainty (dB)	<±0.99		

Verdict: PASS

- Low Channel:



- Middle Channel:



- High Channel:



FCC 15.247 (d) / RSS-247 5.5. Emission limitations radiated (Transmitter)

SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)/RSS-Gen):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 10000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247: Attenuation below the general field strength limits specified in RSS-Gen is not required.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360º and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-17 GHz and at distance of 1 m for the frequency range 17 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Frequency range 30 MHz - 1 GHz:

The spurious frequencies detected do not depend neither on the operating channel nor the modulation mode.

Spurious frequencies at less than 20 dB below the limit:

Spurious Frequency (MHz)	Emission Level (dBµV/m)	Polarization	Detector	Measurement Uncertainty (dB)
41.2035	27.37	V	Quasi Peak	<± 5.17
104.3505	28.31	V	Quasi Peak	<± 5.17
835.7305	29.53	H	Quasi Peak	<± 5.17

Measurement Uncertainty (dB): <± 5.17

Frequency range 1 - 26 GHz:

The results in the next tables show the maximum measured levels in the 1-26 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

Spurious frequencies with peak levels above the average limit (54 dBµV/m at 3 m) are measured with average detector for checking compliance with the average limit.

- LOW CHANNEL. Spurious frequencies closest to the limit:

Spurious Frequency (GHz)	Emission Level (dBµV/m)	Duty Cycle Correction (dB)	Emission Level (dBµV/m)	Polarization	Detector	Measurement Uncertainty (dB)
4.8035	44.94	-	44.94	V	Peak	<± 5.13
	33.42	2.04	35.46		Average	

- MIDDLE CHANNEL. Spurious frequencies closest to the limit:

Spurious Frequency (GHz)	Emission Level (dBµV/m)	Duty Cycle Correction (dB)	Emission Level (dBµV/m)	Polarization	Detector	Measurement Uncertainty (dB)
4.8795	44.36	-	44.36	V	Peak	<± 5.13
	32.4	2.04	34.44		Average	

- HIGH CHANNEL. Spurious frequencies closest to the limit:

Spurious Frequency (GHz)	Emission Level (dBµV/m)	Duty Cycle Correction (dB)	Emission Level (dBµV/m)	Polarization	Detector	Measurement Uncertainty (dB)
4.9595	46.42	-	46.42	V	Peak	<± 5.13
	35.47	2.04	37.51		Average	

Measurement Uncertainty (dB): 1 GHz - 17 GHz <± 5.13
17 GHz - 26 GHz <± 4.81

Verdict: PASS

FREQUENCY RANGE 30 MHz - 1 GHz:

The spurious frequencies detected do not depend neither on the operating channel nor the modulation mode. This plot is valid for the Low, Middle and High Channels.



The above plot shows the results of the scan using peak detector.

FREQUENCY RANGE 1 - 3 GHz:

- Low Channel:



The peak above the limit is the carrier frequency.

- Middle Channel:



The peak above the limit is the carrier frequency.

- High Channel:



The peak above the limit is the carrier frequency.

FREQUENCY RANGE 3 - 17 GHz:

- Low Channel:



- Middle Channel:



- High Channel:



FREQUENCY RANGE 17 - 26 GHz:

This plot is valid for the Low, Middle and High Channels.



FREQUENCY RANGE 2.31-2.39 GHz:

- Low Channel:



- Middle Channel:



- High Channel:



FREQUENCY RANGE 2.4835-2.5 GHz:

- Low Channel:



- Middle Channel:



- High Channel: