



MPE Report

Report No.: STS2604368H01

Issued for

Zhiwei Robotics Corp.

Unit 01, 26/F, A1 Shanghai T & I Tower, No. 1699 Zhongke
Road, Pudong District, Shanghai, P.R.China

Product Name: DFRobot RK3576 evaluation board

Brand Name:



DFROBOT
DRIVE THE FUTURE

Model Name: DFR1218

Series Model(s): N/A

FCC ID: 2AIDM-DFR1218

Test Standard: FCC Part15.247

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

**TEST REPORT**

Applicant's Name: Zhiwei Robotics Corp.
Address: Unit 01, 26/F, A1 Shanghai T & I Tower, No. 1699 Zhongke Road,
Pudong District, Shanghai, P.R.China
Manufacturer's Name: Zhiwei Robotics Corp.
Address: Unit 01, 26/F, A1 Shanghai T & I Tower, No. 1699 Zhongke Road,
Pudong District, Shanghai, P.R.China

Product Description

Product Name: DFRobot RK3576 evaluation board

Brand Name:  **DFROBOT**
DRIVE THE FUTURE

Model Name: DFR1218

Series Model(s): N/A

Test Standards: FCC 47CFR §2.1091
447498 D01 Interim General RF Exposure Guidance v06

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

Date of Test:

Date of receipt of test item: 15 Jan. 2026

Date (s) of performance of tests: 15 Jan. 2026 ~ 14 Apr. 2026

Date of Issue: 15 Apr. 2026

Test Result: **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	7

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	14 Apr. 2026	STS2604368W01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	DFRobot RK3576 evaluation board		
Brand Name	N/A		
Model Name	DFR1218		
Series Model(s)	N/A		
Model Difference	N/A		
Product Description	The EUT is a DFRobot RK3576 evaluation board		
	Operation Frequency:	BT/BLE:2402~2480 MHz 2.4G WIFI:802.11b/g/n 20: 2412~2462 MHz 802.11n40:2422~2452MHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11ac(VHT80): 5.210GHz IEEE 802.11a/ n(HT20)/ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/ n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11ac(VHT80): 5.775GHz	
	Modulation Type:	BT:GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps), 8DPSK(3Mbps) BLE:GFSK 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11b/g Support SISO 802.11n Support SISO IEEE 802.11a/ n(HT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40): 5.190GHz-5.230GHz IEEE 802.11a/ n(HT20): 5.745GHz-5.825GHz IEEE 802.11n(HT40):5.755GHz-5.795GHz 802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11a Support SISO 802.11n Support SISO	
	Antenna gain:	Bluetooth/WLAN 2.4 GHz: 1.49 dBi WLAN 5 GHz: 2.42 dBi	
	Antenna Designation:	FPC Antenna	
Power Rating	DC 12V from adapter		
Adapter	N/A		
Battery	N/A		
Hardware Version	N/A		

101, Building B, Zhuoke Science Park, No. 190 Chongqing Road, Zhancheng Shequ, Fuhai Sub-District, Bao'an District, Shenzhen, G

+86-755 3688 6288 Fax: +86-755 3688 6277 Http://www.stsapp.com E-mail:sts@stsapp.com



Software Version	N/A
------------------	-----

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
3.0-30	1842/f	4.89/f	*(900/f ²)
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1.34-30	824/f	2.19/f	*(180f ²)
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 TEST RESULT

Tune up

Mode	Detector	Tune up Power
BT	Peak	5±1dBm
BLE	Peak	7±1dBm
2.4G WIFI	Peak	11±1dBm
5G WIFI	AV	13±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	Max Tune up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
BT	2.402	20	6	1.49	7.49	5.610	0.0011	1	0.0011	Pass
BLE	2.402	20	8	1.49	9.49	8.892	0.0018	1	0.0018	Pass
2.4G WIFI	2.412	20	12	1.49	13.49	22.336	0.0044	1	0.0044	Pass
5G WIFI	5.785	20	14	2.42	16.42	43.853	0.0087	1	0.0087	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. The Bluetooth and WLAN can't simultaneous transmission at the same time.

3. ERP = EIRP - 2.15

*****END OF THE REPORT*****