

FCC TEST REPORT

FCC ID: 2AIEGM9

Product Name : Wooden Bluetooth Alarm Clock Speaker

Model Name : M9, HM9, M9qi

Brand : Homtime

Report No. : PT800269160422E-FC02

Prepared for

All Best Technology Limited

Yincheng 1st Rd., Yincheng Industrial Zone, Xiabian Village, Chang'an Town, Dongguan City,
Guangdong Province, China

Prepared by

DongGuan Precise Testing Service Co., Ltd.

Building D, Baoding Technology Park, Guangming Road 2, Guangming Community

Dongcheng District, Dongguan, Guangdong, China

TEST RESULT CERTIFICATION

Applicant's name : All Best Technology Limited

Address : Yincheng 1st Rd., Yincheng Industrial Zone, Xiabian Village, Chang'an Town, Dongguan City, Guangdong Province, China

Manufacture's name : All Best Technology Limited

Address : Yincheng 1st Rd., Yincheng Industrial Zone, Xiabian Village, Chang'an Town, Dongguan City, Guangdong Province, China

Product name : Wooden Bluetooth Alarm Clock Speaker

Model name : M9, HM9, M9qi

Standards : FCC CFR47 Part 15 Section 15.247

Test procedure : ANSI C63.10:2013, DA 00-705

Test Date : Apr .27, 2016 ~ May.18, 2016

Date of Issue : May.19, 2016


Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.


Testing Engineer

August Qiu




Technical Manager

Hack Ye



Authorized Signatory

Chris Du



Contents

	Page
2 TEST SUMMARY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T.	5
4 RF EXPOSURE	5
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Wooden Bluetooth Alarm Clock Speaker
Model Name	:	M9, HM9, M9qi
Model Description	:	Only the models name is different
Bluetooth Version	:	V4.1 classic
Operating frequency	:	2402-2480MHz, 79 channels
Antenna installation:	:	PCB Printed Antenna
Antenna Gain:	:	0dBi
The lowest oscillator:	:	26MHz
Type of Modulation	:	GFSK, Pi/4DQPSK, 8DPSK
Power supply	:	AC 230V/50Hz Power by Adapter, DC 5V charging by USB port

4 RF Exposure

Test Requirement : FCC Part 1.1307

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v05

4.1 Requirements

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances $\leq$ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz

2. Power and distance are rounded to the nearest mW and mm before calculation

3. The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

4.2 The procedures / limit

Item	Max output power include tune-up tolerance (dBm)	Max output power include tune-up tolerance(mW)	Source-based time-averaged Max output power include tune-up tolerance (mW)	Minimum test separation distance required for the exposure conditions (mm)	SAR Test Exclusion Thresholds(mW)
BT	5.0	3.16	3.16	5	9.525
Remark:					
BT: The power tune up tolerance is 4.0 ± 1.0 dBm					
Max. duty factor is 100%					
Calculation formula: Source-based time-averaged maximum conducted output power(mW) = Conducted peak power(mW)*Duty factor					

Max output power include tune-up tolerance

*****THE END REPORT*****