

TEST REPORT

Applicant: Darmuoba, S.A. de C.V

Address of Applicant: Mar Negro 1, Col. Tacuba, CDMX. C.P 11410 Miguel Hidalgo, Distrito Federal, Mexico

Manufacturer/Factory: Z-TECH COMMUNICATION(SZ)CO;LTD

Address of Manufacturer/Factory: 7L BLK D BAO'AN ZHIGU YIN'TIAN ROAD NO.4 XI'XIANG, BAO'AN DISTRICT SZ CHINA

Equipment Under Test (EUT)

Product Name: MOBIE PHONE

Model No.: SD50

Trade Mark: UNEONE

FCC ID: 2AIFYSD50

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: April 28, 2019

Date of Test: April 29, 2019-May 30, 2019

Date of report issued: May 31, 2019

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature in blue ink is written over a circular blue stamp. The stamp contains the text "GLOBAL UNITED TECHNOLOGY SERVICES" around the perimeter and "GTS" in the center. The signature appears to be "Robinson Lo" and is dated "May 31, 2019".

Robinson Lo

Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	May 31, 2019	Original

Prepared By:

Bill. Yuan

Date:

May 31, 2019

Project Engineer

Check By:

Robinson

Date:

May 31, 2019

Reviewer

3 Contents

1	COVER PAGE	1
2	VERSION	2
3	CONTENTS	3
4	TEST SUMMARY	4
5	GENERAL INFORMATION	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE AND TEST VOLTAGE.....	5
5.3	DESCRIPTION OF SUPPORT UNITS.....	6
5.4	DEVIATION FROM STANDARDS.....	6
5.5	ABNORMALITIES FROM STANDARD CONDITIONS	6
5.6	TEST FACILITY.....	6
5.7	TEST LOCATION.....	6
6	TEST INSTRUMENTS LIST	7
7	TEST RESULTS AND MEASUREMENT DATA	9
7.1	RADIATED EMISSION.....	9
7.2	CONDUCTED EMISSIONS	15
8	TEST SETUP PHOTO	18
9	EUT CONSTRUCTIONAL DETAILS.....	18

4 Test Summary

Test Item	Test Requirement	Test Method	Class / Severity	Result
Conducted Emission	FCC Part15.107	ANSI C63.4	Class B	PASS
Radiated Emissions #	FCC Part15.109	ANSI C63.4	Class B	PASS

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. # Refer to FCC Part 15.33 (b)(1) conditional testing procedure :

The highest frequency generated or used in the EUT	Test frequency range of Radiated emission
<108MHz	30MHz ~ 1GHz
108MHz ~ 500MHz	30MHz ~ 2GHz
500MHz ~ 1GHz	30MHz ~ 5GHz
>1GHz	30MHz ~ 5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Note: the EUT Internal clock frequency above 108MHz.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30MHz ~ 200MHz	± 3.92dB	(1)
Radiated Emission	200MHz~1000 MHz	± 4.10dB	(1)
Radiated Emission	1GHz ~ 6GHz	± 5.34dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	MOBIE PHONE
Model No.:	SD50
Serial No.:	356888100000437
Hardware Version:	SD50_V1.1
Software Version:	SD50_002R
Test sample(s) ID:	GTS201904000204-2
Sample(s) Status:	Normal sample
Power Supply:	Adaptor Model:SD50-A Input: AC 100-240V, 50-60Hz, 150mA Output: DC 5V, 800mA Or Battery: DC 3.8V, 2000mAh, 7.6W

5.2 Test mode and Test voltage

Test mode:	
PC mode	Keep the EUT in exchanging data mode.
REC mode	Keep the EUT in REC mode.
Audio play mode	Keep the EUT in Audio play mode.
Video play mode	Keep the EUT in Video play mode.
Test voltage	
AC 120V and DC 3.8V	

5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook PC	E40-80	N/A
Canon	Printer	IP1600	N/A
DELL	KEYBOARD	SK-8115	GTS237-2
DELL	MOUSE	MOC5UO	GTS237-3
SanDisk	TF card	16GB	N/A

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2.

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0

5.7 Test Location

The test was performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list



Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Oct. 20 2018	Oct. 19 2019
22	Amplifier	TDK	PA-02-02	GTS574	Oct. 20 2018	Oct. 19 2019
23	Amplifier	TDK	PA-02-03	GTS576	Oct. 20 2018	Oct. 19 2019
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	June. 27 2018	June. 26 2019

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.15 2019	May.14 2022
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	Shanghai	ZJ1-2B	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test Results and Measurement Data

7.1 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2014				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.00		Quasi-peak Value
	88MHz-216MHz		43.50		Quasi-peak Value
	216MHz-960MHz		46.00		Quasi-peak Value
	960MHz-1GHz		54.00		Quasi-peak Value
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:	For radiated emissions from 30MHz to1GHz				
					
	For radiated emissions above 1GHz				
					

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Test Instruments:	Refer to section 6 for details					
Test mode:	Refer to section 5.2 for details, only show the worst case.					
Test results:	Pass					

Measurement Data


Below 1GHz

Test mode:	PC mode	Antenna Polarity:	Horizontal
------------	---------	-------------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
55.221	43.96	11.78	0.82	36.26	20.30	40.00	-19.70	QP
74.657	53.18	7.45	0.98	36.49	25.12	40.00	-14.88	QP
197.893	56.41	10.31	1.83	37.32	31.23	43.50	-12.27	QP
290.017	53.66	13.35	2.31	37.41	31.91	46.00	-14.09	QP
383.932	62.60	15.08	2.78	37.51	42.95	46.00	-3.05	QP
801.786	41.46	21.40	4.46	37.62	29.70	46.00	-16.30	QP


Test mode:	PC mode	Antenna Polarity:	Vertical
------------	---------	-------------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
42.900	48.64	12.23	0.69	35.83	25.73	40.00	-14.27	QP
51.121	48.75	12.18	0.78	36.20	25.51	40.00	-14.49	QP
78.139	49.28	7.42	1.01	36.53	21.18	40.00	-18.82	QP
191.745	60.51	9.99	1.80	37.29	35.01	43.50	-8.49	QP
383.932	62.10	15.08	2.78	37.51	42.45	46.00	-3.55	QP
576.644	41.35	19.00	3.63	37.53	26.45	46.00	-19.55	QP


Above 1GHz

Test mode:	PC mode	Antenna Polarity:	Horizontal
------------	---------	-------------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
1170.000	61.99	0.00	4.44	35.88	30.55	74.00	-43.45	Peak
2005.000	58.43	0.00	4.97	36.51	26.89	74.00	-47.11	Peak
3410.000	63.67	0.00	6.78	37.34	33.11	74.00	-40.89	Peak
4590.000	65.09	0.00	8.41	37.64	35.86	74.00	-38.14	Peak
5385.000	64.76	0.00	9.33	37.24	36.85	74.00	-37.15	Peak
5785.000	65.42	0.00	9.90	36.69	38.63	74.00	-35.37	Peak

Test mode:	PC mode	Antenna Polarity:	Vertical
------------	---------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
1195.000	37.27	25.33	4.46	35.91	31.15	74.00	-42.85	Peak
2335.000	31.61	27.77	5.32	36.80	27.90	74.00	-46.10	Peak
3415.000	35.92	28.67	6.80	37.35	34.04	74.00	-39.96	Peak
4435.000	33.29	31.20	8.27	37.58	35.18	74.00	-38.82	Peak
5165.000	33.03	32.04	9.01	37.56	36.52	74.00	-37.48	Peak
5745.000	33.99	32.56	9.86	36.73	39.68	74.00	-34.32	Peak

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

7.2 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)		Limit (dBμV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	0.5-30		60		50	
Test setup:	Reference Plane  Test table/Insulation plane					
	<i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Test Instruments:	Refer to section 6 for details					
Test mode:	Refer to section 5.2 for details, only show the worst case.					
Test results:	Pass					


Measurement Data

Test mode:	REC mode	Phase Polarity:	Line
------------	----------	-----------------	------



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.19	48.25	0.40	0.11	48.76	63.84	-15.08	QP
0.19	32.66	0.40	0.11	33.17	53.84	-20.67	Average
0.26	41.84	0.40	0.10	42.34	61.38	-19.04	QP
0.26	27.28	0.40	0.10	27.78	51.38	-23.60	Average
0.46	36.58	0.33	0.11	37.02	56.63	-19.61	QP
0.46	21.20	0.33	0.11	21.64	46.63	-24.99	Average
0.59	35.45	0.29	0.12	35.86	56.00	-20.14	QP
0.59	18.78	0.29	0.12	19.19	46.00	-26.81	Average
1.66	31.40	0.20	0.17	31.77	56.00	-24.23	QP
1.66	13.41	0.20	0.17	13.78	46.00	-32.22	Average
12.65	35.29	0.20	0.21	35.70	60.00	-24.30	QP
12.65	29.87	0.20	0.21	30.28	50.00	-19.72	Average

Test mode:	REC mode	Phase Polarity:	Neutral
------------	----------	-----------------	---------



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.20	50.41	0.40	0.11	50.92	63.76	-12.84	QP
0.20	37.51	0.40	0.11	38.02	53.76	-15.74	Average
0.26	43.34	0.40	0.10	43.84	61.29	-17.45	QP
0.26	28.89	0.40	0.10	29.39	51.29	-21.90	Average
0.32	39.90	0.39	0.10	40.39	59.66	-19.27	QP
0.32	28.13	0.39	0.10	28.62	49.66	-21.04	Average
0.58	41.74	0.29	0.12	42.15	56.00	-13.85	QP
0.58	24.94	0.29	0.12	25.35	46.00	-20.65	Average
1.61	38.47	0.20	0.17	38.84	56.00	-17.16	QP
1.61	22.18	0.20	0.17	22.55	46.00	-23.45	Average
12.65	35.47	0.20	0.21	35.88	60.00	-24.12	QP
12.65	29.69	0.20	0.21	30.10	50.00	-19.90	Average

Notes:

- The following Quasi-Peak and Average measurements were performed on the EUT:
- Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----