

## Appendix I- RF Exposure statement

Evaluate standard : FCC KDB # 447498 D01 V06  
 RSS-102 Issue 5

### Calculated Output Power

The maximum measured transmitter power is the following:

| Frequency<br>[GHz] | Field Strength of<br>Fundamental<br>Emissions<br>[dBuV/m] | Field Strength of<br>Fundamental<br>Emissions<br>[dBm] | Field Strength of<br>Fundamental<br>Emissions<br>[mW] |
|--------------------|-----------------------------------------------------------|--------------------------------------------------------|-------------------------------------------------------|
| 0.908430           | 89.454                                                    | -5.77                                                  | 0.265                                                 |

Note:Relation between power, electric field strength,E

A simple relation can be established for perfect, ideal cases (which means free space, far field conditions) between E(V/m), D distance between the transmitting radio equipment and the point of measurement (m), e.i.r.p.(W).

$$E = \sqrt{\frac{30(e.i.r.p.)}{D}}$$

This represents a site gain of 4dB. The field strength as E(V/m) can be converted to dB(uV/m) as follows:

$$E(dB(uV / m)) = 120 + 20 \log E$$

### Evaluation for FCC

According to FCC KDB # 447498 D01 V06, Clause 4.3.1

- (a) For 100MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\frac{(\text{max. power of channel, including tune - up tolerance, mW})}{(\text{min. test separation distance, mm})} \times \sqrt{f(\text{GHz})}$$

$\leq 3.0$ , for 1-g SAR, and  $\leq 7.5$ , for 10-g extremity SAR

So, the max allowed power for 1-g SAR with distance 5mm at 0.908430GHz is 15.73785mW

And the max allowed power for 10-g extremity SAR with distance 5mm at 0.908430GHz is 39.34464mW

The maximum conducted output power of the EUT is: 0.265mW which is totally lower than the SAR test exclusion thresholds.

## Evaluation for IC

According to table 1 and note 4 of RSS-102 Issue 5, March 2015

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                 |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
|                 | At separation distance of ≤5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤300            | 71 mW                           | 101 mW                          | 132 mW                          | 162 mW                          | 193 mW                          |
| 450             | 52 mW                           | 70 mW                           | 88 mW                           | 106 mW                          | 123 mW                          |
| 835             | 17 mW                           | 30 mW                           | 42 mW                           | 55 mW                           | 67 mW                           |
| 1900            | 7 mW                            | 10 mW                           | 18 mW                           | 34 mW                           | 60 mW                           |
| 2450            | 4 mW                            | 7 mW                            | 15 mW                           | 30 mW                           | 52 mW                           |
| 3500            | 2 mW                            | 6 mW                            | 16 mW                           | 32 mW                           | 55 mW                           |
| 5800            | 1 mW                            | 6 mW                            | 15 mW                           | 27 mW                           | 41 mW                           |

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                  |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
|                 | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥50 mm |
| ≤300            | 223 mW                          | 254 mW                          | 284 mW                          | 315 mW                          | 345 mW                           |
| 450             | 141 mW                          | 159 mW                          | 177 mW                          | 195 mW                          | 213 mW                           |
| 835             | 80 mW                           | 92 mW                           | 105 mW                          | 117 mW                          | 130 mW                           |
| 1900            | 99 mW                           | 153 mW                          | 225 mW                          | 316 mW                          | 431 mW                           |
| 2450            | 83 mW                           | 123 mW                          | 173 mW                          | 235 mW                          | 309 mW                           |
| 3500            | 86 mW                           | 124 mW                          | 170 mW                          | 225 mW                          | 290 mW                           |
| 5800            | 56 mW                           | 71 mW                           | 85 mW                           | 97 mW                           | 106 mW                           |

For frequencies (835 MHz to 1900 MHz), the conservative limit of 1900MHz can be used for exemption limits.

So, the max allowed power for 1-g SAR with distance 5mm at 908.430MHz is 7mW

The maximum conducted output power of the EUT is: 0.265mW which is totally lower than the SAR test exclusion thresholds.

## Conclusion

Since the distance of the device in generally using is lower than 5mm, so a distance of 5mm is applied to determine SAR test exclusion.  
 SAR data is not required for either FCC or IC.