FCC Test Report

Part 15 subpart C

Client Information:

Applicant: DONGGUAN ZHONGSHENG METAL ELECTRICAL CO.,LTD.

Applicant add.: No.21 TianJingFo Industrial Zone，Xin Tang Village，Da Ling Shan Town，Dong guan，Guang dong

Product Information:

EUT Name: WIFI WITH ELECTRIC FIREPLACE

Model No.: ZHS-32-D, ZHS-32-E, ZHS-32-F, ZHS-42-D, ZHS-42-E, ZHS-42-F, ZHS-36-D, ZHS-36-E, ZHS-36-F

Brand Name: FEBO FLAME

FCC ID: 2AILSZHS-32-D

Standards: FCC PART 15 Subpart C: 2016 section 15.247

Prepared By:

ATS Electronic Technology Co., Ltd.

Add. : 3/F, Building A, No. 1 Hedong Three Road, Jinxia Communityt, Changan Town, DongGuan City, GuangDong, P.R.China

Date of Receipt:	Jun. 03, 2016	Date of Test:	Jun. 03~07, 2016
Date of Issue:	Jun. 08, 2016	Test Result:	Pass

This device described above has been tested by ATS Electronic Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

*This test report must not be used by the client to claim product endorsement by any agency of the U.S. government.

Reviewed by: Vera Wang **Approved by:** Simon Zeng

1 Contents

		Page
	COVER PAGE	
1	**CONTENTS**	**2**
2	**VERSION**	**3**
3	**TEST SUMMARY**	**4**
3.1	COMPLIANCE WITH FCC PART 15 SUBPART C	4
3.2	MEASUREMENT UNCERTAINTY	5
3.3	TEST LOCATION	5
4	**GENERAL INFORMATION**	**6**
4.1	GENERAL DESCRIPTION OF EUT	6
4.2	EUT PERIPHERAL LIST	8
4.3	TEST PERIPHERAL LIST	8
5	**EQUIPMENTS LIST FOR ALL TEST ITEMS**	**9**
6	**TEST RESULT**	**10**
6.1	DESCRIPTION OF TEST CONDITIONS	10
6.2	ANTENNA REQUIREMENT	11
6.3	CONDUCTION EMISSIONS MEASUREMENT	12
6.4	RADIATED EMISSIONS MEASUREMENT	16
6.5	6 DB BANDWIDTH	53
6.6	MAXIMUM PEAK OUTPUT POWER	61
6.7	PEAK POWER SPECTRAL DENSITY	63
6.8	BAND EDGES REQUIREMENT	72
7	**PHOTOGRAPHS**	**78**
7.1	RADIATED SPURIOUS EMISSION TEST SETUP	78
7.2	CONDUCTED EMISSION TEST SETUP	79
8	**APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS**	**80**

2 Version

Revision Record				
Version	**Chapter**	**Date**	**Modifier**	**Remark**
00	--	Jun 08, 2016	--	--

3 Test Summary

3.1 Compliance with FCC Part 15 subpart C

TEST	TEST REQUIREMENT	TEST METHOD	RESULT
Antenna Requirement	FCC PART 15 C section 15.247 (c) and Section 15.203	FCC PART 15 C section 15.247 (c) and Section 15.203	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS
Radiated Spurious Emission (30 MHz to 25 GHz)	FCC PART 15 C section 15.209 &15.247(d)	ANSI C63.10: Clause 6.4, 6.5 and 6.6	PASS
6 dB Bandwidth	FCC PART 15 C section 15.247 (a)(2)	ANSI C63.10: Clause 6.9.1	PASS
Maximum Peak Output Power	FCC PART 15 C section 15.247(b)(3)	FCC/KDB-558074 D01 v03r05 Clause 9.1.2	PASS
Peak Power Spectral Density	FCC PART 15 C section 15.247(e)	ANSI C63.10: Clause 6.11.2.3	PASS
Band Edges Measurement	FCC PART 15 C section 15.247 (d) &15.205	FCC/KDB-558074 D01 v03r05 Clause 13.3.1	PASS

Remark:
N/A: not applicable. Refer to the relative section for the details.
EUT: In this whole report EUT means Equipment Under Test.
Tx: In this whole report Tx (or tx) means Transmitter.
Rx: In this whole report Rx (or rx) means Receiver.
RF: In this whole report RF means Radio Frequency.
ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.

According to the confirmation from the applicant, since the electrical circuit design, layout, components used and internal wiring were identical for the all models, with difference being the model name and appearance color.
Therefore only one model **ZHS-32-D** was tested in this report.

Since the WiFi module(SNIOT505) of EUT has been certified(FCC ID: 2AFO5-SNIOT505), therefore we just test the Conducted Emissions at Mains Terminals & Radiated Spurious Emission, the test data of other item reference from the test report of WiFi module(SNIOT505).

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, the following measurements uncertainty Levels have estimated based on standards, the maximum value of the uncertainty as below:

No.	Item	Uncertainty
1	Conducted Emission Test	1.20dB
2	Radiated Emission Test	3.30dB

3.3 Test Location

All tests were performed at:

Dongguan Yaxu (AiT) Technology Limited
No.22, Jinqianling Third Street, Jitigang, Huangjiang,Dongguan, Guangdong, China
Tel.: +86.769.82020499 Fax.: +86.769.82020495
The FCC Registration No. of Dongguan Yaxu (AiT) Technology Limited is 248337.

4 General Information

4.1 General Description of EUT

Manufacturer:	DONGGUAN ZHONGSHENG METAL ELECTRICAL CO.,LTD.
Manufacturer Address:	No.21 TianJingFo Industrial Zone，Xin Tang Village，Da Ling Shan Town，Dong guan，Guang dong
EUT Name:	WIFI WITH ELECTRIC FIREPLACE
Model No:	ZHS-32-D
Brand Name:	FEBO FLAME
Derivative model No.:	ZHS-32-E, ZHS-32-F, ZHS-42-D, ZHS-42-E, ZHS-42-F, ZHS-36-D, ZHS-36-E, ZHS-36-F
Operation frequency:	2412 MHz to 2462 MHz for 802.11b/g/n(HT20) 2422 MHz to 2452 MHz for 802.11n(HT40)
Number of Channels:	11 Channels for 802.11b/g/n(HT20) 7 Channels for 802.11n(HT40)
Modulation Technology:	802.11b: CCK/QPSK/BPSK 802.11g/n: OFDM
Transmit Data Rate:	802.11b :1/2/5.5/11 Mbps 802.11g :6/9/12/18/24/36/48/54 Mbps 802.11n(HT20): 6.5/13/19.5/26/39/52/58.8/65/72.2 Mbps 802.11n(HT40): 13.5/15/27/30/40.5/45/54/60/81/90/108/120/121.5/135/150 Mbps
Channel Separation:	5 MHz
Antenna Type:	integral antenna
Antenna Gain:	maximum 3.0 dBi
H/W No.:	V2.1A
S/W No.:	V1.0
Power Supply Range:	AC 120V/60Hz
Power Cord:	2.0 m x three-wire unscreened AC cable
Note:	
1.	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

EUT channels and frequencies list:

1. Test frequencies are lowest channel: 2412 MHz, middle channel: 2437 MHz and highest channel: 2462 MHz for 802.11b/g/n(HT20)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

2. Test frequencies are lowest channel: 2422 MHz, middle channel: 2437 MHz and highest channel: 2452 MHz for 802.11n(HT40)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437		

4.2 EUT Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

4.3 Test Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	Lap top	ASUS	X401A	X16-96072	N/A	N/A
2	Adapter (laptop)	ASUS	EXA0703YH	N/A	1.8m/unshielded /detachable	N/A

5 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.29	2016.06.28
2	EMI Measuring Receiver	R&S	ESR	101660	2015.06.29	2016.06.28
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.29	2016.06.28
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2015.06.29	2016.06.28
5	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2015.06.29	2016.06.28
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2015.06.29	2016.06.28
7	SHF-EHF Horn	SCHWARZBECK	BBHA9170	BBHA9170367	2015.06.29	2016.06.28
8	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.29	2016.06.28
9	EMI Test Receiver	R&S	ESCI	100124	2015.06.29	2016.06.28
10	LISN	Kyoritsu	KNW-242	8-837-4	2015.06.29	2016.06.28
11	LISN	Kyoritsu	KNW-407	8-1789-3	2015.06.29	2016.06.28
12	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.29	2016.06.28
13	Loop Antenna	ETS	6512	00165355	2015.06.29	2016.06.28
14	Radiated Cable 1#（30MHz-1GHz）	FUJIKURA	5D-2W	01	2016.01.04	2017.01.03
15	Radiated Cable 2#（1GHz -25GHz）	FUJIKURA	10D2W	02	2016.01.04	2017.01.03
16	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2016.01.04	2017.01.03
17	Power Meter	Anritsu	ML2495A	N/A	2015.06.29	2016.06.28
18	Power sensor	Anritsu	MA2411B	N/A	2015.06.29	2016.06.28
19	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A
Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.						

6 Test Result

6.1 Description of Test conditions

(1) EUT was tested in normal configuration (Please See following Block diagram)

1. Block diagram of EUT configuration(TX Mode)

Note: 1. The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

2. Using the software (MP Tool) to control the fixed transmitting power index (0-63): 32, frequency, date rate and other test mode.

(2) E.U.T. test conditions:

15.31(e): For intentional radiators, measurements of the variation of the input power or the adiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

15.32: Power supplies and CPU boards used with personal computers and for which separate authorizations are required to be obtained shall be tested as follows: Testing shall be in accordance with the procedures specified in Section 15.31 of this part.

(3) Test frequencies:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and. If required reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

(4) Frequency range of radiated measurements:

According to the 15.33, the test range will be up to the tenth harmonic of the highest fundamental frequency.

(5) Pre-test the EUT in all transmitting mode at the lowest, middle and highest channel with different data rate and conducted to determine the worst-case mode, only the worst-case results are recorded in this report.

6.2 Antenna Requirement

6.2.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

6.2.2 EUT Antenna

The antenna is an integral antenna and no consideration of replacement. Antenna gain is maximum 3.0 dBi from 2.4GHz to 2.5GHz.

6.3 Conduction Emissions Measurement

Test Requirement: FCC Part 15 C section 15.207

Test Method: ANSI C63.10: Clause 6.2

Frequency Range: 150 kHz to 30 MHz

Detector: Peak for pre-scan (9kHz Resolution Bandwidth)

Test Limit

Limits for conducted disturbance at the mains ports of class B

Frequency Range (MHz)	Class B Limit (dBuV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50
NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.		

EUT Operation: Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Test procedure

1. The mains terminal disturbance voltage test was conducted in a shielded room.

2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

Test setup



6.3.1 Test results

EUT:	WIFI WITH ELECTRIC FIREPLACE	Model Name. :	ZHS-32-D
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Test Date :	2016-06-06
Test Mode:	TX 802.11b (11Mbps) CH1 (worst case)	Phase :	Line
Test Voltage :	AC 120V/60Hz		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector
1		0.8500	8.16	9.91	18.07	56.00	-37.93	QP
2		1.1380	-2.28	9.91	7.63	46.00	-38.37	AVG
3		13.3579	24.65	1.24	25.89	60.00	-34.11	QP
4		14.1539	15.92	1.24	17.16	50.00	-32.84	AVG
5		23.7099	31.80	2.08	33.88	60.00	-26.12	QP
6	*	24.4860	23.98	2.16	26.14	50.00	-23.86	AVG

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name. ：	ZHS-32-D
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Test Date :	2016-06-06
Test Mode：	TX 802.11b (11Mbps) CH1 (worst case)	Phase :	Neutral
Test Voltage ：	AC 120V/60Hz		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector
1		0.2185	-1.87	11.00	9.13	52.87	-43.74	AVG
2		0.2740	7.57	10.82	18.39	60.99	-42.60	QP
3		1.0339	7.70	9.90	17.60	56.00	-38.40	QP
4	*	1.6340	-2.31	9.94	7.63	46.00	-38.37	AVG
5		23.2979	17.93	2.04	19.97	60.00	-40.03	QP
6		24.4860	8.43	2.16	10.59	50.00	-39.41	AVG

6.4 Radiated Emissions Measurement

Test Requirement:	FCC Part 15 C section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Detector:	For PK value: RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold For AV value: RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz VBW =10Hz Sweep = auto Detector function = peak Trace = max hold
15.209 Limit:	40.0 dBμV/m between 30MHz & 88MHz 43.5 dBμV/m between 88MHz & 216MHz 46.0 dBμV/m between 216MHz & 960MHz 54.0 dBμV/m above 960MHz

Test Configuration:

1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 40 GHz emissions:



Test procedure:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

The receiver was scanned from 30MHz to 25GHz.When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

From 30MHz to 1GHz, read the Quasi-Peak field strength of the emissions with receiver QP detector RBW=120KHz.

Above 1GHz, read the Peak field strength and Average field strength.

Read the Peak field strength through RBW=1MHz,VBW=3MHz in spectrum analyzer setting;

Read the Average field strength through RBW=1MHz,VBW=10Hz in spectrum analyzer setting;

For measurement at frequency above 1GHz

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

While maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the average field strength reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit.

6.4.1 Test Result

6.4.1.1 Radiated Emissions Test Data Below 30MHz

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1005 hPa	Relative Humidity：	60%
Test Mode ：	TX	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	9KHz to 30MHz
RBW/VBW	9KHz~150KHz/RB 200Hz for QP, 150KHz~30MHz/RB 9KHz for QP		

No emission found between lowest internal used/generated frequencies to 30MHz.

6.4.1.2 Radiated Emissions Test Data 30MHz-1000MHz

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.412 GHz-1Mbps (worst-case)	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

Test at Channel 1 (2.412 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		44.1200	44.67	-17.60	27.07	40.00	-12.93	QP
2		140.3420	37.02	-14.98	22.04	43.50	-21.46	QP
3		252.9482	41.40	-13.37	28.03	46.00	-17.97	QP
4		379.9141	33.30	-7.54	25.76	46.00	-20.24	QP
5		590.9737	31.26	-2.08	29.18	46.00	-16.82	QP
6	*	900.1473	30.55	2.80	33.35	46.00	-12.65	QP

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		43.0504	29.86	-14.62	15.24	40.00	-24.76	QP
2		102.7192	31.32	-15.76	15.56	43.50	-27.94	QP
3		180.0165	31.51	-12.21	19.30	43.50	-24.20	QP
4		360.4476	34.26	-7.59	26.67	46.00	-19.33	QP
5		607.7866	30.45	-1.94	28.51	46.00	-17.49	QP
6	*	696.8567	30.62	0.24	30.86	46.00	-15.14	QP

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.437 GHz-1Mbps (worst-case)	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

Test at Channel 6 (2.437 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		44.1200	44.10	-17.60	26.50	40.00	-13.50	QP
2		112.5243	34.39	-13.77	20.62	43.50	-22.88	QP
3		140.8351	37.70	-15.11	22.59	43.50	-20.91	QP
4		252.9482	37.64	-13.37	24.27	46.00	-21.73	QP
5		379.9141	34.59	-7.54	27.05	46.00	-18.95	QP
6	*	798.9796	29.29	3.44	32.73	46.00	-13.27	QP

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		46.0162	29.34	-14.34	15.00	40.00	-25.00	QP
2		182.5592	30.53	-11.36	19.17	43.50	-24.33	QP
3		252.9482	35.13	-13.37	21.76	46.00	-24.24	QP
4		337.2155	31.99	-8.63	23.36	46.00	-22.64	QP
5		400.4318	32.54	-6.89	25.65	46.00	-20.35	QP
6	*	691.9867	30.63	-0.16	30.47	46.00	-15.53	QP

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.462 GHz-1Mbps (worst-case)	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

Test at Channel 11 (2.462 GHz) in transmitting status

30 MHz~1 GHz Spurious Emissions .Quasi-Peak Measurement

Vertical:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		44.1200	41.49	-17.60	23.89	40.00	-16.11	QP
2		112.5243	32.50	-13.77	18.73	43.50	-24.77	QP
3		140.3420	36.59	-14.98	21.61	43.50	-21.89	QP
4		252.9482	37.76	-13.37	24.39	46.00	-21.61	QP
5		360.4476	31.73	-7.59	24.14	46.00	-21.86	QP
6	*	798.9796	29.94	3.44	33.38	46.00	-12.62	QP

Horizontal:

Peak scan

Level (dBμV/m)



Quasi-peak measurement

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		46.0162	28.41	-14.34	14.07	40.00	-25.93	QP
2		92.1388	30.57	-16.69	13.88	43.50	-29.62	QP
3		175.0365	31.84	-13.23	18.61	43.50	-24.89	QP
4		360.4476	31.30	-7.59	23.71	46.00	-22.29	QP
5		612.0642	31.03	-1.97	29.06	46.00	-16.94	QP
6	*	714.1734	30.86	-0.44	30.42	46.00	-15.58	QP

6.4.1.3 Radiated Emissions Test Data above 1GHz

802.11b mode with 11Mbps data rate

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.412 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	43.41	5.08	48.49	74.00	-25.51	PEAK
4824.000	32.12	5.08	37.20	54.00	-16.80	AVERAGE
7236.000	43.22	7.16	50.38	74.00	-23.62	PEAK
7236.000	30.24	7.16	37.40	54.00	-16.60	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	43.76	5.08	48.84	74.00	-25.16	PEAK
4824.000	28.52	5.08	33.60	54.00	-20.40	AVERAGE
7236.000	41.29	7.16	48.45	74.00	-25.55	PEAK
7236.000	31.09	7.16	38.25	54.00	-15.75	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.437 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.34	5.13	48.47	74.00	-25.53	PEAK
4874.000	31.56	5.13	36.69	54.00	-17.31	AVERAGE
7311.000	40.10	7.49	47.59	74.00	-26.41	PEAK
7311.000	29.05	7.49	36.54	54.00	-17.46	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.94	5.13	49.07	74.00	-24.93	PEAK
4874.000	30.87	5.13	36.00	54.00	-18.00	AVERAGE
7311.000	39.84	7.49	47.33	74.00	-26.67	PEAK
7311.000	31.05	7.49	38.54	54.00	-15.46	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11b 2.462 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	46.54	5.18	51.72	74.00	-22.28	PEAK
4924.000	33.67	5.18	38.85	54.00	-15.15	AVERAGE
7386.000	38.62	7.82	46.44	74.00	-27.56	PEAK
7386.000	28.25	7.82	36.07	54.00	-17.93	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	44.08	5.18	49.26	74.00	-24.74	PEAK
4924.000	30.95	5.18	36.13	54.00	-17.87	AVERAGE
7386.000	40.15	7.82	47.97	74.00	-26.03	PEAK
7386.000	29.04	7.82	36.86	54.00	-17.14	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.
As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
No any other emissions level which are attenuated less than 20dB below the limit. According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

802.11g mode with 54Mbps data rate

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11g 2.412 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	44.18	5.08	49.26	74.00	-24.74	PEAK
4824.000	32.40	5.08	37.48	54.00	-16.52	AVERAGE
7236.000	43.97	7.16	51.13	74.00	-22.87	PEAK
7236.000	30.88	7.16	38.04	54.00	-15.96	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	43.17	5.08	48.25	74.00	-25.75	PEAK
4824.000	28.99	5.08	34.07	54.00	-19.93	AVERAGE
7236.000	41.55	7.16	48.71	74.00	-25.29	PEAK
7236.000	31.84	7.16	39.00	54.00	-15.00	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11g 2.437 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	44.21	5.13	49.34	74.00	-24.66	PEAK
4874.000	31.47	5.13	36.60	54.00	-17.40	AVERAGE
7311.000	40.65	7.49	48.14	74.00	-25.86	PEAK
7311.000	29.82	7.49	37.31	54.00	-16.69	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.17	5.13	48.30	74.00	-25.70	PEAK
4874.000	30.44	5.13	35.57	54.00	-18.43	AVERAGE
7311.000	39.19	7.49	46.68	74.00	-27.32	PEAK
7311.000	31.57	7.49	39.06	54.00	-14.94	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11g 2.462 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	46.86	5.18	52.04	74.00	-21.96	PEAK
4924.000	33.17	5.18	38.35	54.00	-15.65	AVERAGE
7386.000	38.43	7.82	46.25	74.00	-27.75	PEAK
7386.000	28.39	7.82	36.21	54.00	-17.79	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	44.43	5.18	49.61	74.00	-24.39	PEAK
4924.000	30.57	5.18	35.75	54.00	-18.25	AVERAGE
7386.000	40.60	7.82	48.42	74.00	-25.58	PEAK
7386.000	29.69	7.82	37.51	54.00	-16.49	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor –Preamplifier Factor.
As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
No any other emissions level which are attenuated less than 20dB below the limit. According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

802.11n(HT20) mode with 72.2Mbps data rate

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT20) 2.412 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	44.37	5.08	49.45	74.00	-24.55	PEAK
4824.000	32.85	5.08	37.93	54.00	-16.07	AVERAGE
7236.000	43.74	7.16	50.90	74.00	-23.10	PEAK
7236.000	31.25	7.16	38.41	54.00	-15.59	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4824.000	43.55	5.08	48.63	74.00	-25.37	PEAK
4824.000	31.98	5.08	37.06	54.00	-16.94	AVERAGE
7236.000	43.52	7.16	50.68	74.00	-23.32	PEAK
7236.000	32.04	7.16	39.20	54.00	-14.80	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT20) 2.437 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.79	5.13	48.92	74.00	-25.08	PEAK
4874.000	31.11	5.13	36.24	54.00	-17.76	AVERAGE
7311.000	40.88	7.49	48.37	74.00	-25.63	PEAK
7311.000	29.64	7.49	37.13	54.00	-16.87	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.47	5.13	48.60	74.00	-25.40	PEAK
4874.000	30.19	5.13	35.32	54.00	-18.68	AVERAGE
7311.000	39.23	7.49	46.72	74.00	-27.28	PEAK
7311.000	31.86	7.49	39.35	54.00	-14.65	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT20) 2.462 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	45.33	5.18	50.51	74.00	-23.49	PEAK
4924.000	33.21	5.18	38.39	54.00	-15.61	AVERAGE
7386.000	40.47	7.82	48.29	74.00	-25.71	PEAK
7386.000	28.99	7.82	36.81	54.00	-17.19	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4924.000	42.89	5.18	48.07	74.00	-25.93	PEAK
4924.000	30.14	5.18	35.32	54.00	-18.68	AVERAGE
7386.000	40.57	7.82	48.39	74.00	-25.61	PEAK
7386.000	29.66	7.82	37.48	54.00	-16.52	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.
As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
No any other emissions level which are attenuated less than 20dB below the limit. According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.

802.11n(HT40) mode with 150Mbps data rate

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT40) 2.422 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4844.000	42.89	5.08	47.97	74.00	-26.03	PEAK
4844.000	32.54	5.08	37.62	54.00	-16.38	AVERAGE
7266.000	44.35	7.16	51.51	74.00	-22.49	PEAK
7266.000	31.75	7.16	38.91	54.00	-15.09	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4844.000	43.08	5.08	48.16	74.00	-25.84	PEAK
4844.000	30.34	5.08	35.42	54.00	-18.58	AVERAGE
7266.000	41.52	7.16	48.68	74.00	-25.32	PEAK
7266.000	29.06	7.16	36.22	54.00	-17.78	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT40) 2.437 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	44.55	5.13	49.68	74.00	-24.32	PEAK
4874.000	32.16	5.13	37.29	54.00	-16.71	AVERAGE
7311.000	41.23	7.49	48.72	74.00	-25.28	PEAK
7311.000	29.87	7.49	37.36	54.00	-16.64	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4874.000	43.17	5.13	48.30	74.00	-25.70	PEAK
4874.000	30.28	5.13	35.41	54.00	-18.59	AVERAGE
7311.000	39.14	7.49	46.63	74.00	-27.37	PEAK
7311.000	26.77	7.49	34.26	54.00	-19.74	AVERAGE

EUT：	WIFI WITH ELECTRIC FIREPLACE	Model Name ：	ZHS-32-D
Temperature：	25 ℃	Test Data	2016-06-06
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX:802.11n(HT40) 2.452 GHz	Test Voltage ：	AC 120V/60Hz
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	Spurious emission: 1MHz/3MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4904.000	43.59	5.18	48.77	74.00	-25.23	PEAK
4904.000	33.76	5.18	38.94	54.00	-15.06	AVERAGE
7356.000	39.35	7.82	47.17	74.00	-26.83	PEAK
7356.000	28.10	7.82	35.92	54.00	-18.08	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4904.000	44.74	5.18	49.92	74.00	-24.08	PEAK
4904.000	30.35	5.18	35.53	54.00	-18.47	AVERAGE
7356.000	40.76	7.82	48.58	74.00	-25.42	PEAK
7356.000	29.88	7.82	37.70	54.00	-16.30	AVERAGE

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.
As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
No any other emissions level which are attenuated less than 20dB below the limit. According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part. Hence there no other emissions have been reported.
Test result: The unit does meet the FCC requirements.

6.4.2 Radiated Emissions which fall in the restricted bands

Test Requirement:	FCC Part 15 C section 15.247
	(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method:	ANSI C63.10: Clause 6.4, 6.5 and 6.6
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)
Limit:	40.0 dBμV/m between 30MHz & 88MHz;
	43.5 dBμV/m between 88MHz & 216MHz;
	46.0 dBμV/m between 216MHz & 960MHz;
	54.0 dBμV/m above 960MHz.
Detector:	For PK value:
	RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
	VBW ≥ RBW
	Sweep = auto
	Detector function = peak
	Trace = max hold
	For AV value:
	RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
	VBW =10Hz
	Sweep = auto
	Detector function = peak
	Trace = max hold

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

Test Result:

802.11b mode with 11Mbps data rate

Test at Channel 1 (2.412 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	53.78	27.93	4.74	35.09	51.36	74.00	Vertical
2390.000	55.46	27.63	4.96	35.05	53.00	74.00	V
2483.500	54.95	27.55	4.90	34.99	52.41	74.00	V
2500.000	56.61	27.55	5.00	34.98	54.18	74.00	V
2310.000	54.93	27.93	4.74	35.09	52.51	74.00	Horizontal
2390.000	54.46	27.63	4.96	35.05	52.00	74.00	H
2483.500	54.24	27.55	4.90	34.99	51.70	74.00	H
2500.000	57.57	27.55	5.00	34.98	55.14	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.84	27.93	4.74	35.09	41.42	54.00	Vertical
2390.000	44.11	27.63	4.96	35.05	41.65	54.00	V
2483.500	43.50	27.55	4.90	34.99	40.96	54.00	V
2500.000	42.68	27.55	5.00	34.98	40.25	54.00	V
2310.000	43.84	27.93	4.74	35.09	41.42	54.00	Horizontal
2390.000	45.23	27.63	4.96	35.05	42.77	54.00	H
2483.500	44.07	27.55	4.90	34.99	41.53	54.00	H
2500.000	43.55	27.55	5.00	34.98	41.12	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna actors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	53.84	27.93	4.74	35.09	51.42	74.00	Vertical
2390.000	54.01	27.63	4.96	35.05	51.55	74.00	V
2483.500	55.18	27.55	4.90	34.99	52.64	74.00	V
2500.000	53.55	27.55	5.00	34.98	51.12	74.00	V
2310.000	54.38	27.93	4.74	35.09	51.96	74.00	Horizontal
2390.000	54.19	27.63	4.96	35.05	51.73	74.00	H
2483.500	53.66	27.55	4.90	34.99	51.12	74.00	H
2500.000	54.50	27.55	5.00	34.98	52.07	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.44	27.93	4.74	35.09	41.02	54.00	Vertical
2390.000	42.23	27.63	4.96	35.05	39.77	54.00	V
2483.500	42.78	27.55	4.90	34.99	40.24	54.00	V
2500.000	44.44	27.55	5.00	34.98	42.01	54.00	V
2310.000	43.23	27.93	4.74	35.09	40.81	54.00	Horizontal
2390.000	44.31	27.63	4.96	35.05	41.85	54.00	H
2483.500	42.44	27.55	4.90	34.99	39.90	54.00	H
2500.000	43.66	27.55	5.00	34.98	41.23	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	54.70	27.93	4.74	35.09	52.28	74.00	Vertical
2390.000	53.57	27.63	4.96	35.05	51.11	74.00	V
2483.500	53.61	27.55	4.90	34.99	51.07	74.00	V
2500.000	54.94	27.55	5.00	34.98	52.51	74.00	V
2310.000	53.82	27.93	4.74	35.09	51.40	74.00	Horizontal
2390.000	54.75	27.63	4.96	35.05	52.29	74.00	H
2483.500	54.83	27.55	4.90	34.99	52.29	74.00	H
2500.000	52.70	27.55	5.00	34.98	50.27	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	44.95	27.93	4.74	35.09	42.53	54.00	Vertical
2390.000	41.83	27.63	4.96	35.05	39.37	54.00	V
2483.500	44.06	27.55	4.90	34.99	41.52	54.00	V
2500.000	44.49	27.55	5.00	34.98	42.06	54.00	V
2310.000	43.38	27.93	4.74	35.09	40.96	54.00	Horizontal
2390.000	45.06	27.63	4.96	35.05	42.60	54.00	H
2483.500	45.59	27.55	4.90	34.99	43.05	54.00	H
2500.000	43.94	27.55	5.00	34.98	41.51	54.00	H

802.11g mode with 54Mbps data rate

Test at Channel 1 (2.412 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	56.17	27.93	4.74	35.09	53.75	74.00	Vertical
2390.000	54.32	27.63	4.96	35.05	51.86	74.00	V
2483.500	54.95	27.55	4.90	34.99	52.41	74.00	V
2500.000	53.03	27.55	5.00	34.98	50.60	74.00	V
2310.000	53.88	27.93	4.74	35.09	51.46	74.00	Horizontal
2390.000	54.30	27.63	4.96	35.05	51.84	74.00	H
2483.500	53.46	27.55	4.90	34.99	50.92	74.00	H
2500.000	55.99	27.55	5.00	34.98	53.56	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.51	27.93	4.74	35.09	41.09	54.00	Vertical
2390.000	43.82	27.63	4.96	35.05	41.36	54.00	V
2483.500	43.65	27.55	4.90	34.99	41.11	54.00	V
2500.000	44.56	27.55	5.00	34.98	42.13	54.00	V
2310.000	43.34	27.93	4.74	35.09	40.92	54.00	Horizontal
2390.000	44.60	27.63	4.96	35.05	42.14	54.00	H
2483.500	43.97	27.55	4.90	34.99	41.43	54.00	H
2500.000	43.23	27.55	5.00	34.98	40.80	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	53.44	27.93	4.74	35.09	51.02	74.00	Vertical
2390.000	54.18	27.63	4.96	35.05	51.72	74.00	V
2483.500	53.62	27.55	4.90	34.99	51.08	74.00	V
2500.000	55.04	27.55	5.00	34.98	52.61	74.00	V
2310.000	53.70	27.93	4.74	35.09	51.28	74.00	Horizontal
2390.000	55.23	27.63	4.96	35.05	52.77	74.00	H
2483.500	54.15	27.55	4.90	34.99	51.61	74.00	H
2500.000	53.44	27.55	5.00	34.98	51.01	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	44.08	27.93	4.74	35.09	41.66	54.00	Vertical
2390.000	42.80	27.63	4.96	35.05	40.34	54.00	V
2483.500	43.25	27.55	4.90	34.99	40.71	54.00	V
2500.000	44.12	27.55	5.00	34.98	41.69	54.00	V
2310.000	44.29	27.93	4.74	35.09	41.87	54.00	Horizontal
2390.000	43.03	27.63	4.96	35.05	40.57	54.00	H
2483.500	43.91	27.55	4.90	34.99	41.37	54.00	H
2500.000	42.60	27.55	5.00	34.98	40.17	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	54.21	27.93	4.74	35.09	51.79	74.00	Vertical
2390.000	53.19	27.63	4.96	35.05	50.73	74.00	V
2483.500	53.34	27.55	4.90	34.99	50.80	74.00	V
2500.000	54.43	27.55	5.00	34.98	52.00	74.00	V
2310.000	53.10	27.93	4.74	35.09	50.68	74.00	Horizontal
2390.000	54.24	27.63	4.96	35.05	51.78	74.00	H
2483.500	53.58	27.55	4.90	34.99	51.04	74.00	H
2500.000	54.30	27.55	5.00	34.98	51.87	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	42.93	27.93	4.74	35.09	40.51	54.00	Vertical
2390.000	44.06	27.63	4.96	35.05	41.60	54.00	V
2483.500	42.16	27.55	4.90	34.99	39.62	54.00	V
2500.000	43.33	27.55	5.00	34.98	40.90	54.00	V
2310.000	44.11	27.93	4.74	35.09	41.69	54.00	Horizontal
2390.000	43.69	27.63	4.96	35.05	41.23	54.00	H
2483.500	43.34	27.55	4.90	34.99	40.80	54.00	H
2500.000	42.32	27.55	5.00	34.98	39.89	54.00	H

802.11n(HT20) mode with 72.2Mbps data rate

Test at Channel 1 (2.412 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	56.41	27.93	4.74	35.09	53.99	74.00	Vertical
2390.000	55.39	27.63	4.96	35.05	52.93	74.00	V
2483.500	55.54	27.55	4.90	34.99	53.00	74.00	V
2500.000	56.63	27.55	5.00	34.98	54.20	74.00	V
2310.000	55.30	27.93	4.74	35.09	52.88	74.00	Horizontal
2390.000	56.44	27.63	4.96	35.05	53.98	74.00	H
2483.500	55.78	27.55	4.90	34.99	53.24	74.00	H
2500.000	56.50	27.55	5.00	34.98	54.07	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.83	27.93	4.74	35.09	41.41	54.00	Vertical
2390.000	44.96	27.63	4.96	35.05	42.50	54.00	V
2483.500	43.06	27.55	4.90	34.99	40.52	54.00	V
2500.000	44.23	27.55	5.00	34.98	41.80	54.00	V
2310.000	45.01	27.93	4.74	35.09	42.59	54.00	Horizontal
2390.000	44.59	27.63	4.96	35.05	42.13	54.00	H
2483.500	44.24	27.55	4.90	34.99	41.70	54.00	H
2500.000	43.22	27.55	5.00	34.98	40.79	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	55.30	27.93	4.74	35.09	52.88	74.00	Vertical
2390.000	56.07	27.63	4.96	35.05	53.61	74.00	V
2483.500	55.11	27.55	4.90	34.99	52.57	74.00	V
2500.000	53.62	27.55	5.00	34.98	51.19	74.00	V
2310.000	54.13	27.93	4.74	35.09	51.71	74.00	Horizontal
2390.000	55.32	27.63	4.96	35.05	52.86	74.00	H
2483.500	53.01	27.55	4.90	34.99	50.47	74.00	H
2500.000	54.68	27.55	5.00	34.98	52.25	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.16	27.93	4.74	35.09	40.74	54.00	Vertical
2390.000	44.02	27.63	4.96	35.05	41.56	54.00	V
2483.500	43.28	27.55	4.90	34.99	40.74	54.00	V
2500.000	41.90	27.55	5.00	34.98	39.47	54.00	V
2310.000	41.07	27.93	4.74	35.09	38.65	54.00	Horizontal
2390.000	41.97	27.63	4.96	35.05	39.51	54.00	H
2483.500	39.39	27.55	4.90	34.99	36.85	54.00	H
2500.000	40.52	27.55	5.00	34.98	38.09	54.00	H

Test at Channel 11 (2.462 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	57.93	27.93	4.74	35.09	55.51	74.00	Vertical
2390.000	57.09	27.63	4.96	35.05	54.63	74.00	V
2483.500	57.54	27.55	4.90	34.99	55.00	74.00	V
2500.000	56.66	27.55	5.00	34.98	54.23	74.00	V
2310.000	54.31	27.93	4.74	35.09	51.89	74.00	Horizontal
2390.000	55.53	27.63	4.96	35.05	53.07	74.00	H
2483.500	55.45	27.55	4.90	34.99	52.91	74.00	H
2500.000	53.91	27.55	5.00	34.98	51.48	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	44.78	27.93	4.74	35.09	42.36	54.00	Vertical
2390.000	43.64	27.63	4.96	35.05	41.18	54.00	V
2483.500	44.30	27.55	4.90	34.99	41.76	54.00	V
2500.000	40.05	27.55	5.00	34.98	37.62	54.00	V
2310.000	41.42	27.93	4.74	35.09	39.00	54.00	Horizontal
2390.000	44.56	27.63	4.96	35.05	42.10	54.00	H
2483.500	46.33	27.55	4.90	34.99	43.79	54.00	H
2500.000	45.37	27.55	5.00	34.98	42.94	54.00	H

802.11n(HT40) mode with 150Mbps data rate

Test at Channel 1 (2.422 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	55.96	27.93	4.74	35.09	53.54	74.00	Vertical
2390.000	54.94	27.63	4.96	35.05	52.48	74.00	V
2483.500	55.09	27.55	4.90	34.99	52.55	74.00	V
2500.000	56.18	27.55	5.00	34.98	53.75	74.00	V
2310.000	54.85	27.93	4.74	35.09	52.43	74.00	Horizontal
2390.000	55.99	27.63	4.96	35.05	53.53	74.00	H
2483.500	55.33	27.55	4.90	34.99	52.79	74.00	H
2500.000	56.05	27.55	5.00	34.98	53.62	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	44.68	27.93	4.74	35.09	42.26	54.00	Vertical
2390.000	45.81	27.63	4.96	35.05	43.35	54.00	V
2483.500	43.91	27.55	4.90	34.99	41.37	54.00	V
2500.000	45.08	27.55	5.00	34.98	42.65	54.00	V
2310.000	45.86	27.93	4.74	35.09	43.44	54.00	Horizontal
2390.000	45.44	27.63	4.96	35.05	42.98	54.00	H
2483.500	45.09	27.55	4.90	34.99	42.55	54.00	H
2500.000	44.07	27.55	5.00	34.98	41.64	54.00	H

Test at Channel 6 (2.437 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	55.86	27.93	4.74	35.09	53.44	74.00	Vertical
2390.000	56.63	27.63	4.96	35.05	54.17	74.00	V
2483.500	55.67	27.55	4.90	34.99	53.13	74.00	V
2500.000	54.18	27.55	5.00	34.98	51.75	74.00	V
2310.000	54.69	27.93	4.74	35.09	52.27	74.00	Horizontal
2390.000	55.88	27.63	4.96	35.05	53.42	74.00	H
2483.500	53.57	27.55	4.90	34.99	51.03	74.00	H
2500.000	55.24	27.55	5.00	34.98	52.81	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	45.80	27.93	4.74	35.09	43.38	54.00	Vertical
2390.000	46.66	27.63	4.96	35.05	44.20	54.00	V
2483.500	45.92	27.55	4.90	34.99	43.38	54.00	V
2500.000	44.54	27.55	5.00	34.98	42.11	54.00	V
2310.000	43.71	27.93	4.74	35.09	41.29	54.00	Horizontal
2390.000	44.61	27.63	4.96	35.05	42.15	54.00	H
2483.500	42.03	27.55	4.90	34.99	39.49	54.00	H
2500.000	43.16	27.55	5.00	34.98	40.73	54.00	H

Test at Channel 9 (2.452 GHz) in transmitting status

Peak Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	56.61	27.93	4.74	35.09	54.19	74.00	Vertical
2390.000	55.77	27.63	4.96	35.05	53.31	74.00	V
2483.500	56.22	27.55	4.90	34.99	53.68	74.00	V
2500.000	55.34	27.55	5.00	34.98	52.91	74.00	V
2310.000	52.99	27.93	4.74	35.09	50.57	74.00	Horizontal
2390.000	54.21	27.63	4.96	35.05	51.75	74.00	H
2483.500	54.13	27.55	4.90	34.99	51.59	74.00	H
2500.000	52.59	27.55	5.00	34.98	50.16	74.00	H

Average Measurement:

Frequency (MHz)	Reading Level (dBμV)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Antenna polarization
2310.000	43.46	27.93	4.74	35.09	41.04	54.00	Vertical
2390.000	42.32	27.63	4.96	35.05	39.86	54.00	V
2483.500	42.98	27.55	4.90	34.99	40.44	54.00	V
2500.000	40.43	27.55	5.00	34.98	38.00	54.00	V
2310.000	40.10	27.93	4.74	35.09	37.68	54.00	Horizontal
2390.000	43.24	27.63	4.96	35.05	40.78	54.00	H
2483.500	45.01	27.55	4.90	34.99	42.47	54.00	H
2500.000	44.05	27.55	5.00	34.98	41.62	54.00	H

6.5 6 dB Bandwidth

Test Requirement: FCC Part 15 C section 15.247

(a)(2)Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Method: ANSI C63.10: Clause 6.9.1

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =1.5dB) from the antenna port to the spectrum.
2. Set the spectrum analyzer:

   Sweep = auto; Detector Function = Peak; ace = Max Hold

   RBW: 1%~5% OBW; VBW: ⩾3*RBW

   Span: two times and five times the OBW.
3. Mark the peak power frequency and -6dB (upper and lower) power frequency.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured 6dB bandwidth (MHz)	Limit	Result
1	2412	802.11b	11 Mbps	10.03	≥500KHz	Pass
6	2437		11 Mbps	10.04		Pass
11	2462		11 Mbps	10.04		Pass
1	2412	802.11g	54 Mbps	15.43	≥500KHz	Pass
6	2437		54 Mbps	15.36		Pass
11	2462		54 Mbps	15.13		Pass
1	2412	802.11n (HT20)	72.2 Mbps	15.47	≥500KHz	Pass
6	2437		72.2 Mbps	16.89		Pass
11	2462		72.2 Mbps	15.46		Pass
3	2422	802.11n (HT40)	150 Mbps	35.46	≥500KHz	Pass
6	2437		150 Mbps	35.47		Pass
9	2452		150 Mbps	35.35		Pass

Test result: The unit does meet the FCC requirements.

Result plot as follows:

802.11b mode with 11Mbps data rate

Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



802.11g mode with 54Mbps data rate

Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



802.11n(HT20) mode with 72.2Mbps data rate

Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



802.11n(HT40) mode with 150Mbps data rate

Channel 3: 2.422GHz:



Channel 6: 2.437GHz:



Channel 9: 2.452GHz:



6.6 Maximum Peak Output Power

Test Requirement: FCC Part 15 C section 15.247

(b)(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b) (1), (b) (2), and (b) (3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Method: FCC/KDB-558074 D01 v03r05 9.2.3 Measurement using an RF average power meter

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (Cable loss =0.5dB) from the antenna port to the power meter.
2. Measurement using an RF average power meter.
3. Report the worse case.

Test result:

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Power (dBm)	Limit	Result
1	2412	802.11b	11 Mbps	15.17	1W(30dBm)	Pass
6	2437		11 Mbps	15.22		Pass
11	2462		11 Mbps	15.04		Pass
1	2412	802.11g	54 Mbps	12.78		Pass
6	2437		54 Mbps	13.96		Pass
11	2462		54 Mbps	12.54		Pass
1	2412	802.11n (HT20)	72.2 Mbps	12.23		Pass
6	2437		72.2 Mbps	14.28		Pass
11	2462		72.2 Mbps	13.01		Pass
3	2422	802.11n (HT40)	150 Mbps	10.44		Pass
6	2437		150 Mbps	12.85		Pass
9	2452		150 Mbps	11.32		Pass

Remark: Level = Read Level + Cable Loss.

The unit does meet the FCC requirements.

6.7 Peak Power Spectral Density

Test Requirement: FCC Part 15 C section 15.247

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Method: ANSI C63.10: Clause 6.11.2.3

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low attention attenuation RF cable (cable loss =1.0 dB) from the antenna port to the spectrum analyzer or power meter.
2. Set the spectrum analyzer:

   a) Set CENTER FREQUENCY = Frequency from Power Spectral Density Test Matrix (see 6.10.2)
   b) Set SPAN = 20 MHz (For devices with a nominal 40 MHz BW, 50 MHz span will be needed)
   c) Set REFERENCE LEVEL = 20 dBm
   d) Set ATTENUATION = 0 dB (add internal attenuation, if necessary)
   e) Set SWEEP TIME = Coupled
   f) Set RBW = 3 kHz
   g) Set VBW = 10 kHz
   h) Set DETECTOR = Peak
   i) Set MKR = Center Frequency
   j) Set TRACE = CLEAR WRITE

   Place the radio in continuous transmit mode. Set the TRACE to MAX HOLD, and after the trace stabilizes, the TRACE to VIEW. Set the marker on the peak of the signal and then adjust the center frequency of the spectrum analyzer to the marker frequency.
3. Measure the Power Spectral Density of the test frequency with special test status.
4. Repeat until all the test status is investigated.
5. Report the worse case.

Channel No.	Frequency (MHz)	Mode	Data Rate	Measured Peak Power Spectral Density (dBm/3KHz)	Limit	Result
1	2412	802.11b	11 Mbps	-13.161	8dBm/3KHz	Pass
6	2437		11 Mbps	-11.990		Pass
11	2462		11 Mbps	-12.144		Pass
1	2412	802.11g	54 Mbps	-18.158		Pass
6	2437		54 Mbps	-17.035		Pass
11	2462		54 Mbps	-18.636		Pass
1	2412	802.11n (HT20)	72.2 Mbps	-18.718		Pass
6	2437		72.2 Mbps	-17.032		Pass
11	2462		72.2 Mbps	-18.710		Pass
3	2422	802.11n (HT40)	150 Mbps	-24.664		Pass
6	2437		150 Mbps	-22.212		Pass
9	2452		150 Mbps	-23.398		Pass

Test result: Level = Read Level + Cable Loss.

The unit does meet the FCC requirements.

Result plot as follows:

802.11b mode with 11Mbps data rate

Channel 1: 2.412GHz:

Channel 6: 2.437GHz:

Channel 11: 2.462GHz:

802.11g mode with 54Mbps data rate

Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



802.11n(HT20) mode with 72.2Mbps data rate

Channel 1: 2.412GHz:



Channel 6: 2.437GHz:



Channel 11: 2.462GHz:



802.11n(HT40) mode with 150Mbps data rate

Channel 3: 2.422GHz:



Channel 6: 2.437GHz:



Channel 9: 2.452GHz:



6.8 Band Edges Requirement

Test Requirement: FCC Part 15 C section 15.247

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Frequency Band: 2400 MHz to 2483.5 MHz

Test Method: FCC/KDB-558074 D01 v03r05 Clause 13.3.1

Test Status: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum analyzer or power meter.
2. Set instrument center frequency to the frequency of the emission to be measured(must be within 2MHz of the authorized band edge).
3. Set span to 2MHz,
4. RBW=100kHz,
5. VBW⩾3×RBW
6. Detector=peak
7. Sweep time =auto,
8. Trace mode=max hold.
9. Allow sweep to continue until the trace stabilizes(required measurement time may increase for low

duty cycle applications)

10. Compute the power by integrating the spectrum over 1MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency($f_{emission}$)±0.5MHz.If the instrument does not have a band power function,the sum the amplitude levels(in power units) at 100kHz intervals extending across the 1MHz spectrum defined by femission±0.5MHz.

Test result with plots as follows:

Compare with the output power of the lowest frequency, the Lower Edges attenuated more than 20dB

Compare with the output power of the highest frequency, the Upper Edges attenuated more than 20dB.

802.11b mode with 11 Mbps data rate

Channel1: 2.412 GHz

802.11b mode with 11 Mbps data rate

Channel11: 2.462 GHz

802.11g mode with 54 Mbps data rate

Channel1: 2.412 GHz

802.11g mode with 54 Mbps data rate

Channel11: 2.462 GHz



802.11n(HT20) mode with 72.2Mbps data rate

Channel1: 2.412 GHz



802.11n(HT20) mode with 72.2Mbps data rate

Channel11: 2.462 GHz

802.11n(HT40) mode with 150Mbps data rate

Channel3: 2.422 GHz

802.11n(HT40) mode with 150Mbps data rate

Channel9: 2.452 GHz



7 Photographs

7.1 Radiated Spurious Emission Test Setup

Below 1GHz



Above 1GHz



7.2 Conducted Emission Test Setup

8 APPENDIX-Photographs of EUT Constructional Details







JUN JT TUO
TY-50B E212993
AC:110-120V 50/60Hz
≤4 W Z.P. 10/12 r/min
CCW
ZHAOQING LONGTOU
ELECTRONIC & ELECTRIC CO.,LTD








ANT
GOLDEN
GK-C-1A-12D


FW1
C1
C4
R1
R2
Q1
R6
R5
Q2
C2
R10
TX1
TX
CN4
MZ-DBL60207(ZS)-B
V01 2016-04-09


3.3V TXD RST
GND RXD
P1
MZ-WFI-C V04
2016-04-09
P2
0.5 mm
1 2 3 4 5 6 7


FW1
TXD RXT RST 3V3 GND
GND ANT GND
C2
R10
C3
C1 C4
R1 R2
Q1 R6 R5 Q2
0.5 mm
1 2 3 4 5 6


2015/09/25
SNIOT505 GND3V3RST RX TX
www.scinan.com
GND
ANT
GND
94V-0
S Y15M11D04
JUB7.820.1425-2
T1
SCINAN
G0 G1 G2 G3 G4
0.5 mm




WZA12047
CN1
REL
RT1
0.5 mm
1
3
4


0.5 mm
1
3
4
5
mm


0.5 mm
1 2 3 4


0.5 mm
1 2 3 4 5
mm

PLD61-120
·120V 60Hz
Class: B Z.P.
LEPUDA MOTOR

End of report