

FCC 47 CFR PART 15 SUBPART C

Applicant : Wisdom Garden Hong Kong Limited

Product Type : Intelligent Space Management Terminal

Trade Name : ROOMIS

Model Number : RM1000

Test Specification : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013

Receive Date : May 23, 2016

Test Period : May 25 ~ Jun. 14, 2016

Issue Date : Jun. 17, 2016

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Rev.	Issue Date	Revisions	Revised By
00	Jun. 17, 2016	Initial Issue	Snow Wang

Verification of Compliance

Issued Date: Jun. 17, 2016

Applicant : Wisdom Garden Hong Kong Limited
Product Type : Intelligent Space Management Terminal
Trade Name : ROOMIS
Model Number : RM1000
FCC ID : 2AILZROOMIS10
EUT Rated Voltage : DC 56V, 0.536A / DC 12V, 2.5A
Test Voltage : 120 Vac / 60 Hz
Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013
Test Result : Complied
Performing Lab. : A Test Lab Techno Corp.

No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C)

Tel : +886-3-2710188 / Fax : +886-3-2710190

Taiwan Accreditation Foundation accreditation number: 1330

<http://www.atl-lab.com.tw/e-index.htm>



A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.


Approved By :



(Manager)

(Fly Lu)

Reviewed By :



(Testing Engineer)

(Eric Ou Yang)

TABLE OF CONTENTS

1	General Information	5
2	EUT Description	6
3	Test Methodology	7
3.1.	Mode of Operation.....	7
3.2.	EUT Exercise Software	7
3.3.	Configuration of Test System Details.....	8
3.4.	Test Site Environment	9
4	Conducted Emission Measurement	10
4.1.	Limit.....	10
4.2.	Test Instruments	10
4.3.	Test Setup	10
4.4.	Test Procedure	11
4.5.	Test Result.....	12
5	Radiated Emissions Measurement.....	14
5.1.	Limit.....	14
5.2.	Test Instruments	15
5.3.	Setup.....	16
5.4.	Test Procedure	17
5.5.	Test Result.....	19
6	Frequency Stability Measurement.....	29
6.1.	Limit.....	29
6.2.	Test Setup	29
6.3.	Test Instruments	29
6.4.	Test Procedure	30
6.5.	Test Result.....	30
7	20dB Bandwidth Measurement.....	31
7.1.	Limit.....	31
7.2.	Test Setup	31
7.3.	Test Instruments	31
7.4.	Test Procedure	32
7.5.	Test Result.....	33
7.6.	Test Graphs	33
8	Antenna Requirement.....	34
8.1.	Require.....	34
8.2.	Antenna Connector Construction	34

1 General Information

1.1 Summary of Test Result

Reference	Test	Results	Remark
47 CFR Part 15.225			
15.203	Antenna Requirement	Meet Require	---
15.207(a)	Conducted Emissions Voltage	PASS	---
15.225 (a), (b), (c), (d) 15.209	Radiated Emission Limits	PASS	---
15.225(e)	Frequency Stability	PASS	---
15.215(c)	20dB Bandwidth	PASS	---
CFR 47 Part 15.225 / ANSI C63.10:2013			

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conducted Emission	9kHz ~ 150KHz	2.7 dB
	150kHz ~ 30MHz	2.8 dB
Radiated Emission	9kHz ~ 30MHz	1.457 dB
	30MHz ~ 1000MHz	6.300 dB
	1000MHz ~ 18000MHz	5.474 dB
	18000MHz ~ 26500MHz	5.630 dB
	26500MHz ~ 40000MHz	5.054 dB
RF Bandwidth		4.96%
Frequency Stability		+ 2.212 x 10 ⁻⁷ % / - 2.170 x 10 ⁻⁷

2 EUT Description

Applicant	Wisdom Garden Hong Kong Limited Room 502, Bank of America Tower,12 Harcourt Road, Central, Hong Kong
Manufacturer	Wisdom Garden Hong Kong Limited Room 502, Bank of America Tower,12 Harcourt Road, Central, Hong Kong
Product	Intelligent Space Management Terminal
Trade Name	ROOMIS
Model Number	RM1000
FCC ID	2AILZROOMIS10
Frequency Range	13.56 MHz
Modulation Type	ASK
Number of Channels	1 Channel
Antenna Type	Coil Antenna

3 Test Methodology

3.1. Mode of Operation

The following test mode(s) were scanned during the preliminary test :

Pre-Test Mode
Mode 1: Normal Operation Mode
Mode 2: Transmit Mode
Mode 3: Receive Mode

ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation.


3.2. EUT Exercise Software

1.	Setup the EUT as shown on 3.3.
2.	Turn on the power of all equipment.
3.	The EUT will start to operate function.


Measurement Software	
1	EZ-EMC Ver. ATL-03A1-1
2	EZ-EMC Ver ATL-ITC-3A1-1

3.3. Configuration of Test System Details

Conducted Emission



Radiated Emission



3.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

4 Conducted Emission Measurement

4.1. Limit


Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/25/2015	1 year
LISN	R&S	ENV216	101040	03/15/2016	1 year
LISN	R&S	ENV216	101041	03/07/2016	1 year
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	02/23/2016	1 year
Test Site	ATL	TE02	TE02	N.C.R.	-----

NOTE: N.C.R. = No Calibration Request.

4.3. Test Setup



4.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\Omega//50\mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\Omega//50\mu\text{H}$ coupling impedance with 50ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12mm insulating material.


Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150kHz to 30MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0,8 m from the AMN. If the mains power cable is longer than 1m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4m. All of interconnecting cables that hang closer than 40cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.5. Test Result

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	05/25/2016
		Test By:	Eric Ou Yang
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1580	36.64	36.64	0.03	36.67	36.67	65.57	55.57	-28.90	-18.90	Pass
2	0.2100	38.13	38.13	0.03	38.16	38.16	63.21	53.21	-25.05	-15.05	Pass
3	0.3020	31.10	31.10	0.04	31.14	31.14	60.19	50.19	-29.05	-19.05	Pass
4	2.5940	33.33	33.33	0.13	33.46	33.46	56.00	46.00	-22.54	-12.54	Pass
5	5.2780	31.95	31.95	0.18	32.13	32.13	60.00	50.00	-27.87	-17.87	Pass
6	11.0340	24.90	24.90	0.26	25.16	25.16	60.00	50.00	-34.84	-24.84	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	05/25/2016
		Test By:	Eric Ou Yang
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1580	42.85	42.85	0.03	42.88	42.88	65.57	55.57	-22.69	-12.69	Pass
2	0.2060	33.84	33.84	0.03	33.87	33.87	63.37	53.37	-29.50	-19.50	Pass
3	0.2780	28.09	28.09	0.04	28.13	28.13	60.88	50.88	-32.75	-22.75	Pass
4	0.3820	24.43	24.43	0.04	24.47	24.47	58.24	48.24	-33.77	-23.77	Pass
5	2.5740	37.53	37.53	0.13	37.66	37.66	56.00	46.00	-18.34	-8.34	Pass
6	5.5060	31.49	31.49	0.19	31.68	31.68	60.00	50.00	-28.32	-18.32	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5 Radiated Emissions Measurement

5.1. Limit

According to §15.225,

- (a) The field strength of any emissions within the band 13.553 – 13.567 MHz shall not exceed 15,848 microvolt / meter at 30 meters.
- (b) Within the bands 13.410 – 13.553 MHz and 13.567 -13.710 MHz, the field strength of any emissions shall not exceed 334 microvolt / meter at 30 meters.
- (c) Within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz the field strength of any emissions shall not exceed 106 microvolt / meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110 – 14.010 MHz and shall not exceed the general radiated emission limits in §15.209.

According to §15.225(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.




5.2. Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/08/2016	1 year
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/08/2016	1 year
Pre Amplifier	Agilent	8449B	3008A02237	10/07/2015	1 year
Pre Amplifier	Agilent	8447D	2944A11119	01/11/2016	1 year
Broadband Antenna	Schwarzbeck	VULB9168	416	09/25/2015	1 year
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/12/2015	1 year
Horn Antenna (18~40GHz)	ETS	3116	86467	09/01/2015	1 year
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	02/01/2016	1 year
Microwave Cable	EMCI	EMC102-KM-KM-14000	151001	10/15/2015	1 year
Microwave Cable	EMCI	EMC-104-SM-SM-14000	140202	10/15/2015	1 year
Microwave Cable	EMCI	EMC104-SM-SM-600	140301	10/15/2015	1 year
Test Site	ATL	TE01	888001	08/27/2015	1 year


NOTE: N.C.R. = No Calibration Request.

5.3. Setup

9kHz ~ 30MHz



30MHz ~ 1 GHz



5.4. Test Procedure

Final radiation measurements were made on a three-meter Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 3 Hz to 44 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

Broadband/Horn Antenna were used in frequency 30MHz to 18 GHz at a distance of 3 meter. Loop/Horn Antenna was used in frequency 9kHz to 30MHz and 18 to 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade, except below 30MHz).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in microvolt pre-meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in microvolt per-meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10


Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



5.5. Test Result

Fundamental Test Result:

Standard:	FCC Part 15C	Test Distance:	1m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	10/06/2015
Ant.Polar.:	Horizontal	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	13.5600	41.09	14.18	55.27	14.80	84.00	-69.20	peak

Note: The level is measured at 1 meter and is converted into result at 30 meter.

The converted formula listed below:

Measure result (1 meter distance): a

Compute result (30 meter distance): A


$d_{\text{near field}} = \lambda/2\pi$, $d_{\text{measure}} = 1$ meter distance

$A = a - 40 \cdot \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \cdot \log(d_{\text{limit}} / d_{\text{near field}})$

ex. $a = 55.27$ dBuV, $A = 55.27 - 40 \cdot \log(3.52 / 1) - 20 \cdot \log(30 / 3.52)$ dBuV = 14.8 dBuV



Standard:	FCC Part 15C	Test Distance:	1m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	06/02/2016
Ant.Polar.:	Vertical	Test By:	Eric Ou Yang




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	13.5602	44.42	14.18	58.60	18.13	84.00	-65.87	peak

Note: The level is measured at 1 meter and is converted into result at 30 meter.

9kHz ~ 30MHz:

Standard:	FCC Part 15C	Test Distance:	1m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	06/02/2016
Ant.Polar.:	Horizontal	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV/m)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.8185	58.75	14.49	73.24	8.38	29.34	-20.96	QP
2	3.9077	46.71	14.78	61.49	10.21	29.54	-19.34	QP
3	9.546	40.19	15.44	55.63	12.11	29.54	-17.43	QP
4	17.8231	35.91	15.54	51.45	13.34	29.54	-16.20	QP
5	21.4222	37.28	15.23	52.51	16.00	29.54	-13.54	QP
6	23.8518	36.30	14.71	51.01	15.45	29.54	-14.10	QP

Note: The level is measured at 1 meter and is converted into result at 300 or 30 meter.



Standard:	FCC Part 15C	Test Distance:	1m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	06/02/2016
Ant.Polar.:	Vertical	Test By:	Eric Ou Yang




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV/m)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.9082	60.80	14.55	75.35	11.39	28.44	-17.05	QP
2	3.458	45.03	14.63	59.66	7.31	29.54	-22.23	QP
3	6.577	40.01	15.24	55.25	8.49	29.54	-21.05	QP
4	11.1057	39.74	15.47	55.21	13.00	29.54	-16.54	QP
5	18.933	37.17	15.53	52.70	15.13	29.54	-14.41	QP
6	21.4222	37.23	15.23	52.46	15.95	29.54	-13.59	QP

Note: The level is measured at 1 meter and is converted into result at 300 or 30 meter.



Standard:	FCC Part 15C	Test Distance:	300/30m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	06/02/2016
Ant.Polar.:	Horizontal	Test By:	Eric Ou Yang




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV/m)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	1.238	61.02	14.60	75.62	14.35	25.75	-11.40	QP
2	4.1774	42.57	14.87	57.44	6.74	29.54	-22.81	QP
3	9.516	41.42	15.44	56.86	13.30	29.54	-16.24	QP
4	16.0542	37.80	15.51	53.31	14.31	29.54	-15.23	QP
5	20.133	36.63	15.50	52.13	15.09	29.54	-14.45	QP
6	22.1722	38.56	15.07	53.63	17.44	29.54	-12.10	QP

Note: The level is measured at 1 meter and is converted into result at 300 or 30 meter.



Standard:	FCC Part 15C	Test Distance:	300/30m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	06/02/2016
Ant.Polar.:	Vertical	Test By:	Eric Ou Yang




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Near-Field Result (dBuV/m)	Derived Value (dBuV)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.7588	61.23	14.46	75.69	10.17	30.00	-19.83	QP
2	4.1774	42.23	14.87	57.10	6.40	29.54	-23.15	QP
3	9.186	41.81	15.42	57.23	13.37	29.54	-16.17	QP
4	12.2751	40.81	15.47	56.28	14.94	29.54	-14.60	QP
5	17.8836	39.63	15.54	55.17	17.10	29.54	-12.45	QP
6	21.4526	37.79	15.23	53.02	16.55	29.54	-12.99	QP

Note: The level is measured at 1 meter and is converted into result at 300 or 30 meter.

**30MHz ~ 1GHz:**


Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	06/02/2016
Ant.Polar.:	Horizontal	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	250.0000	39.08	-5.28	33.80	46.00	-12.20	QP
2	280.5000	39.62	-3.90	35.72	46.00	-10.28	QP
3	396.0000	30.72	-1.78	28.94	46.00	-17.06	QP
4	528.0000	30.90	1.15	32.05	46.00	-13.95	QP
5	625.0000	32.44	3.41	35.85	46.00	-10.15	QP
6	943.0000	26.58	9.50	36.08	46.00	-9.92	QP




Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	06/02/2016
Ant.Polar.:	Vertical	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	250.0000	34.64	-5.28	29.36	46.00	-16.64	QP
2	375.0000	34.81	-2.18	32.63	46.00	-13.37	QP
3	462.0000	39.85	0.05	39.90	46.00	-6.10	QP
4	528.0000	36.52	1.15	37.67	46.00	-8.33	QP
5	594.0000	33.89	2.74	36.63	46.00	-9.37	QP
6	625.0000	35.91	3.41	39.32	46.00	-6.68	QP




Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	06/02/2016
Ant.Polar.:	Horizontal	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	250.0000	38.89	-5.28	33.61	46.00	-12.39	QP
2	280.5000	40.19	-3.90	36.29	46.00	-9.71	QP
3	462.0000	30.34	0.05	30.39	46.00	-15.61	QP
4	528.0000	30.69	1.15	31.84	46.00	-14.16	QP
5	625.0000	32.74	3.41	36.15	46.00	-9.85	QP
6	726.0000	30.26	5.37	35.63	46.00	-10.37	QP



Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	RM1000	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 3	Date:	06/02/2016
Ant.Polar.:	Vertical	Test By:	Eric Ou Yang



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	250.5000	34.33	-5.27	29.06	46.00	-16.94	QP
2	375.0000	33.49	-2.18	31.31	46.00	-14.69	QP
3	462.0000	39.74	0.05	39.79	46.00	-6.21	QP
4	528.0000	36.20	1.15	37.35	46.00	-8.65	QP
5	594.0000	34.34	2.74	37.08	46.00	-8.92	QP
6	625.0000	35.66	3.41	39.07	46.00	-6.93	QP




6 Frequency Stability Measurement

6.1. Limit

According to §15.207(e), the frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2. Test Setup



6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/27/2015	1 year
Temperature & Humidity Chamber	TAICHY	MHU-225LA	980729	04/18/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

NOTE: N.C.R. = No Calibration Request.

6.4. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the environment into appropriate environment.
4. Set the spectrum analyzer as RBW=1kHz, VBW = RBW, Span = 200kHz, Sweep = auto.
5. Mark the peak frequency and measure the frequency tolerance using frequency counter function.
6. Repeat until all the results are investigated.

6.5. Test Result

Temperature Variations

Model Number	RM1000					
Mode	Mode 2					
Date of Test	06/14/2016			Test Site	TE05	
Temp. (°C)	Voltage (VAC)	Measured Frequency (MHz)	Delta Frequency (Hz)	Tolerance (%)	Limit (±%)	Result (Pass/Fail)
-10	120	13.5606	600.0000	0.0044	±0.01	Pass
0		13.5608	800.0000	0.0059	±0.01	Pass
10		13.5611	1100.0000	0.0081	±0.01	Pass
20		13.5609	900.0000	0.0066	±0.01	Pass
30		13.5604	400.0000	0.0029	±0.01	Pass
40		13.5608	800.0000	0.0059	±0.01	Pass
50		13.5607	700.0000	0.0052	±0.01	Pass

Voltage Variations


Model Number	RM1000					
Mode	Mode 2					
Date of Test	06/14/2016			Test Site	TE05	
Temp. (°C)	Voltage (VAC)	Measured Frequency (MHz)	Delta Frequency (Hz)	Tolerance (%)	Limit (±%)	Result (Pass/Fail)
20	102	13.5609	900.0000	0.0066	±0.01	Pass
	120	13.5604	400.0000	0.0029	±0.01	Pass
	138	13.5608	800.0000	0.0059	±0.01	Pass

7 20dB Bandwidth Measurement

7.1. Limit

N/A

7.2. Test Setup



7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY46181986	05/19/2016	1 year
Test Site	ATL	TE05	TE05	N.C.R.	-----

NOTE: N.C.R. = No Calibration Request.



7.4. Test Procedure

Connect RF output port to the input of the spectrum analyzer. Connect the DUT to appropriate power supply. Turn RFID function of DUT on.

Analyzer used the following settings:

1. Span = 30 kHz
2. RBW $\geq$ 1% of the 20dB span
3. VBW $\geq$ RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate. The marker-to-peak function was used to set the marker to the peak of the emission. The marker-delta function was used to measure 20dB down one side of the emission. The marker-delta function and marker was moved to the other side of the emission until it was even with the reference marker. The marker-delta reading at this point was the 20dB bandwidth of the emission.



7.5. Test Result

Model Number	RM1000			
Mode	Mode 2			
Date of Test	06/14/2016	Test Site	TE05	
20dBc Low Point (MHz)	20dBc High Point (MHz)	Operating Frequency Band (MHz)		Result
13.55793	13.56201	13.553~13.567		Pass

7.6. Test Graphs





8 Antenna Requirement

8.1. Require

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

8.2. Antenna Connector Construction

The antenna connector used in this product is Coil Antenna , cannot be replaced by the end-user.