

FCC ID:2AIOOH30

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz;}$$

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.


Maximum measured transmitter power:

BLE:

Modulation	Channel Freq. (MHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Result calculation	1g SAR
GFSK	2402	-3.266	0.47	-3 $\pm$ 1	-2.00	0.63	0.19558	3.00
	2440	-3.692	0.43	-3 $\pm$ 1	-2.00	0.63	0.19700	3.00
	2480	-3.957	0.40	-3 $\pm$ 1	-2.00	0.63	0.19873	3.00

Conclusion:

For the max result : $0.19873 \leq 3.0$ for 1-g SAR, No SAR is required.

**Signature:****Date:** 2016-12-31**NAME AND TITLE** (Please print or type): Jason Chen /Manager**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E,
Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.