



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Thirty Five

Model: SOL-001

Description: Wireless Health & Environmental Monitor

Serial Number: N/A

FCC ID: 2AIQE-S1

To

FCC Part 1.1310

Date of Issue: June 14, 2016

On the behalf of the applicant:

**Thirty Five
297 Kingbury Grade
Suite 236
State Line, NV 89499**

Attention of:

**Avard Fairbanks
Ph: (512)897-9562
Email: AKF@35engineering.com**

**Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1660005**

**Kenneth Lee
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 10, 2016	Kenneth Lee	Original Document



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: SOL 001 Key Fob

Description: Key fob for monitoring sun exposure

Firmware: N/A

Software: N/A

Serial Number: N/A

Additional Information: None



MPE Evaluation

This is a portable device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	2440
Power, Conducted, mW (P)	3.36
Antenna Gain Isotropic	1 dBi
Antenna Gain Numeric (G)	1.26
Antenna Type	Integral
Distance (R)	1 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) =	0.33691
Limit =(from above table) =	1.0

END OF TEST REPORT