REPORT No. : SZ16090154S01

RF EXPOSURE EVALUATION REPORT

APPLICANT	:	Midea Smart Technology Co.，Ltd
PRODUCT NAME	:	WIFI module
MODEL NAME	:	MM591050-10
TRADE NAME	:	N/A
BRAND NAME	:	Midea
FCC ID	:	2AIRV0002
STANDARD(S)	:	47CFR 2.1091 KDB 447498 D01 General RF Exposure Guidance v06
ISSUE DATE	:	2016-10-20

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China Tel: 86-755-36698555 Http://www.morlab.com Fax: 86-755-36698525 E-mail: service@morlab.cn

DIRECTORY

TEST REPORT DECLARATION 3

1. TECHNICAL INFORMATION 4

1.1. IDENTIFICATION OF APPLICANT 4
1.2. IDENTIFICATION OF MANUFACTURER 4
1.3. EQUIPMENT UNDER TEST (EUT) 4
1.3.1. PHOTOGRAPHS OF THE EUT 5
1.3.2. IDENTIFICATION OF ALL USED EUT 5
1.4. APPLIED REFERENCE DOCUMENTS 5

2. DEVICE CATEGORY AND RF EXPOSURE LIMIT 6

3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER 7

3. RF EXPOSURE EVALUATION 7

ANNEX GENERAL INFORMATION 8

Change History		
Issue	Date	Reason for change
1.0	2016-10-20	First edition

TEST REPORT DECLARATION

Applicant	Midea Smart Technology Co. , Ltd
Applicant Address	Yi Financial Tower,NO.95 Xuefu Road, Nanshan District,Shenzhen, Guangdong, 518000,P.R.China
Manufacturer	Midea Smart Technology Co. , Ltd
Manufacturer Address	Yi Financial Tower,NO.95 Xuefu Road, Nanshan District,Shenzhen, Guangdong, 518000,P.R.China
Product Name	WIFI module
Model Name	MM591050-10
Brand Name	Midea
HW Version	N/A
SW Version	N/A
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2016-10-20
SAR Evaluation	Not Required

Tested by : Chen Sheng kui

Chen Shengkui

Reviewed by : Liu Jun

Liu Jun

Approved by : Zeng Dexin

Zeng Dexin

1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	Midea Smart Technology Co. , Ltd
Address:	Yi Financial Tower,NO.95 Xuefu Road, Nanshan District,Shenzhen, Guangdong, 518000,P.R.China

1.2. Identification of Manufacturer

Company Name:	Midea Smart Technology Co. , Ltd
Address:	Yi Financial Tower,NO.95 Xuefu Road, Nanshan District,Shenzhen, Guangdong, 518000,P.R.China

1.3. Equipment Under Test (EUT)

Model Name:	MM591050-10
Trade Name:	N/A
Brand Name:	Midea
Hardware Version:	N/A
Software Version:	N/A
Frequency Bands:	WIFI 802.11b/g/n20/n40;
Modulation Mode:	WIFI802.11b: DSSS;WIFI802.11g: OFDM; WIFI802.11n: OFDM;
Antenna type:	PCB Antenna
Development Stage:	Identical prototype

1.3.1. Photographs of the EUT

1. EUT front view

2. EUT rear view

1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	N/A	N/A

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	**47 CFR§2.1091**	Radiofrequency Radiation Exposure Evaluation: mobile devices
2	**KDB 447498 D01v06**	General RF Exposure Guidance

2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, this device Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f^2)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

Wifi average output power

Band	Channel	Frequency (MHz)	Output Power(dBm)		
			802.11B	802.11G	802.11N 20
Wifi	1	2412	9.45	10.13	10.04
	6	2437	10.33	9.92	9.79
	11	2462	10.31	9.71	9.57

Band	Channel	Frequency (MHz)	Output Power(dBm)
			802.11n40
Wifi	3	2422	7.63
	6	2437	7.75
	9	2452	7.89

3. RF EXPOSURE EVALUATION

Standalone transmission MPE evaluation

Bands	**Frequency (MHz)**	**Antenna Gain (dBi)**	**Conducted Average Power (dBm)**	**Time-averaging EIRP (mW)**	**Power density (mW/cm²)**	**Limit for MPE (mW/cm²)**
2.4GHz	2437	-0.8	10.33	8.97	0.002	1.0

Note:

1. MPE calculation method

$$\text{Power Density} = EIRP/4\pi R^2$$

Where: EIRP = P·G

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)

ANNEX GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

***** END OF REPORT *****