

RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05
The 1-g and 10-g SAR test exclusion thresholds for 100 MHz
to 6 GHz at test separation distances ≤ 50 mm are determined
by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance,} \\ \text{mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]}{\leq 3.0}$$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Worse case of BLE is as below: [2480 MHz -5.369dBm (0.29mW)
output power]

$$(0.29\text{mW} / 5\text{mm}) \cdot [\sqrt{2.480(\text{GHz})}] = 0.1 < 3.0 \text{ for 1-g SAR}$$

Worse case of WIFI is as below: [2437 MHz 9.30dBm (8.51 mW)
output power]

$$(8.51\text{mW} / 5\text{mm}) \cdot [\sqrt{2.437(\text{GHz})}] = 2.67 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required