

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AISN-N5

EUT Specification

EUT	AUTOMOTIVE DIAGNOSTIC & ANALYSIS SYSTEM
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.24GHz ☒ WLAN: 5.745GHz ~ 5.825GHz ☒ Others: 2.402GHz~2.480GHz (BT4.0 BDR+EDR+BLE)
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	BT 4.0 :-4.260 dBm (0.0004W) 2.4 G Wifi: 17.62 dBm (0.0578W) BT 3.0: -0.218 dBm (0.0010W) 5.8 G Wifi: 15.94 dBm (0.0393W)
Antenna gain (Max)	2.5 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Operating Mode	Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)	band
	(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)		
802.11a	5745	15.13	15.13±1	16.13	2.5	0.0145	1	5.8G Wifi
	5785	14.10	14.10±1	15.1	2.5	0.0114	1	
	5825	13.32	13.32±1	14.32	2.5	0.0096	1	
802.11n20	5745	15.94	15.94±1	16.94	2.5	0.0175	1	
	5785	14.03	14.03±1	15.03	2.5	0.0113	1	
	5825	13.41	13.41±1	14.41	2.5	0.0098	1	
802.11ac20	5745	15.12	15.12±1	16.12	2.5	0.0145	1	
	5785	13.33	13.33±1	14.33	2.5	0.0096	1	
	5825	12.72	12.72±1	13.72	2.5	0.0083	1	
802.11n40	5755	14.05	14.05±1	15.05	2.5	0.0113	1	
	5795	13.15	13.15±1	14.15	2.5	0.0092	1	
802.11ac40	5755	14.39	14.39±1	15.39	2.5	0.0122	1	
	5795	12.50	12.50±1	13.5	2.5	0.0079	1	
802.11ac80	5775	12.61	12.61±1	13.61	2.5	0.0081	1	
802.11b	2412	17.62	17.62±1	18.62	2.5	0.0257	1	2.4G Wifi
	2437	17.23	17.23±1	18.23	2.5	0.0235	1	
	2462	17.56	17.56±1	18.56	2.5	0.0254	1	
802.11g	2412	16.75	16.75±1	17.75	2.5	0.0211	1	
	2437	16.45	16.45±1	17.45	2.5	0.0197	1	
	2462	15.20	15.20±1	16.2	2.5	0.0147	1	
802.11n20	2412	15.34	15.34±1	16.34	2.5	0.0152	1	
	2437	15.75	15.75±1	16.75	2.5	0.0167	1	
	2462	12.33	12.33±1	13.33	2.5	0.0076	1	
802.11n40	2422	14.87	14.87±1	15.87	2.5	0.0137	1	
	2437	14.23	14.23±1	15.23	2.5	0.0118	1	
	2452	14.32	14.32±1	15.32	2.5	0.0120	1	
BDR+EDR	2402	-3.844	-3.844±1	-2.844	2.5	0.0002	1	BDR+EDR
	2441	-3.867	-3.867±1	-2.867	2.5	0.0002	1	
	2480	-4.316	-4.316±1	-3.316	2.5	0.0002	1	
	2402	-0.218	-0.218±1	0.782	2.5	0.0004	1	
	2441	-0.238	-0.238±1	0.762	2.5	0.0004	1	
	2480	-0.647	-0.647±1	0.353	2.5	0.0004	1	
BLE	2402	-4.667	-4.667±1	-3.667	2.5	0.0002	1	BLE
	2440	-4.710	-4.710±1	-3.71	2.5	0.0002	1	
	2480	-4.260	-4.260±1	-3.26	2.5	0.0002	1	

