



FCC ID:2AITM-IOT3288E

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

mW=10^{^(dBm/10)}



11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

Antenna gain: 2dBi,

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2402	GFSK	4.24	6.270	5.5±1	6.5	1.585	0.001408	1
2440		3.67	5.649	5.5±1	6.5	1.585	0.001408	1
2480		3.06	4.861	5.5±1	6.5	1.585	0.001408	1

Bluetooth DSS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2402	GFSK	6.95	8.421	8±1	9	1.585	0.002504	1
2440		7.12	8.525	8±1	9	1.585	0.002504	1
2480		7.17	8.557	8±1	9	1.585	0.002504	1
2402	Pi/4 DQPSK	3.85	5.860	5±1	6	1.585	0.001255	1
2440		3.19	5.036	5±1	6	1.585	0.001255	1
2480		2.60	4.150	5±1	6	1.585	0.001255	1
2402	8DPSK	4.36	6.395	5.5±1	6.5	1.585	0.001408	1
2440		3.52	5.467	5.5±1	6.5	1.585	0.001408	1
2480		2.97	4.724	5.5±1	6.5	1.585	0.001408	1

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz,

802.11n HT40: 2422-2452MHz,

Power density limited: $1\text{mW}/\text{cm}^2$

Antenna Type: External Antenna

Antenna gain: 2dBi

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

802.11b/g/n:



Shenzhen BCTC Testing Co., Ltd.

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2412	802.11b	23.23	13.66	13±1	14	1.585	0.007920	1
2437	802.11b	23.07	13.63	13±1	14	1.585	0.007920	1
2462	802.11b	23.99	13.80	13±1	14	1.585	0.007920	1
2412	802.11g	18.54	12.68	12±1	13	1.585	0.006291	1
2437	802.11g	18.11	12.58	12±1	13	1.585	0.006291	1
2462	802.11g	17.74	12.49	12±1	13	1.585	0.006291	1
2412	802.11n H20	18.97	12.78	12±1	13	1.585	0.006291	1
2437	802.11n H20	18.58	12.69	12±1	13	1.585	0.006291	1
2462	802.11n H20	18.07	12.57	12±1	13	1.585	0.006291	1

simultaneous emission

Power density Limits (mW/cm ²) WIFI	Power density Limits (mW/cm ²) BLE	Power density Limits (mW/cm ²) BT	Calculate Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
0.007920	0.001408	0.002504	0.011832	1

Conclusion:

For the max result : $0.011832 \leq 1.0$, compliance with FCC's RF Exposure.